

# SAFETY DATA SHEET



Date of issue/Date of revision

: 26 October 2023

Version

: 1.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : HI-TEMP 707HB LTGRAY LIQ INSUL  
**Product code** : HT707HB902  
**Product description** :  
**Product type** : Liquid.  
**Other means of identification** : Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications.  
**Use of the substance/mixture** : Coating.  
**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG France Business Support SAS, 3, ZAE "Les Dix Muids", B.P. 89, 59583 Marly Cedex, France, 33 (0)3 27 19 35 00

- Technical contact : Product Compliance EMEA

- Tel : +33 (0)3 27 19 35 00

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

PPG Architectural Coatings UK Ltd, Huddersfield Road, Birstall, West Yorkshire WF17 9XA, Tel: +44 (0) 1924 354000

### 1.4 Emergency telephone number

#### Supplier

+33 (0)3 27 19 35 00 (0800-1700)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to UK CLP/GHS

Skin Irrit. 2, H315

Eye Irrit. 2, H319

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

#### **Hazard pictograms**

:



#### **Signal word**

: Warning

#### **Hazard statements**

: Causes skin irritation.  
Causes serious eye irritation.

#### Precautionary statements

##### **Prevention**

: Wear protective gloves. Wear eye or face protection. Wash thoroughly after handling.

Code	: HT707HB902	Date of issue/Date of revision	: 26 October 2023
HI-TEMP 707HB LTGRAY LIQ INSUL			

SECTION 2: Hazards identification

Response	: Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P264, P362 + P364, P302 + P352, P305 + P351 + P338, P501
Supplemental label elements	: Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirements	
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

Mixture				
3.2 Mixtures				
Product/ingredient name	Identifiers	%	Classification	Type
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≥5.0 - ≤10	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
ammonium hydroxide	REACH #: 01-2119982985-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	≥1.0 - <3.0	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1)	[1] [2]
methanol	REACH #: 01-2119433307-44 EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	≥1.0 - <3.0	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370	[1] [2]
Distillates (petroleum), hydrotreated heavy naphthenic	REACH #: 01-2119467170-45 EC: 265-155-0 CAS: 64742-52-5 Index: 649-465-00-7	≥1.0 - ≤5.0	Asp. Tox. 1, H304	[1]
aliphatic polyether	CAS: SUB138636	≥0.30 - ≤2.6	Acute Tox. 4, H332	[1]
Nonylphenol, branched, ethoxylated (EO>14 mol)	EC: 500-209-1 CAS: 68412-54-4	≤0.30	Aquatic Chronic 3, H412	[1] [3]
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5	<0.050	Acute Tox. 4, H302 Acute Tox. 2, H330	[1]
English (GB)		United Kingdom (UK)		2/15

**Code** : HT707HB902 **Date of issue/Date of revision** : 26 October 2023  
**HI-TEMP 707HB LTGRAY LIQ INSUL**

### SECTION 3: Composition/information on ingredients

pyrithione zinc	Index: 613-088-00-6  REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7 Index: 613-333-00-7	≤0.0039	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411 Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 (M=1000) Aquatic Chronic 1, H410 (M=10) <b>See Section 16 for the full text of the H statements declared above.</b>	[1]
-----------------	--------------------------------------------------------------------------------------------------------------------	---------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard  
 [2] Substance with a workplace exposure limit  
 [3] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : No known significant effects or critical hazards.

##### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness
- Inhalation** : No specific data.

<b>Code</b> : HT707HB902	<b>Date of issue/Date of revision</b> : 26 October 2023
<b>HI-TEMP 707HB LTGRAY LIQ INSUL</b>	

## SECTION 4: First aid measures

- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
metal oxide/oxides  
Formaldehyde.

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

<b>Code</b> : HT707HB902	<b>Date of issue/Date of revision</b> : 26 October 2023
<b>HI-TEMP 707HB LTGRAY LIQ INSUL</b>	

**SECTION 6: Accidental release measures**

<b>Large spill</b>	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
<b>6.4 Reference to other sections</b>	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

**SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**7.1 Precautions for safe handling**

<b>Protective measures</b>	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
<b>Advice on general occupational hygiene</b>	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**7.2 Conditions for safe storage, including any incompatibilities**

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

**7.3 Specific end use(s)**


See Section 1.2 for Identified uses.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**Occupational exposure limits**

Product/ingredient name	Exposure limit values
 -butoxyethanol	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m³ 15 minutes. TWA: 123 mg/m³ 8 hours.
ammonium hydroxide	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia</b>

Code : HT707HB902

Date of issue/Date of revision

: 26 October 2023

HI-TEMP 707HB LTGRAY LIQ INSUL

**SECTION 8: Exposure controls/personal protection**

methanol

**anhydrous]**STEL: 25 mg/m<sup>3</sup> 15 minutes. Form: anhydrous

STEL: 35 ppm 15 minutes. Form: anhydrous

TWA: 25 ppm 8 hours. Form: anhydrous

TWA: 18 mg/m<sup>3</sup> 8 hours. Form: anhydrous**EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.**STEL: 333 mg/m<sup>3</sup> 15 minutes.

STEL: 250 ppm 15 minutes.

TWA: 266 mg/m<sup>3</sup> 8 hours.

TWA: 200 ppm 8 hours.

**Biological exposure indices**

Product/ingredient name	Exposure indices
2-butoxyethanol	2-BUTOXY ETHANOL

**Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
2-butoxyethanol	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	59 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	98 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	246 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	426 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	1091 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	20 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	20 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	26 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	26 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	26 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	26 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	130 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	130 mg/m <sup>3</sup>	Workers	Local
methanol	DNEL	Short term Inhalation	130 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	130 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m <sup>3</sup>	General population	Local
Distillates (petroleum), hydrotreated heavy naphthenic	DNEL	Long term Inhalation	2.73 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	4.7 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	66.7 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.345 mg/kg bw/day	General population	Systemic
Nonylphenol, branched, ethoxylated (EO>14 mol)	DNEL	Long term Dermal	0.966 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	0.01 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.01 mg/kg bw/day	Workers	Systemic

**PNECs**

**Code** : HT707HB902 **Date of issue/Date of revision** : 26 October 2023  
**HI-TEMP 707HB LTGRAY LIQ INSUL**

## SECTION 8: Exposure controls/personal protection

Product/ingredient name	Compartment Detail	Value	Method Detail
2-butoxyethanol	Fresh water	8.8 mg/l	Assessment Factors
	Marine water	0.88 mg/l	Assessment Factors
	Fresh water sediment	34.6 mg/kg	Equilibrium Partitioning
	Marine water sediment	3.46 mg/kg	Equilibrium Partitioning
	Soil	3.13 mg/kg	Equilibrium Partitioning
	Sewage Treatment Plant	463 mg/l	Assessment Factors
	Fresh water	20.8 mg/l	Assessment Factors
	Marine water	2.08 mg/l	Assessment Factors
	Sewage Treatment Plant	100 mg/l	Assessment Factors
	Fresh water sediment	77 mg/kg	Equilibrium Partitioning
methanol	Marine water sediment	7.7 mg/kg	Equilibrium Partitioning
	Soil	100 mg/kg	Assessment Factors

### 8.2 Exposure controls

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber, butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN140. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Mask type: full-face mask half-face mask Filter type: organic vapour filter (Type A) particulate filter P3 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

<b>Code</b> : HT707HB902	<b>Date of issue/Date of revision</b> : 26 October 2023
<b>HI-TEMP 707HB LTGRAY LIQ INSUL</b>	

**SECTION 8: Exposure controls/personal protection**

<b>Environmental exposure controls</b>	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
----------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**9.1 Information on basic physical and chemical properties**

<b>Appearance</b>	
<b>Physical state</b>	: Liquid.
<b>Colour</b>	: Grey.
<b>Odour</b>	: Characteristic.
<b>Odour threshold</b>	: Not available.
<b>Melting point/freezing point</b>	: May start to solidify at the following temperature: 0°C (32°F) This is based on data for the following ingredient: water. Weighted average: -10.97°C (12.3°F)
<b>Initial boiling point and boiling range</b>	: >37.78°C (>100°F)
<b>Flammability (solid, gas)</b>	: liquid
<b>Upper/lower flammability or explosive limits</b>	: Greatest known range: Lower: 6% Upper: 44% (methanol)
<b>Flash point</b>	: Closed cup: Not applicable.
<b>Auto-ignition temperature</b>	:

<b>Ingredient name</b>	<b>°C</b>	<b>°F</b>	<b>Method</b>
2-butoxyethanol	230	446	DIN 51794

<b>Decomposition temperature</b>	:
<b>pH</b>	: Not available.
<b>Viscosity</b>	: Kinematic (40°C): >21 mm²/s
<b>Solubility(ies)</b>	:

<b>Media</b>	<b>Result</b>
cold water	Soluble

<b>Miscible with water</b>	: Yes.
<b>Partition coefficient: n-octanol/ water</b>	: Not applicable.
<b>Vapour pressure</b>	:

<b>Ingredient name</b>	<b>Vapour Pressure at 20°C</b>			<b>Vapour pressure at 50°C</b>		
	<b>mm Hg</b>	<b>kPa</b>	<b>Method</b>	<b>mm Hg</b>	<b>kPa</b>	<b>Method</b>
ammonium hydroxide	360.03	48				

<b>Relative density</b>	: 0.5
<b>Vapour density</b>	: Highest known value: 4.1 (Air = 1) (2-butoxyethanol). Weighted average: 2.86 (Air = 1)
<b>Explosive properties</b>	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
<b>Oxidising properties</b>	: Product does not present an oxidizing hazard.
<b>Particle characteristics</b>	
<b>Median particle size</b>	: Not applicable.

<b>Code</b> : HT707HB902	<b>Date of issue/Date of revision</b> : 26 October 2023
<b>HI-TEMP 707HB LTGRAY LIQ INSUL</b>	

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability : The product is stable.
- 10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.  
Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:  
oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following  
materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

**SECTION 11: Toxicological information**

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LC50 Inhalation Vapour	Rat	3 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
ammonium hydroxide	LD50 Oral	Rat	350 mg/kg	-
	LC50 Inhalation Vapour	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	-
methanol	LD50 Oral	Rat	5600 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Oral	Rat	15 g/kg	-
	LD50 Oral	Rat	2.21 g/kg	-
	LC50 Inhalation Dusts and mists	Rat	0.4 mg/l	4 hours
Nonylphenol, branched, ethoxylated (EO>14 mol)	LD50 Oral	Rat	1020 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	0.14 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
1,2-benzisothiazol-3(2H)-one	LD50 Oral	Rat	177 mg/kg	-
pyrithione zinc				

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
HI-TEMP 707HB LTGRAY LIQ INSUL	4806.7	18292.9	N/A	41.2	N/A
2-butoxyethanol	1200	N/A	N/A	3	N/A
methanol	100	300	64000	3	N/A
Distillates (petroleum), hydrotreated heavy naphthenic	15000	N/A	N/A	N/A	N/A
aliphatic polyether	N/A	N/A	N/A	11	N/A
Nonylphenol, branched, ethoxylated (EO>14 mol)	2210	N/A	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	1020	N/A	N/A	N/A	0.4
pyrithione zinc	221	N/A	N/A	N/A	0.14

Code	: HT707HB902	Date of issue/Date of revision	: 26 October 2023
HI-TEMP 707HB LTGRAY LIQ INSUL			

SECTION 11: Toxicological information

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethanol pyrithione zinc	Eyes - Irritant	Rabbit	-	24 hours	21 days
	Skin - Moderate irritant	Rabbit	-	4 hours	28 days
	Eyes - Cornea opacity	Rabbit	4	24 hours	24 hours

Conclusion/Summary : Not available.  
Skin : There are no data available on the mixture itself.  
Eyes : There are no data available on the mixture itself.  
Respiratory : There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
2-benzisothiazol-3(2H)-one	skin	Guinea pig	Sensitising

Conclusion/Summary :  
Skin : There are no data available on the mixture itself.  
Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary :  
There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ammonium hydroxide	Category 3	-	Respiratory tract irritation
methanol	Category 1	-	-

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
pyrithione zinc	Category 1	-	-

Aspiration hazard

Product/ingredient name	Result
Distillates (petroleum), hydrotreated heavy naphthenic	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.  
Inhalation : No known significant effects or critical hazards.  
Skin contact : Causes skin irritation.  
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Code** : HT707HB902 **Date of issue/Date of revision** : 26 October 2023  
**HI-TEMP 707HB LTGRAY LIQ INSUL**

## SECTION 11: Toxicological information

**Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness

**Inhalation** : No specific data.

**Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness

**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-butoxyethanol	Acute LC50 1474 mg/l	Fish	96 hours
methanol	Chronic NOEC >100 mg/l	Fish	21 days
Distillates (petroleum), hydrotreated heavy naphthenic	Acute LC50 13 mg/l Fresh water	Fish - Trout	96 hours
1,2-benzisothiazol-3(2H)-one	Acute LC50 >100 mg/l	Fish	96 hours
pyrithione zinc	Acute EC50 0.11 mg/l	Algae	72 hours
	Chronic NOEC 0.09 mg/l	Fish - Trout	28 days
	Acute EC50 5.513 µg/l Marine water	Algae - Diatom - <i>Nitzschia pungens</i>	96 hours
	Acute LC50 0.0082 mg/l	Daphnia	48 hours
	Chronic NOEC 1.889 µg/l Marine water	Algae - Diatom - <i>Nitzschia pungens</i>	96 hours
	Chronic NOEC 0.0027 mg/l	Daphnia	21 days

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
pyrithione zinc	-	39 % - 28 days	-	-

**Code** : HT707HB902 **Date of issue/Date of revision** : 26 October 2023  
**HI-TEMP 707HB LTGRAY LIQ INSUL**

## SECTION 12: Ecological information

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-butoxyethanol	-	-	Readily
1,2-benzisothiazol-3(2H)-one	-	-	Readily
pyrithione zinc	-	50%; < 28 day(s)	Not readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2-butoxyethanol	0.81	-	Low
methanol	-0.77	-	Low
Nonylphenol, branched, ethoxylated (EO>14 mol)	5.39	-	High
1,2-benzisothiazol-3(2H)-one	0.7	-	Low
pyrithione zinc	0.9	0.9	Low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

#### Waste catalogue

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Code	: HT707HB902	Date of issue/Date of revision	: 26 October 2023
HI-TEMP 707HB LTGRAY LIQ INSUL			

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID	: None identified.
ADN	: The product is only regulated as a dangerous good when transported in tank vessels.
IMDG	: None identified.
IATA	: None identified.

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.


14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  
[UK \(GB\)/REACH](#)

[Annex XIV - List of substances subject to authorisation](#)


[Annex XIV](#)

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
 Substance of equivalent concern for environment	4-nonylphenol, branched and linear, ethoxylated substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, ethoxylated covering UVCB- and well-defined substances, polymers and homologues, which include any of the individual isomers and/or combinations thereof	Listed	43	1/1/2021

[Substances of very high concern](#)

Code	: HT707HB902	Date of issue/Date of revision	: 26 October 2023
HI-TEMP 707HB LTGRAY LIQ INSUL			

SECTION 15: Regulatory information

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
 Substance of equivalent concern for environment	4-nonylphenol, branched and linear, ethoxylated substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, ethoxylated covering UVCB- and well-defined substances, polymers and homologues, which include any of the individual isomers and/or combinations thereof	Candidate	-	6/20/2013

Ozone depleting substances


Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Seveso Directive

This product is not controlled under the Seveso Directive.

SECTION 16: Other information


 Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate  
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = GB CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Skin Irrit. 2, H315 Eye Irrit. 2, H319	Calculation method Calculation method

Full text of abbreviated H statements

 H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

<b>Code</b>	<b>: HT707HB902</b>	<b>Date of issue/Date of revision</b>	<b>: 26 October 2023</b>
<b>HI-TEMP 707HB LTGRAY LIQ INSUL</b>			

**SECTION 16: Other information**

H360D	May damage the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

<b>Date of issue/ Date of revision</b>	<b>: 26 October 2023</b>
<b>Date of previous issue</b>	<b>: 8 November 2022</b>
<b>Prepared by</b>	<b>: EHS</b>
<b>Version</b>	<b>: 1.01</b>

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.