

# SAFETY DATA SHEET



Date of issue/Date of revision

: 27 October 2023

Version

: 1.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : SIGMACOVER 256S BASE 5177

Product code : 00316061

Product description :

Product type : Liquid.

Other means of identification : Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### Supplier

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### Classification according to UK CLP/GHS

Fam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Carc. 1B, H350

STOT RE 1, H372

Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Hazard pictograms :



Signal word : Danger



Code : 00316061

Date of issue/Date of revision

: 27 October 2023

SIGMACOVER 256S BASE 5177

**SECTION 3: Composition/information on ingredients**

xylene	Index: 030-011-00-6 EC: 215-535-7 CAS: 1330-20-7	≥5.0 - ≤8.5	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1] [2]
epoxy resin (MW ≤ 700)	REACH #: 01-2119456619-26 EC: 500-033-5 CAS: 25068-38-6	≥5.0 - ≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≥0.30 - ≤2.9	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1] [2]
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	REACH #: 01-2119979085-27 EC: 309-629-8 CAS: 100545-48-0	≤0.30	Skin Sens. 1B, H317 Aquatic Chronic 3, H412  <b>See Section 16 for the full text of the H statements declared above.</b>	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

**Type**

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

**SECTION 4: First aid measures****4.1 Description of first aid measures****Eye contact**

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**Inhalation**

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**Skin contact**

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

**Ingestion**

: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Code : 00316061

Date of issue/Date of revision

: 27 October 2023

SIGMACOVER 256S BASE 5177

**SECTION 4: First aid measures**

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

**4.2 Most important symptoms and effects, both acute and delayed****Potential acute health effects**

**Eye contact** : Causes serious eye irritation.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.  
**Ingestion** : No known significant effects or critical hazards.

**Over-exposure signs/symptoms**

**Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness  
**Inhalation** : No specific data.  
**Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness  
 dryness  
 cracking  
**Ingestion** : No specific data.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.  
**Specific treatments** : No specific treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.  
**Unsuitable extinguishing media** : Do not use water jet.

**5.2 Special hazards arising from the substance or mixture**

**Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.  
**Hazardous combustion products** : Decomposition products may include the following materials:  
 carbon oxides  
 sulfur oxides  
 phosphorus oxides  
 halogenated compounds  
 metal oxide/oxides

**5.3 Advice for firefighters**

**Code** : 00316061  
**SIGMACOVER 256S BASE 5177**

**Date of issue/Date of revision** : 27 October 2023

## SECTION 5: Firefighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
 See Section 8 for information on appropriate personal protective equipment.  
 See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when

<b>Code</b> : 00316061	<b>Date of issue/Date of revision</b> : 27 October 2023
<b>SIGMACOVER 256S BASE 5177</b>	

**SECTION 7: Handling and storage**

not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

<b>Advice on general occupational hygiene</b>	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
---	---

**7.2 Conditions for safe storage, including any incompatibilities**

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

**7.3 Specific end use(s)**

See Section 1.2 for Identified uses.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

Product/ingredient name	Exposure limit values
Crystalline silica, respirable powder (<10 microns)	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). [silica, respirable crystalline respirable fraction]</b> TWA: 0.1 mg/m³ 8 hours. Form: Respirable fraction
xylene	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). [xylene, o-,m-,p- or mixed isomers] Absorbed through skin.</b> STEL: 441 mg/m³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 220 mg/m³ 8 hours. TWA: 50 ppm 8 hours.
2-methoxy-1-methylethyl acetate	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> STEL: 548 mg/m³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 274 mg/m³ 8 hours. TWA: 50 ppm 8 hours.
ethylbenzene	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> STEL: 552 mg/m³ 15 minutes. STEL: 125 ppm 15 minutes. TWA: 441 mg/m³ 8 hours. TWA: 100 ppm 8 hours.

Biological exposure indices

Product/ingredient name	Exposure indices
xylene	XYLENES

Code : 00316061

Date of issue/Date of revision

: 27 October 2023

SIGMACOVER 256S BASE 5177

**SECTION 8: Exposure controls/personal protection**

**Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons, C9, aromatics > 0.1% cumene	DNEL	Long term Inhalation	150 mg/m <sup>3</sup>	Workers	Systemic
trizinc bis(orthophosphate)	DNEL	Long term Dermal	25 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	32 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	11 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	11 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	2.5 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	5 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Systemic
xylene	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Local
epoxy resin (MW ≤ 700)	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Systemic
2-methoxy-1-methylethyl acetate	DNEL	Long term Inhalation	12.25 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	12.25 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	3.571 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	3.571 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	33 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	33 mg/m <sup>3</sup>	General population	Systemic
ethylbenzene	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	275 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	320 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	550 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	796 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic

Code : 00316061

Date of issue/Date of revision

: 27 October 2023

SIGMACOVER 256S BASE 5177

**SECTION 8: Exposure controls/personal protection**

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	DNEL	Long term Inhalation	15 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	77 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	293 mg/m <sup>3</sup>	Workers	Local
	DMEL	Long term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
	DMEL	Short term Inhalation	884 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	0.055 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	0.308 mg/m <sup>3</sup>	Workers	Local

**PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
trizinc bis(orthophosphate)	Fresh water	20.6 µg/l	Sensitivity Distribution
	Marine water	6.1 µg/l	Sensitivity Distribution
	Sewage Treatment Plant	100 µg/l	Assessment Factors
	Fresh water sediment	117.8 mg/kg dwt	Sensitivity Distribution
	Marine water sediment	56.5 mg/kg dwt	Equilibrium Partitioning
xylene	Soil	35.6 mg/kg dwt	Sensitivity Distribution
	Fresh water	0.327 mg/l	-
	Marine water	0.327 mg/l	-
	Sewage Treatment Plant	6.58 mg/l	-
	Fresh water sediment	12.46 mg/kg dwt	-
epoxy resin (MW ≤ 700)	Marine water sediment	12.46 mg/kg dwt	-
	Soil	2.31 mg/kg	-
	Fresh water	0.006 mg/l	Assessment Factors
	Marine water	0.001 mg/l	Assessment Factors
	Sewage Treatment Plant	10 mg/l	Assessment Factors
2-methoxy-1-methylethyl acetate	Fresh water sediment	0.996 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	0.1 mg/kg dwt	Equilibrium Partitioning
	Fresh water	0.635 mg/l	-
	Marine water	0.0635 mg/l	-
	Fresh water sediment	3.29 mg/kg	-
ethylbenzene	Marine water sediment	0.329 mg/kg	-
	Soil	0.29 mg/kg	-
	Sewage Treatment Plant	100 mg/l	-
	Fresh water	0.1 mg/l	Assessment Factors
	Marine water	0.01 mg/l	Assessment Factors
	Sewage Treatment Plant	9.6 mg/l	Assessment Factors
	Fresh water sediment	13.7 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	1.37 mg/kg dwt	Equilibrium Partitioning
	Soil	2.68 mg/kg dwt	Equilibrium Partitioning
	Secondary Poisoning	20 mg/kg	-

**8.2 Exposure controls****Appropriate engineering controls**

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Individual protection measures****Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection**

: Chemical splash goggles.

**Skin protection**

<b>Code</b> : 00316061	<b>Date of issue/Date of revision</b> : 27 October 2023
<b>SIGMACOVER 256S BASE 5177</b>	

**SECTION 8: Exposure controls/personal protection**

<b>Hand protection</b>	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. butyl rubber
<b>Body protection</b>	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
<b>Other skin protection</b>	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Respiratory protection</b>	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
<b>Environmental exposure controls</b>	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**9.1 Information on basic physical and chemical properties**

<b>Appearance</b>	
<b>Physical state</b>	: Liquid.
<b>Colour</b>	: Grey.
<b>Odour</b>	: Aromatic.
<b>Odour threshold</b>	: Not available.
<b>Melting point/freezing point</b>	: May start to solidify at the following temperature: -43.77°C (-46.8°F) This is based on data for the following ingredient: 1,2,4-trimethylbenzene. Weighted average: -75.53°C (-104°F)
<b>Initial boiling point and boiling range</b>	: >37.78°C (>100°F)
<b>Flammability (solid, gas)</b>	: liquid
<b>Upper/lower flammability or explosive limits</b>	: Greatest known range: Lower: 1.4% Upper: 7.6% (Solvent naphtha (petroleum), light aromatic)
<b>Flash point</b>	: Closed cup: 34°C (93.2°F)
<b>Auto-ignition temperature</b>	:

<b>Ingredient name</b>	<b>°C</b>	<b>°F</b>	<b>Method</b>
2-methoxy-1-methylethyl acetate	333	631.4	DIN 51794

<b>Code</b> : 00316061	<b>Date of issue/Date of revision</b> : 27 October 2023
<b>SIGMACOVER 256S BASE 5177</b>	

**SECTION 9: Physical and chemical properties**

Decomposition temperature :

pH : Not applicable.  
Not applicable. insoluble in water.

Viscosity : Kinematic (40°C): >21 mm²/s

Solubility(ies) :

Media	Result
cold water	Not soluble

Miscible with water : No.

Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
ethylbenzene	9.3	1.2				

Relative density : 1.4

Vapour density : Highest known value: 4.6 (Air = 1) (2-methoxy-1-methylethyl acetate). Weighted average: 3.9 (Air = 1)

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

Particle characteristics

Median particle size : Not applicable.

**SECTION 10: Stability and reactivity**

<b>10.1 Reactivity</b>	:	No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	:	The product is stable.
<b>10.3 Possibility of hazardous reactions</b>	:	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	:	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
<b>10.5 Incompatible materials</b>	:	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
<b>10.6 Hazardous decomposition products</b>	:	Depending on conditions, decomposition products may include the following materials: carbon oxides sulfur oxides phosphorus oxides halogenated compounds metal oxide/oxides

**SECTION 11: Toxicological information**

<b>11.1 Information on toxicological effects</b>	
<b>Acute toxicity</b>	

Code : 00316061

Date of issue/Date of revision

: 27 October 2023

SIGMACOVER 256S BASE 5177

**SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
Hydrocarbons, C9, aromatics > 0.1% cumene	LD50 Dermal	Rabbit	>3160 mg/kg	-
trizinc bis(orthophosphate)	LD50 Oral	Rat - Female	3492 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
xylene	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
epoxy resin (MW ≤ 700)	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	>2 g/kg	-
2-methoxy-1-methylethyl acetate	LC50 Inhalation Vapour	Rat	30 mg/l	4 hours
	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	6190 mg/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	LC50 Inhalation Dusts and mists	Rat	5.05 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.**Acute toxicity estimates**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMACOVER 256S BASE 5177	N/A	21522.6	N/A	125.6	N/A
Hydrocarbons, C9, aromatics > 0.1% cumene	3492	N/A	N/A	N/A	N/A
xylene	4300	1700	N/A	11	N/A
2-methoxy-1-methylethyl acetate	6190	N/A	N/A	30	N/A
ethylbenzene	3500	17800	N/A	17.8	N/A
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	N/A	N/A	N/A	N/A	5.05

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
epoxy resin (MW ≤ 700)	Eyes - Mild irritant	Rabbit	-	-	-
	Skin - Mild irritant	Rabbit	-	-	-

**Conclusion/Summary** : Not available.**Skin** : There are no data available on the mixture itself.**Eyes** : There are no data available on the mixture itself.**Respiratory** : There are no data available on the mixture itself.**Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
epoxy resin (MW ≤ 700)	skin	Mouse	Sensitising
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	skin	Guinea pig	Sensitising

**Conclusion/Summary****Skin** : There are no data available on the mixture itself.

<b>Code</b> : 00316061	<b>Date of issue/Date of revision</b> : 27 October 2023
<b>SIGMACOVER 256S BASE 5177</b>	

**SECTION 11: Toxicological information**

**Respiratory** : There are no data available on the mixture itself.

**Mutagenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Carcinogenicity**

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

**Conclusion/Summary** : There are no data available on the mixture itself.

**Reproductive toxicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Teratogenicity**

**Conclusion/Summary** :  
There are no data available on the mixture itself.

**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9, aromatics > 0.1% cumene	Category 3	-	Respiratory tract irritation
xylene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
2-methoxy-1-methylethyl acetate	Category 3	-	Narcotic effects

**Specific target organ toxicity (repeated exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
crystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-
ethylbenzene	Category 2	-	hearing organs

**Aspiration hazard**

Product/ingredient name	Result
Hydrocarbons, C9, aromatics > 0.1% cumene	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** : Not available.

**Potential acute health effects**

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : No specific data.

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

**Ingestion** : No specific data.

Code : 00316061

Date of issue/Date of revision

: 27 October 2023

SIGMACOVER 256S BASE 5177

**SECTION 11: Toxicological information****Delayed and immediate effects as well as chronic effects from short and long-term exposure****Short term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**Long term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**Potential chronic health effects**

Not available.

**Conclusion/Summary** : Not available.**General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.**Carcinogenicity** : ☒ May cause cancer. Risk of cancer depends on duration and level of exposure.**Mutagenicity** : No known significant effects or critical hazards.**Reproductive toxicity** : No known significant effects or critical hazards.**Other information** : Not available.**SECTION 12: Ecological information****12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
<input checked="" type="checkbox"/> Hydrocarbons, C9, aromatics > 0.1% cumene	EC50 3.2 mg/l	Daphnia	48 hours
trizinc bis(orthophosphate)	LC50 9.2 mg/l	Fish	96 hours
epoxy resin (MW ≤ 700)	Acute LC50 0.112 mg/l	Fish	96 hours
	Chronic NOEC 0.026 mg/l	Fish	30 days
2-methoxy-1-methylethyl acetate	Acute LC50 1.8 mg/l	Daphnia	48 hours
ethylbenzene	Chronic NOEC 0.3 mg/l	Daphnia	21 days
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	Acute LC50 134 mg/l Fresh water	Fish - Trout - <i>Oncorhynchus mykiss</i>	96 hours
	Acute EC50 1.8 mg/l Fresh water	Daphnia	48 hours
	Chronic NOEC 1 mg/l Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	-
	Acute EC50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours
	Acute EC50 >10 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 >10 mg/l	Fish - <i>Oncorhynchus mykiss</i>	96 hours

**Conclusion/Summary** : Not available.**12.2 Persistence and degradability**

**Code** : 00316061**Date of issue/Date of revision**

: 27 October 2023

**SIGMACOVER 256S BASE 5177****SECTION 12: Ecological information**

Product/ingredient name	Test	Result	Dose	Inoculum
Hydrocarbons, C9, aromatics > 0.1% cumene	-	75 % - Readily - 28 days	-	-
epoxy resin (MW ≤ 700)	OECD 301F	5 % - 28 days	-	-
2-methoxy-1-methylethyl acetate	-	83 % - Readily - 28 days	-	-
ethylbenzene	-	79 % - Readily - 10 days	-	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	301D Ready Biodegradability - Closed Bottle Test	22 % - 28 days	-	-

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9, aromatics > 0.1% cumene	-	-	Readily
xylene	-	-	Readily
epoxy resin (MW ≤ 700)	-	-	Not readily
2-methoxy-1-methylethyl acetate	-	-	Readily
ethylbenzene	-	-	Readily
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	-	-	Inherent

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
epoxy resin (MW ≤ 700)	3	31	Low
2-methoxy-1-methylethyl acetate	1.2	-	Low
ethylbenzene	3.6	79.43	Low
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	>5.86	-	High

**12.4 Mobility in soil****Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.**Mobility** : Not available.**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**Code** : 00316061**Date of issue/Date of revision**

: 27 October 2023

**SIGMACOVER 256S BASE 5177****SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**Waste catalogue**

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue
Container	15 01 06 mixed packaging

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number</b>	UN1263	UN1263	UN1263	UN1263
<b>14.2 UN proper shipping name</b>	PAINT	PAINT	PAINT	PAINT
<b>14.3 Transport hazard class(es)</b>	3	3	3	3
<b>14.4 Packing group</b>	III	III	III	III
<b>14.5 Environmental hazards</b>	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
<b>Marine pollutant substances</b>	Not applicable.	Not applicable.	(trizinc bis (orthophosphate), Solvent naphtha (petroleum), light aromatic)	Not applicable.

**Additional information**

**ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**Tunnel code** : (D/E)

<b>Code</b> : 00316061	<b>Date of issue/Date of revision</b> : 27 October 2023
<b>SIGMACOVER 256S BASE 5177</b>	

**SECTION 14: Transport information**

<b>ADN</b>	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
<b>IMDG</b>	: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
<b>IATA</b>	: The environmentally hazardous substance mark may appear if required by other transportation regulations.

<b>14.6 Special precautions for user</b>	: <b>Transport within user’s premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
--	---

<b>14.7 Transport in bulk according to IMO instruments</b>	: Not available.
--	------------------

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**UK (GB)/REACH**

Annex XIV - List of substances subject to authorisation

Annex XIV


None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	:  Restricted to professional users.
---	---

Seveso Directive

This product is controlled under the Seveso Directive.


Danger criteria

<b>Category</b>
P5c E2

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
Quartz (SiO2)	UK Occupational Exposure Limits EH40 - WEL	silica, respirable crystalline respirable fraction	Carc.	-

**SECTION 16: Other information**

 Indicates information that has changed from previously issued version.

<b>Abbreviations and acronyms</b>	: ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available
-----------------------------------	--

**Code** : 00316061 **Date of issue/Date of revision** : 27 October 2023  
**SIGMACOVER 256S BASE 5177**

## SECTION 16: Other information

PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification

Classification	Justification
Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Carc. 1B, H350 STOT RE 1, H372 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method

### Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### Full text of classifications

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 1B	CARCINOGENICITY - Category 1B
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

### History

**Date of issue/ Date of revision** : 27 October 2023

**Date of previous issue** : 9 November 2022

**Prepared by** : EHS

**Version** : 1.01

### Disclaimer

<b>Code</b>	<b>: 00316061</b>	<b>Date of issue/Date of revision</b>	<b>: 27 October 2023</b>
<b>SIGMACOVER 256S BASE 5177</b>			

**SECTION 16: Other information**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*