# **SAFETY DATA SHEET**



Date of issue 10/30/2023 (month/day/year)

Version 18

# Section 1. Chemical product and company identification

A. Product name : PSX 700 BASE SPECIAL COLOR

Product code : 00295059

B. Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against

: Product is not intended, labelled or packaged for consumer use.

C. Supplier's or Importer's

information

**Email Address** 

: PPG SSC

(680-090)

19, Yeocheon-ro 217beon-gil, Nam-gu,

Ulsan, Korea

Tel: +82-52-210-8222 Korea.MSDS@PPG.COM

**Emergency telephone** 

number:

: +82-52-210-8222

# Section 2. Hazards identification

A. Hazard classification : FLAMMABLE LIQUIDS - Category 4

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

AQUATIC HAZARD (LONG-TERM) - Category 3

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol :





Signal word : Danger

**Hazard statements**: H227 - Combustible liquid.

H317 - May cause an allergic skin reaction.

H350 - May cause cancer.

H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

Korea (GHS) Page: 1/13

**Product name PSX 700 BASE SPECIAL COLOR** 

### Section 2. Hazards identification

**Prevention**: P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P273 - Avoid release to the environment.

P261 - Avoid breathing vapor.

**Response** : P308 + P313 - IF exposed or concerned: Get medical advice or attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

Storage : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

C. Other hazards which do

not result in classification

: None known.

# Section 3. Composition/information on ingredients

#### **CAS** number/other identifiers

**CAS number** : Not applicable.

Chemical name	Common name	Identifiers	%
	cyclohexanol, 4,4'-(1-methylethylidene)	CAS: 30583-72-3	30 -
oligomeric reaction products with	bis-, polymer with (chloromethyl)oxirane		<40
1-chloro-2,3-epoxypropane			
titanium dioxide	TITANIUM DIOXIDE	CAS: 13463-67-7	1 - <5
bis(1,2,2,6,6-pentamethyl-4-piperidyl)	BIS(PENTAMETHYLPIPERIDYL)	CAS: 41556-26-7	1 - <5
sebacate	SEBACATE		
iron hydroxide oxide yellow	IRON HYDROXIDE OXIDE	CAS: 51274-00-1	1 - <5
nonylphenol ethoxylates	POLYOXYETHYLENE NONYLPHENYL	CAS: 68412-53-3	1 - <5
	ETHER PHOSPHATE		
methyl 1,2,2,6,6-pentamethyl-4-piperidyl	METHYL-(1,2,2,6,6-PENTAMETHYL-	CAS: 82919-37-7	0.1 - <1
sebacate	4-PIPERDIYL) SEBACATE		
crystalline silica, respirable powder (<10		CAS: 14808-60-7	0.1 - <1
microns)	,		
methyl alcohol	METHYL ALCOHOL	CAS: 67-56-1	0.1 - <1
octamethylcyclotetrasiloxane	OCTAMETHYLCYCLOTETRASILOXANE	CAS: 556-67-2	<0.1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Korea (GHS) Page: 2/13

**Product name PSX 700 BASE SPECIAL COLOR** 

### Section 4. First aid measures

A. Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**B.** Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

C. Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

: If swallowed, seek medical advice immediately and show this container or label. **D.** Ingestion

Keep person warm and at rest. Do NOT induce vomiting.

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. E. Notes to physician

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### A. Extinguishing media

Suitable extinguishing

media

**Unsuitable** extinguishing media : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

: Do not use water jet.

B. Specific hazards arising

from the chemical

: Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and

prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products Decomposition products may include the following materials:

carbon oxides nitrogen oxides

mode.

halogenated compounds metal oxide/oxides

C. Special equipment for fire-fighting

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Fire-fighting procedures :

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

> Korea (GHS) Page: 3/13

Date of issue 10/30/2023 (month/day/year)

Product code 00295059

**Product name PSX 700 BASE SPECIAL COLOR** 

Version 18

### Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures
- : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- B. Environmental precautions
- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- C. Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

- A. Precautions for safe handling
- Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.
- B. Conditions for safe storage, including any incompatibilities
- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Korea (GHS) Page: 4/13

**Product name PSX 700 BASE SPECIAL COLOR** 

### Section 8. Exposure controls/personal protection

#### A. Occupational exposure limits

Ingredient name	Exposure limits
iffanium dioxide	Ministry of Employment and Labor (Republic of Korea, 1/2020).  TWA: 10 mg/m³ 8 hours. Form: total dust with less than 1% of free SiO2
iron hydroxide oxide yellow	Ministry of Employment and Labor (Republic of Korea, 1/2020). [Iron oxide (Fume, as Fe)] TWA: 5 mg/m³, (as Fe) 8 hours. Form:
	Fume Ministry of Employment and Labor (Republic of Korea, 1/2020). [Iron oxide as Fe] TWA: 5 mg/m³, (as Fe) 8 hours.
crystalline silica, respirable powder (<10 microns)	Ministry of Employment and Labor (Republic of Korea, 1/2020).  TWA: 0.05 mg/m³ 8 hours. Form: Respirable fraction
methyl alcohol	Ministry of Employment and Labor (Republic of Korea, 1/2020). Absorbed through skin. STEL: 250 ppm 15 minutes. TWA: 200 ppm 8 hours.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

# B. Appropriate engineering : controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Environmental** exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### C. Personal protective equipment

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

**Eye protection** 

: Chemical splash goggles.

Korea (GHS) Page: 5/13

**Product name PSX 700 BASE SPECIAL COLOR** 

### Section 8. Exposure controls/personal protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** 

butyl rubber

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

A. Appearance

**Physical state** : Liquid. : Various Color B. Odor : Aromatic. C. Odor threshold : Not available. D. pH : Not applicable. E. Melting/freezing point : Not available. F. Boiling point/boiling : >37.78°C (>100°F)

range

: Closed cup: 70°C (158°F) G. Flash point

H. Evaporation rate : Not available. Flammability (solid, gas) : Not available. J. Lower and upper : Not available.

explosive (flammable) limits

K. Vapor pressure : Not available.

Media **Result** 

L. Solubility(ies) cold water Not soluble

Solubility in water : Not available. Vapor density : Not available.

**Relative density** : 1.31

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition** i

temperature

Korea (GHS) Page: 6/13

**Product name PSX 700 BASE SPECIAL COLOR** 

### Section 9. Physical and chemical properties

S.

Ingredient name	°C	°F	Method
v(2,3-dihydro-2-oxo-1H-benzimidazol-5-yl)-3-oxo-2-[[2-(trifluoromethyl)phenyl]azo]butyramide	290	554	

**Decomposition** temperature

: Not available.

**Viscosity** : Kinematic (40°C (104°F)): >21 mm<sup>2</sup>/s (>21 cSt)

Flow time (ISO 2431) : Not available. Molecular weight : Not applicable.

### Section 10. Stability and reactivity

A. Chemical stability : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

B. Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

C. Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Depending on conditions, decomposition products may include the following D. Hazardous materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/ decomposition products

oxides

## **Section 11. Toxicological information**

A. Information on the likely : Not available. routes of exposure

#### Potential acute health effects

Inhalation No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

: May cause an allergic skin reaction. Skin contact

: No known significant effects or critical hazards. Eye contact

### Over-exposure signs/symptoms

Inhalation : No specific data. Ingestion : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

**Eye contact** : No specific data.

B. Health hazards **Acute toxicity** 

> Korea (GHS) Page: 7/13

**Product name PSX 700 BASE SPECIAL COLOR** 

### **Section 11. Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	LD50 Oral	Rat	3.125 g/kg	-
iron hydroxide oxide yellow	LC50 Inhalation Dusts and mists	Rat	>5.05 mg/l	4 hours
	LD50 Oral	Rat	>10 g/kg	-
methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	LD50 Oral	Rat	3.125 g/kg	-
methyl alcohol	LC50 Inhalation Vapor	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	-
	LD50 Oral	Rat	5600 mg/kg	-
octamethylcyclotetrasiloxane	LC50 Inhalation Vapor	Rat	36 g/m³	4 hours
	LD50 Dermal	Rat	>2375 mg/kg	-
	LD50 Oral	Rat	>4800 mg/kg	-

**Conclusion/Summary**: There are no data available on the mixture itself.

### **Irritation/Corrosion**

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Name	Classification	Route of exposure	Target organs
methyl alcohol	Category 1	-	-

#### Specific target organ toxicity (repeated exposure)

	Korea (GHS)	Page: 8/13
--	-------------	------------

**Product name PSX 700 BASE SPECIAL COLOR** 

### **Section 11. Toxicological information**

Not available.

#### **Aspiration hazard**

Not available.

#### Potential chronic health effects

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

**Carcinogenicity**: May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity: No known significant effects or critical hazards.Reproductive toxicity: No known significant effects or critical hazards.

#### **Additional information**

Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness.

Chemical name	Identifiers	GHS Classification
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	CAS: 30583-72-3	SKIN SENSITIZATION - Category 1B
		AQUATIC HAZARD (LONG-TERM) - Category 3
titanium dioxide	CAS: 13463-67-7	CARCINOGENICITY - Category 2
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	CAS: 41556-26-7	SKIN SENSITIZATION - Category 1B
		TOXIC TO REPRODUCTION - Category 2
		AQUATIC HAZARD (ACUTE) - Category 1
land to the set to set to set the set	040 54074 00 4	AQUATIC HAZARD (LONG-TERM) - Category 1
iron hydroxide oxide yellow	CAS: 51274-00-1 CAS: 68412-53-3	Not classified.
nonylphenol ethoxylates	CAS. 66412-33-3	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4
methyl 1,2,2,6,6-pentamethyl-4-piperidyl	CAS: 82919-37-7	SKIN SENSITIZATION - Category 1B
sebacate		TOXIC TO REPRODUCTION - Category 2
		AQUATIC HAZARD (ACUTE) - Category 1
		AQUATIC HAZARD (LONG-TERM) - Category 1
crystalline silica, respirable powder (<10 microns)	CAS: 14808-60-7	CARCINOGENICITY - Category 1A
methyl alcohol	CAS: 67-56-1	FLAMMABLE LIQUIDS - Category 2
		ACUTE TOXICITY (oral) - Category 3
		ACUTE TOXICITY (dermal) - Category 3
		ACUTE TOXICITY (inhalation) - Category 3
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
		AQUATIC HAZARD (LONG-TERM) - Category 3
octamethylcyclotetrasiloxane	CAS: 556-67-2	FLAMMABLE LIQUIDS - Category 3
		TOXIC TO REPRODUCTION - Category 2
		AQUATIC HAZARD (LONG-TERM) - Category 1

Korea (GHS) Page: 9/13

Product code 00295059 Date of issue 10/30/2023 (month/day/year) Version 18
Product name PSX 700 BASE SPECIAL COLOR

# **Section 12. Ecological information**

#### A. **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours
titanium dioxide iron hydroxide oxide yellow methyl alcohol	Acute LC50 >100 mg/l Fresh water Acute LC50 >100000 mg/l Acute LC50 13 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> Fish Fish	48 hours 96 hours 96 hours

#### B. Persistence and degradability

Not available.

#### C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
methyl alcohol	-0.77	-	Low
octamethylcyclotetrasiloxane	6.488	-	High

#### D. Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

#### E. Other adverse effects : N

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

#### A. Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

#### **B.** Disposal precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Korea (GHS) Page: 10/13

**Product name PSX 700 BASE SPECIAL COLOR** 

### **Section 14. Transport information**

	UN	IMDG	IATA
A. UN number	Not regulated.	Not regulated.	Not regulated.
B. UN proper shipping name	-	-	-
C. Transport hazard class(es)	-	-	-
D. Packing group	-	-	-
Environmental hazards	No.	No.	No.
E. Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

UN : None identified. **IMDG** : None identified. **IATA** : None identified.

#### F. Special precaution which a user to be aware of or needs to comply with in connection with transport or tranportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not applicable. to IMO instruments

**Section 15. Regulatory information** 

#### A. Regulation according to ISHA

**ISHA** article 117 (Harmful substances prohibited from manufacture)

: None of the components are listed.

**ISHA** article 118 : None of the components are listed.

(Harmful substances requiring permission)

**Article 2 of Youth Protection** 

**Act on Substances Hazardous** to Youth

: It is not allowed to sell to persons under the age of 19.

#### **Exposure Limits of Chemical Substances and Physical Factors**

The following components have an OEL:

titanium dioxide

iron hydroxide oxide yellow

crystalline silica, respirable powder (<10 microns)

methyl alcohol

Korea (GHS) Page: 11/13

**Product name PSX 700 BASE SPECIAL COLOR** 

### Section 15. Regulatory information

ISHA Enforcement Regs : The following components are listed: methanol

**Annex 19 (Exposure** standards established for harmful factors)

**ISHA Enforcement Regs** 

Annex 21 (Harmful factors subject to Work

**Environment** Measurement)

**Annex 22 (Harmful Factors Subject to Special Health Check**up)

Standard of Industrial **Safety and Health Annex 12 (Hazardous** substances subject to

control)

: The following components are listed: titanium dioxide, iron oxide

ISHA Enforcement Regs : The following components are listed: Iron oxide (dust, fume)

: The following components are listed: titanium dioxide, iron and its compounds

B. Regulation according to Chemicals Control Act

Article 11 (TRI) : None of the components are listed. : None of the components are listed.

**Article 18 Prohibited (K-Reach Article 27)** 

**Article 19 Subject to** authorization (K-Reach

Article 25)

**Article 20 Restricted (K-**Reach Article 27)

**Article 20 Toxic** 

**Chemicals (K-Reach** 

Article 20)

: The following components are listed: nonylphenol ethoxylates

: The following components are listed: nonylphenol ethoxylates

: Not applicable

: All components are listed or exempted. **Korea inventory** 

**Article 39 (Accident Precaution Chemicals**)

C. <u>Dangerous Materials</u> : Class: Class 4 - Flammable Liquid

Safety Management Act Item: 5. Class 3 petroleums - Water-insoluble liquid

> Threshold: 2000 L Danger category: III

Signal word: Contact with sources of ignition prohibited

D. Wastes regulation : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

: None of the components are listed.

E. Regulation according to other foreign laws

Safety, health and environmental

regulations specific for

the product

: No known specific national and/or regional regulations applicable to this product

(including its ingredients).

Korea (GHS) Page: 12/13

**Product name PSX 700 BASE SPECIAL COLOR** 

### Section 16. Other information

A. References : Korean Ministry of Environment; Chemical Control Act

Korean Ministry of Labor; Industrial Safety and Health Act

**NIER Notice** 

Registry of Toxic Effects of Chemical Substances (RTECS)

U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information

Retrieval) ECOTOX Database System.

B. Date of issue/Date of

revision

: 10/30/2023

C. Version : 18 **Prepared by** 

: EHS

D. Other

▼ Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Korea (GHS) Page: 13/13