# **SAFETY DATA SHEET**

#### SIGMAPRIME CSF LT HARDENER



Date of issue 3 November 2023

Version 4.05

# 1. Product and company identification

Product name : SIGMAPRIME CSF LT HARDENER

Product code : 00452827 Product type : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against : Not applicable.

Supplier's details : PPG PMC Japan Co., Ltd., 8F, Shintetsu Bldg., 1-1, Daikaidori 1-chome, Kobe

652-0803 Japan; Tel: +81-78-574-2777

**Emergency telephone** 

number

: 078 574 2777

## 2. Hazards identification

GHS Classification : ACUTE TOXICITY (oral) - Category 4

ACUTE TOXICITY (dermal) - Category 4

SKIN CORROSION - Category 1
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1
TOXIC TO REPRODUCTION - Category 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2 HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category 2

HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD - Categor

Category 2

**GHS label elements** 

Hazard pictograms :









Signal word : Danger

**Hazard statements**: Harmful if swallowed or in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child. May cause damage to organs. (nervous system) Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

Japan Page: 1/13

### 2. Hazards identification

#### **Prevention**

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eve or face protection. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

#### Response

: Collect spillage. IF exposed or concerned: Call a POISON CENTER or doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

### **Storage**

: Store locked up.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

# result in classification

Other hazards which do not : Contains a substance that may emit formaldehyde if stored beyond its shelf life and/ or during cure at curing temperatures greater than 60C (140F).

# 3. Composition/information on ingredients

Substance/mixture : Mixture

### **CAS** number/other identifiers

**CAS** number : Not applicable. **CSCL** number : Not available.

| Ingredient name   | %        | CAS number   | CSCL                   |
|---|----------|--------------|------------------------|
| 2-Propenenitrile reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated | 50 - 100 | 1173092-74-4 | Not available.         |
| 2,4,6-Tris(dimethylaminomethyl)phenol   | 7 - <10  | 90-72-2      | 3-714; 3-762;<br>3-776 |
| 2,6-tert-Butyl-p-cresol   | 7 - <10  | 128-37-0     | 3-540; 9-1805          |
| Formaldehyde, oligomeric reaction products with phenol  | 3 - <5   | 9003-35-4    | 7-903                  |
| 3-(Diethylamino)propylamine   | 3 - <5   | 104-78-9     | 2-158                  |
| bis[(dimethylamino)methyl]phenol  | 1 - <2   | 71074-89-0   | 3-2868                 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Japan Page: 2/13

Date of issue 3 November 2023 Version 4.05

Product code 00452827

**Product name SIGMAPRIME CSF LT HARDENER** 

### 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes severe burns. Harmful in contact with skin. May cause damage to organs

following a single exposure in contact with skin. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed. May cause damage to organs following a single exposure if

swallowed.

#### **Over-exposure signs/symptoms**

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

### See toxicological information (Section 11)

Japan Page: 3/13

# 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon oxides

nitrogen oxides Formaldehyde.

for fire-fighters

Special protective actions : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

> Japan Page: 4/13

# 7. Handling and storage

### **Precautions for safe** handling

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# 8. Exposure controls/personal protection

**Control parameters** 

Occupational exposure limits

None.

# procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye protection **Skin protection Hand protection**

: Chemical splash goggles and face shield.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

> **Japan** Page: 5/13

Product code 00452827

Date of issue 3 November 2023 Version 4.05

**Product name SIGMAPRIME CSF LT HARDENER** 

# 8. Exposure controls/personal protection

**Gloves** 

: nitrile neoprene

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.

Odor : Characteristic.

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 157°C (314.6°F)

Relative density : 1

Solubility(ies)

 Media
 Result

 cold water
 Not soluble

# 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: When exposed to high temperatures may produce hazardous decomposition products.

**Incompatible materials** 

: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde.

Japan Page: 6/13

# 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

| Product/ingredient name   | Result      | Species | Dose        | Exposure |
|---|-------------|---------|-------------|----------|
| 2-Propenenitrile reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated | LD50 Oral   | Rat     | 500 mg/kg   | -        |
| 2,4,6-Tris<br>(dimethylaminomethyl)<br>phenol   | LD50 Dermal | Rabbit  | 1.28 g/kg   | -        |
| '   | LD50 Dermal | Rat     | 1280 mg/kg  | -        |
|   | LD50 Oral   | Rat     | 1200 mg/kg  | -        |
| 2,6-tert-Butyl-p-cresol   | LD50 Dermal | Rabbit  | >5000 mg/kg | -        |
| 3-(Diethylamino)propylamine   | LD50 Dermal | Rabbit  | 524 mg/kg   | -        |
|   | LD50 Oral   | Rat     | 830 mg/kg   | -        |

### **Irritation/Corrosion**

| Product/ingredient name               | Result                  | Species | Score | Exposure  | Observation |
|---------------------------------------|-------------------------|---------|-------|-----------|-------------|
| 2,4,6-Tris<br>(dimethylaminomethyl)   | Skin - Visible necrosis | Rabbit  | -     | 4 hours   | 7 days      |
| phenol<br>3-(Diethylamino)propylamine | Skin - Visible necrosis | Rabbit  | -     | 1 minutes | 8 days      |

### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

### **Reproductive toxicity**

Not available.

### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

| Name   | Category                 | Route of exposure | Target organs                                     |
|--|--------------------------|-------------------|---|
| <b>2</b> ,6-tert-Butyl-p-cresol Formaldehyde, oligomeric reaction products with phenol | Category 1<br>Category 3 | -                 | nervous system<br>Respiratory tract<br>irritation |

### Specific target organ toxicity (repeated exposure)

| Name                    | Category   | Route of exposure | Target organs |
|-------------------------|------------|-------------------|---------------|
| 2,6-tert-Butyl-p-cresol | Category 2 | -                 | liver, lungs  |

### **Aspiration hazard**

Not available.

Japan Page: 7/13

Date of issue 3 November 2023 Version 4.05

### Product code 00452827

**Product name SIGMAPRIME CSF LT HARDENER** 

# 11. Toxicological information

Information on the likely routes of exposure

: Not available.

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes severe burns. Harmful in contact with skin. May cause damage to organs

following a single exposure in contact with skin. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed. May cause damage to organs following a single exposure if

swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : Suspected of damaging fertility or the unborn child.

### **Numerical measures of toxicity**

**Acute toxicity estimates** 

Japan Page: 8/13

# 11. Toxicological information

| Product/ingredient name  | Oral (mg/<br>kg) | Dermal<br>(mg/kg) | Inhalation<br>(gases)<br>(ppm) | Inhalation<br>(vapors)<br>(mg/l) | Inhalation<br>(dusts<br>and mists)<br>(mg/l) |
|--|------------------|-------------------|--------------------------------|----------------------------------|--|
| SIGMAPRIME CSF LT HARDENER 2-Propenenitrile reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated | 638.1<br>500     | 1439.2<br>N/A     |                                | N/A<br>N/A                       | N/A<br>N/A                                   |
| 2,4,6-Tris(dimethylaminomethyl)phenol<br>3-(Diethylamino)propylamine   | 1200<br>830      | 1280<br>524       |                                | N/A<br>N/A                       | N/A<br>N/A                                   |

#### Other information

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C (140F). Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

# 12. Ecological information

### **Toxicity**

| Product/ingredient name                | Result  | Species         | Exposure             |
|--|---|-----------------|----------------------|
| 2,4,6-Tris (dimethylaminomethyl)phenol | Acute LC50 175 mg/l                           | Fish            | 96 hours             |
|  | Acute EC50 172 mg/l                           | Daphnia         | 48 hours             |
|  | Acute EC50 30.2 mg/l<br>Acute EC50 146.6 mg/l | Daphnia<br>Fish | 48 hours<br>96 hours |

### Persistence/degradability

| Product/ingredient name     | Test              | Result                   |            | Dose |         | Inoculum   |
|-----------------------------|-------------------|--------------------------|------------|------|---------|------------|
| 3-(Diethylamino)propylamine | OECD 301A         | 90 % - Readily - 28 days |            | -    |         | -          |
| Product/ingredient name     | Aquatic half-life |                          | Photolysis |      | Biodeg  | radability |
| 3-(Diethylamino)propylamine | -                 |                          | -          |      | Readily | 1          |

### **Bioaccumulative potential**

| Product/ingredient name                 | LogPow | BCF     | Potential |
|---|--------|---------|-----------|
| 2,4,6-Tris (dimethyl)phenol             | 0.219  | -       | Low       |
| ` , , , , , , , , , , , , , , , , , , , | 5.1    | 1071.52 | High      |

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

Japan Page: 9/13

Product code 00452827

Date of issue 3 November 2023 Version 4.05

**Product name SIGMAPRIME CSF LT HARDENER** 

# 12. Ecological information

Other adverse effects

: No known significant effects or critical hazards.

# 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# 14. Transport information

|                             | UN   | IMDG                         | IATA   |
|-----------------------------|--|------------------------------|--|
| UN number                   | UN3066   | UN3066                       | UN3066   |
| UN proper shipping name     | PAINT  | PAINT                        | PAINT  |
| Transport hazard class(es)  | 8  | 8                            | 8  |
| Packing group               | II   | II                           | II   |
| Environmental hazards       | Yes. The environmentally hazardous substance mark is not required. | Yes.                         | Yes. The environmentally hazardous substance mark is not required. |
| Marine pollutant substances | Not applicable.  | (2,6-di-tert-butyl-p-cresol) | Not applicable.  |

#### **Additional information**

UN : None identified.

**IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

: The environmentally hazardous substance mark may appear if required by other transportation IATA

regulations.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

**Japan** Page: 10/13

# 15. Regulatory information

### **Fire Service Law**

| Category    | Substance name/Type  | Danger category | Signal word                | Designated quantity |
|-------------|----------------------|-----------------|----------------------------|---------------------|
| Category IV | Class III petroleums | III             | Flammable - Keep Fire Away | 2000 L              |

### Pollutant Release and Transfer Registers (PRTR)

| Ingredient name            | %   | Status  | Reference number |
|----------------------------|-----|---------|------------------|
| 2,6-Di-tert-butyl-4-cresol | 8.8 | Class 1 | 207              |

### **Industrial Safety and Health Act**

### Ordinance on the Prevention of the Hazard due to Specified Chemical Substances

% **Status** Reference number

None of the components are listed.

### Substance(s) requiring labelling

| Ingredient name            | %   | Status | Reference number |
|----------------------------|-----|--------|------------------|
| 2,6-Di-tert-butyl-4-cresol | ≤10 | Listed | 262              |

### **Chemicals requiring notification**

| Ingredient name            | %   | Status | Reference number |
|----------------------------|-----|--------|------------------|
| 2,6-Di-tert-butyl-4-cresol | ≤10 | Listed | 262              |

### Carcinogen

None of the components are listed.

#### **Mutagen**

None of the components are listed.

**Corrosive liquid** : Not listed

**Occupational Safety and Health Law** 

: Not listed

: Not applicable.

Regulations on the **Prevention of Tetraalkyl** 

**Lead Poisoning** 

**Harmful Substances** 

**Subject to Obtaining** 

**Permission for Manufacturing** 

Harmful Substances,

**Prohibited for Manufacturing**  : Not listed

: Not listed

Lead regulation : Not listed **Organic solvents** : Not applicable.

poisoning prevention

### **Poisonous and Deleterious Substances**

Page: 11/13 **Japan** 

Product code 00452827 Date of issue 3 November 2023 Version 4.05

**Product name SIGMAPRIME CSF LT HARDENER** 

# 15. Regulatory information

None of the components are listed.

### **Chemical Substances Control Law (CSCL)**

| Ingredient name                  | %      |                     | Reference number |
|----------------------------------|--------|---------------------|------------------|
| 2,6-Di-tert-butyl-4-methylphenol | 8.8397 | Priority assessment | 64               |

**High Pressure Gas Control** : Not available.

Law

#### **Explosives Control Law**

None of the components are listed.

Law concerning prevention : Not available. of pollution of the ocean

### **Maritime Safety Law**

### Notification Regulating Transportation of Dangerous Materials by Sea

None of the components are listed.

### **Container class**

None of the components are listed.

: Not listed **JSOH Carcinogen** List of Specially Controlled : Not listed

**Industrial Waste** 

Japan inventory : At least one component is not listed.

**Road law** : Not available.

### 16. Other information

**History** 

Date of issue/Date of

revision

: 3 November 2023

Date of previous issue : 5/11/2023 **Version** : 4.05 **Prepared by** : EHS

Key to abbreviations : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

Indicates information that has changed from previously issued version.

Page: 12/13 **Japan** 

Product code 00452827 Date of issue 3 November 2023 Version 4.05

**Product name SIGMAPRIME CSF LT HARDENER** 

### 16. Other information

### **Notice to reader**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Japan Page: 13/13