SAFETY DATA SHEET



Date of issue/Date of revision3 November 2023Version 1.04

| Section 1. Identification | | |
|--|---|--|
| Product code | : 00452827 | |
| Product name | : SIGMAPRIME CSF LT HARDENER | |
| Product type | : Liquid. | |
| Relevant identified uses of | the substance or mixture and uses advised against | |
| Product use | Coating. Professional applications, Used by spraying. | |
| Supplier's details | : PPG Industries (Singapore) Pte. Ltd., No. 1 Tuas Basin Close, Singapore 638803. Tel +65 68653737 | |
| Emergency telephone number (with hours of operation) | : CHEMTREC +(65)-31581349 (CCN 17704) | |

Section 2. Hazards identification

| Classification of the | : ACUTE TOXICITY (oral) - Category 4 |
|-----------------------|---|
| substance or mixture | ACUTE TOXICITY (dermal) - Category 4 |
| | SKIN CORROSION/IRRITATION - Category 1B |
| | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| | SKIN SENSITISATION - Category 1 |
| | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 |

GHS label elements, including precautionary statements

| Hazard pictograms | | |
|--------------------------|---|--|
| Signal word | : Danger | |
| Hazard statements | Harmful if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects. | |
| Precautionary statements | | |
| Prevention | : Wear protective gloves, protective clothing and eye or face protection. Average release to the environment. Avoid breathing vapour. Wash thoroughly after handling. | |

| | Singapore | English (GB) | Page: 1/12 | |
|--|-----------|--------------|------------|--|
|--|-----------|--------------|------------|--|

Section 2. Hazards identification

| Response | : | Collect spillage. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. |
|---|---|---|
| Storage | 1 | Not applicable. |
| Disposal | : | Not applicable. |
| Other hazards which do not result in classification | : | Contains a substance that may emit formaldehyde if stored beyond its shelf life and/ or during cure at curing temperatures greater than 60C/140F. |

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

CAS number/other identifiers

| | Not applicable. Mixture. | | |
|--|-----------------------------|--------------------------------|-------------------------------------|
| Ingredient name | | % | CAS number |
| reaction products with benzaldel triethylenetetramine, hydrogenat 2,4,6-tris(dimethylaminomethyl)p 2,6-di-tert-butyl-p-cresol | ed bhenol | 50 - 100 5 - <10 5 - <10 | 1173092-74-4 90-72-2 128-37-0 |
| Formaldehyde, oligomeric reacti 3-aminopropyldiethylamine bis[(dimethylamino)methyl]phen | | 3 - <5 3 - <5 1 - <3 | 9003-35-4 104-78-9 71074-89-0 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

| Description of necessary fire | st aid measures |
|-------------------------------|--|
| Eye contact | Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention. |
| Inhalation | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| Skin contact | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. |
| Singapore English (GB) | Page: 2/12 |

Section 4. First aid measures

Ingestion

: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

| most important symptoms/e | <u>s, acute and delayed</u> | |
|-------------------------------|--|-----|
| Potential acute health effect | | |
| Eye contact | Causes serious eye damage. | |
| Inhalation | No known significant effects or critical hazards. | |
| Skin contact | Causes severe burns. Harmful in contact with skin. May cause an allergic sk reaction. | in |
| Ingestion | Harmful if swallowed. | |
| Over-exposure signs/symp | <u>></u> | |
| Eye contact | Adverse symptoms may include the following: pain watering redness | |
| Inhalation | No specific data. | |
| Skin contact | Adverse symptoms may include the following: pain or irritation redness blistering may occur | |
| Ingestion | Adverse symptoms may include the following: stomach pains | |
| Indication of immediate med | attention and special treatment needed, if necessary | |
| Notes to physician | In case of inhalation of decomposition products in a fire, symptoms may be de The exposed person may need to be kept under medical surveillance for 48 h | |
| Specific treatments | No specific treatment. | |
| Protection of first-aiders | No action shall be taken involving any personal risk or without suitable training is suspected that fumes are still present, the rescuer should wear an appropri mask or self-contained breathing apparatus. It may be dangerous to the pers providing aid to give mouth-to-mouth resuscitation. Wash contaminated cloth thoroughly with water before removing it, or wear gloves. | ate |

See toxicological information (Section 11)

Section 5. Firefighting measures

| Extinguishing media | | |
|--------------------------------|---|--|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. | |
| Unsuitable extinguishing media | : None known. | |

Section 5. Firefighting measures

| Specific hazards arising from the chemical | In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
|---|--|
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

| Personal precautions, protec | tive equipment and emergency procedures |
|--------------------------------|--|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| Environmental precautions | : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage. |
| Methods and material for con | tainment and cleaning up |
| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

| Precautions | for safe | handling |
|--------------------|----------|----------|
| roodationo | | Harrand |

| Protective measures | : | Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|---|---|
| Advice on general occupational hygiene | : | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | : | Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | | | Exposure limits | |
|-----------------------------------|---|---|---|--|
| 2,6-di-tert-butyl-p-cresol | | | Workplace Safety and Health Act (Singapore, 2/2006). PEL (long term): 10 mg/m ³ 8 hours. | |
| Recommended monitoring procedures | : | Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required. | | |
| Appropriate engineering controls | : | If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. | | |
| Environmental exposure controls | : | | | |

Individual protection measures

| Singapore English (GB) | Page: 5/12 |
|------------------------|------------|
|------------------------|------------|

Section 8. Exposure controls/personal protection

| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
|--|---|
| Eye/face protection Skin protection | : Chemical splash goggles and face shield. |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Gloves | : nitrile neoprene |
| Body protection | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. |

Section 9. Physical and chemical properties

| <u>Appearance</u> | |
|---------------------------|--|
| Physical state | : Liquid. |
| Odour | : Characteristic. |
| рН | insoluble in water. |
| Boiling point | : >37.78°C (>100°F) |
| Flash point | : Closed cup: 157°C (314.6°F) |
| Evaporation rate | : Not available. |
| Flammability (solid, gas) | : liquid |
| Vapour pressure | Highest known value: 0.2 kPa (1.5 mm Hg) (at 20°C) (3-aminopropyldiethylamine). Weighted average: 0.01 kPa (0.08 mm Hg) (at 20°C) |
| Vapour density | : Highest known value: 4.48 (Air = 1) (3-aminopropyldiethylamine). |
| Relative density | : 1 |

Section 9. Physical and chemical properties

| Solubility(ies) | Media | Result |
|-----------------------------|---------------------------|--|
| | cold water | Not soluble |
| Auto-ignition temperature : | Lowest known value: 382° | C (719.6°F) (2,4,6-tris(dimethylaminomethyl)phenol). |
| Viscosity : | Kinematic (40°C (104°F)): | >21 mm²/s (>21 cSt) |

Section 10. Stability and reactivity

| | , | |
|------------------------------------|--|-------|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredie | ents. |
| Chemical stability | : The product is stable. | |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occu | ır. |
| Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition products. | |
| Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions oxidising agents, strong alkalis, strong acids. | : |
| Hazardous decomposition products | : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. | |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|-------------|---------|-------------|----------|
| 2-Propenenitrile reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated | LD50 Oral | Rat | 500 mg/kg | - |
| 2,4,6-tris (dimethylaminomethyl) phenol | LD50 Dermal | Rabbit | 1.28 g/kg | - |
| • | LD50 Dermal | Rat | 1280 mg/kg | - |
| | LD50 Oral | Rat | 1200 mg/kg | - |
| 2,6-di-tert-butyl-p-cresol | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| 3-aminopropyldiethylamine | LD50 Dermal | Rabbit | 524 mg/kg | - |
| | LD50 Oral | Rat | 830 mg/kg | - |

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Section 11. Toxicological information

| | | <u> </u> | | | | |
|---|--------|-----------------------------|----------------|------------|-----------|-------------|
| Product/ingredient nam | ne | Result | Species | Score | Exposure | Observation |
| 2,4,6-tris (dimethylaminomethyl) phenol | | Skin - Visible necrosis | Rabbit | - | 4 hours | 7 days |
| 3-aminopropyldiethylami | ne | Skin - Visible necrosis | Rabbit | - | 1 minutes | 8 days |
| Conclusion/Summary | | | | | | |
| Skin | : 1 | There are no data available | on the mixtur | e itself. | | |
| Eyes | : | There are no data available | on the mixtur | e itself. | | |
| Respiratory | : | There are no data available | on the mixtur | e itself. | | |
| Sensitisation | | | | | | |
| Conclusion/Summary | | | | | | |
| Skin | : | There are no data available | on the mixtur | e itself. | | |
| Respiratory | : 1 | There are no data available | on the mixtur | e itself. | | |
| Mutagenicity | | | | | | |
| Conclusion/Summary | : | There are no data available | e on the mixtu | re itself. | | |
| Carcinogenicity | | | | | | |
| Conclusion/Summary | : | There are no data available | e on the mixtu | re itself. | | |
| Reproductive toxicity | | | | | | |
| Conclusion/Summary | : | There are no data available | e on the mixtu | re itself. | | |
| Teratogenicity | | | | | | |
| Conclusion/Summary | : | There are no data available | e on the mixtu | re itself. | | |
| Specific target organ to: | xicity | <u>/ (single exposure)</u> | | | | |

| Name | | Route of exposure | Target organs |
|--|------------|-------------------|---------------------------------|
| Formaldehyde, oligomeric reaction products with phenol | Category 3 | | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

| Name | | Route of exposure | Target organs |
|----------------------------|------------|-------------------|---------------|
| 2,6-di-tert-butyl-p-cresol | Category 2 | - | - |

Aspiration hazard

Not available.

| Information on likely routes of exposure | : Not available. |
|--|---|
| Potential acute health effects | |
| Eye contact | : Causes serious eye damage. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction. |

| • | | |
|-----------|--------------|------------|
| Singapore | English (GB) | Page: 8/12 |
| · · · | • • • | - |

Section 11. Toxicological information

Ingestion

: Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

| Eye contact | : Adverse symptoms may include the following: pain watering redness |
|--------------|--|
| Inhalation | : No specific data. |
| Skin contact | : Adverse symptoms may include the following: pain or irritation redness blistering may occur |
| Ingestion | : Adverse symptoms may include the following: stomach pains |

Delayed and immediate effects as well as chronic effects from short and long-term exposure Short term exposure **Potential immediate** : Not available. effects : Not available. Potential delayed effects Long term exposure **Potential immediate** : Not available. effects Potential delayed effects : Not available. Potential chronic health effects

: Once sensitized, a severe allergic reaction may occur when subsequently exposed General to very low levels. Carcinogenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Mutagenicity** : No known significant effects or critical hazards. **Reproductive toxicity**

Numerical measures of toxicity

÷.

Acute toxicity estimates

| Route | ATE value |
|--------|---------------|
| Oral | 638.15 mg/kg |
| Dermal | 1439.15 mg/kg |

Other information

Section 11. Toxicological information

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F. Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

Section 12. Ecological information

| т | OX | C | itv | |
|---|----|---|------|--|
| ÷ | UA | | L, Y | |

| Product/ingredient name | Result | Species | Exposure |
|---|---|-----------------|----------------------|
| 2,4,6-tris (dimethylaminomethyl)phenol | Acute LC50 175 mg/l | Fish | 96 hours |
| | Acute EC50 172 mg/l | Daphnia | 48 hours |
| | Acute EC50 30.2 mg/l Acute EC50 146.6 mg/l | Daphnia Fish | 48 hours 96 hours |

Persistence/degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|---------------------------|-------------------|-----------------------------|-------------|------------------|
| 3-aminopropyldiethylamine | OECD 301A | 90 % - Readily - 28 days | - | - |
| Conclusion/Summary | : There are no | data available on the mixtu | ire itself. | |
| Product/ingredient name | Aquatic half-life | Pho | tolysis | Biodegradability |
| 3-aminopropyldiethylamine | - | | | Readily |

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|---|--------|---------|-----------|
| 2,4,6-tris (dimethylaminomethyl)phenol | 0.219 | - | Low |
| | 5.1 | 1071.52 | High |

| <u>Mobility in soil</u> | |
|--|------------------|
| Soil/water partition coefficient (Koc) | : Not available. |

Other adverse effects : No known significant effects or critical hazards.

| | Singapore | English | (GB) |
|--|-----------|---------|------|
|--|-----------|---------|------|

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | | INDO | 1474 |
|-------------------------------|--|------------------------------|--|
| | UN | IMDG | IATA |
| UN number | UN3066 | UN3066 | UN3066 |
| UN proper shipping name | PAINT | PAINT | PAINT |
| Transport hazard class(es) | 8 | 8 | 8 |
| Packing group | I | = | I |
| Environmental hazards | Yes. The environmentally hazardous substance mark is not required. | Yes. | Yes. The environmentally hazardous substance mark is not required. |
| Marine pollutant substances | Not applicable. | (2,6-di-tert-butyl-p-cresol) | Not applicable. |

Additional information

| UN | : None identified. |
|------|--|
| IMDG | : The marine pollutant mark is not required when transported in sizes of \leq 5 L or \leq 5 kg. |
| IATA | : The environmentally hazardous substance mark may appear if required by other transportation regulations. |

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

| Singapore | English (GB) |
|-----------|--------------|
|-----------|--------------|

Section 15. Regulatory information

Singapore - hazardous chemicals under government control

None.

International regulations Montreal Protocol Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

| <u>History</u> | |
|--------------------------------|--|
| Date of issue/Date of revision | : 3 November 2023 |
| Date of previous issue | : 4/12/2023 |
| Version | : 1.04 |
| Prepared by | : EHS |
| Key to abbreviations | ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations |

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.