SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to GHS UN rev. 7

Date of issue/Date of revision 15 November 2023

Version 3

Section 1. Identification

Product code : 00359402

Product name : STEELGUARD 651 WHITE

Product type : Liquid.

Other means of identification

Not available.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Coating

Professional applications, Used by spraying, Application by non spray methods..

Uses advised against : Product is not intended, labelled or packaged for consumer use.

Supplier's information : PPG Asian Paints Private Limited

6A Shanti Nagar Santa Cruz (East) Mumbai - 400055

India

Emergency telephone

number:

: +91 22 6815 8700

Section 2. Hazards identification

Classification of the substance or mixture

: KARCINOGENICITY - Category 2

REPRODUCTIVE TOXICITY - Category 2

SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 19.1%

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : Suspected of causing cancer.

Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention: Do not handle until all safety precautions

have been read and understood. Wear protective gloves, protective clothing and

eve or face protection. Avoid release to the environment.

Response : F exposed or concerned: Get medical advice or attention.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

India Page: 1/11

Product name STEELGUARD 651 WHITE

Section 2. Hazards identification

Other hazards which do not : Contains isothiazolinones. May cause allergic reaction.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

CAS number : Not applicable.

| Ingredient name | % | CAS number |
|---|-------------|------------|
| Polyphosphoric acids, ammonium salts | 25 - <50 | 68333-79-9 |
| melamine | 5 - <10 | 108-78-1 |
| isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol | 1 - <3 | 25265-77-4 |
| 9(or 10)-sulphooctadecanoic acid, potassium salt | 0.1 - < 0.3 | 67968-63-2 |
| octhilinone (ISO) | <0.1 | 26530-20-1 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation: Remove to fresh air. Keep person warm and at rest. If not breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

India Page: 2/11

Product name STEELGUARD 651 WHITE

Section 4. First aid measures

Ingestion

: Adverse symptoms may include the following: reduced foetal weight

increase in foetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments
Protection of first-aiders

: No specific treatment.

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon oxides

nitrogen oxides phosphorus oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

India Page: 3/11

Product name STEELGUARD 651 WHITE

Section 6. Accidental release measures

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Evit on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 10 to 30°C (50 to 86°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Vuser operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

India Page: 4/11

Product name STEELGUARD 651 WHITE

Section 8. Exposure controls/personal protection

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves

: For prolonged or repeated handling, use the following type of gloves:

Recommended: Viton®

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid. Colour : White.

Odour : Not available.

Odour threshold : Not available.

Melting point/freezing point : Not available.

Boiling point, initial boiling : >37.78°C (>100°F)

point, and boiling range

: Not available.

Flammability
Lower and upper explosive

(flammable) limits

: Not available.

India Page: 5/11

Product name STEELGUARD 651 WHITE

Section 9. Physical and chemical properties

Flash point

: Closed cup: Not applicable.

Auto-ignition temperature

Ingredient name °C °F Method sobutyric acid, monoester with 393 739.4 2,2,4-trimethylpentane-1,3-diol

Decomposition temperature

pН

: Not available. Not available.

Viscosity

Kinematic (40°C): >21 mm²/s

Viscosity

: > 100 s (ISO 6mm)

Solubility(ies)

Media Result cold water Soluble

Partition coefficient: noctanol/water

Vapour pressure

: Not applicable.

| | Vapour Pressure at 20°C | | | Vapour pressure at 50°C | | re at 50°C |
|-----------------|-------------------------|-----|--------|-------------------------|-----|------------|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method |
| water | 17.5 | 2.3 | | | | |

Relative density

Relative vapour density

Particle characteristics

: Not available.

: 1.41

Median particle size

: Not applicable. : Not available. **Evaporation rate**

Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: When exposed to high temperatures may produce hazardous decomposition products.

Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Hazardous decomposition products

Hazardous polymerisation

: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides phosphorus oxides metal oxide/oxides

: Under normal conditions of storage and use, hazardous polymerisation will not occur.

> India Page: 6/11

Product name STEELGUARD 651 WHITE

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|---------------------------------|---------------|-------------------------|----------|
| olyphosphoric acids, ammonium salts | LD50 Oral | Rat | 4.74 g/kg | - |
| melamine | LC50 Inhalation Dusts and mists | Rat | >5190 mg/m ³ | 4 hours |
| | LD50 Oral | Rat | 3161 mg/kg | - |
| isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol | LD50 Dermal | Rabbit | >15.2 g/kg | - |
| , | LD50 Oral | Rat | 6.5 g/kg | - |
| octhilinone (ISO) | LC50 Inhalation Dusts and mists | Rat | 0.27 mg/l | 4 hours |
| , , | LD50 Dermal LD50 Oral | Rabbit Rat | 311 mg/kg 125 mg/kg | - |

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

Sensitisation

| 3 | Route of exposure | Species | Result |
|-------------------|-------------------|---------|-------------|
| octhilinone (ISO) | skin | Mouse | Sensitising |

Conclusion/Summary

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|----------|------------|-------------------|----------------|
| melamine | Category 2 | - | urinary system |

Aspiration hazard

Not available.

| India | Page: 7/11 |
|-------|------------|
|-------|------------|

Product name STEELGUARD 651 WHITE

Section 11. Toxicological information

Information on likely routes

of exposure

: Not available.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|-------|----------------|
| Oral | 11353.18 mg/kg |

Other information :

| | India | Page: 8/11 |
|--|-------|------------|
|--|-------|------------|

Product name STEELGUARD 651 WHITE

Section 11. Toxicological information

Contains isothiazolinones. May cause allergic reaction.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|--|--|----------------------------------|
| Polyphosphoric acids, ammonium salts melamine isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol | Acute EC50 730.5 mg/l Fresh water Acute EC50 200 mg/l Acute LC50 33 mg/l | Daphnia - <i>Daphnia magna</i> - Neonate Daphnia Fish | 48 hours 48 hours 96 hours |

Persistence and degradability

| Product/ingredient name | Test | Result | | Dose | | Inoculum |
|---|-------------------|------------|-----------------|------|--------|------------|
| sobutyric acid, monoester with 2,2,4-trimethylpentane- 1,3-diol | OECD 301B | >76 % - Re | adily - 28 days | - | | - |
| Product/ingredient name | Aquatic half-life | | Photolysis | | Biodeg | radability |

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|--|-------------------|------------|------------------|
| sobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol | - | - | Readily |

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|--|--------------|-----|------------|
| melamine isobutyric acid, monoester with 2,2,4-trimethylpentane- 1,3-diol | -1.22 3.2 | 3.8 | Low Low |
| octhilinone (ISO) | 2.45 | - | Low |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff

Page: 9/11 India

Product name STEELGUARD 651 WHITE

Section 13. Disposal considerations

and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | UN | IMDG | IATA |
|-----------------------------|-----------------|-----------------|-----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - |
| Transport hazard class(es) | - | - | - |
| Packing group | - | - | - |
| Environmental hazards | No. | No. | No. |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. |

Additional information

UN : None identified.IMDG : None identified.IATA : None identified.

Special precautions for user: **Transport within user's premises:** always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

Section 15. Regulatory information

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

History

Date of issue/Date of : 15 November 2023

revision

Date of previous issue : 10/11/2022

Version : 3
Prepared by : EHS

India Page: 10/11

Product name STEELGUARD 651 WHITE

Section 16. Other information

key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Procedure used to derive the classification

| Classification | Justification |
|--|---|
| REPRODUCTIVE TOXICITY - Category 2 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 | Calculation method Calculation method Calculation method Calculation method |

▼ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

India Page: 11/11