SAFETY DATA SHEET

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013



Date of issue/Date of revision

Date of issue/Date of fevis

17 November 2023

Version 2.01

Section 1. Chemical product and company identification

Product code : 000001114907

Product name : STEELGUARD 651 WHITE
Product name : STEELGUARD 651 WHITE
Other means of : 00359402; 00434337; 00467243

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying, Application by non spray methods...

Use of the substance/

mixture

: Coating.

Uses advised against : Not applicable.

Supplier's details : PPG Coatings (Kunshan) Co., Ltd

53 Jinyang Road, Lujia Town,

215331 Kunshan City, Jiangsu Province, P.R. China Tel: 86 512 57678859 Fax: 86 512 57678857

Emergency telephone number (with hours of

operation)

: 00 86 532 83889090

Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

Emergency overview

Liquid.

White.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

Contains isothiazolinones. May cause allergic reaction.

IF exposed or concerned: Get medical advice or attention.

See Section 12 for environmental precautions.

Classification of the substance or mixture : CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION - Category 2
AQUATIC HAZARD (ACUTE) - Category 3
AQUATIC HAZARD (LONG-TERM) - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 19.1%

China Page: 1/12

Product name STEELGUARD 651 WHITE

Section 2. Hazards identification

GHS label elements

Hazard pictograms



Signal word Warning

Hazard statements Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Wear protective gloves, protective clothing and

eye or face protection. Avoid release to the environment.

: IF exposed or concerned: Get medical advice or attention. Response : Use an extinguishing agent suitable for the surrounding fire.

Suitable extinguishing

media

: Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Physical and chemical

hazards

Storage

: No known significant effects or critical hazards.

Health hazards : Suspected of causing cancer. Suspected of damaging fertility or the unborn child.

Symptoms related to the physical, chemical and toxicological characteristics

Eve contact : No specific data.

Inhalation : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

China Page: 2/12

Date of issue 17 November 2023 Version 2.01

Product name STEELGUARD 651 WHITE

Section 2. Hazards identification

Potential immediate

effects

: Not available.

Potential delayed effects

: Not available.

Environmental hazards

: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Other hazards which do not : None known.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification

: 00359402; 00434337; 00467243

CAS number/other identifiers

CAS number : Not applicable.

Ingredient name	%	CAS number
olyphosphoric acids, ammonium salts melamine	25 - <40 1 - <10	68333-79-9 108-78-1
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol 9(or 10)-sulphooctadecanoic acid, potassium salt	1 - <10 0.1 - <1	25265-77-4 67968-63-2
octhilinone (ISO)	<0.1	26530-20-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the **Eye contact**

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and Skin contact

water or use recognized skin cleanser. Do NOT use solvents or thinners.

: If swallowed, seek medical advice immediately and show this container or label. Ingestion

Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards. Inhalation No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards.

China Page: 3/12

Date of issue 17 November 2023 Version 2.01

Product name STEELGUARD 651 WHITE

Section 4. First aid measures

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

: Adverse symptoms may include the following: Ingestion

> reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

: No specific treatment. **Specific treatments**

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising

from the chemical

This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Decomposition products may include the following materials:

carbon oxides nitrogen oxides phosphorus oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

China Page: 4/12

Product name STEELGUARD 651 WHITE

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material. kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 10 to 30°C (50 to 86°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

> China Page: 5/12

Section 7. Handling and storage

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Skin protection : Safety glasses with side shields.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated

Gloves

: For prolonged or repeated handling, use the following type of gloves:

Recommended: Viton®

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

China Page: 6/12

Product code 000001114907 Date of issue 17 November 2023 Version 2.01

Product name STEELGUARD 651 WHITE

Section 8. Exposure controls/personal protection

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.
Color : White.

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: Not applicable.

Lower and upper explosive

(flammable) limits

: Greatest known range: Lower: 0.6% Upper: 4.2% (isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol)

Relative density : 1.41

elative delisity . 1.4

Solubility(ies) : Media Result

cold water Soluble

Viscosity : Kinematic (40°C): >21 mm²/s

Viscosity : > 100 s (ISO 6mm)

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition

products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides nitrogen oxides phosphorus oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

China Page: 7/12

Product code 000001114907 Date of issue 17 November 2023 Version 2.01

Product name STEELGUARD 651 WHITE

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
olyphosphoric acids, ammonium salts	LD50 Oral	Rat	4.74 g/kg	-
melamine	LC50 Inhalation Dusts and mists	Rat	>5190 mg/m³	4 hours
	LD50 Oral	Rat	3161 mg/kg	-
isobutyric acid, monoester with	LD50 Dermal	Rabbit	>15.2 g/kg	-
2,2,4-trimethylpentane-1,3-diol				
	LD50 Oral	Rat	6.5 g/kg	-
octhilinone (ISO)	LC50 Inhalation Dusts and mists	Rat	0.27 mg/l	4 hours
	LD50 Dermal	Rabbit	311 mg/kg	_
	LD50 Oral	Rat	125 mg/kg	-

Irritation/Corrosion

Not available.

Sensitization

3	Route of exposure	Species	Result
octhilinone (ISO)	skin	Mouse	Sensitizing

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
melamine	Category 2	-	urinary system

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

China Page: 8/12

Date of issue 17 November 2023 Version 2.01

Product code 000001114907

Product name STEELGUARD 651 WHITE

Section 11. Toxicological information

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

: Not available.

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
STEELGUARD 651 WHITE Polyphosphoric acids, ammonium salts melamine isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	11353.2 4740 3161 6500	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A
octhilinone (ISO)	125	311	N/A	N/A	0.27

Other information :

Date of issue 17 November 2023 Version 2.01

Product name STEELGUARD 651 WHITE

Section 11. Toxicological information

Contains isothiazolinones. May cause allergic reaction.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Polyphosphoric acids, ammonium salts	Acute EC50 730.5 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
melamine isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	Acute EC50 200 mg/l Acute LC50 33 mg/l	Daphnia Fish	48 hours 96 hours

Persistence/degradability

Product/ingredient name	Test	Result		Dose		Inoculum
sobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	OECD 301B	>76 % - Re	eadily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	gradability
sobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	-		-		Readily	У

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
melamine isobutyric acid, monoester with 2,2,4-trimethylpentane-	-1.22 3.2	3.8	Low Low
1,3-diol octhilinone (ISO)	2.45	-	Low

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling

China Page: 10/12

Product name STEELGUARD 651 WHITE

Section 13. Disposal considerations

emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	China	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

: None identified. CN UN : None identified. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

Section 15. Regulatory information

China inventory (IECSC)

: All components are listed or exempted.

References

: Production Safety Law of the People's Republic of China

Code of Occupational Disease Prevention of the People's Republic of China

Environmental Protection Law of the People's Republic of China

Fire Control Law of the People's Republic of China

Regulations on the Control over Safety of Dangerous Chemicals

Occupational exposure limits for hazardous agents in the workplace chemical

hazardous agents (GBZ2.1)

General rule for classification and hazard communication of chemicals (GB13690)

Safety data sheet for chemical products - Content and order of sections (GB/

T16483)

Guidance on the compilation of safety data sheet for chemical products (GB/

T17519)

General rule for preparation of precautionary label for chemicals (GB15258)

China Page: 11/12 Product code 000001114907 Date of issue 17 November 2023 Version 2.01

Product name STEELGUARD 651 WHITE

Section 15. Regulatory information

Safety rules for classification, precautionary labeling and precautionary statements of chemicals (GB30000.2-29)

Section 16. Other information

History

Date of issue/Date of

revision

: 17 November 2023

Date of previous issue

: 6/6/2023 : 2.01

Version

EHS

Key to abbreviations

: ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

China Page: 12/12