SAFETY DATA SHEET

Date of issue/Date of revision 20 December 2023

Section 1. Identification

| Product code | : 00373328 |
|--|--|
| Product name | : PSX 700 BASE OEM RAL 7035 |
| CAS number | : Not applicable. |
| EC number | : Mixture. |
| Product type | : Liquid. |
| Relevant identified uses | of the substance or mixture and uses advised against |
| Product use | Coating. Professional applications, Used by spraying. |
| Uses advised against | : Product is not intended, labelled or packaged for consumer use. |
| Supplier's details | : PPG Yung Chi Coatings Co. Ltd Lot 219, Amata Street, Long Binh IZ Bien Hoa City, Dong Nai Province Vietnam Tel : +84 61 3936121/22 |
| Emergency telephone number (with hours of operation) | : CHEMTREC +(84)-444581938 (CCN 17704) |

Section 2. Hazards identification

| Classification of the substance or mixture | N SENSITIZATION - Category 1 JATIC TOXICITY (ACUTE) - Category 3 JATIC TOXICITY (CHRONIC) - Category 3 centage of the mixture consisting of ingredient(s) of unknow atic environment: 44.9% | vn hazards to the |
|--|---|-------------------|
| GHS label elements | | |
| Hazard pictograms | ^ | |
| Signal word | ning | |
| Hazard statements | r cause an allergic skin reaction. nful to aquatic life with long lasting effects. | |
| Precautionary statements | | |
| Prevention | ar protective gloves. Avoid release to the environment. Av taminated work clothing should not be allowed out of the w | |
| Response | e off contaminated clothing and wash it before reuse. IF C ty of water. If skin irritation or rash occurs: Get medical ac | |
| Storage | applicable. | |
| | | |



Version2.02

Product name PSX 700 BASE OEM RAL 7035

Section 2. Hazards identification

| Disposal | : | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
|---|---|---|
| Routes of entry | : | Not available. |
| Other hazards which do not result in classification | : | None known. |

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

| EC number | : Mixture. |
|------------|-------------------|
| CAS number | : Not applicable. |
| | |

| Ingredient name | CAS number | Chemical formula | % |
|--|------------|-------------------------|-------------------------|
| ₩,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane | | (C15H28O2. C3H5ClO)x | ≥25 - ≤50 |
| barium sulfate bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | 41556-26-7 | • • • • • • | ≥10 - ≤18 <2.5 <1 |

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

| Description of necess | sary first aid measures |
|-----------------------|--|
| Eye contact | Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. |
| Inhalation | Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| Skin contact | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. |
| Ingestion | If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting. |
| | |

Most important symptoms/effects, acute and delayed

| Potential acute health effect | <u>s</u> |
|-------------------------------|---|
| Eye contact | : No known significant effects or critical hazards. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : May cause an allergic skin reaction. |
| Ingestion | : No known significant effects or critical hazards. |
| Over-exposure signs/sympt | <u>oms</u> |
| Eye contact | : No specific data. |
| Inhalation | : No specific data. |
| | |

Section 4. First aid measures

| Skin contact | : Adverse symptoms may include the following: irritation redness |
|------------------------|--|
| Ingestion | : No specific data. |
| Indication of immediat | te medical attention and special treatment needed, if necessary |

| indication of inineutate met | ical attention and special treatment needed, in necessary |
|------------------------------|---|
| Notes to physician | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures **Extinguishing media** Suitable extinguishing : Use an extinguishing agent suitable for the surrounding fire. media

| Unsuitable extinguishing | : None known. |
|--------------------------|---------------|
| media | |

| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
|--|--|
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |

Special protective : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure equipment for fire-fighters mode.

Section 6. Accidental release measures

| Personal precautions, protec | tiv | e equipment and emergency procedures |
|--------------------------------|-----|--|
| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | - | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| | | Viet Nam Page: 3/11 |

Product code 00373328

Product name PSX 700 BASE OEM RAL 7035

Section 6. Accidental release measures

| Environmental precautions | : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. | |
|------------------------------|---|--|
| Methods and materials for co | ntainment and cleaning up | |
| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. | |
| Large spill | : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. | |

Section 7. Handling and storage

| Precautions for safe handling | | |
|--|---|--|
| Protective measures | : | Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| Advice on general occupational hygiene | : | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | : | Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | | | Exposure limits |
|--|------------|---|--|
| <mark>ቓ</mark> arium sulfate | | | ACGIH TLV (United States, 1/2023). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction |
| Recommended monitoring procedures | : | Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required. | |
| Appropriate engineering controls | : | Good general ventilation should be sufficient to control worker exposure to airborne contaminants. | |
| Environmental exposure controls | : | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. | |
| Individual protection measu | <u>res</u> | | |
| Hygiene measures | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. | |
| Eye/face protection Skin protection | : | Safety glasses with side shields. | |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. | |
| Gloves | : | butyl rubber | |
| Body protection | : | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. | |
| Other skin protection | : | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. | |
| Respiratory protection | : | hazards of the product and the safe w workers are exposed to concentration appropriate, certified respirators. Use | n known or anticipated exposure levels, the rorking limits of the selected respirator. If is above the exposure limit, they must use a properly fitted, air-purifying or air-fed a standard if a risk assessment indicates this is |

Section 9. Physical and chemical properties

Appearance

| Physical state | : | Liquid. | |
|--|---|----------------------------|-------------------|
| Color | : | Not available. | |
| Odor | : | Aromatic. | |
| Odor threshold | : | Not available. | |
| рН | : | Not applicable. | |
| Melting point | : | Not available. | |
| Boiling point | : | >37.78°C (>100°F) | |
| Flash point | : | Closed cup: Not applicable | ۶. |
| Evaporation rate | : | Not available. | |
| Flammability (solid, gas) | : | Not available. | |
| Lower and upper explosive (flammable) limits | : | Not available. | |
| Vapor pressure | : | Not available. | |
| Vapor density | : | Not available. | |
| Relative density | : | 1.47 | |
| Solubility(ies) | | Media | Result |
| Solubility(les) | 1 | cold water | Not soluble |
| Partition coefficient: n- octanol/water | : | Not applicable. | |
| Auto-ignition temperature | : | Not available. | |
| Decomposition temperature | : | Not available. | |
| Viscosity | : | Kinematic (40°C): >21 mm | l ² /s |
| | | | |

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|---|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition products. |
| Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids. |
| Hazardous decomposition products | : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|----------------------------------|--------------------------|---------------------------|----------|
| barium sulfate | LD50 Dermal | Rat | >2000 mg/kg | - |
| bis(1,2,2,6,6-pentamethyl- | LD50 Oral LD50 Oral | Rat Rat | >5000 mg/kg 3.125 g/kg | - |
| 4-piperidyl) sebacate | | | 5.125 g/kg | - |
| methyl | LD50 Oral | Rat | 3.125 g/kg | - |
| 1,2,2,6,6-pentamethyl- | | | | |
| 4-piperidyl sebacate | | | | |
| Conclusion/Summary | : There are no data available or | n the mixture itse | lf. | |
| Irritation/Corrosion | | | | |
| Conclusion/Summary | - | | | |
| Skin | : There are no data available or | | | |
| Eyes | : There are no data available or | | | |
| Respiratory | : There are no data available or | i the mixture itse | IT. | |
| Sensitization | | d | 16 | |
| Skin Beenington | : There are no data available or | | | |
| Respiratory | : There are no data available or | i the mixture itse | ·II. | |
| <u>Mutagenicity</u> | | | | |
| Conclusion/Summary | : There are no data available or | n the mixture itse | llt. | |
| <u>Carcinogenicity</u> | | | | |
| Conclusion/Summary | : There are no data available or | n the mixture itse | lf. | |
| Reproductive toxicity | | | | |
| Conclusion/Summary | : There are no data available or | n the mixture itse | lf. | |
| Teratogenicity | | | | |
| Conclusion/Summary | : There are no data available or | n the mixture itse | lf. | |
| Specific target organ toxicit | <u>v (single exposure)</u> | | | |
| Not available. | | | | |
| Specific target organ toxicit | v (repeated exposure) | | | |
| Not available. | | | | |
| Aspiration hazard | | | | |
| Not available. | | | | |
| INUL AVAIIANE. | | | | |
| nformation on the likely | : Not available. | | | |
| outes of exposure | | | | |
| otential acute health effects | <u>1</u> | | | |
| Eye contact | : No known significant effects o | r critical hazards | | |
| Inhalation | : No known significant effects o | r critical hazards | | |
| Skin contact | : May cause an allergic skin rea | | | |
| Ingestion | : No known significant effects o | | | |
| and the second | | l alaganata statt | _ | |
| | sical, chemical and toxicologica | <u>ai characteristic</u> | <u>'S</u> | |
| Eye contact | : No specific data. | | | |

Section 11. Toxicological information

| Inhalation | : No specific data. | |
|------------------------------|---|--|
| Skin contact | Adverse symptoms may include the following: irritation redness | |
| Ingestion | : No specific data. | |
| Delayed and immediate effect | s and also chronic effects from short and long term exposure | |
| Short term exposure | | |
| Potential immediate effects | : There are no data available on the mixture itself. | |
| Potential delayed effects | : There are no data available on the mixture itself. | |
| Long term exposure | | |
| Potential immediate effects | : There are no data available on the mixture itself. | |
| Potential delayed effects | : There are no data available on the mixture itself. | |
| Potential chronic health eff | <u>2ts</u> | |
| General | Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. | |
| Carcinogenicity | : No known significant effects or critical hazards. | |
| Mutagenicity | : No known significant effects or critical hazards. | |
| Reproductive toxicity | : No known significant effects or critical hazards. | |
| - | | |

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|--------|----------------|
| Oral | 82009.32 mg/kg |
| Dermal | 7351.95 mg/kg |

Other information

Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness.

Section 12. Ecological information

ż

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|--|----------------|---------|----------|
| 4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane | LC50 11.5 mg/l | Fish | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

| Disposal methods | : The generation of waste should be avoided or minimized wherever possible. |
|------------------|---|
| | Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling |
| | emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |

Section 14. Transport information

| | UN | IMDG | IATA |
|--------------------------------|-----------------|-----------------|-----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - |
| Transport hazard class(es) | - | - | - |
| Packing group | - | - | - |
| Environmental hazards | No. | No. | No. |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. |

Additional information

| UN | : None identified. |
|------|--------------------|
| IMDG | : None identified. |
| ΙΑΤΑ | : None identified. |

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Product name PSX 700 BASE OEM RAL 7035

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

Circular no. 05/1999/TT-BYT

| Ingredient name | Category | Notes | |
|---------------------------|------------|-------|--|
| 1-chloro-2,3-epoxypropane | Category 2 | | |
| benzene | Category 1 | | |
| toluene | Category 2 | | |
| xylene | Category 2 | | |
| 1,4-dioxane | Category 2 | | |
| Formaldehyde, solution | Category 2 | | |
| ethylene oxide | Category 2 | | |
| selenium | Category 1 | | |
| lead massive | Category 2 | | |
| antimony | Category 2 | | |
| arsenic | Category 1 | | |

Toxic classification (TCVN : 4

3164-79)

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

History

| Date of issue/Date of revision | : 20 December 2023 |
|--------------------------------|---|
| Date of previous issue | : 8/18/2023 |
| Version | : 2.02 |
| Prepared by | : EHS |
| Key to abbreviations | ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations |
| References | : Not available. |

Indicates information that has changed from previously issued version.

Notice to reader

Product name PSX 700 BASE OEM RAL 7035

Section 16. Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.