# **SAFETY DATA SHEET**

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013



40 1 2024

Date of issue/Date of revision16 January 2024Version 6.02				
Section 1. Chemical product and company identification				
Product code	: 000001176643			
Product name	: PITT-CHAR NX BASE WHITE			
Product name	: PITT-CHAR NX BASE WHITE			
Other means of identification	: 00424801; 00471806			
Product type	: Liquid.			
Relevant identified uses o	f the substance or mixture and uses advised against			
Product use	: Professional applications, Used by spraying.			
Use of the substance/ mixture	: Coating.			
Uses advised against	: Not applicable.			
Supplier's details	: PPG Coatings (Kunshan) Co., Ltd 53 Jinyang Road, Lujia Town, 215331 Kunshan City, Jiangsu Province, P.R. China Tel: 86 512 57678859 Fax: 86 512 57678857			
Emergency telephone number (with hours of operation)	: 00 86 532 83889090			

## Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

#### **Emergency overview**

Liquid. White. Characteristic. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

IF exposed or concerned: Get medical advice or attention. If skin irritation or rash occurs: Get medical advice or attention. If eye irritation persists: Get medical advice or attention.

#### See Section 12 for environmental precautions.

Section 2. Hazard	s identification
Classification of the substance or mixture	<ul> <li>SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 11.9%</li> </ul>
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	<ul> <li>Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	: Collect spillage. IF exposed or concerned: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Physical and chemical hazards	: No known significant effects or critical hazards.
Health hazards	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child.

#### Symptoms related to the physical, chemical and toxicological characteristics

### Section 2. Hazards identification

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	<ul> <li>Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations</li> </ul>
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effect	ts and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Environmental hazards	: Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Other hazards which do not result in classification	: None known.

## Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: 00424801; 00471806

#### **CAS number/other identifiers**

CAS number	: Not applicable.
------------	-------------------

## Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
hexaboron dizinc undecaoxide	10 - <25	12767-90-7
Borate(5-), bis[µ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	10 - <25	12046-04-7
bis-[4-(2,3-epoxipropoxi)phenyl]propane	10 - <25	1675-54-3
tris(2-chloro-1-methylethyl) phosphate	1 - <10	13674-84-5
Polyphosphoric acids, ammonium salts	1 - <10	68333-79-9
triphenyl phosphate	1 - <10	115-86-6
Epoxy resin (MW $\leq$ 700)	1 - <10	25068-38-6
cashew nut shell oil	1 - <10	8007-24-7
2,2-bis(acryloyloxymethyl)butyl acrylate	1 - <10	15625-89-5
Quaternary ammonium compounds, benzylbis(hydrogenated tallow alkyl) methyl, chlorides	0.1 - <1	61789-73-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
		In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effe	<u>cts</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>ptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness

### Section 4. First aid measures

Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides phosphorus oxides halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Product code 000001176643 Product name PITT-CHAR NX BASE WHITE

### Section 5. Fire-fighting measures

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	•	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions Methods and materials for co		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Small spill		Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

Precautions for safe handling
 Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Section 7. Handling and storage

Conditions for safe storage,	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in
including any	accordance with local regulations. Store in original container protected from direct
incompatibilities	sunlight in a dry, cool and well-ventilated area, away from incompatible materials
	(see Section 10) and food and drink. Store locked up. Keep container tightly closed
	and sealed until ready for use. Containers that have been opened must be carefully
	resealed and kept upright to prevent leakage. Do not store in unlabeled containers.
	Use appropriate containment to avoid environmental contamination. See Section 10
	for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name			Exposure limits		
hexaboron dizinc undecaoxid Borate(5-), bis[µ-oxotetraoxoo dihydrate, (T-4)-		orato(4-)]-, ammonium tetrahydrogen,	ACGIH TLV (United States, 1/2013). TWA: 10 mg/m <sup>3</sup> , (Dusts and mists) Form: Inhalable fraction TWA: 3 mg/m <sup>3</sup> , (Dusts and mists) Form: Respirable fraction ACGIH TLV (United States). TWA: 3 mg/m <sup>3</sup> Form: Respirable dust		
triphenyl phosphate			TWA: 3 mg/m <sup>2</sup> Form: inhalable dust		
			ACGIH TLV (United States, 1/2023). TWA: 3 mg/m <sup>3</sup> 8 hours.		
Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.			
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.			
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.			
ndividual protection measur	<u>es</u>				
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.			
Eye protection	:	Chemical splash goggles.			
Skin protection					

Product name PITT-CHAR NX BASE WHITE

## Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: polyethylene butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## Section 9. Physical and chemical properties

: Liquid.
: White.
: Characteristic.
: >37.78°C (>100°F)
: Closed cup: Not applicable.
: Not available.
: 1.56
Media Result
cold water Not soluble
: Kinematic (40°C): >21 mm <sup>2</sup> /s

## Section 10. Stability and reactivity

	China Page: 8/15
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

Product name PITT-CHAR NX BASE WHITE

### Section 10. Stability and reactivity

Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides phosphorus oxides halogenated compounds metal oxide/oxides

## Section 11. Toxicological information

### Information on toxicological effects

<u>Acute toxicity</u>				
Product/ingredient name	Result	Species	Dose	Exposure
hexaboron dizinc undecaoxide	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Borate(5-), bis[µ- oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen,	LD50 Dermal	Rabbit	>2000 mg/kg	-
dihydrate, (T-4)-				
	LD50 Oral	Rat	4200 mg/kg	-
bis-[4-(2,3-epoxipropoxi)phenyl] propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
tris(2-chloro-1-methylethyl) phosphate	LC50 Inhalation Dusts and mists	Rat	>7 mg/l	4 hours
	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	1500 mg/kg	-
Polyphosphoric acids, ammonium salts	LD50 Oral	Rat	4.74 g/kg	-
triphenyl phosphate	LD50 Dermal	Rabbit	>7900 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
Epoxy resin (MW ≤ 700)	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	>2 g/kg	-
2,2-bis(acryloyloxymethyl)butyl acrylate	LD50 Dermal	Rabbit	5170 mg/kg	-
-	LD50 Oral	Rat	5.19 g/kg	-

#### Irritation/Corrosion

Result	Species	Score	Exposure	Observation74 hours	
Eyes - Cornea opacity	Rabbit	33	24 hours 0.083g		
Eyes - Mild irritant	Rabbit	-	24 hours	-	
Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-	
Skin - Edema	Rabbit	0.5	4 hours	-	
Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-	
Skin - Mild irritant	Rabbit	-	4 hours	-	
Eyes - Mild irritant	Rabbit	-	-	-	
Skin - Mild irritant	Rabbit	-	-	-	
Skin - Irritant	Rabbit	-	-	-	
	Eyes - Cornea opacity Eyes - Mild irritant Eyes - Redness of the conjunctivae Skin - Edema Skin - Erythema/Eschar Skin - Mild irritant Eyes - Mild irritant Skin - Mild irritant	Eyes - Cornea opacityRabbitEyes - Mild irritantRabbitEyes - Redness of the conjunctivaeRabbitSkin - EdemaRabbitSkin - Erythema/EscharRabbitSkin - Mild irritantRabbitEyes - Mild irritantRabbitSkin - Mild irritantRabbitSkin - Mild irritantRabbit	Eyes - Cornea opacityRabbit33Eyes - Mild irritantRabbit-Eyes - Redness of the conjunctivaeRabbit0.4Skin - EdemaRabbit0.5Skin - Edema/EscharRabbit0.8Skin - Mild irritantRabbit-Eyes - Mild irritantRabbit-Skin - Mild irritantRabbit-	Eyes - Cornea opacityRabbit3324 hoursEyes - Mild irritantRabbit-24 hoursEyes - Redness of the conjunctivaeRabbit0.424 hoursSkin - EdemaRabbit0.424 hoursSkin - EdemaRabbit0.54 hoursSkin - Erythema/Eschar Skin - Mild irritantRabbit-4 hoursSkin - Mild irritant Eyes - Mild irritantRabbitSkin - Mild irritant Eyes - Mild irritantRabbit Rabbit	

China Page: 9/15

### Section 11. Toxicological information

butvl	acrylate
Duty	adiyiato

Sensitization							
Product/ingredient name	Route of exposure	Species	Result				
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitizing				
Epoxy resin (MW ≤ 700) 2,2-bis(acryloyloxymethyl) butyl acrylate	skin skin	Mouse Rabbit	Sensitizing Sensitizing				

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
hexaboron dizinc undecaoxide	Positive	Positive	Positive		Oral: 375 mg/kg	90 days; 7 days per week

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	•••	Route of exposure	Target organs
cashew nut shell oil	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

### Information on the likely : Not available.

routes of exposure Potential acute health effects

Eye contact: Causes serious eye irritation.Inhalation: No known significant effects or critical hazards.Skin contact: Causes skin irritation. May cause an allergic skin reaction.Ingestion: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

## Section 11. Toxicological information

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure		
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>s</u>
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	Suspected of damaging fertility or the unborn child.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
TT-CHAR NX BASE WHITE	6262.0	9412.0	N/A	N/A	N/A
Borate(5-), bis[µ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	4200	2500	N/A	N/A	N/A
bis-[4-(2,3-epoxipropoxi)phenyl]propane	15000	23000	N/A	N/A	N/A
tris(2-chloro-1-methylethyl) phosphate	1500	N/A	N/A	N/A	N/A
Polyphosphoric acids, ammonium salts	4740	N/A	N/A	N/A	N/A
triphenyl phosphate	3500	N/A	N/A	N/A	N/A
				China	Page: 11/1

Product code 000001176643 Product name PITT-CHAR NX BASE WHITE	Date of is	sue 16 Jan	uary 2024	Version 6.02				
Section 11. Toxicological information								
Epoxy resin (MW ≤ 700) 2,2-bis(acryloyloxymethyl)butyl acrylate	2500 5190	2500 5170	N/A N/A	N/A N/A	N/A N/A			

#### **Other information**

Sanding and grinding dusts may be harmful if inhaled. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.

### Section 12. Ecological information

<u>Toxicity</u>					
Product/ingredient name	Result	Species	Exposure		
hexaboron dizinc undecaoxide	Acute EC50 76 mg/l	Daphnia - Daphnia magna	48 hours		
	Acute LC50 2.17 mg/l	Fish - Salmo gairdneri	96 hours		
Borate(5-), bis[µ- oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	Acute LC50 >100 mg/l	Fish	96 hours		
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours		
	Chronic NOEC 0.3 mg/l	Daphnia	21 days		
Polyphosphoric acids, ammonium salts	Acute EC50 730.5 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours		
triphenyl phosphate	Acute LC50 0.09 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours		
	Chronic NOEC 0.1 mg/l	Algae - Desmodesmus subspicatus	3 days		
Epoxy resin (MW ≤ 700)	Acute LC50 1.8 mg/l	Daphnia	48 hours		
	Chronic NOEC 0.3 mg/l	Daphnia	21 days		
2,2-bis(acryloyloxymethyl) butyl acrylate	Acute LC50 0.87 mg/l	Fish	96 hours		

#### Persistence/degradability

Product/ingredient name	Test	Result		Dose		Inoculum
Epoxy resin (MW ≤ 700)	OECD 301F	5 % - 28 days ·		-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-		-		Not rea	adily
Epoxy resin (MW ≤ 700)	-		-		Not rea	adily

#### **Bioaccumulative potential**

### Product name PITT-CHAR NX BASE WHITE

## Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
hexaboron dizinc undecaoxide	-	60960	High
tris(2-chloro-1-methylethyl) phosphate	2.68	7.94	Low
triphenyl phosphate	4.63	190.55	Low
Epoxy resin (MW $\leq$ 700)	3	31	Low
cashew nut shell oil	>4.78	-	High
2,2-bis(acryloyloxymethyl) butyl acrylate	0.67	-	Low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and
	liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

			1
UN3082	UN3082	UN3082	UN3082
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(hexaboron dizinc undecaoxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(hexaboron dizinc undecaoxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(hexaboron dizinc undecaoxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(hexaboron dizinc undecaoxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane)
9	9	9	9
Ш	Ш	111	Ш
Yes.	Yes.	Yes.	Yes.
_	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexaboron dizinc undecaoxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane) 9	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexaboron dizinc undecaoxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane)ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexaboron dizinc undecaoxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane)99	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(hexaboron dizinc undecaoxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane)ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.9999

Product code000001176643Date of issue16 January 2024Version 6.02Product namePITT-CHAR NX BASE WHITE					
Section 14	. Tran	sport inf	ormation		
Marine pollutan substances	t Not a	pplicable.	Not applicable.	(hexaboron dizinc undecaoxide)	Not applicable.
Additional infor	nation				
CN	: None	identified.			
UN			5	s good when transported in rovisions of 4.1.1.1, 4.1.1.2	<b>.</b>
IMDG				s good when transported in rovisions of 4.1.1.1, 4.1.1.2	
ΙΑΤΑ				s good when transported in rovisions of 5.0.2.4.1, 5.0.2	
Special precaut	ions for u	upright	-	<b>ises:</b> always transport in c t persons transporting the age.	
Transport in bu to IMO instrume		<b>ng :</b> Not ap	plicable.		
Section 15	5. Regi	latory in	formation		

China inventory (IECSC)	: All components are listed or exempted.
References	<ul> <li>Production Safety Law of the People's Republic of China Code of Occupational Disease Prevention of the People's Republic of China Environmental Protection Law of the People's Republic of China Fire Control Law of the People's Republic of China Regulations on the Control over Safety of Dangerous Chemicals Occupational exposure limits for hazardous agents in the workplace chemical hazardous agents (GBZ2.1) General rule for classification and hazard communication of chemicals (GB13690) Safety data sheet for chemical products - Content and order of sections (GB/ T16483) Guidance on the compilation of safety data sheet for chemical products (GB/ T17519) General rule for preparation of precautionary label for chemicals (GB15258) Safety rules for classification, precautionary labeling and precautionary statements of chemicals (GB30000.2-29)</li> </ul>

## Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 16 January 2024
Date of previous issue	: 12/26/2023
Version	: 6.02
	EHS

#### Product name PITT-CHAR NX BASE WHITE

### Section 16. Other information

Key to abbreviations	: ADN = European Provisions concerning the International Carriage of Dangerous
	Goods by Inland Waterway
	ADR = The European Agreement concerning the International Carriage of
	Dangerous Goods by Road
	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	RID = The Regulations concerning the International Carriage of Dangerous Goods
	by Rail
	UN = United Nations
<b>—</b>	

✓ Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.