SAFETY DATA SHEET



Date of issue 2/1/2024 (month/day/year)

Version 3.01

Section 1. Chemical product and company identification

A. Product name
Product code: PSX 700 BASE RAL 9016
: 00289191

B. Relevant identified uses of the substance or mixture and uses advised against

| Product use | : Professional applications, Used by spraying. |
|--------------------------------------|---|
| Use of the substand mixture | ce/ : Coating. |
| Uses advised agair | ist : Product is not intended, labelled or packaged for consumer use. |
| C. Supplier's or Impo information | rter's : PPG SSC (680-090) 19, Yeocheon-ro 217beon-gil, Nam-gu, Ulsan, Korea Tel: +82-52-210-8222 |
| Email Address | Korea.MSDS@PPG.COM |
| Emergency telephone number: | one : ₱82-52-210-8331 |

Section 2. Hazards identification

A. Hazard classification : FLAMMABLE LIQUIDS - Category 4 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 3

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol



| Signal word | : Warning |
|-------------------|---|
| Hazard statements | H227 - Combustible liquid. H317 - May cause an allergic skin reaction. H351 - Suspected of causing cancer. H412 - Harmful to aquatic life with long lasting effects. |
| | |

Precautionary statements

Section 2. Hazards identification

| Prevention | P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves, protective clothing and eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273 - Avoid release to the environment. P261 - Avoid breathing vapor. |
|------------|--|
| Response | P308 + P313 - IF exposed or concerned: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. |
| Storage | : Not applicable. |
| Disposal | P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |

C. Other hazards which do : None known. not result in classification

Section 3. Composition/information on ingredients

CAS number/other identifiers

CAS number

: Not applicable.

| Chemical name | Common name | Identifiers | % |
|--|--|------------------------------------|----------------------|
| 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane | cyclohexanol, 4,4'-(1-methylethylidene) bis-, polymer with (chloromethyl)oxirane | CAS: 30583-72-3 | 30 - <40 |
| titanium dioxide nonylphenol ethoxylates | TITANIUM DIOXIDE POLYOXYETHYLENE NONYLPHENYL ETHER PHOSPHATE | CAS: 13463-67-7 CAS: 68412-53-3 | 10 -<20 1 - <5 |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | BIS(PENTAMETHYLPIPERIDYL) SEBACATE | CAS: 41556-26-7 | 1 - <5 |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | METHYL-(1,2,2,6,6-PENTAMETHYL- 4-PIPERDIYL) SEBACATE | CAS: 82919-37-7 | 0.1 - <1 |
| methyl alcohol Nonylphenol, branched, ethoxylated | METHYL ALCOHOL Poly(oxy-1,2-ethanediyl), a-(nonylphenyl) -w-hydroxy-, branched | CAS: 67-56-1 CAS: 68412-54-4 | 0.1 - <1 0.1 - <1 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

A. Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

- B. Skin contact
- : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Section 4. First aid measures

| C. | Inhalation | : | Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
|----|----------------------------|---|---|
| D. | Ingestion | : | If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting. |
| Е. | Notes to physician | : | In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| | Specific treatments | 4 | No specific treatment. |
| | Protection of first-aiders | : | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Α. | Extinguishing media | | |
|----|--|---|---|
| | Suitable extinguishing media | 1 | Use dry chemical, CO ₂ , water spray (fog) or foam. |
| | Unsuitable extinguishing media | : | Do not use water jet. |
| В. | Specific hazards arising from the chemical | : | Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| | Hazardous thermal decomposition products | : | Decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides |
| C. | Special equipment for fire-fighting | : | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |
| | Fire-fighting procedures | : | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. |

Product name PSX 700 BASE RAL 9016

Section 6. Accidental release measures

| A. Personal precautions, protective equipment and emergency procedures | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
|--|----|---|
| B. Environmental precautions | : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. |
| C. Methods and materials for | СС | ontainment and cleaning up |
| Small spill | : | Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : | Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

Section 7. Handling and storage

| Α. | Precautions for safe handling | : | Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|----|--|---|---|
| В. | Conditions for safe storage, including any incompatibilities | : | Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |

Korea (GHS) Page: 4/12

Product name PSX 700 BASE RAL 9016

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

| | Ingredient name | | | Exposure limits |
|----|--------------------------------------|----|---|---|
| | Manium dioxide methyl alcohol | | | Ministry of Employment and Labor (Republic of Korea, 1/2020). TWA: 10 mg/m ³ 8 hours. Form: total dust with less than 1% of free SiO2 Ministry of Employment and Labor (Republic of Korea, 1/2020). Absorbed through skin. STEL: 250 ppm 15 minutes. TWA: 200 ppm 8 hours. |
| | Recommended monitoring procedures | : | Reference should be made to appropri- national guidance documents for methor substances will also be required. | ate monitoring standards. Reference to ods for the determination of hazardous |
| В. | Appropriate engineering controls | : | | s to keep worker exposure to airborne d or statutory limits. The engineering controls oncentrations below any lower explosive |
| | Environmental exposure controls | : | | |
| C. | Personal protective equip | me | ent | |
| | Respiratory protection | | hazards of the product and the safe we workers are exposed to concentrations appropriate, certified respirators. Use respirator complying with an approved necessary. | n known or anticipated exposure levels, the orking limits of the selected respirator. If s above the exposure limit, they must use a properly fitted, air-purifying or air-fed standard if a risk assessment indicates this is |
| | Eye protection | | Chemical splash goggles. | |
| | Hand protection | : | be worn at all times when handling che this is necessary. Considering the par check during use that the gloves are s should be noted that the time to break | ers. In the case of mixtures, consisting of |
| | Gloves | 1 | butyl rubber | |
| | Body protection | : | | body should be selected based on the task d and should be approved by a specialist |
| | Hygiene measures | : | Wash hands, forearms and face thoro eating, smoking and using the lavatory Appropriate techniques should be use | ughly after handling chemical products, before and at the end of the working period. d to remove potentially contaminated clothing t be allowed out of the workplace. Wash |
| | | | | Ensure that eyewash stations and safety |

Product name PSX 700 BASE RAL 9016

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

| Α. | Appearance | | | |
|----------------------------|--|-------|---|--------------------|
| | Physical state | 1 | Liquid. | |
| | Color | : | Various | |
| В. | Odor | : | Aromatic. | |
| С. | Odor threshold | : | Not available. | |
| D. | рН | 1 | Not applicable. | |
| Ε. | Melting/freezing point | 1 | Not available. | |
| F. | Boiling point/boiling range | : | >37.78°C (>100°F) | |
| G. | Flash point | : | Closed cup: 70°C (158°F) | |
| н. | Evaporation rate | : | Not available. | |
| Т. | Flammability (solid, gas) | : | Not available. | |
| J. | Lower and upper explosive (flammable) limits | : | Not available. | |
| Κ. | Vapor pressure | : | Not available. | |
| | | | | |
| L. | Solubility(ies) | | Media | Result |
| L. | Solubility(ies) | : | Media cold water | Result Not soluble |
| L. | Solubility(ies) Solubility in water | : | | |
| | | | cold water | |
| М. | Solubility in water | : | cold water Not available. | |
| | Solubility in water Vapor density | : | cold water Not available. Not available. | |
| М. N. | Solubility in water Vapor density Relative density Partition coefficient: n- | : : : | cold water Not available. Not available. 1.34 | |
| M. N. O. | Solubility in water Vapor density Relative density Partition coefficient: n- octanol/water Auto-ignition | | cold water Not available. Not available. 7.34 Not applicable. | |
| М. N. О. Р. Q. | Solubility in water Vapor density Relative density Partition coefficient: n- octanol/water Auto-ignition temperature Decomposition | | cold water Not available. Not available. 7.34 Not applicable. Not available. | Not soluble |
| М. N. О. Р. | Solubility in water Vapor density Relative density Partition coefficient: n- octanol/water Auto-ignition temperature Decomposition temperature | | cold water Not available. Not available. 7.34 Not applicable. Not available. Not available. | Not soluble |

Section 10. Stability and reactivity

| Α. | Chemical stability | 1 | The product is stable. |
|----|------------------------------------|---|--|
| | Possibility of hazardous reactions | : | Under normal conditions of storage and use, hazardous reactions will not occur. |
| В. | Conditions to avoid | : | When exposed to high temperatures may produce hazardous decomposition products. |
| C. | Incompatible materials | : | Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids. |
| | | | Korea (GHS) Page: 6/12 |

Section 10. Stability and reactivity

 D. Hazardous decomposition products
 Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/ oxides

Section 11. Toxicological information

A. Information on the likely : routes of exposure

Potential acute health effects

| Inhalation | : No known significant effects or critical hazards. |
|--------------|---|
| Ingestion | : No known significant effects or critical hazards. |
| Skin contact | : May cause an allergic skin reaction. |
| Eye contact | : No known significant effects or critical hazards. |

Over-exposure signs/symptoms

| Inhalation | : No specific data. |
|--------------|--|
| Ingestion | : No specific data. |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Eye contact | : No specific data. |

B. Health hazards

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|---------------------------------|---------|-------------|----------|
| Manium dioxide | LC50 Inhalation Dusts and mists | Rat | >6.82 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | LD50 Oral | Rat | 3.125 g/kg | - |
| methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate | LD50 Oral | Rat | 3.125 g/kg | - |
| methyl alcohol | LC50 Inhalation Vapor | Rat | 64000 ppm | 4 hours |
| | LD50 Dermal | Rabbit | 15800 mg/kg | - |
| | LD50 Oral | Rat | 5600 mg/kg | - |
| Nonylphenol, branched, ethoxylated | LD50 Oral | Rat | 2.21 g/kg | - |

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

| Conclusion/Summary | |
|-------------------------------------|--|
| Skin | : There are no data available on the mixture itself. |
| Eyes | : There are no data available on the mixture itself. |
| Respiratory | : There are no data available on the mixture itself. |
| Sensitization Conclusion/Summary | |
| Skin | : There are no data available on the mixture itself. |
| Respiratory | : There are no data available on the mixture itself. |

Korea (GHS) Page: 7/12

Section 11. Toxicological information

| <u>Mutagenicity</u> Conclusion/Summary | : There are no data available on the mixture itself. |
|--|--|
| <u>Carcinogenicity</u> Conclusion/Summary | : There are no data available on the mixture itself. |
| Reproductive toxicity Conclusion/Summary | : There are no data available on the mixture itself. |
| <u>Teratogenicity</u> Conclusion/Summary | : There are no data available on the mixture itself. |

Specific target organ toxicity (single exposure)

| Name | Classification | Route of exposure | Target organs |
|----------------|----------------|-------------------|---------------|
| methyl alcohol | Category 1 | - | - |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Potential chronic health effects

| General | : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
|-----------------------|---|
| Carcinogenicity | : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Reproductive toxicity | : No known significant effects or critical hazards. |

Additional information

Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness.

| Chemical name | Identifiers | GHS Classification | |
|--|-----------------|--|--|
| 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane | CAS: 30583-72-3 | SKIN SENSITIZATION - Category 1B | |
| | | AQUATIC HAZARD (LONG-TERM) - Category 3 | |
| titanium dioxide | CAS: 13463-67-7 | CARCINOGENICITY - Category 2 | |
| nonylphenol ethoxylates | CAS: 68412-53-3 | ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 | |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | CAS: 41556-26-7 | | |
| | | TOXIC TO REPRODUCTION - Category 2 | |
| | | AQUATIC HAZARD (ACUTE) - Category 1 | |
| | | Korea (GHS) Page: 8/12 | |

Section 11. Toxicological information

| 5 | | | |
|---|-----------------|--|--|
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | CAS: 82919-37-7 | AQUATIC HAZARD (LONG-TERM) - Category 1 SKIN SENSITIZATION - Category 1B | |
| methyl alcohol | CAS: 67-56-1 | TOXIC TO REPRODUCTION - Category 2 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE | |
| Nonylphenol, branched, ethoxylated | CAS: 68412-54-4 | EXPOSURE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A AQUATIC HAZARD (LONG-TERM) - Category 2 | |

Section 12. Ecological information

A. Ecotoxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------------|----------------------------------|--------------------------------|----------|
| 4 ,4'- | LC50 11.5 mg/l | Fish | 96 hours |
| Isopropylidenedicyclohexanol, | | | |
| oligomeric reaction | | | |
| products with 1-chloro- | | | |
| 2,3-epoxypropane | | | |
| titanium dioxide | Acute LC50 >100 mg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 48 hours |
| methyl alcohol | Acute LC50 13 mg/l Fresh water | Fish | 96 hours |

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|---|---------------|-----|-------------|
| methyl alcohol Nonylphenol, branched, ethoxylated | -0.77 5.39 | - | Low High |

D. Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

E. Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

- A. Disposal methods
 The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- B. Disposal precautions
 This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | UN | IMDG | IATA |
|--------------------------------------|-----------------|-----------------|-----------------|
| A. UN number | Not regulated. | Not regulated. | Not regulated. |
| B. UN proper shipping name | - | - | - |
| C. Transport hazard class(es) | - | - | - |
| D. Packing group | - | - | - |
| Environmental hazards | No. | No. | No. |
| E. Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. |

Additional information

- UN: None identified.IMDG: None identified.
- IATA : None identified.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Product name PSX 700 BASE RAL 9016

Section 15. Regulatory information

| Α. | A. <u>Regulation according to ISHA</u> | | | | |
|----|---|---|--|--|--|
| | ISHA article 117 (Harmful substances prohibited from manufacture) | : None of the components are listed. | | | |
| | ISHA article 118 (Harmful substances requiring permission) | : None of the components are listed. | | | |
| | Article 2 of Youth Protection Act on Substances Hazardous to Youth | : It is not allowed to sell to persons under the age of 19. | | | |
| | Exposure Limits of Chemical Substances and Physical Factors | | | | |
| | The following components Intanium dioxide methyl alcohol | s have an OEL: | | | |
| | ISHA Enforcement Regs Annex 19 (Exposure standards established for harmful factors) | : The following components are listed: methanol | | | |
| | ISHA Enforcement Regs Annex 21 (Harmful factors subject to Work Environment Measurement) | : The following components are listed: titanium dioxide | | | |
| | ISHA Enforcement Regs Annex 22 (Harmful Factors Subject to Special Health Check- up) | : None of the components are listed. | | | |
| | Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control) | : The following components are listed: titanium dioxide | | | |
| В. | Regulation according to Chemicals Control Act | | | | |
| | Article 11 (TRI) | : None of the components are listed. | | | |
| | Article 18 Prohibited (K- Reach Article 27) | : None of the components are listed. | | | |
| | Article 19 Subject to authorization (K-Reach Article 25) | : None of the components are listed. | | | |
| | Article 20 Restricted (K- Reach Article 27) | : The following components are listed: nonylphenol ethoxylates, nonylphenol ethoxylates | | | |
| | Article 20 Toxic Chemicals (K-Reach Article 20) | : Not applicable | | | |
| | Korea inventory | : All components are listed or exempted. | | | |

Date of issue 2/1/2024 (month/day/year)

Product name PSX 700 BASE RAL 9016

Section 15. Regulatory information

| | Article 39 (Accident Precaution Chemicals) | : | The following components are listed: nonylphenol ethoxylates, nonylphenol ethoxylates | |
|----|--|---|--|--|
| C. | Dangerous Materials Safety Management Act | : | Class: Class 4 - Flammable Liquid Item: 5. Class 3 petroleums - Water-insoluble liquid Threshold: 2000 L Danger category: III Signal word: Contact with sources of ignition prohibited | |
| D. | Wastes regulation | : | Dispose of contents and container in accordance with all local, regional, national and international regulations. | |
| Ε. | Regulation according to other foreign laws | | | |
| | Safety, health and environmental regulations specific for the product | : | No known specific national and/or regional regulations applicable to this product (including its ingredients). | |

Section 16. Other information

| Α. | References | : | Korean Ministry of Environment; Chemical Control Act Korean Ministry of Labor; Industrial Safety and Health Act NIER Notice Registry of Toxic Effects of Chemical Substances (RTECS) U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information Retrieval) ECOTOX Database System. |
|----|--------------------------------|---|---|
| в. | Date of issue/Date of revision | : | 2/1/2024 |
| С. | Version | : | 3.01 |
| | Prepared by | : | EHS |
| - | Others | | |

D. Other

✓ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.