SAFETY DATA SHEET

Date of issue/Date of revision

: 6 February 2024

Version

: 1



pPg

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: NOVAGUARD 615/650 HARDENER
Product code	: 000001201355
Other means of identification 00475993	on
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
1.3 Details of the supplier of Sigma Paint Saudi Arabia Ltd PO Box 7509, Dammam 3147 Saudi Arabia Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34	
e-mail address of person responsible for this SDS	: PS.ACEMEA@ppg.com
1.4 Emergency telephone number	: 00966 138473100 extn 1001

SECTION 2: Hazards identification

 2.1 Classification of the substance or mixture

 Product definition
 : Mixture

 Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Acute Tox. 4, H302

 Acute Tox. 4, H312

 Skin Corr. 1B, H314

 Eye Dam. 1, H318

 Skin Sens. 1, H317

 Aquatic Chronic 2, H411

 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Code : 000001201355	Date of issue/Date of revision : 6 February 2024
NOVAGUARD 615/650 HARDI	INER
SECTION 2: Hazards	identification
Hazard pictograms	
	: Danger
Hazard statements	: Harmful if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Avoid release t the environment.
Response	: Collect spillage. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P273, P391, P304 + P310, P301 + P310, P501
Hazardous ingredients	 Propylidynetrimethanol, propoxylated, reaction products with ammonia 3-aminomethyl-3,5,5-trimethylcyclohexylamine Epoxy Amine Resin 2,4,6-tris(dimethylaminomethyl)phenol
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	<u>ents</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPv
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Code: 000001201355Date of issue/Date of revision: 6 February 2024NOVAGUARD 615/650 HARDENER

SECTION 3: Composition/information on ingredients

		1	-		
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Propylidynetrimethanol, propoxylated, reaction products with ammonia	REACH #: 01-2119556886-20 EC: 500-105-6 CAS: 39423-51-3	≥50 - ≤75	Acute Tox. 4, H302 Acute Tox. 4, H312 Eye Dam. 1, H318 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/ kg ATE [Dermal] = 1100 mg/kg	[1]
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	REACH #: 01-2119514687-32 EC: 220-666-8 CAS: 2855-13-2 Index: 612-067-00-9	≥10 - ≤25	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	ATE [Oral] = 1030 mg/ kg Skin Sens. 1, H317: C ≥ 0.001%	[1]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥10 - ≤25	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	ATE [Oral] = 1230 mg/ kg ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1] [2]
Epoxy Amine Resin	CAS: SUB114180	≥5.0 - ≤10	Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥1.0 - ≤5.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 1200 mg/ kg ATE [Dermal] = 1280 mg/kg	[1]
salicylic acid	REACH #: 01-2119486984-17 EC: 200-712-3 CAS: 69-72-7 Index: 607-732-00-5	≥1.0 - <3.0	Acute Tox. 4, H302 Eye Dam. 1, H318 Repr. 2, H361d	ATE [Oral] = 891 mg/ kg	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid me	asures
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

English	(GB)
---------	------

Code : 000001201355	Date of issue/Date of revision : 6 February 2024				
NOVAGUARD 615/650 HARDI	ENER				
SECTION 4: First aid	measures				
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.				
	s and effects, both acute and delayed				
Potential acute health effect					
Eye contact	: Causes serious eye damage.				
Inhalation	: No known significant effects or critical hazards.				
Skin contact	: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction				
Ingestion	: Harmful if swallowed.				
Over-exposure signs/sympt	<u>oms</u>				
Eye contact	: Adverse symptoms may include the following: pain watering redness				
Inhalation	: No specific data.				
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur				
Ingestion	: Adverse symptoms may include the following: stomach pains				
4.3 Indication of any immedia	ate medical attention and special treatment needed				
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.				
Specific treatments	: No specific treatment.				
SECTION 5: Firefight	ing measures				
5.1 Extinguishing media					
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.				
Unsuitable extinguishing media	: None known.				
5.2 Special hazards arising fi	rom the substance or mixture				
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.				
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides				
5.3 Advice for firefighters					
Special precautions for	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable				
fire-fighters	training.				

Code : 000001201355	;	Date of issue/Date of revision	: 6 February 2024
NOVAGUARD 615/650 HARDI	ENER		
SECTION 5: Firefight	ing measures		
Special protective equipment for fire-fighters	apparatus (SCBA) w for fire-fighters (inclu	wear appropriate protective equipment and ith a full face-piece operated in positive pr iding helmets, protective boots and gloves I provide a basic level of protection for che	essure mode. Clothing) conforming to European
SECTION 6: Acciden	tal release meas	ures	
6.1 Personal precautions, pro	otective equipment and	l emergency procedures	
For non-emergency personnel	Evacuate surroundin entering. Do not tou Provide adequate ve	ken involving any personal risk or without og areas. Keep unnecessary and unprotec ch or walk through spilt material. Do not b entilation. Wear appropriate respirator whe appropriate personal protective equipment	cted personnel from breathe vapour or mist. en ventilation is
For emergency responders		g is required to deal with the spillage, take and unsuitable materials. See also the ir el".	
6.2 Environmental precautions	sewers. Inform the r pollution (sewers, wa	oilt material and runoff and contact with so relevant authorities if the product has caus aterways, soil or air). Water polluting mate eleased in large quantities. Collect spillage	ed environmental erial. May be harmful to
6.3 Methods and material for	containment and clear	ning up	
Small spill	if water-soluble. Alte	isk. Move containers from spill area. Dilu ernatively, or if water-insoluble, absorb with ate waste disposal container. Dispose of v	n an inert dry material and
Large spill	upwind. Prevent ent spillages into an efflu spillage with non-cor diatomaceous earth Dispose of via a licer	isk. Move containers from spill area. App ry into sewers, water courses, basements uent treatment plant or proceed as follows mbustible, absorbent material e.g. sand, e and place in container for disposal accord nsed waste disposal contractor. Contamir hazard as the spilt product.	or confined areas. Wash . Contain and collect arth, vermiculite or ing to local regulations.
6.4 Reference to other sections	See Section 8 for inf	nergency contact information. formation on appropriate personal protective dditional waste treatment information.	ve equipment.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU)	
2020/878	

Code : 000001201355

NOVAGUARD 615/650 HARDENER

Date of issue/Date of revision

: 6 February 2024

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name		Exposure limit values			
benzyl alcohol		IPEL (-). TWA: 5 ppm STEL: 10 ppm			
Recommended monitoring procedures	Standard EN 689 by inhalation to c strategy) Europe application and u biological agents requirements for agents) Referen	 (Workplace atmosphe hemical agents for con ean Standard EN 14042 use of procedures for th) European Standard I the performance of pro- 	g standards, such as the following eres - Guidance for the assessme nparison with limit values and mea 2 (Workplace atmospheres - Guid the assessment of exposure to che EN 482 (Workplace atmospheres ocedures for the measurement of a documents for methods for the o quired.	nt of exposure asurement e for the mical and - General chemical	
8.2 Exposure controls					
Appropriate engineering controls	local exhaust ver	ntilation or other engine	, gas, vapour or mist, use process ering controls to keep worker exp nmended or statutory limits.		
Individual protection measur	<u>'es</u>				
Hygiene measures	eating, smoking a Appropriate tech Contaminated wo contaminated clo	and using the lavatory niques should be used ork clothing should not	ghly after handling chemical produ and at the end of the working perio to remove potentially contaminate be allowed out of the workplace. Ensure that eyewash stations and cation.	od. ed clothing. Wash	
Eye/face protection Skin protection	: Chemical splash	goggles and face shie	ld.		
Hand protection	worn at all times necessary. Cons during use that th noted that the tim glove manufactur protection time o	when handling chemic sidering the parameters ne gloves are still retair ne to breakthrough for rers. In the case of min f the gloves cannot be	complying with an approved stands al products if a risk assessment in s specified by the glove manufactu- ning their protective properties. It any glove material may be differen- xtures, consisting of several subst accurately estimated. When proto a glove with a protection class of	ndicates this is urer, check should be nt for different ances, the onged or	
		English (GB)	Saudi Arabia	6/13	

Code : 000001201	355	Date of issue/Date of revision : 6 February 2024	
NOVAGUARD 615/650 HA	RDEN	ER	
		(breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use as included in the user's risk assessment.)
Gloves	:	butyl rubber	
Body protection	:	Personal protective equipment for the body should be selected based on the task bein performed and the risks involved and should be approved by a specialist before handling this product.	ıg
Other skin protection		Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by specialist before handling this product.	
Respiratory protection	:		
Environmental exposur controls	e :	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>					
Physical state	:	Liquid.			
Colour	1	Clear.	ilear.		
Odour	1	Aromatic. [Slight]	romatic. [Slight]		
Odour threshold	:	Not available.			
Melting point/freezing point	:	for the following ingredient: 3-an	May start to solidify at the following temperature: 8°C (46.4°F) This is based on data for the following ingredient: 3-aminomethyl-3,5,5-trimethylcyclohexylamine. Weighted average: -14.18°C (6.5°F)		
Initial boiling point and boiling range	:	>37.78°C			
Flammability	1	Not available.			
Upper/lower flammability or explosive limits	1	Greatest known range: Lower: 1	.3% Upper:	13% (benzyl	alcohol)
Flash point	:	Closed cup: 120°C			
Auto-ignition temperature	:	Ingredient name	°C	°F	Method
		Propylidynetrimethanol, propoxylated, reaction products with ammonia	320	608	EU A.15
		reaction products with ammonia			
Decomposition temperature	:	Stable under recommended stor	rage and har	dling conditio	ons (see Section 7).
Decomposition temperature pH		· · ·	rage and har	Idling condition	ons (see Section 7).
		Stable under recommended stor	l rage and har	l Idling conditic	ons (see Section 7).
рН		Stable under recommended stor Not applicable.	l rage and har	dling conditic	ons (see Section 7).
pH Viscosity		Stable under recommended stor Not applicable. Kinematic (40°C): >21 mm²/s	rage and har	dling conditio	ons (see Section 7).
pH Viscosity Viscosity		Stable under recommended stor Not applicable. Kinematic (40°C): >21 mm²/s	l rage and har	dling conditio	ons (see Section 7).
pH Viscosity Viscosity Solubility(ies)		Stable under recommended stor Not applicable. Kinematic (40°C): >21 mm²/s 30 - <40 s (ISO 6mm)	rage and har	dling conditio	ons (see Section 7).
pH Viscosity Viscosity Solubility(ies) Media	:	Stable under recommended stor Not applicable. Kinematic (40°C): >21 mm²/s 30 - <40 s (ISO 6mm) Result Not soluble	rage and har	dling conditio	ons (see Section 7).

Code : 000001201355 Date of issue/Date of revision

: 6 February 2024

NOVAGUARD 615/650 HARDENER

SECTION 9: Physical and chemical properties

		Ingredient name	Vapor	apour Pressure at 20°C		Vapour pressure at 50		sure at 50°C
			mm Hg	kPa	Method	mm Hg	kPa	Method
		Propylidynetrimethanol, propoxylated, reaction products with ammonia	5.12	0.68	EU A.4			
Evaporation rate	:	0.007 (benzyl alcoho	l) compar	ed with	butyl acetate		•	
Relative density	:	0.98						
Vapour density	:	Highest known value	: 3.7 (Air	= 1) (b	enzyl alcohol).			
Explosive properties	:	The product itself is r vapour or dust with a			the formation	of an ex _l	olosible n	nixture of
Oxidising properties	:	Product does not pre	sent an o	xidizing	hazard.			
Particle characteristics								
		Not applicable.						

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.			
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.			
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides			

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propylidynetrimethanol, propoxylated, reaction products with ammonia	LD50 Dermal	Rabbit	0.4 g/kg	-
	LD50 Oral	Rat	0.22 g/kg	-
3-aminomethyl-	LC50 Inhalation Dusts and	Rat	>5.01 mg/l	4 hours
3,5,5-trimethylcyclohexylamine	mists		C C	
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m ³	4 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
	English (GB)	Saud	i Arabia	8/13

Code	: 000001201355	Date of issue/Date of revision	: 6 February 2024
NOVAGUAR	D 615/650 HARDENER		

SECTION 11: Toxicological information

2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
salicylic acid	LD50 Oral	Rat	0.891 g/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,4,6-tris(dimethylaminomethyl)phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days
Conclusion/Summary		- -			

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.

- : There are no data available on the mixture itself.
- Eyes : There are no data available on the mixture itself. Respiratory

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
3-aminomethyl-3,5,5-trimethylcyclohexylamine	skin	Guinea pig	Sensitising

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
<u>Mutagenicity</u>	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Information on likely	: Not available.
routes of exposure	
Potential acute health effect	
Inhalation	: No known significant effects or critical hazards.
Ingestion	: Harmful if swallowed.
Skin contact	: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Eye contact	: Causes serious eye damage.
Symptoms related to the p	hysical, chemical and toxicological characteristics
Inhalation	: No specific data.
Ingestion	: Adverse symptoms may include the following: stomach pains
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Eye contact	: Adverse symptoms may include the following: pain watering redness
Delayed and immediate eff	ects as well as chronic effects from short and long-term exposure

English (GB)

Code: 000001201355Date of issue/Date of revision: 6 February 2024NOVAGUARD 615/650 HARDENER

SECTION 11: Toxicological information

	-
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	<u>cts</u>
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Other information	: Not available.

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

11.2 Information on other hazards

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2,4,6-tris(dimethylaminomethyl)phenol salicylic acid	Acute LC50 175 mg/l Acute EC50 1147.57 mg/l Fresh water Chronic NOEC 5.6 mg/l	Fish Daphnia - <i>Daphnia</i> <i>longispina</i> - Neonate Daphnia - <i>Daphnia</i>	96 hours 48 hours 21 days
	Fresh water	<i>magna</i> - Neonate	

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol	-	-	Readily

12.3 Bioaccumulative potential

Code: 000001201355Date of issue/Date of revision: 6 February 2024NOVAGUARD 615/650 HARDENER

SECTION 12: Ecological information

Product/ingredient name	LogPow	BCF	Potential
Propylidynetrimethanol, propoxylated, reaction products with ammonia	-1.13	-	Low
3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.99	-	Low
benzyl alcohol	0.87	-	Low
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	Low
salicylic acid	2.21 to 2.26	-	Low

12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC) 15 01 06 mixed packaging	
Container		
Special precautions	taken when Empty conta	al and its container must be disposed of in a safe way. Care should be handling emptied containers that have not been cleaned or rinsed out. ainers or liners may retain some product residues. Avoid dispersal of spilt I runoff and contact with soil, waterways, drains and sewers.

English (GB)	Saudi Arabia 1	1/13
--------------	----------------	------

Code: 000001201355Date of issue/Date of revision: 6 February 2024NOVAGUARD 615/650 HARDENER

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	11	11	II
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(Polyoxy propylene diamine)	Not applicable.

Additional information

ADR/RID Tunnel code IMDG IATA	≤5 kg. : (E) : The marine	mentally hazardous substance mark is not required when transported in sizes of \leq 5 L or pollutant mark is not required when transported in sizes of \leq 5 L or \leq 5 kg. mentally hazardous substance mark may appear if required by other transportation
14.6 Special preduser	cautions for :	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport in	n bulk :	Not applicable.

according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain

dangerous substances,

mixtures and articles

Other national and international regulations.

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Code : 00000120135 NOVAGUARD 615/650 HARD		evision : 6 February 2024
SECTION 15: Regula	atory information	
15.2 Chemical safety assessment	: No Chemical Safety Assessment has been carried	out.
SECTION 16: Other	information	
Indicates information that	has changed from previously issued version.	
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number 	
Full text of abbreviated H statements	 H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye dama H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H361d Suspected of damaging the unborn child. H411 Toxic to aquatic life with long lasting effect 	
Full text of classifications [CLP/GHS]	Eye Dam. 1SERIOUS EYE DAMAGEye Irrit. 2SERIOUS EYE DAMAGRepr. 2REPRODUCTIVE TOXSkin Corr. 1BSKIN CORROSION/IRI	IIC) AQUATIC HAZARD - Category GE/EYE IRRITATION - Category 1 GE/EYE IRRITATION - Category 2 (ICITY - Category 2 RITATION - Category 1B RITATION - Category 1C I - Category 1
<u>History</u> Date of issue/ Date of revision	: 6 February 2024	
Date of previous issue	: No previous validation	
Prepared by	: EHS	
Version	: 1	
Dicoloimor		

<u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.