SAFETY DATA SHEET

PPG AQUACOVER ONE 625 BUFF



Date of issue 19 February 2024

Version 3.01

1. Product and company identification

Product name : PPG AQUACOVER ONE 625 BUFF

Product code : 000001192153 Other means of : 000001192153 identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against : Not applicable.

Supplier's details : PPG PMC Japan Co., Ltd., 8F, Shintetsu Bldg., 1-1, Daikaidori 1-chome, Kobe

652-0803 Japan; Tel: +81-78-574-2777

Emergency telephone

number

: 078 574 2777

2. Hazards identification

GHS Classification : CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION - Category 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category 2

HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD -

Category 2

GHS label elements

Hazard pictograms :





Signal word : Warning

Hazard statements : Suspected of causing cancer.

Suspected of damaging fertility or the unborn child. May cause damage to organs. (respiratory organs)

May cause damage to organs through prolonged or repeated exposure. (blood

system, liver, respiratory organs)

Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Japan Page: 1/13

Product code 000001192153

Product name PPG AQUACOVER ONE 625 BUFF

2. Hazards identification

Response

: Collect spillage. IF exposed or concerned: Call a POISON CENTER or doctor.

Storage

: Store locked up.

Disposal

: Dispose of contents and container in accordance with all local, regional, national

and international regulations.

result in classification

Other hazards which do not : Contains isothiazolinones. May cause allergic reaction.

3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

CAS number : Not applicable. **CSCL** number : Not available.

| Ingredient name | % | CAS number | CSCL |
|--|----------|------------|----------------|
| titanium dioxide (excluding nanoparticle) zinc phosphate Talc containing no asbestos or quartz Diethylene glycol mono butyl ether [2- | 7 - <10 | 13463-67-7 | 1-558; 5-5225 |
| | 5 - <7 | 7779-90-0 | 1-1181; 1-526 |
| | 3 - <5 | 14807-96-6 | Not available. |
| | 1 - <2 | 112-34-5 | 2-422; 7-97 |
| (2-buthoxyethoxy)ethanol] Zinc oxide reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt Zinc salt of 2-pyridinethiol 1-oxide | 0.5 - <1 | 1314-13-2 | 1-561 |
| | <0.1 | SUB141402 | Not available. |
| | <0.1 | 13463-41-7 | 5-3725; 9-1110 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

4. First aid measures

Description of necessary first aid measures

Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and **Skin contact**

water or use recognized skin cleanser. Do NOT use solvents or thinners.

: If swallowed, seek medical advice immediately and show this container or label. Ingestion

Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards.

Skin contact : May cause damage to organs following a single exposure in contact with skin.

: May cause damage to organs following a single exposure if swallowed. Ingestion

Over-exposure signs/symptoms

Japan Page: 2/13 **Product code 000001192153**

Date of issue 19 February 2024 Version 3.01

Product name PPG AQUACOVER ONE 625 BUFF

4. First aid measures

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway,

sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon oxides phosphorus oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Japan Page: 3/13

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage: Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

> Japan Page: 4/13

8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|---------------------------------------|---|
| Talc containing no asbestos or quartz | Japan Society for Occupational Health (Japan, 9/2022). [Class 1 dusts (Activated charcoal, Alumina, Aluminium, Bentonite, Diatomite, Graphite, Kaolinite, Pagodite, Pyrites, Pyrite cinder, Talc)] OEL-M: 0.5 mg/m³ 8 hours. Form: Respirable dust (Class 1 Dust) OEL-M: 2 mg/m³ 8 hours. Form: Total dust (Class 1 Dust) |

procedures

Recommended monitoring: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Skin protection

: Safety glasses with side shields.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves

: For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber, Chloroprene, butyl rubber

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

> Japan Page: 5/13

Product code 000001192153

Date of issue 19 February 2024 Version 3.01

Product name PPG AQUACOVER ONE 625 BUFF

8. Exposure controls/personal protection

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Beige.

Odor : Odorless.

pH : 8.5

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 120°C (248°F)

Relative density : 1.2

Solubility(ies) : Media Result

cold water Partially soluble

Viscosity : > 100 s (ISO 6mm)

10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition

products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides phosphorus oxides metal oxide/oxides

11. Toxicological information

Information on toxicological effects

Acute toxicity

Japan Page: 6/13

11. Toxicological information

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|----------------------------------|---------|-------------------------|----------|
| titanium dioxide (excluding nanoparticle) | LC50 Inhalation Dusts and mists | Rat | >6.82 mg/l | 4 hours |
| , | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| zinc phosphate | LC50 Inhalation Dusts and mists | Rat | >5.7 mg/l | 4 hours |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Diethylene glycol mono butyl | LD50 Dermal | Rabbit | 2700 mg/kg | - |
| ether [2-(2-buthoxyethoxy) ethanol] | | | | |
| | LD50 Oral | Rat | 4500 mg/kg | - |
| Zinc oxide | LC50 Inhalation Dusts and mists | Rat | >5700 mg/m ³ | 4 hours |
| | LD50 Dermal | Rat | >2000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt | LC50 Inhalation Dusts and mists | Rat | 0.047 mg/l | 4 hours |
| 1. | L CEO Inhalation Duats and mists | Dot | 0.14 mg/l | 4 hours |
| Zinc salt of 2-pyridinethiol 1-oxide | LC50 Inhalation Dusts and mists | Rat | 0.14 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >2 g/kg | - |
| | LD50 Oral | Rat | 177 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--------------------------------------|-----------------------|---------|-------|----------|-------------|
| Zinc salt of 2-pyridinethiol 1-oxide | Eyes - Cornea opacity | Rabbit | 4 | 24 hours | 24 hours |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|--|--------------------------|-------------------|--|
| Talc containing no asbestos or quartz Diethylene glycol mono butyl ether [2-(2-buthoxyethoxy) ethanol] | Category 1 Category 3 | - | respiratory organs Narcotic effects |
| Zinc oxide | Category 1 | - | respiratory organs, systemic toxicity |
| Zinc salt of 2-pyridinethiol 1-oxide | Category 1 | - | nervous system |

Specific target organ toxicity (repeated exposure)

Japan Page: 7/13

Product code 000001192153

Product name PPG AQUACOVER ONE 625 BUFF

11. Toxicological information

| Name | Category | Route of exposure | Target organs |
|--|------------|-------------------|------------------------------------|
| titanium dioxide (excluding nanoparticle) | Category 1 | - | respiratory organs |
| zinc phosphate | Category 1 | - | blood system |
| Talc containing no asbestos or quartz | Category 1 | - | respiratory organs |
| Diethylene glycol mono butyl ether [2-(2-buthoxyethoxy) ethanol] | Category 1 | - | liver, respiratory organs |
| reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt | Category 2 | - | liver |
| Zinc salt of 2-pyridinethiol 1-oxide | Category 1 | - | nervous system, respiratory system |

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: May cause damage to organs following a single exposure in contact with skin.

Ingestion : May cause damage to organs following a single exposure if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General: May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Japan Page: 8/13

Product code 000001192153

Product name PPG AQUACOVER ONE 625 BUFF

11. Toxicological information

Mutagenicity: No known significant effects or critical hazards.Reproductive toxicity: Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|------------------|-------------------|--------------------------------|----------------------------------|--|
| Diethylene glycol mono butyl ether [2- (2-buthoxyethoxy)ethanol] | 4500 | 2700 | N/A | N/A | N/A |
| Zinc oxide | N/A | 2500 | N/A | N/A | N/A |
| reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt | N/A | N/A | N/A | N/A | 0.047 |
| Zinc salt of 2-pyridinethiol 1-oxide | 177 | 2500 | N/A | N/A | 0.14 |

Other information

Sanding and grinding dusts may be harmful if inhaled. Contains isothiazolinones. May cause allergic reaction.

12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|--------------------------------------|--|----------|
| titanium dioxide (excluding nanoparticle) | Acute LC50 >100 mg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| zinc phosphate | Acute LC50 0.112 mg/l | Fish | 96 hours |
| | Chronic NOEC 0.026 mg/l | Fish | 30 days |
| Zinc oxide | Acute EC50 0.17 mg/l | Algae | 72 hours |
| | Acute EC50 0.481 mg/l Fresh water | Daphnia - <i>Daphnia magna</i> - Neonate | 48 hours |
| | Chronic NOEC 0.017 mg/l Fresh water | Algae | 72 hours |
| Zinc salt of 2-pyridinethiol 1-oxide | Acute EC50 5.513 μg/l Marine water | Algae - Nitzschia pungens | 96 hours |
| | Acute LC50 0.0082 mg/l | Daphnia | 48 hours |
| | Chronic NOEC 1.889 µg/l Marine water | Algae - Nitzschia pungens | 96 hours |
| | Chronic NOEC 0.0027 mg/l | Daphnia | 21 days |

Persistence/degradability

| Product/ingredient name | Test | Result | | Dose | | Inoculum |
|--------------------------------------|-------------------|----------------|------------------|------|---------|------------|
| Zinc salt of 2-pyridinethiol 1-oxide | - | 39 % - 28 days | | - | | - |
| Product/ingredient name | Aquatic half-life | | Photolysis | | Biodeg | radability |
| Zinc salt of 2-pyridinethiol | _ | | 50%; < 28 day(s) | | Not rea | dilv |

Bioaccumulative potential

Japan Page: 9/13

Product code 000001192153

Product name PPG AQUACOVER ONE 625 BUFF

12. Ecological information

| Product/ingredient name | LogPow | BCF | Potential |
|--|--------|-----|-----------|
| Diethylene glycol mono butyl ether [2-(2-buthoxyethoxy) ethanol] | 1 | - | Low |
| Zinc salt of 2-pyridinethiol 1-oxide | 0.9 | 0.9 | Low |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

| | UN | IMDG | IATA |
|-----------------------------|---|---|---|
| UN number | UN3082 | UN3082 | UN3082 |
| UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. |
| | (trizinc bis(orthophosphate)) | (trizinc bis(orthophosphate)) | (trizinc bis(orthophosphate)) |
| Transport hazard class(es) | 9 | 9 | 9 |
| Packing group | III | III | III |
| Environmental hazards | Yes. | Yes. | Yes. |
| Marine pollutant substances | Not applicable. | (trizinc bis(orthophosphate)) | Not applicable. |

Additional information

UN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Japan Page: 10/13

14. Transport information

IATA

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg. provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

15. Regulatory information

Fire Service Law

| Category | Substance name/Type | Danger category | Signal word | Designated quantity |
|----------------------|---------------------|-------------------|----------------|---------------------|
| Specified flammables | Combustible liquid | Not applicable | Not applicable | 2 m³ |

Pollutant Release and Transfer Registers (PRTR)

| Ingredient name | % | Status | Reference number |
|--|-----|---------|------------------|
| Trizinc bis(phosphate) Diethylene glycol monobutyl ether | 5.9 | Class 2 | 793 |
| | 1.8 | Class 1 | 627 |

Industrial Safety and Health Act

Ordinance on the Prevention of the Hazard due to Specified Chemical Substances

None of the components are listed.

Substance(s) requiring labelling

| Ingredient name | % | | Reference number |
|---|------------|------------------|-------------------------------------|
| Titanium(IV) oxide Diethylene glycol monobutyl ether | ≤10 ≤10 | Listed Listed | 191 224-3, 224-4 (2024-04) |

Chemicals requiring notification

| Ingredient name | % | Status | Reference number |
|---|------------|------------------|-------------------------------------|
| Titanium(IV) oxide Diethylene glycol monobutyl ether | ≤10 ≤10 | Listed Listed | 191 224-3, 224-4 (2024-04) |
| Zinc oxide | ≤10 | Listed | 188 |

Carcinogens based on Article 577-2 of the Ordinance on ISH

None of the components are listed.

Mutagen

None of the components are listed.

: Not listed **Corrosive liquid**

Japan Page: 11/13

Product code 000001192153

Product name PPG AQUACOVER ONE 625 BUFF

15. Regulatory information

Occupational Safety and

Health Law

: Oxidizing, Combustible

Health Law

Regulations on the

Prevention of Tetraalkyl

Lead Poisoning

traalkyl

Harmful Substances Subject to Obtaining

Permission for Manufacturing

: Not listed

: Not listed

Manufacturing
Harmful Substances,

Prohibited for

Manufacturing

: Not listed

ISHL Enforcement Order Appendix 1 - Dangerous

Appendix 1 - Dan

: Oxidizing, Combustible

Substances

Lead regulation : Not listed
Organic solvents : Not applicable.

poisoning prevention

. .

Poisonous and Deleterious Substances

None of the components are listed.

Chemical Substances Control Law (CSCL)

| Ingredient name | % | Status | Reference number |
|---|-----|---------------------|------------------|
| [alpha-(Alkyl(C16-18))-omega-hydroxypoly(oxyethane-1,2-diyl) or alpha-(alkenyl(C16-18))-omega-hydroxypoly (oxyethane-1,2-diyl)] (It is limited that the number-average molecular weight of the polymer is less than 1,000.) | ≤10 | Priority assessment | 250 |
| (T-4)-Bis[2-(thioxo-kappaS)-pyridin-1(2H)-olato-kappaO] zinc(II) | ≤10 | Priority assessment | 139 |
| 2-Butoxyethanol | ≤10 | Priority assessment | 109 |
| alpha-(Álkyl(C6-18))-omega-hydroxypoly[oxyethane-1,2-diyl/oxy(methylethane-1,2-diyl)] (It is limited that the number-average molecular weight of the polymer is less than 1,000.) | ≤10 | Priority assessment | 271 |
| Propane-1,2-diol | ≤10 | Priority assessment | 106 |
| 2,2,4,4,6,6,8,8-Octamethyl- 1,3,5,7,2,4,6,8-tetraoxatetrasilocane | ≤10 | Monitoring | 40 |
| Sodium alkyl(C8-18) sulfate | ≤10 | Priority assessment | 214 |
| Ethyl acrylate | ≤10 | Priority assessment | 32 |
| 2-(2-Ethoxyethoxy)ethanol | ≤10 | Priority assessment | 110 |
| Acetaldehyde | ≤10 | Priority assessment | 26 |
| Formaldehyde | ≤10 | Priority assessment | 25 |
| 1,4-Dioxane | ≤10 | Priority assessment | 80 |
| Ethylene oxide | ≤10 | Priority assessment | 19 |
| Chloromethane | ≤10 | Priority assessment | 6 |
| Ethylbenzene | ≤10 | Priority assessment | 50 |
| Toluene | ≤10 | Priority assessment | 46 |
| Cumene | ≤10 | Priority assessment | 126 |

High Pressure Gas Control: Not available.

Law

Explosives Control Law

None of the components are listed.

Japan Page: 12/13

Product code 000001192153 Date of issue 19 February 2024 Version 3.01

Product name PPG AQUACOVER ONE 625 BUFF

15. Regulatory information

Law concerning prevention : Not available. of pollution of the ocean

Maritime Safety Law

Notification Regulating Transportation of Dangerous Materials by Sea

None of the components are listed.

Container class

None of the components are listed.

JSOH Carcinogen List of Specially Controlled

Industrial Waste

Japan inventory

: Not listed : Not listed

: At least one component is not listed.

Road law : Not available.

16. Other information

History

Date of issue/Date of

: 19 February 2024

revision

Version

Date of previous issue

: 1/25/2024

Prepared by

: 3.01 : EHS

Key to abbreviations

: ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

bv Rail

UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Japan Page: 13/13