

# SAFETY DATA SHEET

Date of issue/Date of revision

: 19 February 2024

Version

: 1.05



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : PPG AQUACOVER ONE 645 WHITE

Product code : 000001189977

Other means of identification

00452711

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying, Application by non spray methods..

Use of the substance/  
mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd.  
PO Box 7509  
Dammam 31472  
Saudi Arabia  
Tel: 00966 138 47 31 00  
Fax: 00966 138 47 17 34

e-mail address of person  
responsible for this SDS : ndpic@sfga.gov.sa

1.4 Emergency telephone  
number : 00966 138473100 extn 1001

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Signal word : No signal word.

Hazard statements : Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Code : 000001189977

Date of issue/Date of revision : 19 February 2024

PPG AQUACOVER ONE 645 WHITE

SECTION 2: Hazards identification


Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.  
P273, P501

Hazardous ingredients

: Not applicable.

Supplemental label elements

:  Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

| Product/ingredient name  | Identifiers   | %           | Classification   | Specific Conc. Limits, M-factors and ATEs  | Type    |
|--|---|-------------|--|--|---------|
| 2-(2-butoxyethoxy)ethanol  | REACH #:<br>01-2119475104-44<br>EC: 203-961-6<br>CAS: 112-34-5<br>Index: 603-096-00-8 | ≥1.0 - ≤5.0 | Eye Irrit. 2, H319   | -  | [1] [2] |
| 3-iodo-2-propynyl butylcarbamate   | EC: 259-627-5<br>CAS: 55406-53-6<br>Index: 616-212-00-7                               | <0.10       | Acute Tox. 4, H302<br>Acute Tox. 3, H331<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>STOT RE 1, H372 (larynx)<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 | ATE [Oral] = 1470 mg/kg<br>ATE [Inhalation (dusts and mists)] = 0.67 mg/l<br>M [Acute] = 10<br>M [Chronic] = 1 | [1]     |
| reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt | CAS: SUB141402  | <0.10       | Acute Tox. 1, H330<br>STOT RE 2, H373 (liver)<br>Aquatic Chronic 1, H410   | ATE [Inhalation (dusts and mists)] = 0.047 mg/l<br>M [Chronic] = 10  | [1]     |
| 1,2-benzisothiazol-3(2H)-one   | EC: 220-120-9<br>CAS: 2634-33-5   | <0.050      | Acute Tox. 4, H302<br>Acute Tox. 2, H330   | ATE [Oral] = 1020 mg/kg  | [1]     |

English (GB)

United Arab Emirates

2/14

Code : 000001189977 Date of issue/Date of revision : 19 February 2024  
PPG AQUACOVER ONE 645 WHITE

SECTION 3: Composition/information on ingredients

|   |  |         |  |  |     |
|---|--|---------|--|--|-----|
|   | Index: 613-088-00-6  |         | Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 2, H411  | ATE [Inhalation (dusts and mists)] = 0.4 mg/l<br>Skin Sens. 1, H317: C ≥ 0.05%<br>M [Acute] = 1  |     |
| pyrithione zinc   | REACH #: 01-2119511196-46<br>EC: 236-671-3<br>CAS: 13463-41-7<br>Index: 613-333-00-7 | <0.010  | Acute Tox. 3, H301<br>Acute Tox. 2, H330<br>Eye Dam. 1, H318<br>Repr. 1B, H360D<br>STOT RE 1, H372<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410   | ATE [Oral] = 221 mg/kg<br>ATE [Inhalation (dusts and mists)] = 0.14 mg/l<br>M [Acute] = 1000<br>M [Chronic] = 10   | [1] |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) | REACH #: 01-2120764691-48<br>EC: 911-418-6<br>CAS: 55965-84-9<br>Index: 613-167-00-5 | <0.0010 | Acute Tox. 3, H301<br>Acute Tox. 2, H310<br>Acute Tox. 2, H330<br>Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1A, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410<br>EUH071<br><br>See Section 16 for the full text of the H statements declared above. | ATE [Oral] = 53 mg/kg<br>ATE [Dermal] = 50 mg/kg<br>ATE [Inhalation (vapours)] = 0.5 mg/l<br>Skin Corr. 1C, H314: C ≥ 0.6%<br>Skin Irrit. 2, H315: 0.06% ≤ C < 0.6%<br>Eye Dam. 1, H318: C ≥ 0.6%<br>Eye Irrit. 2, H319: 0.06% ≤ C < 0.6%<br>Skin Sens. 1, H317: C ≥ 0.0015%<br>M [Acute] = 100<br>M [Chronic] = 100 | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type  
[1] Substance classified with a health or environmental hazard  
[2] Substance with a workplace exposure limit  
This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.  
Occupational exposure limits, if available, are listed in Section 8.  
SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Code : 000001189977

Date of issue/Date of revision

: 19 February 2024

PPG AQUACOVER ONE 645 WHITE

## SECTION 4: First aid measures

- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Code : 000001189977

Date of issue/Date of revision

: 19 February 2024

PPG AQUACOVER ONE 645 WHITE

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

| Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878  |   |   |                         |                       |                  |   |                           |   |
|---|---|---|-------------------------|-----------------------|------------------|---|---------------------------|---|
| Code  | : 000001189977  | Date of issue/Date of revision : 19 February 2024 |                         |                       |                  |   |                           |   |
| PPG AQUACOVER ONE 645 WHITE   |   |   |                         |                       |                  |   |                           |   |
| SECTION 7: Handling and storage   |   |   |                         |                       |                  |   |                           |   |
| 7.3 Specific end use(s)   |   |   |                         |                       |                  |   |                           |   |
| See Section 1.2 for Identified uses.  |   |   |                         |                       |                  |   |                           |   |
| SECTION 8: Exposure controls/personal protection  |   |   |                         |                       |                  |   |                           |   |
| The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).   |   |   |                         |                       |                  |   |                           |   |
| 8.1 Control parameters  |   |   |                         |                       |                  |   |                           |   |
| Occupational exposure limits  |   |   |                         |                       |                  |   |                           |   |
| <table><tr><th>Product/ingredient name</th><th>Exposure limit values</th></tr><tr><td>titanium dioxide</td><td>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016).<br/>TWA: 10 mg/m³ 8 hours.<br/>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006).<br/>TWA: 10 mg/m³ 8 hours.<br/>ACGIH TLV (United States, 1/2023).<br/>TWA: 2.5 mg/m³ 8 hours. Form: respirable fraction, finescale particles</td></tr><tr><td>2-(2-butoxyethoxy)ethanol</td><td>ACGIH TLV (United States, 1/2023).<br/>TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor</td></tr></table> |   |   | Product/ingredient name | Exposure limit values | titanium dioxide | Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016).<br>TWA: 10 mg/m³ 8 hours.<br>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006).<br>TWA: 10 mg/m³ 8 hours.<br>ACGIH TLV (United States, 1/2023).<br>TWA: 2.5 mg/m³ 8 hours. Form: respirable fraction, finescale particles | 2-(2-butoxyethoxy)ethanol | ACGIH TLV (United States, 1/2023).<br>TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor |
| Product/ingredient name   | Exposure limit values   |   |                         |                       |                  |   |                           |   |
| titanium dioxide  | Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016).<br>TWA: 10 mg/m³ 8 hours.<br>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006).<br>TWA: 10 mg/m³ 8 hours.<br>ACGIH TLV (United States, 1/2023).<br>TWA: 2.5 mg/m³ 8 hours. Form: respirable fraction, finescale particles   |   |                         |                       |                  |   |                           |   |
| 2-(2-butoxyethoxy)ethanol   | ACGIH TLV (United States, 1/2023).<br>TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor   |   |                         |                       |                  |   |                           |   |
| Recommended monitoring procedures   | : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.   |   |                         |                       |                  |   |                           |   |
| 8.2 Exposure controls   |   |   |                         |                       |                  |   |                           |   |
| Appropriate engineering controls  | : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.  |   |                         |                       |                  |   |                           |   |
| Individual protection measures  |   |   |                         |                       |                  |   |                           |   |
| Hygiene measures  | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.   |   |                         |                       |                  |   |                           |   |
| Eye/face protection   | : Safety glasses with side shields.   |   |                         |                       |                  |   |                           |   |
| Skin protection   |   |   |                         |                       |                  |   |                           |   |
| Hand protection   | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. |   |                         |                       |                  |   |                           |   |
| English (GB) United Arab Emirates 6/14  |   |   |                         |                       |                  |   |                           |   |



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

|                                 |   |  |                    |
|---------------------------------|---|--|--------------------|
| Code                            | : 000001189977  | Date of issue/Date of revision   | : 19 February 2024 |
| PPG AQUACOVER ONE 645 WHITE     |   |  |                    |
|                                 | The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. |  |                    |
| Gloves                          | :   | For prolonged or repeated handling, use the following type of gloves:<br><br>Recommended: butyl rubber   |                    |
| Body protection                 | :   | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |                    |
| Other skin protection           | :   | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |                    |
| Respiratory protection          | :   |  |                    |
| Environmental exposure controls | :   | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |                    |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

| Appearance                                   |     |  |           |                 |    |    |        |                           |     |     |           |
|--|-----|--|-----------|-----------------|----|----|--------|---------------------------|-----|-----|-----------|
| Physical state                               | :   | Liquid.  |           |                 |    |    |        |                           |     |     |           |
| Colour                                       | :   | White.   |           |                 |    |    |        |                           |     |     |           |
| Odour  | :   | Faint odour.   |           |                 |    |    |        |                           |     |     |           |
| Odour threshold                              | :   | Not available.   |           |                 |    |    |        |                           |     |     |           |
| Melting point/freezing point                 | :   | May start to solidify at the following temperature: 0°C (32°F) This is based on data for the following ingredient: water. Weighted average: -2.75°C (27.1°F)               |           |                 |    |    |        |                           |     |     |           |
| Initial boiling point and boiling range      | :   | >37.78°C   |           |                 |    |    |        |                           |     |     |           |
| Flammability                                 | :   | Not available.   |           |                 |    |    |        |                           |     |     |           |
| Upper/lower flammability or explosive limits | :   | Greatest known range: Lower: 0.8% Upper: 9.4% (2-(2-butoxyethoxy)ethanol)  |           |                 |    |    |        |                           |     |     |           |
| Flash point                                  | :   | Closed cup: Not applicable.  |           |                 |    |    |        |                           |     |     |           |
| Auto-ignition temperature                    | :   | <table><tr><th>Ingredient name</th><th>°C</th><th>°F</th><th>Method</th></tr><tr><td>2-(2-butoxyethoxy)ethanol</td><td>210</td><td>410</td><td>DIN 51794</td></tr></table> |           | Ingredient name | °C | °F | Method | 2-(2-butoxyethoxy)ethanol | 210 | 410 | DIN 51794 |
| Ingredient name                              | °C  | °F   | Method    |                 |    |    |        |                           |     |     |           |
| 2-(2-butoxyethoxy)ethanol                    | 210 | 410  | DIN 51794 |                 |    |    |        |                           |     |     |           |
| Decomposition temperature                    | :   | Stable under recommended storage and handling conditions (see Section 7).  |           |                 |    |    |        |                           |     |     |           |
| pH   | :   | 8.4  |           |                 |    |    |        |                           |     |     |           |
| Viscosity                                    | :   | Kinematic (40°C): >21 mm²/s  |           |                 |    |    |        |                           |     |     |           |
| Viscosity                                    | :   | > 100 s (ISO 6mm)  |           |                 |    |    |        |                           |     |     |           |
| Solubility(ies)                              | :   |  |           |                 |    |    |        |                           |     |     |           |
| Media  |     | Result   |           |                 |    |    |        |                           |     |     |           |
| cold water                                   |     | Partially soluble  |           |                 |    |    |        |                           |     |     |           |
| Partition coefficient: n-octanol/ water      | :   | Not applicable.  |           |                 |    |    |        |                           |     |     |           |
| Vapour pressure                              | :   |  |           |                 |    |    |        |                           |     |     |           |

Code : 000001189977

Date of issue/Date of revision : 19 February 2024

PPG AQUACOVER ONE 645 WHITE

SECTION 9: Physical and chemical properties

|  | Ingredient name | Vapour Pressure at 20°C |     |        | Vapour pressure at 50°C |     |        |
|--|-----------------|-------------------------|-----|--------|-------------------------|-----|--------|
|  |                 | mm Hg                   | kPa | Method | mm Hg                   | kPa | Method |
|  | water           | 17.5                    | 2.3 |        |                         |     |        |

Evaporation rate

: 0.003 (2-(2-butoxyethoxy)ethanol) compared with butyl acetate

Relative density

: 1.2

Vapour density

: Highest known value: 5.6 (Air = 1) (2-(2-butoxyethoxy)ethanol).

Explosive properties

: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties

: Product does not present an oxidizing hazard.

Particle characteristics

Median particle size

: Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

|   |   |
|---|---|
| 10.1 Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.  |
| 10.2 Chemical stability                 | : The product is stable.  |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.   |
| 10.4 Conditions to avoid                | : When exposed to high temperatures may produce hazardous decomposition products.<br>Refer to protective measures listed in sections 7 and 8. |
| 10.5 Incompatible materials             | : Keep away from the following materials to prevent strong exothermic reactions:<br>oxidising agents, strong alkalis, strong acids.           |
| 10.6 Hazardous decomposition products   | : Depending on conditions, decomposition products may include the following materials:<br>carbon oxides metal oxide/oxides                    |

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name  | Result                          | Species | Dose       | Exposure |
|--|---------------------------------|---------|------------|----------|
| 2-(2-butoxyethoxy)ethanol  | LD50 Dermal                     | Rabbit  | 2700 mg/kg | -        |
|  | LD50 Oral                       | Rat     | 4500 mg/kg | -        |
| 3-iodo-2-propynyl butylcarbamate   | LC50 Inhalation Dusts and mists | Rat     | 0.67 mg/l  | 4 hours  |
|  | LD50 Dermal                     | Rabbit  | >2 g/kg    | -        |
| reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt | LD50 Oral                       | Rat     | 1470 mg/kg | -        |
|  | LC50 Inhalation Dusts and mists | Rat     | 0.047 mg/l | 4 hours  |
| 1,2-benzisothiazol-3(2H)-one   | LC50 Inhalation Dusts and mists | Rat     | 0.4 mg/l   | 4 hours  |



|                             |                |                                |                    |
|-----------------------------|----------------|--------------------------------|--------------------|
| Code                        | : 000001189977 | Date of issue/Date of revision | : 19 February 2024 |
| PPG AQUACOVER ONE 645 WHITE |                |                                |                    |

SECTION 11: Toxicological information

|  |                                 |        |            |         |
|--|---------------------------------|--------|------------|---------|
| pyrithione zinc<br><br>reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | LD50 Oral                       | Rat    | 1020 mg/kg | -       |
|  | LC50 Inhalation Dusts and mists | Rat    | 0.14 mg/l  | 4 hours |
|  | LD50 Dermal                     | Rabbit | >2 g/kg    | -       |
|  | LD50 Oral                       | Rat    | 177 mg/kg  | -       |
|  | LD50 Oral                       | Rat    | 53 mg/kg   | -       |

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

| Product/ingredient name                             | Result                 | Species | Score | Exposure | Observation |
|---|------------------------|---------|-------|----------|-------------|
| 3-iodo-2-propynyl butylcarbamate<br>pyrithione zinc | Eyes - Severe irritant | Rabbit  | -     | -        | -           |
|   | Eyes - Cornea opacity  | Rabbit  | 4     | 24 hours | 24 hours    |

Conclusion/Summary

Skin : There are no data available on the mixture itself.  
Eyes : There are no data available on the mixture itself.  
Respiratory : There are no data available on the mixture itself.

Sensitisation

| Product/ingredient name      | Route of exposure | Species    | Result      |
|------------------------------|-------------------|------------|-------------|
| 1,2-benzisothiazol-3(2H)-one | skin              | Guinea pig | Sensitising |

Conclusion/Summary

Skin : There are no data available on the mixture itself.  
Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

| Product/ingredient name   | Category   | Route of exposure | Target organs   |
|---|------------|-------------------|-----------------|
| 3-iodo-2-propynyl butylcarbamate<br>reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt<br>pyrithione zinc | Category 1 | -                 | larynx<br>liver |
|   | Category 2 | -                 |                 |
|   | Category 1 | -                 | -               |

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

|                             |                |                                |                    |
|-----------------------------|----------------|--------------------------------|--------------------|
| Code                        | : 000001189977 | Date of issue/Date of revision | : 19 February 2024 |
| PPG AQUACOVER ONE 645 WHITE |                |                                |                    |

SECTION 11: Toxicological information

- Inhalation : No known significant effects or critical hazards.
- Ingestion : No known significant effects or critical hazards.
- Skin contact : No known significant effects or critical hazards.
- Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation : No specific data.
- Ingestion : No specific data.
- Skin contact : No specific data.
- Eye contact : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects : Not available.
- Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects : Not available.
- Potential delayed effects : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary : Not available.
- General : No known significant effects or critical hazards.
- Carcinogenicity : No known significant effects or critical hazards.
- Mutagenicity : No known significant effects or critical hazards.
- Reproductive toxicity : No known significant effects or critical hazards.
- Other information : Not available.

Contains isothiazolinones. May cause allergic reaction.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name          | Result                   | Species                          | Exposure |
|----------------------------------|--------------------------|----------------------------------|----------|
| 3-iodo-2-propynyl butylcarbamate | Acute EC50 0.186 mg/l    | Daphnia - <i>Daphnia magna</i>   | 48 hours |
|                                  | Fresh water              |                                  |          |
|                                  | Acute LC50 0.067 mg/l    | Fish                             | 96 hours |
| 1,2-benzisothiazol-3(2H)-one     | Chronic NOEC 0.049 mg/l  | Fish                             | 96 hours |
|                                  | Acute EC50 0.11 mg/l     | Algae                            | 72 hours |
|                                  | Acute EC50 2.9 mg/l      | Daphnia                          | 48 hours |
| pyrithione zinc                  | Acute LC50 2.15 mg/l     | Fish                             | 96 hours |
|                                  | Chronic NOEC 0.0403 mg/l | Algae                            | 72 hours |
|                                  | Acute EC50 5.513 µg/l    | Algae - <i>Nitzschia pungens</i> | 96 hours |
|                                  | Marine water             |                                  |          |
|                                  | Acute LC50 0.0082 mg/l   | Daphnia                          | 48 hours |
|                                  | Chronic NOEC 1.889 µg/l  | Algae - <i>Nitzschia</i>         | 96 hours |

|                             |                |                                |                    |
|-----------------------------|----------------|--------------------------------|--------------------|
| Code                        | : 000001189977 | Date of issue/Date of revision | : 19 February 2024 |
| PPG AQUACOVER ONE 645 WHITE |                |                                |                    |

SECTION 12: Ecological information

|  |  |                           |         |
|--|--|---------------------------|---------|
|  | Marine water<br>Chronic NOEC 0.0027 mg/l | <i>pungens</i><br>Daphnia | 21 days |
|--|--|---------------------------|---------|

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

| Product/ingredient name                             | Test | Result                    | Dose | Inoculum |
|---|------|---------------------------|------|----------|
| 3-iodo-2-propynyl butylcarbamate<br>pyrithione zinc | -    | 25 % - Inherent - 28 days | -    | -        |
|   | -    | 39 % - 28 days            | -    | -        |

Conclusion/Summary : There are no data available on the mixture itself.

| Product/ingredient name          | Aquatic half-life | Photolysis       | Biodegradability |
|----------------------------------|-------------------|------------------|------------------|
| 3-iodo-2-propynyl butylcarbamate | -                 | -                | Inherent         |
| 1,2-benzisothiazol-3(2H)-one     | -                 | -                | Readily          |
| pyrithione zinc                  | -                 | 50%; < 28 day(s) | Not readily      |

12.3 Bioaccumulative potential

| Product/ingredient name      | LogP <sub>ow</sub> | BCF | Potential |
|------------------------------|--------------------|-----|-----------|
| 2-(2-butoxyethoxy)ethanol    | 1                  | -   | Low       |
| 1,2-benzisothiazol-3(2H)-one | 0.7                | -   | Low       |
| pyrithione zinc              | 0.9                | 0.9 | Low       |

12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

|                             |                |                                |                    |
|-----------------------------|----------------|--------------------------------|--------------------|
| Code                        | : 000001189977 | Date of issue/Date of revision | : 19 February 2024 |
| PPG AQUACOVER ONE 645 WHITE |                |                                |                    |

SECTION 13: Disposal considerations

European waste catalogue (EWC)

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

|                                 | ADR/RID         | IMDG            | IATA            |
|---------------------------------|-----------------|-----------------|-----------------|
| 14.1 UN number or ID number     | Not regulated.  | Not regulated.  | Not regulated.  |
| 14.2 UN proper shipping name    | -               | -               | -               |
| 14.3 Transport hazard class(es) | -               | -               | -               |
| 14.4 Packing group              | -               | -               | -               |
| 14.5 Environmental hazards      | No.             | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable. | Not applicable. |

Additional information

ADR/RID : None identified.  
IMDG : None identified.  
IATA : None identified.

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information


15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)  
[Annex XIV - List of substances subject to authorisation](#)  
[Annex XIV](#)  
None of the components are listed.  
[Substances of very high concern](#)  
None of the components are listed.  
[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#) : Not applicable.  
[Other national and international regulations.](#)  
[Explosive precursors](#) : Not applicable.  
[Ozone depleting substances \(1005/2009/EU\)](#)  
Not listed.

[Biocidal products regulation](#) : Contains a biocidal product; C(M)IT/MIT (3:1)

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

 Indicates information that has changed from previously issued version.

[Abbreviations and acronyms](#)

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number

[Full text of abbreviated H statements](#)

: H301 Toxic if swallowed.  
H302 Harmful if swallowed.  
H310 Fatal in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H331 Toxic if inhaled.  
H360D May damage the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
EUH071 Corrosive to the respiratory tract.

[Full text of classifications \[CLP/GHS\]](#)

|                             |                |                                |                    |
|-----------------------------|----------------|--------------------------------|--------------------|
| Code                        | : 000001189977 | Date of issue/Date of revision | : 19 February 2024 |
| PPG AQUACOVER ONE 645 WHITE |                |                                |                    |

SECTION 16: Other information

|                   |   |
|-------------------|---|
| : Acute Tox. 1    | ACUTE TOXICITY - Category 1                                     |
| Acute Tox. 2      | ACUTE TOXICITY - Category 2                                     |
| Acute Tox. 3      | ACUTE TOXICITY - Category 3                                     |
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Acute 1   | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1                  |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1                 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2                 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3                 |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                  |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                  |
| Repr. 1B          | REPRODUCTIVE TOXICITY - Category 1B                             |
| Skin Corr. 1C     | SKIN CORROSION/IRRITATION - Category 1C                         |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                          |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                                 |
| Skin Sens. 1A     | SKIN SENSITISATION - Category 1A                                |
| STOT RE 1         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| STOT RE 2         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |

History

|                                 |                    |
|---------------------------------|--------------------|
| Date of issue/ Date of revision | : 19 February 2024 |
| Date of previous issue          | : 11 January 2024  |
| Prepared by                     | : EHS              |
| Version                         | : 1.05             |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.