SAFETY DATA SHEET

United Arab Emirates

: 2.03

Date of issue/Date of revision

: 28 February 2024 Version

undertaking	
1.1 Product identifier Product name	
Product name Product code	: SIGMAGUARD CSF 585 BASE : 00256987
Other means of identifica Not available.	tion
1.2 Relevant identified use	s of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
1.3 Details of the supplier of	of the safety data sheet
Sigma Paint Saudi Arabia L PO Box 7509 Dammam 31472 Saudi Arabia Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34	td.
e-mail address of person responsible for this SDS	: ndpic@sfda.gov.sa
1.4 Emergency telephone number	: 00966 138473100 extn 1001

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture **Product definition** : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Skin Irrit. 2, H315

Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements				
Hazard pictograms		¥2		
Signal word	: Warning			
		English (GB)	United Arab Emirates	

1/13

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU))
2020/878	

Code : 00256987	Date of issue/Date of revision	: 28 February 2024
SIGMAGUARD CSF 585 BASE		

SECTION 2: Hazards identification

Hazard statements	 Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapour. Wash thoroughly after handling.
Response	: Collect spillage.
Storage	: Not applicable.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P273, P261, P264, P391, P501
Hazardous ingredients	 bis-[4-(2,3-epoxipropoxi)phenyl]propane 1,6-Hexanediol, reaction products with epichlorohydrin Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine
Supplemental label elements	: Contains epoxy constituents. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	nents
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
bis-[4-(2,3-epoxipropoxi) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
1,6-Hexanediol, reaction products with epichlorohydrin	REACH #: 01-2119463471-41 CAS: 933999-84-9	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]
		English	(GB) United Arab Er	mirates	2/13

_	ode GMAGUAR	: 00256987 D CSF 585 BA	ASE		Date of issue/Date of rev	vision	: 28 February 202	24
S	ECTION	3: Compo	osition/inforr	mation on	ingredients			
C	octadecanoi	c acid,	REACH #:	<1.0	Skin Sens. 1B, H317	-	[1]	

12-hydroxy-, reaction products with ethylenediamine	REACH #: 01-2119979085-27 EC: 309-629-8 CAS: 100545-48-0	<1.0	Aquatic Chronic 3, H412	-	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

This mixture contains \geq 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effec	ts
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>ioms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Conforms to Regulation (EC) 2020/878	No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU)
Code : 00256987	Date of issue/Date of revision : 28 February 2024
SIGMAGUARD CSF 585 BASE	E
SECTION 4: First aid	measures
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
SECTION 5: Firefight	ing measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising fi	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
SECTION 6: Acciden	tal release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

4/13

 Code
 : 00256987
 Date of issue/Date of revision
 : 28 February 2024

SIGMAGUARD CSF 585 BASE

SECTION 6: Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Code : 00256987	Date of issue/Date of revision	: 28 February 2024
SIGMAGUARD CSF 585 BASE		

Product/ingredi	ent name	Exposure limit values		
Talc , not containing asbestiform fibres titanium dioxide		 Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016). TWA: 2 mg/m³ 8 hours. Form: measured as respirable fraction of the aerosol Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006). TWA: 2 mg/m³ 8 hours. ACGIH TLV (United States, 1/2023). TWA: 2 mg/m³ 8 hours. Form: Respirable Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016). TWA: 10 mg/m³ 8 hours. Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 7/2016). TWA: 10 mg/m³ 8 hours. Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006). TWA: 10 mg/m³ 8 hours. Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006). TWA: 10 mg/m³ 8 hours. ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m³ 8 hours. Form: respirable fraction, finescale particles 		
Recommended monitoring procedures	Standard EN 68 by inhalation to strategy) Europ application and biological agents requirements fo agents) Referen	Id be made to monitoring standards, such as the following: European 99 (Workplace atmospheres - Guidance for the assessment of exposur chemical agents for comparison with limit values and measurement bean Standard EN 14042 (Workplace atmospheres - Guide for the use of procedures for the assessment of exposure to chemical and s) European Standard EN 482 (Workplace atmospheres - General r the performance of procedures for the measurement of chemical nce to national guidance documents for methods for the determination ubstances will also be required.		
.2 Exposure controls Appropriate engineering controls	: Good general ve contaminants.	entilation should be sufficient to control worker exposure to airborne		
ndividual protection meas	ures			
Hygiene measures	eating, smoking Appropriate tech Contaminated w contaminated cl	rearms and face thoroughly after handling chemical products, before and using the lavatory and at the end of the working period. Inniques should be used to remove potentially contaminated clothing. Work clothing should not be allowed out of the workplace. Wash othing before reusing. Ensure that eyewash stations and safety se to the workstation location.		
Eye/face protection Skin protection	: Chemical splash	h goggles.		
Hand protection	worn at all times necessary. Cor during use that the noted that the the glove manufactu protection time of frequently repea (breakthrough ti When only brief (breakthrough ti	ant, impervious gloves complying with an approved standard should be swhen handling chemical products if a risk assessment indicates this i nsidering the parameters specified by the glove manufacturer, check the gloves are still retaining their protective properties. It should be me to breakthrough for any glove material may be different for differen urers. In the case of mixtures, consisting of several substances, the of the gloves cannot be accurately estimated. When prolonged or ated contact may occur, a glove with a protection class of 6 me greater than 480 minutes according to EN 374) is recommended. contact is expected, a glove with a protection class of 2 or higher me greater than 30 minutes according to EN 374) is recommended. check that the final choice of type of glove selected for handling this		

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves

: butyl rubber

Conforms to Regulation (EC 2020/878) No	. 1907/2006 (REACH), Annex II, as amended by Commissio	on Regulation (EU)
Code : 00256987		Date of issue/Date of revision	: 28 February 2024
SIGMAGUARD CSF 585 BAS	Ε		
Body protection	:	Personal protective equipment for the body should be selected performed and the risks involved and should be approved by handling this product.	
Other skin protection		Appropriate footwear and any additional skin protection meas based on the task being performed and the risks involved and specialist before handling this product.	
Respiratory protection	:		
Environmental exposure controls	:	Emissions from ventilation or work process equipment should they comply with the requirements of environmental protectio cases, fume scrubbers, filters or engineering modifications to will be necessary to reduce emissions to acceptable levels.	n legislation. In some

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>								
Physical state	:	Liquid.						
Colour	1	Various						
Odour	:	Characteristic.						
Odour threshold	:	Not available.						
Melting point/freezing point	:	May start to solidify a based on data for the Weighted average: 3	following	ingredie				
nitial boiling point and boiling range	:	>37.78°C						
Flammability	:	Not available.						
Upper/lower flammability or explosive limits	:	Not available.						
Flash point	:	Closed cup: 130°C						
Auto-ignition temperature	:	Not available.						
Decomposition temperature	:	Stable under recomm	nended st	orage an	d handling co	onditions	(see Sec	tion 7).
рН	:	Not applicable. insolu	ıble in wa	ter.				
/iscosity	:	Kinematic (40°C): >2	1 mm²/s					
Viscosity	:	60 - 100 s (ISO 6mm)					
Solubility(ies)	:							
Media		Result						
cold water		Not soluble						
Partition coefficient: n-octanol water	/:	Not applicable.						
Vapour pressure	:		Vapour Pressure at 20°C		Vapour pressure at 50°C			
		Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
		bis-[4-(2,3-epoxipropoxi) phenyl]propane	<0.000075006	<0.00001				
Evaporation rate	1	Not available.						
Relative density	:	1.41						
verative defisity	:	Highest known value	: 11.7 (A	r = 1) (bi	s-[4-(2,3-epc	xipropox	i)phenyl]p	oropane).
			not explos	ive, but th	ne formation	of an exp	olosible m	nixture of
Vapour density Explosive properties	:	The product itself is r vapour or dust with a						

Code : 00256987	Date of issue/Date of revision : 28 February 2024
SIGMAGUARD CSF 585 BA	SE
SECTION 9: Physic	al and chemical properties
Particle characteristics	
Median particle size	: Not applicable.
9.2 Other information	
No additional information.	
SECTION 10: Stabil	ity and reactivity
SECTION 10: Stabil 10.1 Reactivity	ity and reactivity : No specific test data related to reactivity available for this product or its ingredients.
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous
decomposition products: Depending on conditions, decomposition products may include the following materials:
carbon oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxi)phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
1,6-Hexanediol, reaction products with epichlorohydrin	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-
	LD50 Oral	Rat - Male, Female	2189 mg/kg	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	LC50 Inhalation Dusts and mists	Rat	5.05 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Eyes

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Oedema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-
Conclusion/Summary					·
Skin : There are	no data available on the r	nixture itself			

:	There are no data available on the mixture itself.	

Respiratory : There are no data available on the mixture itself.

English (GB) United Arab Emirates

Code: 00256987Date of issue/Date of revision: 28 February 2024SIGMAGUARD CSF 585 BASE

SECTION 11: Toxicological information

Sensitisation

Sensitisation				
Product/ingred	lient name	Route of exposure	Species	Result
	•		Mouse Guinea pig	Sensitising Sensitising
Conclusion/Summary				
Skin	: There are no data avai	lable on the mixtur	e itself.	
Respiratory	: There are no data avai	lable on the mixtur	e itself.	
Mutagenicity				
Conclusion/Summary	: There are no data avai	lable on the mixtur	e itself.	
Carcinogenicity				
Conclusion/Summary	: There are no data avai	lable on the mixtur	e itself.	
Reproductive toxicity				
Conclusion/Summary	: There are no data avai	lable on the mixtur	e itself.	
Teratogenicity				
Conclusion/Summary	: There are no data avai	lable on the mixtur	e itself.	
Specific target organ toxicit	<u>y (single exposure)</u>			
Not available.				
Specific target organ toxicit	<u>y (repeated exposure)</u>			
Not available.				
Aspiration hazard				
Not available.				
Information on likely routes of exposure	: Not available.			
Potential acute health effect	<u>ts</u>			
Inhalation	: No known significant e	ffects or critical ha	zards.	
Ingestion	: No known significant et	ffects or critical ha	zards.	
Skin contact	: Causes skin irritation.	May cause an alle	rgic skin reaction.	
Eye contact	: Causes serious eye irri	tation.		
Symptoms related to the ph	<u>ysical, chemical and toxi</u>	cological charact	teristics	
Inhalation	: No specific data.			
Ingestion	: No specific data.			
Skin contact	: Adverse symptoms ma irritation redness	y include the follow	wing:	
Eye contact	: Adverse symptoms ma pain or irritation watering redness	ly include the follow	wing:	
Delayed and immediate effe	<u>cts as well as chronic eff</u>	ects from short a	ind long-term exposition	ure
Short term exposure Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
Long term exposure				

Code	: 00256987	Date of issue/Date of revision	: 28 February 2024
SIGMAGUAR	D CSF 585 BASE		

SECTION 11: Toxicological information

	5
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	<u>cts</u>
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Other information	: Not available.
Sanding and grinding dusts ma	ay be harmful if inhaled.
11.2 Information on other ha	zards
11.2.1 Endooring disrupting	a proportion

11.2.1 Endocrine disrupting properties

11.2.2 Other information

Not available.

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia</i> <i>magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
1,6-Hexanediol, reaction products with epichlorohydrin	Acute EC50 47 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 30 mg/l Fresh water	Fish	96 hours
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	Acute EC50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 >10 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 >10 mg/l	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary

: There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
1,6-Hexanediol, reaction products with epichlorohydrin	OECD 301D Ready Biodegradability - Closed Bottle Test	47 % - Not readily - 28 days	-	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	301D Ready Biodegradability - Closed Bottle Test	22 % - 28 days	-	-

English (GB) United Arab Emirates

Code: 00256987Date of issue/Date of revision: 28 February 2024SIGMAGUARD CSF 585 BASE

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1,6-Hexanediol, reaction products with epichlorohydrin Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	-	-	Not readily Not readily Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,6-Hexanediol, reaction products with epichlorohydrin	0.822	-	Low
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	>5.86	-	High

12.4 Mobility in soil

Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered wher recycling is not feasible.

Conforms 2020/878	to Regulation (EC) No. 1907/200	6 (REACH), Annex II, as amended by Commission	n Regulation (EU)
Code	: 00256987	Date of issue/Date of revision	: 28 February 2024
SIGMAGU	JARD CSF 585 BASE		

SECTION 13: Disposal considerations

Type of packaging		European waste catalogue (EWC)
Container	15 01 06	mixed packaging
Special precautions	taken when h Empty contai	and its container must be disposed of in a safe way. Care should be nandling emptied containers that have not been cleaned or rinsed out. ners or liners may retain some product residues. Avoid dispersal of spilt runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)		
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	111	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

Additional information

ADR/RID	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Tunnel code	: (-)
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IATA	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
14.6 Special pr user	ecautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport according to IN instruments	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU	l)
2020/878	

Code : 00256987 Date of issue/Date of revision

SIGMAGUARD CSF 585 BASE

: 28 February 2024

SECTION 15: Regulatory information

_	-			
None of the components a	are listed.			
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.			
Other national and interna	ational regulations.			
Explosive precursors	: Not applicable.			
Ozone depleting substan	<u>ces (1005/2009/EU)</u>			
Not listed.				
15.2 Chemical safety assessment	: No Chemical Safety Assessment has been carried out.			
SECTION 16: Other information				
Indicates information that	t has changed from previously issued version.			
Abbroviations and	ATE - Aguta Taviaity Estimate			

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number 		
Full text of abbreviated H statements	 H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. 		
Full text of classifications [CLP/GHS]	: Aquatic Chronic 2 Aquatic Chronic 3 Eye Irrit. 2 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1B	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1B	
<u>History</u>			
Date of issue/ Date of revision	: 28 February 2024		
Date of previous issue	: 20 December 2023		
Prepared by	: EHS		
Version	: 2.03		
Disclaimer			

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.