SAFETY DATA SHEET

Date of issue/Date of revision 4 March 2024

Version4.01

Section 1. Identification

Product code	: 00241599
Product name	: SIGMAGUARD CSF 650 BASE REDBROWN 6179
CAS number	: Not applicable.
EC number	: Mixture.
Product type	: Liquid.
Relevant identified uses	s of the substance or mixture and uses advised against
Product use	Coating. Professional applications, Used by spraying.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
Supplier's details	: PPG Yung Chi Coatings Co. Ltd Lot 219, Amata Street, Long Binh IZ Bien Hoa City, Dong Nai Province Vietnam Tel : +84 61 3936121/22
Emergency telephone number (with hours of operation)	: CHEMTREC +(84)-444581938 (CCN 17704)

Section 2. Hazards identification

Classification of the substance or mixture : SKIN IRKITATION - Category 2 Substance or mixture : EYE IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 2 AQUATIC TOXICITY (CHRONIC) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38% GHS label elements Image: Skin inflation Hazard pictograms : Signal word : Hazard statements : Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause an allergic skin genet. Precautionary statements Prevention : Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.		Viet Nam Page: 1/1
substance or mixture EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 2 AQUATIC TOXICITY (CHRONIC) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38% GHS label elements Hazard pictograms : Signal word : Hazard statements Hazard statements : Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.		environment. Avoid breathing vapor. Wash thoroughly after handling.
substance or mixture EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 2 AQUATIC TOXICITY (CHRONIC) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38% GHS label elements Image: Comparison of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38% Signal word : Image: Comparison of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38% Signal word : Image: Comparison of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38% Signal word : Image: Comparison of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38% Signal word : Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause an allergic skin reaction.	Precautionary statements	· · · · · · · · · · · · · · · · · · ·
substance or mixture EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 2 AQUATIC TOXICITY (CHRONIC) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38% GHS label elements Image: Comparison of the second of the seco		May cause an allergic skin reaction. Causes serious eye irritation.
substance or mixture EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 2 AQUATIC TOXICITY (CHRONIC) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38% GHS label elements Hazard pictograms :	-	0
substance or mixture EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 2 AQUATIC TOXICITY (CHRONIC) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38% GHS label elements EYE IRRITATION - Category 2A	Signal word	: Warning
substance or mixtureEYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 2 AQUATIC TOXICITY (CHRONIC) - Category 2 	Hazard pictograms	
substance or mixtureEYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 2 AQUATIC TOXICITY (CHRONIC) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the	GHS label elements	
	Classification of the substance or mixture	SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 2 AQUATIC TOXICITY (CHRONIC) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

Viet Nam Page: 1/11

Product code 00241599

Date of issue 4 March 2024

Version 4.01

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

Section 2. Hazards identification

Response	:	Collect spillage. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Routes of entry	:	Not available.
Other hazards which do not result in classification	:	None known.
	_	

Section 3. Composition/information on ingredients

CAS number/other identifiers

CAS number	: Not applicable.
EC number	: Mixture.

Ingredient name	CAS number	Chemical formula	%
Ms-[4-(2,3-epoxipropoxi)phenyl]propane 1,6-bis(2,3-epoxypropoxy)hexane benzyl alcohol Talc , not containing asbestiform fibres	1675-54-3 16096-31-4 100-51-6 14807-96-6	C21-H24-O4 C12H22O4 C7-H8-O 3Mg-O.4Si-O2. H2-O	≥25 - ≤50 ≤10 ≤10 ≤5

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed				
Potential acute health effects				
Eye contact	: Causes serious eye irritation.			
Inhalation	: No known significant effects or critical hazards.			
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.			
Ingestion	: No known significant effects or critical hazards.			

Viet Nam Page: 2/11

Version 4.01

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

Section 4. First aid measures

<u>Over-exposure signs/symptoms</u>					
Eye contact	Adverse symptoms may include the following: pain or irritation watering redness				
Inhalation	No specific data.				
Skin contact	Adverse symptoms may include the following: irritation redness				
Ingestion	No specific data.				
Indication of immediate med	Indication of immediate medical attention and special treatment needed, if necessary				
Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.				
Specific treatments	No specific treatment.				
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitati Wash contaminated clothing thoroughly with water before removing it, or wear gloves.				

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media		
Suitable extinguishing media	lse an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	lone known.	
Specific hazards arising from the chemical	n a fire or if heated, a pressure increase will occur and the container may burs 'his material is toxic to aquatic life with long lasting effects. Fire water ontaminated with this material must be contained and prevented from being ischarged to any waterway, sewer or drain.	st.
Hazardous thermal decomposition products	ecomposition products may include the following materials: arbon oxides alogenated compounds netal oxide/oxides	
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incidenter is a fire. No action shall be taken involving any personal risk or without uitable training.	dent if
Special protective equipment for fire-fighters	ire-fighters should wear appropriate protective equipment and self-contained reathing apparatus (SCBA) with a full face-piece operated in positive pressure node.	

Version 4.01

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handlin	ā
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

Section 7. Handling and storage

Conditions for safe storage,	1	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in
including any		accordance with local regulations. Store in original container protected from direct
incompatibilities		sunlight in a dry, cool and well-ventilated area, away from incompatible materials
		(see Section 10) and food and drink. Keep container tightly closed and sealed until
		ready for use. Containers that have been opened must be carefully resealed and
		kept upright to prevent leakage. Do not store in unlabeled containers. Use
		appropriate containment to avoid environmental contamination. See Section 10 for
		incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	Exposure limits		
Talc , not containing asbestif	s Ministry of Health (Viet N a TWA: 3 mg/m ³ 8 hours. Fo dust TWA: 1 mg/m ³ 8 hours. Fo dust TWA: 2 mg/m ³ 8 hours. Fo concentration	orm: inhalable orm: respirable		
Recommended monitoring procedures	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.			
Appropriate engineering controls	d general ventilation should be sufficient to control worker exp aminants.	osure to airborne		
Environmental exposure controls	sions from ventilation or work process equipment should be o comply with the requirements of environmental protection leg s, fume scrubbers, filters or engineering modifications to the pment will be necessary to reduce emissions to acceptable le	islation. In some process		
ndividual protection measur				
Hygiene measures	h hands, forearms and face thoroughly after handling chemic g, smoking and using the lavatory and at the end of the worki opriate techniques should be used to remove potentially cont aminated work clothing should not be allowed out of the work aminated clothing before reusing. Ensure that eyewash static vers are close to the workstation location.	ing period. aminated clothing place. Wash		
Eye/face protection	nical splash goggles.			
Skin protection				
Hand protection	nical-resistant, impervious gloves complying with an approve orn at all times when handling chemical products if a risk ass s necessary. Considering the parameters specified by the glo k during use that the gloves are still retaining their protective Id be noted that the time to breakthrough for any glove mater rent for different glove manufacturers. In the case of mixtures ral substances, the protection time of the gloves cannot be ac	essment indicates ove manufacturer properties. It ial may be s, consisting of		
	nated.			

Version 4.01

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

Section 8. Exposure controls/personal protection

-	
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance				
Physical state	1	Liquid.		
Color	1	Various		
Odor	1	Aromatic. [Slight]		
Odor threshold	1	Not available.		
рН	1	Not applicable.		
Melting point	1	Not available.		
Boiling point	1	>37.78°C (>100°F)		
Flash point	1	Closed cup: 100°C (212°F)		
Evaporation rate	1	Not available.		
Flammability (solid, gas)	1	Not available.		
Lower and upper explosive (flammable) limits	:	Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)		
Vapor pressure	:	Not available.		
Vapor density	1	Not available.		
Relative density	1	1.4		
Solubility(ies)		Media Result		
oolubility(les)	1	cold water Not soluble		
Partition coefficient: n- octanol/water	:	Not applicable.		
Auto-ignition temperature	1	426°C (798.8°F)		
Decomposition temperature	1	Not available.		
Viscosity	:	Kinematic (40°C): >21 mm²/s		
Viscosity	:	60 - 100 s (ISO 6mm)		

Section 10. Stability and reactivity

Reactivity	1	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.

Product code 00241599

Date of issue 4 March 2024

Version 4.01

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

Section 10. Stability and reactivity

Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity Product/ingredient name Result **Species** Dose **Exposure** bis-[4-(2,3-epoxipropoxi) 23000 mg/kg LD50 Dermal Rabbit _ phenyl]propane LD50 Oral Rat 15000 mg/kg benzyl alcohol LC50 Inhalation Dusts and mists Rat >4178 mg/m³ 4 hours LD50 Dermal Rabbit 2000 mg/kg _ LD50 Oral Rat 1.23 g/kg : There are no data available on the mixture itself. **Conclusion/Summary** Irritation/Corrosion Broduct/ingr с. di. D .14 . 6 Ĺ Oh

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

Conclusion/Summary

Skin : There are no data available on the mixture itse	elf.
--------------------------------------------------------	------

- : There are no data available on the mixture itself. Eyes : There are no data available on the mixture itself.
- Respiratory

Sensitization

Product/ingredient name	Route of exposure	Species	Result	
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitizing	
Skin Respiratory		o data available on the n o data available on the n		
<u>Mutagenicity</u> Conclusion/Summary	: There are n	o data available on the n	nixture itself.	
Carcinogenicity Conclusion/Summary	: There are n	o data available on the n	nixture itself.	
<u>Reproductive toxicity</u> Conclusion/Summary	: There are n	o data available on the n	nixture itself.	
			Viot Nam	Page: 7/11

Version 4.01

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

Section 11. Toxicological information

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Carcinogenicity

Name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

Information on the likely routes of exposure	-	Not available.
Potential acute health effects		
Eye contact	:	Causes serious eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

. . .

Eye contact	:	Adverse symptoms may include the following:
-		pain or irritation
		watering
		redness
Inhalation	÷	No specific data.
Skin contact	1	Adverse symptoms may include the following:
		irritation
		redness
Ingestion	÷	No specific data.
Delayed and immediate effect	ts	and also chronic effects from short and long term exposure
Short term exposure		
Potential immediate	:	There are no data available on the mixture itself.
effects		
Potential delayed effects	:	There are no data available on the mixture itself.
<u>Long term exposure</u>		
Potential immediate	:	There are no data available on the mixture itself.
effects		
Potential delayed effects	:	There are no data available on the mixture itself.
Potential chronic health eff	ect	<u>s</u>
r otentiar enrome neattrent		
General		Once sensitized, a severe allergic reaction may occur when subsequently exposed

: No known significant effects or critical hazards.

Version 4.01

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

Section 11. Toxicological information

Mutagenicity

- : No known significant effects or critical hazards.
- **Reproductive toxicity**
- : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Øral	11602.41 mg/kg
Dermal	17611.26 mg/kg
Inhalation (dusts and mists)	5.72 mg/l

Other information

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
øs-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
L	Chronic NOEC 0.3 mg/l	Daphnia	21 days

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
øs-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily
benzyl alcohol	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
	0.822	-	Low
benzyl alcohol	0.87	-	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

Additional information

UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
Special prec	autions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in	bulk according : Not applicable.

to IMO instruments

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Circular no. 05/1999/TT-BYT

Ingredient name	Category	Notes
1-chloro-2,3-epoxypropane	Category 2	

Toxic classification (TCVN : 4

3164-79)

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 4 March 2024
Date of previous issue	: 3/1/2024
Version	: 4.01
Prepared by	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	: Not available.

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.