## SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to GHS UN rev. 7

Date of issue/Date of revision 4 March 2024 Version 6.02

### Section 1. Identification

Product code	: 00140725
Product name	: SIGMAGUARD CSF 650 BASE OFFWHITE
Product type	: Liquid.
Other means of identification Not available.	
Relevant identified uses of th	e substance or mixture and uses advised against
Product use	<ul> <li>Coating. Professional applications, Used by spraying.</li> </ul>
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
Company/undertaking identification	: PPG Industries Sales, Inc. and PPG Coatings (Philippines), Inc. 3rd Floor First Life Center 174 Salcedo St., Legaspi Village Makati City 1229, Philippines Tel # 00632- 752-6773/ Fax # 00632-752-6771
Emergency telephone number	: CHEMTREC +(63) 2-395-3308 (CCN 17704)

### Section 2. Hazards identification

Classification of the substance or mixture	: SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC HAZARD (ACUTE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38%
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

### Section 2. Hazards identification

Response	:	Collect spillage. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	1	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not	:	None known.

result in classification

### Section 3. Composition/information on ingredients

Substance/mixture

.. .

: Mixture

#### CAS number/other identifiers

CAS number : Not applicable.		
Ingredient name	%	CAS number
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1,6-bis(2,3-epoxypropoxy)hexane benzyl alcohol Talc , not containing asbestiform fibres	25 - <50 5 - <10 5 - <10 3 - <5	1675-54-3 16096-31-4 100-51-6 14807-96-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

Description of necessa	ary first aid measures
Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

Potential acute health ef	fects
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sy	mptoms

### Section 4. First aid measures

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation
	redness
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

0	0
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	<ul> <li>Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides</li> </ul>
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protect	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is
For emergency responders	<ul> <li>inadequate. Put on appropriate personal protective equipment.</li> <li>If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".</li> </ul>

### Product name SIGMAGUARD CSF 650 BASE OFFWHITE

### Section 6. Accidental release measures

Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

Precautions for safe handling	L	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name Talc , not containing asbestiform fibres		Exposure limits
		TLV (Philippines, 4/2016). TLV: 20 mppf 8 hours. Form: Dust
procedures		o appropriate monitoring standards. Reference to s for methods for the determination of hazardous ired.

### Section 8. Exposure controls/personal protection

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**Appearance Physical state** : Liquid. Color : Various Odor : Aromatic. [Slight] **Odor threshold** : Not available. Melting point/freezing point : Not available. : >37.78°C (>100°F) Boiling point, initial boiling point, and boiling range Flammability : Not available.

#### Product name SIGMAGUARD CSF 650 BASE OFFWHITE Section 9. Physical and chemical properties Lower and upper explosive : Not available. (flammable) limits : Closed cup: 100°C (212°F) **Flash point** : 426°C (798.8°F) **Auto-ignition temperature Decomposition temperature** : Not available. pН : Not applicable. Viscosity : Kinematic (40°C): >21 mm<sup>2</sup>/s : 60 - 100 s (ISO 6mm) Viscosity Media Result Solubility(ies) ż cold water Not soluble Partition coefficient: n-: Not applicable. octanol/water Vapor pressure ÷. Vapor Pressure at 20°C Vapor pressure at 50°C mm Hg **Ingredient name** kPa Method mm kPa Method Hg 0.067505535 0.009 1,6-bis (2,3-epoxypropoxy) hexane **Relative density** ŝ, 1.4 **Relative vapor density** Not available. ÷ **Particle characteristics** Median particle size : Not applicable. **Evaporation rate** : Not available. Section 10. Stability and reactivity **Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ofs-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m <sup>3</sup>	4 hours
-	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-

Conclusion/Summary	: There are no
Irritation/Corrosion	

Product/ingredient name	Result	Species	Score	Exposure	Observation
s-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

#### **Conclusion/Summary**

Skin : There are no data available on the mixture	itself.
---	---------

- **Eyes** : There are no data available on the mixture itself.
- Respiratory

: There are no data available on the mixture itself.

#### **Sensitization**

Product/ingredient name	Route of exposure	Species	Result			
øs-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitizing			
Conclusion/Summary						
Skin	: There are n	o data available on the mi	xture itself.			
Respiratory	: There are n	o data available on the mi	xture itself.			
<u>Mutagenicity</u>						
Conclusion/Summary	: There are n	o data available on the mi	xture itself.			
Carcinogenicity						
Conclusion/Summary	: There are n	: There are no data available on the mixture itself.				
Reproductive toxicity						
Conclusion/Summary	: There are no data available on the mixture itself.					
<b>Feratogenicity</b>						
Conclusion/Summary	: There are n	o data available on the mi	xture itself.			
Specific target organ toxici	ty (single expo	<u>sure)</u>				
Name		Category	Route of exposure	Target organs		
Talc , not containing asbesti	form fibres	Category 3	3 -	Respiratory tract		

irritation

### Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Name		Result
benzyl	alcohol	ASPIRATION HAZARD - Category 2

Information on the likely routes of exposure	1	Not available.
Potential acute health effects	5	
Eye contact	:	Causes serious eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	;	No known significant effects or critical hazards.
Symptoms related to the phy	<u>/sic</u>	cal, chemical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following:
-		pain or irritation
		watering
Inhalation		redness No specific data.
Skin contact		Adverse symptoms may include the following:
		irritation
		redness
Ingestion	÷	No specific data.
Delayed and immediate effect	<u>ts</u>	and also chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate	:	Not available.
effects		
Potential delayed effects	:	Not available.
Potential chronic health eff	ect	<u>s</u>
Not available.		
General	1	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.

#### Numerical measures of toxicity

Acute toxicity estimates

### Section 11. Toxicological information

0	
Route	ATE value
Øral	11602.41 mg/kg
Dermal Inhalation (dusts and mists)	17611.26 mg/kg 5.72 mg/l
	5.72 mg/

#### Other information

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

### Section 12. Ecological information

<b>T</b> -		_	4
	וצו	C	TV
	<i>,</i> ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		• •

Product/ingredient name	Result	Species	Exposure
pís-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Interpretended by the second seco	-	-	Not readily
benzyl alcohol	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
	0.822	-	Low
benzyl alcohol	0.87	-	Low

#### **Mobility in soil**

Soil/water partition: Not available.coefficient (Koc)

- Other adverse effects
- : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and

Philippines

### Section 13. Disposal considerations

runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

#### **Additional information**

UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

# Special precautions for user :Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

### Section 15. Regulatory information

#### International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Date of issue 4 March 2024

### Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 4 March 2024
Date of previous issue	: 3/1/2024
Version	: 6.02
Prepared by	: EHS
key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>

#### Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
AQUATIC HAZARD (ACUTE) - Category 2	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 2	Calculation method

#### ✓ Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.