

# SAFETY DATA SHEET



Date of issue/Date of revision

: 18 March 2024

Version

: 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMAFAST 205 BASE RAL 9002  
**Product code** : 000001162217  
**Product type** : Liquid.  
**Other means of identification** : 00242164; 00476216

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.  
**Use of the substance/mixture** : Coating.  
**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### Supplier

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture  
**Classification according to UK CLP/GHS**

Flam. Liq. 3, H226  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Skin Sens. 1, H317  
Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.  
See Section 16 for the full text of the H statements declared above.  
See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** :

Warning

|                             |                |                                |                 |
|-----------------------------|----------------|--------------------------------|-----------------|
| Code                        | : 000001162217 | Date of issue/Date of revision | : 18 March 2024 |
| SIGMAFAST 205 BASE RAL 9002 |                |                                |                 |

SECTION 2: Hazards identification

|  |   |
|--|---|
| Hazard statements  | : Flammable liquid and vapour.<br>Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye irritation.<br>Harmful to aquatic life with long lasting effects.   |
| <u>Precautionary statements</u>  |   |
| Prevention   | : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid breathing vapour. Wash thoroughly after handling. |
| Response   | : Not applicable.   |
| Storage  | : Not applicable.   |
| Disposal   | : Dispose of contents and container in accordance with all local, regional, national and international regulations.<br>P280, P210, P273, P261, P264, P501   |
| Supplemental label elements  | : Contains epoxy constituents. May produce an allergic reaction.  |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : Not applicable.   |
| <u>Special packaging requirements</u>  |   |
| Containers to be fitted with child-resistant fastenings  | : Not applicable.   |
| Tactile warning of danger  | : Not applicable.   |
| 2.3 Other hazards  |   |
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII                                  | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.   |
| Other hazards which do not result in classification  | : Prolonged or repeated contact may dry skin and cause irritation.  |

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

| Product/ingredient name                  | Identifiers  | %          | Classification   | Type    |
|--|--|------------|--|---------|
| xylene                                   | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7                        | ≥10 - ≤16  | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412 | [1] [2] |
| Epoxy Resin (700<MW<=1100)               | CAS: 25036-25-3  | ≥5.0 - ≤10 | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317  | [1]     |
| bis-[4-(2,3-epoxipropoxi)phenyl] propane | REACH #:<br>01-2119456619-26<br>EC: 216-823-5<br>CAS: 1675-54-3<br>Index: 603-073-00-2 | ≥5.0 - ≤10 | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Aquatic Chronic 2, H411   | [1]     |

English (GB)

United Kingdom (UK)

2/16

|                             |                |                                |                 |
|-----------------------------|----------------|--------------------------------|-----------------|
| Code                        | : 000001162217 | Date of issue/Date of revision | : 18 March 2024 |
| SIGMAFAST 205 BASE RAL 9002 |                |                                |                 |

SECTION 3: Composition/information on ingredients

|   |  |             |  |         |
|---|--|-------------|--|---------|
| 2-methylpropan-1-ol                                 | REACH #:<br>01-2119484609-23<br>EC: 201-148-0<br>CAS: 78-83-1<br>Index: 603-108-00-1   | ≥1.0 - <3.0 | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>STOT SE 3, H336                              | [1] [2] |
| ethylbenzene  | REACH #:<br>01-2119489370-35<br>EC: 202-849-4<br>CAS: 100-41-4<br>Index: 601-023-00-4  | ≥1.0 - ≤5.0 | Flam. Liq. 2, H225<br>Acute Tox. 4, H332<br>STOT RE 2, H373<br>(hearing organs)<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412  | [1] [2] |
| trizinc bis(orthophosphate)                         | REACH #:<br>01-2119485044-40<br>EC: 231-944-3<br>CAS: 7779-90-0<br>Index: 030-011-00-6 | ≤1.0        | Aquatic Acute 1, H400 (M=1)<br>Aquatic Chronic 1, H410 (M=1)   | [1]     |
| Octadecanamide, N, N'-1,6-hexanediylbis[12-hydroxy- | CAS: 55349-01-4  | ≤0.30       | Skin Sens. 1, H317<br>Aquatic Chronic 4, H413<br><br><b>See Section 16 for the full text of the H statements declared above.</b> | [1]     |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

|                                    |   |
|------------------------------------|---|
| <b>Code</b> : 000001162217         | <b>Date of issue/Date of revision</b> : 18 March 2024 |
| <b>SIGMAFAST 205 BASE RAL 9002</b> |   |

**SECTION 4: First aid measures**

|  |   |
|--|---|
| <b>Ingestion</b>                           | : No known significant effects or critical hazards.   |
| <b><u>Over-exposure signs/symptoms</u></b> |   |
| <b>Eye contact</b>                         | : Adverse symptoms may include the following:<br>pain or irritation<br>watering<br>redness    |
| <b>Inhalation</b>                          | : No specific data.   |
| <b>Skin contact</b>                        | : Adverse symptoms may include the following:<br>irritation<br>redness<br>dryness<br>cracking |
| <b>Ingestion</b>                           | : No specific data.   |

**4.3 Indication of any immediate medical attention and special treatment needed**

|                            |   |
|----------------------------|---|
| <b>Notes to physician</b>  | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| <b>Specific treatments</b> | : No specific treatment.  |

**SECTION 5: Firefighting measures**

|  |  |
|--|--|
| <b>5.1 Extinguishing media</b>                                   |  |
| <b>Suitable extinguishing media</b>                              | : Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.   |
| <b>Unsuitable extinguishing media</b>                            | : Do not use water jet.  |
| <b>5.2 Special hazards arising from the substance or mixture</b> |  |
| <b>Hazards from the substance or mixture</b>                     | : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| <b>Hazardous combustion products</b>                             | : Decomposition products may include the following materials:<br>carbon oxides<br>metal oxide/oxides   |
| <b>5.3 Advice for firefighters</b>                               |  |
| <b>Special protective actions for fire-fighters</b>              | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.   |
| <b>Special protective equipment for fire-fighters</b>            | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.  |

**SECTION 6: Accidental release measures**

|  |   |
|--|---|
| <b>6.1 Personal precautions, protective equipment and emergency procedures</b> |   |
| <b>For non-emergency personnel</b>   | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |

|                                    |   |
|------------------------------------|---|
| <b>Code</b> : 000001162217         | <b>Date of issue/Date of revision</b> : 18 March 2024 |
| <b>SIGMAFAST 205 BASE RAL 9002</b> |   |

**SECTION 6: Accidental release measures**

|   |  |
|---|--|
| <b>For emergency responders</b>                                 | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".  |
| <b>6.2 Environmental precautions</b>                            | : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.   |
| <b>6.3 Methods and material for containment and cleaning up</b> |  |
| <b>Small spill</b>  | : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.   |
| <b>Large spill</b>  | : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |
| <b>6.4 Reference to other sections</b>                          | : See Section 1 for emergency contact information.<br>See Section 8 for information on appropriate personal protective equipment.<br>See Section 13 for additional waste treatment information.  |

**SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

|   |   |
|---|---|
| <b>7.1 Precautions for safe handling</b>      |   |
| <b>Protective measures</b>                    | : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| <b>Advice on general occupational hygiene</b> | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.   |

**7.2 Conditions for safe storage, including any incompatibilities**

|                             |                |                                |                 |
|-----------------------------|----------------|--------------------------------|-----------------|
| Code                        | : 000001162217 | Date of issue/Date of revision | : 18 March 2024 |
| SIGMAFAST 205 BASE RAL 9002 |                |                                |                 |

SECTION 7: Handling and storage

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

| Product/ingredient name | Exposure limit values  |
|-------------------------|--|
| xylene                  | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020). [xylene, o-,m-,p- or mixed isomers] Absorbed through skin.</b><br>STEL: 441 mg/m³ 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 220 mg/m³ 8 hours.<br>TWA: 50 ppm 8 hours. |
| 2-methylpropan-1-ol     |  |
| ethylbenzene            |  |

Biological exposure indices

| Product/ingredient name | Exposure indices |
|-------------------------|------------------|
| xylene                  | XYLENES          |

**Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure              | Value             | Population         | Effects  |
|-------------------------|------|-----------------------|-------------------|--------------------|----------|
| xylene                  | DNEL | Long term Oral        | 12.5 mg/kg bw/day | General population | Systemic |
|                         | DNEL | Long term Inhalation  | 65.3 mg/m³        | General population | Local    |
|                         | DNEL | Long term Inhalation  | 65.3 mg/m³        | General population | Systemic |
|                         | DNEL | Long term Dermal      | 125 mg/kg bw/day  | General population | Systemic |
|                         | DNEL | Long term Dermal      | 212 mg/kg bw/day  | Workers            | Systemic |
|                         | DNEL | Long term Inhalation  | 221 mg/m³         | Workers            | Local    |
|                         | DNEL | Long term Inhalation  | 221 mg/m³         | Workers            | Systemic |
|                         | DNEL | Short term Inhalation | 260 mg/m³         | General population | Local    |
|                         | DNEL | Short term Inhalation | 260 mg/m³         | General population | Systemic |
|                         | DNEL | Short term Inhalation | 442 mg/m³         | Workers            | Local    |
|                         |      |                       |                   |                    |          |
|                         |      |                       |                   |                    |          |



|                             |                |                                |                 |
|-----------------------------|----------------|--------------------------------|-----------------|
| Code                        | : 000001162217 | Date of issue/Date of revision | : 18 March 2024 |
| SIGMAFAST 205 BASE RAL 9002 |                |                                |                 |

SECTION 8: Exposure controls/personal protection

|   |      |                       |                    |                                |          |
|---|------|-----------------------|--------------------|--------------------------------|----------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | DNEL | Short term Inhalation | 442 mg/m³          | Workers                        | Systemic |
|   | DNEL | Long term Inhalation  | 12.25 mg/m³        | Workers                        | Systemic |
|   | DNEL | Short term Inhalation | 12.25 mg/m³        | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 8.33 mg/kg bw/day  | Workers                        | Systemic |
|   | DNEL | Short term Dermal     | 8.33 mg/kg bw/day  | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 3.571 mg/kg bw/day | General population [Consumers] | Systemic |
|   | DNEL | Short term Dermal     | 3.571 mg/kg bw/day | General population [Consumers] | Systemic |
|   | DNEL | Long term Oral        | 0.75 mg/kg bw/day  | General population [Consumers] | Systemic |
|   | DNEL | Short term Oral       | 0.75 mg/kg bw/day  | General population [Consumers] | Systemic |
|   | DNEL | Long term Dermal      | 89.3 µg/kg bw/day  | General population             | Systemic |
| 2-methylpropan-1-ol                     | DNEL | Long term Oral        | 0.5 mg/kg bw/day   | General population             | Systemic |
|   | DNEL | Long term Dermal      | 0.75 mg/kg bw/day  | Workers                        | Systemic |
|   | DNEL | Long term Inhalation  | 0.87 mg/m³         | General population             | Systemic |
|   | DNEL | Long term Inhalation  | 4.93 mg/m³         | Workers                        | Systemic |
|   | DNEL | Long term Inhalation  | 55 mg/m³           | General population             | Local    |
|   | DNEL | Long term Inhalation  | 310 mg/m³          | Workers                        | Local    |
|   | DMEL | Long term Inhalation  | 442 mg/m³          | Workers                        | Local    |
|   | DMEL | Short term Inhalation | 884 mg/m³          | Workers                        | Systemic |
|   | DNEL | Long term Oral        | 1.6 mg/kg bw/day   | General population             | Systemic |
|   | DNEL | Long term Inhalation  | 15 mg/m³           | General population             | Systemic |
| ethylbenzene                            | DNEL | Long term Inhalation  | 77 mg/m³           | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 180 mg/kg bw/day   | Workers                        | Systemic |
|   | DNEL | Short term Inhalation | 293 mg/m³          | Workers                        | Local    |
|   | DNEL | Long term Oral        | 0.83 mg/kg bw/day  | General population             | Systemic |
|   | DNEL | Long term Inhalation  | 2.5 mg/m³          | General population             | Systemic |
|   | DNEL | Long term Inhalation  | 5 mg/m³            | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | General population             | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
| trizinc bis(orthophosphate)             | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers                        | Systemic |

PNECs

| Product/ingredient name                 | Compartment Detail     | Value           | Method Detail            |
|---|------------------------|-----------------|--------------------------|
| xylene                                  | Fresh water            | 0.327 mg/l      | -                        |
|   | Marine water           | 0.327 mg/l      | -                        |
|   | Sewage Treatment Plant | 6.58 mg/l       | -                        |
|   | Fresh water sediment   | 12.46 mg/kg dwt | -                        |
|   | Marine water sediment  | 12.46 mg/kg dwt | -                        |
|   | Soil                   | 2.31 mg/kg      | -                        |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Fresh water            | 0.006 mg/l      | Assessment Factors       |
|   | Marine water           | 0.001 mg/l      | Assessment Factors       |
|   | Fresh water sediment   | 0.996 mg/kg dwt | Equilibrium Partitioning |
|   | Marine water sediment  | 0.1 mg/kg dwt   | Equilibrium Partitioning |
|   | Soil                   | 0.196 mg/kg dwt | Equilibrium Partitioning |
|   | Sewage Treatment Plant | 10 mg/l         | Assessment Factors       |
| 2-methylpropan-1-ol                     | Secondary Poisoning    | 11 mg/kg        | Assessment Factors       |
|   | Fresh water            | 0.4 mg/l        | Assessment Factors       |
|   | Marine water           | 0.04 mg/l       | Assessment Factors       |
|   | Sewage Treatment Plant | 10 mg/l         | Assessment Factors       |
|   | Fresh water sediment   | 1.56 mg/kg dwt  | Equilibrium Partitioning |
|   | Marine water sediment  | 0.156 mg/kg dwt | -                        |
| ethylbenzene                            | Soil                   | 0.076 mg/kg dwt | Equilibrium Partitioning |
|   | Fresh water            | 0.1 mg/l        | Assessment Factors       |
|   | Marine water           | 0.01 mg/l       | Assessment Factors       |
|   | Sewage Treatment Plant | 9.6 mg/l        | Assessment Factors       |
|   | Fresh water sediment   | 13.7 mg/kg dwt  | Equilibrium Partitioning |
|   | Fresh water sediment   | 13.7 mg/kg dwt  | Equilibrium Partitioning |

|                             |                |                                |                 |
|-----------------------------|----------------|--------------------------------|-----------------|
| Code                        | : 000001162217 | Date of issue/Date of revision | : 18 March 2024 |
| SIGMAFAST 205 BASE RAL 9002 |                |                                |                 |

SECTION 8: Exposure controls/personal protection

|                             |                        |                 |                          |
|-----------------------------|------------------------|-----------------|--------------------------|
| trizinc bis(orthophosphate) | Marine water sediment  | 1.37 mg/kg dwt  | Equilibrium Partitioning |
|                             | Soil                   | 2.68 mg/kg dwt  | Equilibrium Partitioning |
|                             | Secondary Poisoning    | 20 mg/kg        | -                        |
|                             | Fresh water            | 20.6 µg/l       | Sensitivity Distribution |
|                             | Marine water           | 6.1 µg/l        | Sensitivity Distribution |
|                             | Sewage Treatment Plant | 100 µg/l        | Assessment Factors       |
|                             | Fresh water sediment   | 117.8 mg/kg dwt | Sensitivity Distribution |
|                             | Marine water sediment  | 56.5 mg/kg dwt  | Equilibrium Partitioning |
|                             | Soil                   | 35.6 mg/kg dwt  | Sensitivity Distribution |
|                             |                        |                 |                          |

8.2 Exposure controls

- Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Individual protection measures
- Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection

: Chemical splash goggles.
- Skin protection
- Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.  
butyl rubber
- Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.



|                             |                |                                |                 |
|-----------------------------|----------------|--------------------------------|-----------------|
| Code                        | : 000001162217 | Date of issue/Date of revision | : 18 March 2024 |
| SIGMAFAST 205 BASE RAL 9002 |                |                                |                 |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state

Colour

Odour

Odour threshold

Melting point/freezing point

Initial boiling point and boiling range

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flash point

Auto-ignition temperature

Ingredient name

°C

°F

Method

1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich

405

761

ASTM E 659

pH

Viscosity

Solubility(ies)

Media

Result

cold water

Not soluble

Miscible with water

Partition coefficient: n-octanol/ water

Vapour pressure

Ingredient name

mm Hg

kPa

Method

2-methylpropan-1-ol

<12.00102

<1.6

DIN EN 13016-2

Vapour Pressure at 20°C

Vapour pressure at 50°C

mm Hg

kPa

Method

Relative density

Vapour density

Explosive properties

Oxidising properties

Particle characteristics

Median particle size

Not applicable.

Kinematic (room temperature): >400 mm²/s

Kinematic (40°C): >21 mm²/s

No.

Not applicable.

1.6

Highest known value: 15.4 (Air = 1) (1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich). Weighted average: 7.02 (Air = 1)

The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Product does not present an oxidizing hazard.

Not applicable.

|                             |                |                                |                 |
|-----------------------------|----------------|--------------------------------|-----------------|
| Code                        | : 000001162217 | Date of issue/Date of revision | : 18 March 2024 |
| SIGMAFAST 205 BASE RAL 9002 |                |                                |                 |

SECTION 10: Stability and reactivity

- 10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability : The product is stable.
- 10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.  
Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:  
oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following  
materials: carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name                     | Result                             | Species | Dose        | Exposure |
|---|------------------------------------|---------|-------------|----------|
| xylene                                      | LD50 Dermal                        | Rabbit  | 1.7 g/kg    | -        |
|   | LD50 Oral                          | Rat     | 4.3 g/kg    | -        |
| Epoxy Resin (700<MW<br><=1100)              | LD50 Dermal                        | Rat     | >2000 mg/kg | -        |
|   | LD50 Oral                          | Rat     | >2000 mg/kg | -        |
| bis-[4-(2,3-epoxipropoxi)<br>phenyl]propane | LD50 Dermal                        | Rabbit  | 23000 mg/kg | -        |
|   | LD50 Oral                          | Rat     | 15000 mg/kg | -        |
| 2-methylpropan-1-ol                         | LC50 Inhalation Vapour             | Rat     | 24.6 mg/l   | 4 hours  |
|   | LD50 Dermal                        | Rabbit  | 2460 mg/kg  | -        |
|   | LD50 Oral                          | Rat     | 2830 mg/kg  | -        |
| ethylbenzene                                | LC50 Inhalation Vapour             | Rat     | 17.8 mg/l   | 4 hours  |
|   | LD50 Dermal                        | Rabbit  | 17.8 g/kg   | -        |
|   | LD50 Oral                          | Rat     | 3.5 g/kg    | -        |
| trizinc bis(orthophosphate)                 | LC50 Inhalation Dusts and<br>mists | Rat     | >5.7 mg/l   | 4 hours  |
|   | LD50 Oral                          | Rat     | >5000 mg/kg | -        |

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

| Product/ingredient name                 | Oral (mg/<br>kg) | Dermal<br>(mg/kg) | Inhalation<br>(gases)<br>(ppm) | Inhalation<br>(vapours)<br>(mg/l) | Inhalation<br>(dusts<br>and mists)<br>(mg/l) |
|---|------------------|-------------------|--------------------------------|-----------------------------------|--|
| SIGMAFAST 205 BASE RAL 9002             | N/A              | 12527.0           | N/A                            | 73.0                              | N/A  |
| xylene                                  | 4300             | 1700              | N/A                            | 11                                | N/A  |
| bis-[4-(2,3-epoxipropoxi)phenyl]propane | 15000            | 23000             | N/A                            | N/A                               | N/A  |
| 2-methylpropan-1-ol                     | 2830             | 2460              | N/A                            | 24.6                              | N/A  |
| ethylbenzene                            | 3500             | 17800             | N/A                            | 17.8                              | N/A  |

Irritation/Corrosion

|                             |                |                                |                 |
|-----------------------------|----------------|--------------------------------|-----------------|
| Code                        | : 000001162217 | Date of issue/Date of revision | : 18 March 2024 |
| SIGMAFAST 205 BASE RAL 9002 |                |                                |                 |

SECTION 11: Toxicological information

| Product/ingredient name                 | Result                             | Species | Score | Exposure        | Observation |
|---|------------------------------------|---------|-------|-----------------|-------------|
| xylene                                  | Skin - Moderate irritant           | Rabbit  | -     | 24 hours 500 mg | -           |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Eyes - Mild irritant               | Rabbit  | -     | 24 hours        | -           |
|   | Eyes - Redness of the conjunctivae | Rabbit  | 0.4   | 24 hours        | -           |
|   | Skin - Oedema                      | Rabbit  | 0.5   | 4 hours         | -           |
|   | Skin - Erythema/Eschar             | Rabbit  | 0.8   | 4 hours         | -           |
|   | Skin - Mild irritant               | Rabbit  | -     | 4 hours         | -           |

**Conclusion/Summary** : Not available.

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

**Sensitisation**

| Product/ingredient name                 | Route of exposure | Species | Result      |
|---|-------------------|---------|-------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | skin              | Mouse   | Sensitising |

**Conclusion/Summary**

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

**Mutagenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Carcinogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Reproductive toxicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Teratogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| xylene                  | Category 3 | -                 | Respiratory tract irritation |
| 2-methylpropan-1-ol     | Category 3 | -                 | Respiratory tract irritation |
|                         | Category 3 | -                 | Narcotic effects             |

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs  |
|-------------------------|------------|-------------------|----------------|
| ethylbenzene            | Category 2 | -                 | hearing organs |

Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| xylene                  | ASPIRATION HAZARD - Category 1 |
| ethylbenzene            | ASPIRATION HAZARD - Category 1 |

**Information on likely routes of exposure** : Not available.

Potential acute health effects

|                             |                |                                |                 |
|-----------------------------|----------------|--------------------------------|-----------------|
| Code                        | : 000001162217 | Date of issue/Date of revision | : 18 March 2024 |
| SIGMAFAST 205 BASE RAL 9002 |                |                                |                 |

SECTION 11: Toxicological information

|              |   |
|--------------|---|
| Eye contact  | : Causes serious eye irritation.  |
| Inhalation   | : No known significant effects or critical hazards.                                   |
| Skin contact | : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction. |
| Ingestion    | : No known significant effects or critical hazards.                                   |

Symptoms related to the physical, chemical and toxicological characteristics

|              |   |
|--------------|---|
| Eye contact  | : Adverse symptoms may include the following:<br>pain or irritation<br>watering<br>redness    |
| Inhalation   | : No specific data.   |
| Skin contact | : Adverse symptoms may include the following:<br>irritation<br>redness<br>dryness<br>cracking |
| Ingestion    | : No specific data.   |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

|                             |                  |
|-----------------------------|------------------|
| Short term exposure         |                  |
| Potential immediate effects | : Not available. |
| Potential delayed effects   | : Not available. |
| Long term exposure          |                  |
| Potential immediate effects | : Not available. |
| Potential delayed effects   | : Not available. |

|                                  |   |
|----------------------------------|---|
| Potential chronic health effects |   |
| Not available.                   |   |
| Conclusion/Summary               | : Not available.  |
| General                          | : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| Carcinogenicity                  | : No known significant effects or critical hazards.   |
| Mutagenicity                     | : No known significant effects or critical hazards.   |
| Reproductive toxicity            | : No known significant effects or critical hazards.   |

|                   |                  |
|-------------------|------------------|
| Other information | : Not available. |
|-------------------|------------------|

SECTION 12: Ecological information

| 12.1 Toxicity                            |                                 |                                     |          |
|--|---------------------------------|-------------------------------------|----------|
| Product/ingredient name                  | Result                          | Species                             | Exposure |
| bis-[4-(2,3-epoxipropoxy) phenyl]propane | Acute LC50 1.8 mg/l Fresh water | Daphnia - <i>daphnia magna</i>      | 48 hours |
| 2-methylpropan-1-ol ethylbenzene         | Chronic NOEC 0.3 mg/l           | Daphnia                             | 21 days  |
|  | Acute EC50 1100 mg/l            | Daphnia                             | 48 hours |
|  | Acute EC50 1.8 mg/l Fresh water | Daphnia                             | 48 hours |
| trizinc bis(orthophosphate)              | Chronic NOEC 1 mg/l Fresh water | Daphnia - <i>Ceriodaphnia dubia</i> | -        |
|  | Acute LC50 0.112 mg/l           | Fish                                | 96 hours |
|  | Chronic NOEC 0.026 mg/l         | Fish                                | 30 days  |

|                    |                  |
|--------------------|------------------|
| Conclusion/Summary | : Not available. |
|--------------------|------------------|

|                                    |   |
|------------------------------------|---|
| <b>Code</b> : 000001162217         | <b>Date of issue/Date of revision</b> : 18 March 2024 |
| <b>SIGMAFAST 205 BASE RAL 9002</b> |   |

SECTION 12: Ecological information

12.2 Persistence and degradability

| Product/ingredient name | Test | Result                   | Dose | Inoculum |
|-------------------------|------|--------------------------|------|----------|
| ethylbenzene            | -    | 79 % - Readily - 10 days | -    | -        |

Conclusion/Summary : Not available.

| Product/ingredient name                 | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| xylene                                  | -                 | -          | Readily          |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | -                 | -          | Not readily      |
| ethylbenzene                            | -                 | -          | Readily          |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| xylene                  | 3.12               | 7.4 to 18.5 | Low       |
| 2-methylpropan-1-ol     | 1                  | -           | Low       |
| ethylbenzene            | 3.6                | 79.43       | Low       |

12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Waste catalogue

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | Waste catalogue          |
|-------------------|--------------------------|
| Container         | 15 01 06 mixed packaging |

|                             |                |                                |                 |
|-----------------------------|----------------|--------------------------------|-----------------|
| Code                        | : 000001162217 | Date of issue/Date of revision | : 18 March 2024 |
| SIGMAFAST 205 BASE RAL 9002 |                |                                |                 |

SECTION 13: Disposal considerations

|                     |   |
|---------------------|---|
| Special precautions | : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |
|---------------------|---|

SECTION 14: Transport information

|                                 | ADR/RID         | ADN             | IMDG            | IATA            |
|---------------------------------|-----------------|-----------------|-----------------|-----------------|
| 14.1 UN number                  | UN1263          | UN1263          | UN1263          | UN1263          |
| 14.2 UN proper shipping name    | PAINT           | PAINT           | PAINT           | PAINT           |
| 14.3 Transport hazard class(es) | 3               | 3               | 3               | 3               |
| 14.4 Packing group              | III             | III             | III             | III             |
| 14.5 Environmental hazards      | No.             | Yes.            | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

|                        |  |
|------------------------|--|
| Additional information |  |
| ADR/RID                | : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.   |
| Tunnel code            | : (D/E)  |
| ADN                    | : The product is only regulated as an environmentally hazardous substance when transported in tank vessels. This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1. |
| IMDG                   | : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.   |
| IATA                   | : None identified.   |

|   |   |
|---|---|
| 14.6 Special precautions for user                   | : <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. |
| 14.7 Transport in bulk according to IMO instruments | : Not available.  |

SECTION 15: Regulatory information

|   |               |
|---|---------------|
| 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture | UK (GB)/REACH |
| Annex XIV - List of substances subject to authorisation   |               |
| Annex XIV   |               |
| None of the components are listed.  |               |
| Substances of very high concern   |               |
| None of the components are listed.  |               |
| Ozone depleting substances  |               |
| Not listed.   |               |



|                             |                |                                |                 |
|-----------------------------|----------------|--------------------------------|-----------------|
| Code                        | : 000001162217 | Date of issue/Date of revision | : 18 March 2024 |
| SIGMAFAST 205 BASE RAL 9002 |                |                                |                 |

SECTION 15: Regulatory information

**Annex XVII - Restrictions** : Not applicable.  
**on the manufacture,  
placing on the market  
and use of certain  
dangerous substances,  
mixtures and articles**

**Seveso Directive**  
This product is controlled under the Seveso Directive.  
**Danger criteria**  
**Category**  
P5c

SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and  
acronyms** : ATE = Acute Toxicity Estimate  
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and  
Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019  
No. 720 and amendments  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = GB CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

| Classification   | Justification   |
|--|---|
| Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Aquatic Chronic 3, H412 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method |

Full text of abbreviated H statements

|      |  |
|------|--|
| H225 | Highly flammable liquid and vapour.                                |
| H226 | Flammable liquid and vapour.                                       |
| H304 | May be fatal if swallowed and enters airways.                      |
| H312 | Harmful in contact with skin.                                      |
| H315 | Causes skin irritation.  |
| H317 | May cause an allergic skin reaction.                               |
| H318 | Causes serious eye damage.   |
| H319 | Causes serious eye irritation.                                     |
| H332 | Harmful if inhaled.  |
| H335 | May cause respiratory irritation.                                  |
| H336 | May cause drowsiness or dizziness.                                 |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life.  |
| H410 | Very toxic to aquatic life with long lasting effects.              |
| H411 | Toxic to aquatic life with long lasting effects.                   |
| H412 | Harmful to aquatic life with long lasting effects.                 |
| H413 | May cause long lasting harmful effects to aquatic life.            |

Full text of classifications

|                                    |                       |                                       |                        |
|------------------------------------|-----------------------|---------------------------------------|------------------------|
| <b>Code</b>                        | <b>: 000001162217</b> | <b>Date of issue/Date of revision</b> | <b>: 18 March 2024</b> |
| <b>SIGMAFAST 205 BASE RAL 9002</b> |                       |                                       |                        |

**SECTION 16: Other information**

|                   |   |
|-------------------|---|
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Acute 1   | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1                  |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1                 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2                 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3                 |
| Aquatic Chronic 4 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4                 |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                  |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                  |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                  |
| Flam. Liq. 2      | FLAMMABLE LIQUIDS - Category 2                                  |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                  |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                          |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                                 |
| STOT RE 2         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3   |

**History**

|  |                                 |
|--|---------------------------------|
| <b>Date of issue/ Date of revision</b> | <b>: 18 March 2024</b>          |
| <b>Date of previous issue</b>          | <b>: No previous validation</b> |
| <b>Prepared by</b>                     | <b>: EHS</b>                    |
| <b>Version</b>                         | <b>: 1</b>                      |

**Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*