

SAFETY DATA SHEET



SIGMADUR 2800HS BASE G10

Date of issue 20 March 2024

Version 1

1. Product and company identification

Product name : SIGMADUR 2800HS BASE G10
Product code : 00477000
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Coating.

Uses advised against : Not applicable.

Supplier's details : PPG PMC Japan Co., Ltd., 8F, Shintetsu Bldg., 1-1, Daikaidori 1-chome, Kobe
652-0803 Japan; Tel: +81-78-574-2777

**Emergency telephone
number** : 078 574 2777

2. Hazards identification

GHS Classification : FLAMMABLE LIQUIDS - Category 3
EYE IRRITATION - Category 2B
CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract
irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -
Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category 3
HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD -
Category 3

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Flammable liquid and vapor.
Causes eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause cancer.
May damage fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure. (respiratory
organs)

2. Hazards identification

Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage

: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

CAS number : Not applicable.

CSCL number : Not available.

Ingredient name	%	CAS number	CSCL
Butyl acetate	20 - <25	123-86-4	2-731
titanium dioxide (excluding nanoparticle)	20 - <25	13463-67-7	1-558; 5-5225
barium sulfate	7 - <10	7727-43-7	1-89
Propylene glycol monomethyl ether acetate	3 - <5	108-65-6	2-3144
Fatty acids, C14-18 and C16-18-unsatd., maleated	0.5 - <1	85711-46-2	Not available.
Xylene	0.5 - <1	1330-20-7	3-3; 3-60
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.2 - <0.5	41556-26-7	5-5501
Ethylbenzene	0.2 - <0.5	100-41-4	3-28; 3-60
titanium dioxide (excluding nanoparticle)	0.2 - <0.5	13463-67-7	1-558; 5-5225
propylidynetrimethanol	0.1 - <0.2	77-99-6	2-245
Silica silicon dioxide containing crystalline and amorphous	0.1 - <0.2	7631-86-9	1-548
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	0.1 - <0.2	82919-37-7	5-5593

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

4. First aid measures

Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.

- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon oxides
sulfur oxides
halogenated compounds
metal oxide/oxides

The fluoropolymer resins used in this coating begin to decompose, very slowly, at temperatures above 625°F (330°C). Thermal decomposition is more rapid at temperatures above 750°F (400°C). Above 800°F (425°C) fluoropolymer resins give off small amounts of tetrafluoroethylene / hexafluoropropylene / perisofluorobutylene / carbonyl fluoride / hydrogen fluoride. These are toxic and if inhaled, in sufficient quantities, may be harmful. The actual decomposition products depend on temperature and the amount of oxygen.

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6. Accidental release measures

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

8. Exposure controls/personal protection

Ingredient name	Exposure limits
Butyl acetate	Japan Society for Occupational Health (Japan, 9/2022). OEL-M: 475 mg/m ³ 8 hours. OEL-M: 100 ppm 8 hours.
Xylene	Industrial Safety and Health Act (Japan, 6/2020). TWA: 150 ppm 8 hours.
	Industrial Safety and Health Act (Japan, 6/2020). [xylene] TWA: 50 ppm 8 hours.
	Japan Society for Occupational Health (Japan, 9/2022). OEL-M: 50 ppm 8 hours. OEL-M: 217 mg/m ³ 8 hours.
Ethylbenzene	Japan Society for Occupational Health (Japan, 9/2022). Absorbed through skin. OEL-M: 87 mg/m ³ 8 hours. OEL-M: 20 ppm 8 hours.
	Industrial Safety and Health Act (Japan, 6/2020). TWA: 20 ppm 8 hours.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection : Safety glasses with side shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves : butyl rubber

8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Odor** : Characteristic.
- Boiling point** : >37.78°C (>100°F)
- Flash point** : Closed cup: 23°C (73.4°F)
- Relative density** : 1.43

Solubility(ies)

Media	Result
cold water	Not soluble

10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
- Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides sulfur oxides halogenated compounds metal oxide/oxides
The fluoropolymer resins used in this coating begin to decompose, very slowly, at temperatures above 625°F (330°C). Thermal decomposition is more rapid at temperatures above 750°F (400°C). Above 800°F (425°C) fluoropolymer resins give off small amounts of tetrafluoroethylene / hexafluoropropylene / perisofluorobutylene / carbonyl fluoride / hydrogen fluoride. These are toxic and if inhaled, in sufficient quantities, may be harmful. The actual decomposition products depend on temperature and the amount of oxygen. Proper ventilation should be used at all curing temperatures.

10. Stability and reactivity

11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Butyl acetate	LC50 Inhalation Vapor	Rat	>21.1 mg/l	4 hours
	LC50 Inhalation Vapor	Rat	2000 ppm	4 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10.768 g/kg	-
titanium dioxide (excluding nanoparticle)	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
barium sulfate	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
Propylene glycol monomethyl ether acetate	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapor	Rat	30 mg/l	4 hours
Xylene	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	6190 mg/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	LD50 Oral	Rat	4.3 g/kg	-
	LD50 Oral	Rat	3.125 g/kg	-
Ethylbenzene	LC50 Inhalation Vapor	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
titanium dioxide (excluding nanoparticle)	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
propylidyntrimethanol	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rabbit	10 g/kg	-
	LD50 Oral	Rat	14000 mg/kg	-
Silica silicon dioxide containing crystalline and amorphous	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 Oral	Rat	3.125 g/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

11. Toxicological information

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Butyl acetate	Category 3	-	Respiratory tract irritation
Propylene glycol monomethyl ether acetate	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
Fatty acids, C14-18 and C16-18-unsatd., maleated	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
Xylene	Category 1	-	central nervous system (CNS), kidneys, liver, respiratory organs
Ethylbenzene	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
Silica silicon dioxide containing crystalline and amorphous	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
titanium dioxide (excluding nanoparticle)	Category 1	-	respiratory organs
barium sulfate	Category 1	-	respiratory organs
Xylene	Category 1	-	nervous system, respiratory organs
Ethylbenzene	Category 1	-	hearing organs, nervous system
titanium dioxide (excluding nanoparticle)	Category 1	-	respiratory organs
Silica silicon dioxide containing crystalline and amorphous	Category 1	-	immune system, kidneys, respiratory organs

Aspiration hazard

Name	Result
Xylene	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : Defatting to the skin. May cause skin dryness and irritation.

Ingestion : Can cause central nervous system (CNS) depression.

11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

General : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

11. Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMADUR 2800HS BASE G10	N/A	15751.5	N/A	N/A	N/A
Butyl acetate	10768	N/A	N/A	N/A	N/A
barium sulfate	N/A	2500	N/A	N/A	N/A
Propylene glycol monomethyl ether acetate	6190	N/A	N/A	30	N/A
Xylene	4300	1700	N/A	11	N/A
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	3125	N/A	N/A	N/A	N/A
Ethylbenzene	3500	17800	N/A	17.8	N/A
propylidynetrimethanol	14000	10000	N/A	N/A	N/A
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3125	N/A	N/A	N/A	N/A

Other information :

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Butyl acetate	Acute LC50 18 mg/l	Fish	96 hours
titanium dioxide (excluding nanoparticle)	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
Propylene glycol monomethyl ether acetate	Acute LC50 134 mg/l Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
Ethylbenzene	Acute EC50 1.8 mg/l Fresh water	Daphnia	48 hours
titanium dioxide (excluding nanoparticle)	Chronic NOEC 1 mg/l Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	-
propylidynetrimethanol	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
Silica silicon dioxide containing crystalline and amorphous	Acute LC50 >1000 mg/l	Fish	96 hours
	Acute EC50 2.2 g/L Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 >10000 mg/l	Fish	96 hours
	Chronic NOEC 12.5 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Butyl acetate	TEPA and OECD 301D	83 % - Readily - 28 days	-	-
Propylene glycol monomethyl ether acetate	-	83 % - Readily - 28 days	-	-
Ethylbenzene	-	79 % - Readily - 10 days	-	-

12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Butyl acetate	-	-	Readily
Propylene glycol	-	-	Readily
monomethyl ether acetate	-	-	
Xylene	-	-	Readily
Ethylbenzene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Butyl acetate	2.3	-	Low
Propylene glycol	1.2	-	Low
monomethyl ether acetate			
Xylene	3.12	7.4 to 18.5	Low
Ethylbenzene	3.6	79.43	Low
propylidynetrimethanol	-0.47	-	Low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	UN	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3
Packing group	III	III	III

14. Transport information

Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

UN : None identified.

IMDG : None identified.

IATA : None identified.

Special precautions for user : **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

15. Regulatory information

Fire Service Law

Category	Substance name/Type	Danger category	Signal word	Designated quantity
Category IV	Class II petroleum	III	Flammable - Keep Fire Away	1000 L

Pollutant Release and Transfer Registers (PRTR)

None of the components are listed.

Industrial Safety and Health Act

Ordinance on the Prevention of the Hazard due to Specified Chemical Substances

None of the components are listed.

Substance(s) requiring labelling

Ingredient name	%	Status	Reference number
Butyl acetate	≥20 - ≤30	Listed	181
Titanium(IV) oxide	≥20 - ≤30	Listed	191
Xylene	≤10	Listed	136
Ethylbenzene	≤10	Listed	70
Crystalline silica	≤10	Listed	165-2

Chemicals requiring notification

Ingredient name	%	Status	Reference number
Butyl acetate	≥20 - ≤30	Listed	181
Titanium(IV) oxide	≥20 - ≤30	Listed	191
Xylene	≤10	Listed	136
Ethylbenzene	≤10	Listed	70
Crystalline silica	≤10	Listed	165-2

Carcinogens based on Article 577-2 of the Ordinance on ISH

None of the components are listed.

15. Regulatory information

Mutagen

None of the components are listed.

Corrosive liquid	: Not listed
Occupational Safety and Health Law	: Inflammable
Regulations on the Prevention of Tetraalkyl Lead Poisoning	: Not listed
Harmful Substances Subject to Obtaining Permission for Manufacturing	: Not listed
Harmful Substances, Prohibited for Manufacturing	: Not listed
ISHL Enforcement Order Appendix 1 - Dangerous Substances	: Inflammable
Lead regulation	: Not listed
Organic solvents poisoning prevention	: Class 2

Poisonous and Deleterious Substances

None of the components are listed.

Chemical Substances Control Law (CSCL)

Ingredient name	%	Status	Reference number
Xylene	≤10	Priority assessment	125
Ethylbenzene	≤10	Priority assessment	50
Cumene	≤10	Priority assessment	126
2,2,4,4,6,6,8,8-Octamethyl-1,3,5,7,2,4,6,8-tetraoxatetrasilocane	≤10	Monitoring	40
Toluene	≤10	Priority assessment	46
2,6-Di-tert-butyl-4-methylphenol	≤10	Priority assessment	64
Benzene	≤10	Priority assessment	45
Acetaldehyde	≤10	Priority assessment	26
Formaldehyde	≤10	Priority assessment	25
Ethylene oxide	≤10	Priority assessment	19
1,4-Dioxane	≤10	Priority assessment	80
Chloromethane	≤10	Priority assessment	6

High Pressure Gas Control Law : Not available.

Explosives Control Law

None of the components are listed.

Law concerning prevention of pollution of the ocean : Not available.

Maritime Safety Law

Notification Regulating Transportation of Dangerous Materials by Sea

15. Regulatory information

None of the components are listed.

Container class

None of the components are listed.

JSOH Carcinogen : Group 2B

List of Specially Controlled Industrial Waste : Not listed

Japan inventory : At least one component is not listed.

Road law : Not available.

16. Other information

History

Date of issue/Date of revision : 20 March 2024

Date of previous issue : No previous validation

Version : 1

Prepared by : EHS

Key to abbreviations : ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
UN = United Nations

✔ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.