# **SAFETY DATA SHEET**



Date of issue/Date of revision 21 March 2024 Version 10.01

# Section 1. Identification of the substance/mixture and of the company/undertaking

Product code	:	00188976
Product name	:	SIGMAGLIDE 790 HARDENER
Other means of identification	:	Not available.
Product type	÷	Liquid.

Relevant identified uses of the substance or mixture and uses advised against		
Product use	Coating. Professional applications, Used by spraying.	
Uses advised against	: Product is not intended, labelled or packaged for consumer use.	
Supplier's details	: PPG Coatings (Thailand) Co., Ltd. 15 Rama 9 Road, Kwaeng Huamark, Khet Bangkapi, Bangkok 10240 Thailand T: 662-319-4190 #224 F: 662-319-4189	
Emergency telephone number (with hours of operation)	: CHEMTREC 001-800-13-203-9987 (CCN 17704)	

# Section 2. Hazards identification

Classification of the substance or mixture	: ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 5 SKIN CORROSION/IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1B GERM CELL MUTAGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 AQUATIC HAZARD (ACUTE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2

### Section 2. Hazards identification

Fercentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 3.1%

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 96.6%

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 96.6%

#### **GHS label elements** Hazard pictograms Signal word Danger **Hazard statements** : Harmful if swallowed. May be harmful in contact with skin. Causes severe skin burns and eve damage. May cause an allergic skin reaction. Suspected of causing genetic defects. May damage fertility or the unborn child. May cause damage to organs. (thymus) May cause damage to organs through prolonged or repeated exposure. (immune system) Toxic to aquatic life with long lasting effects. **Precautionary statements Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Collect spillage. IF exposed or concerned: Get medical advice or attention. IF Response exposed or if you feel unwell: Call a POISON CENTER or doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. Storage : Store locked up. **Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations. Other hazards which do not : Causes digestive tract burns. result in classification

# Section 3. Composition/information on ingredients

Substance/mixture

**CAS number/other identifiers** 

: Not applicable.

: Mixture

CAS number : Not applicable.		
Ingredient name	%	CAS number
triacetoxyethylsilane dibutyltin di(acetate) 1,1,3,3-Disiloxanetetrol, 1,3-diethyl-, tetraacetate	50-100 3 - <5 1- <3	17689-77-9 1067-33-0 122842-90-4

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

### Description of necessary first aid measures

Eye contact	<ul> <li>Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.</li> </ul>		
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.		
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>		
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.		
Most important sympto	ms/effects, acute and delayed		
Potential acute health	effects		
Eye contact	: Causes serious eye damage.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: Causes severe burns. May be harmful in contact with skin. May cause damage to organs following a single exposure in contact with skin. May cause an allergic skin reaction.		
Ingestion	: Harmful if swallowed. Corrosive to the digestive tract. Causes burns. May cause damage to organs following a single exposure if swallowed.		
Over-exposure signs/symptoms			
Eye contact	: Adverse symptoms may include the following: pain watering redness		
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations		

# Product name SIGMAGLIDE 790 HARDENER Section 4. First aid measures

Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	lical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

ion of first-aiders
 No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Product name SIGMAGLIDE 790 HARDENER

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
·		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	nt	May be harmful to the environment if released in large quantities. Collect spillage.

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section

13 for waste disposal.

### Section 7. Handling and storage

Precautions for safe
 Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Product name SIGMAGLIDE 790 HARDENER

# Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities	accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10
	for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

edient name	Exposure limits	
ityltin di(acetate)	ACGIH TLV (United States, 1/2023). [Tin, organic compounds as Sn] Absorbed through skin. STEL: 0.2 mg/m <sup>3</sup> , (as Sn) 15 minutes. TWA: 0.1 mg/m <sup>3</sup> , (as Sn) 8 hours.	
edures nat	rence should be made to appropriate monitoring standards. Reference to onal guidance documents for methods for the determination of hazardous stances will also be required.	
rols loca	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.	
the cas	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	
dual protection measures		
eat Apj Co cor	In hands, forearms and face thoroughly after handling chemical products, before ng, smoking and using the lavatory and at the end of the working period. Topriate techniques should be used to remove potentially contaminated clothing. taminated work clothing should not be allowed out of the workplace. Wash aminated clothing before reusing. Ensure that eyewash stations and safety vers are close to the workstation location.	
protection : Ch	mical splash goggles and face shield.	
protection		
be this che sho diff sev	mical-resistant, impervious gloves complying with an approved standard should orn at all times when handling chemical products if a risk assessment indicates is necessary. Considering the parameters specified by the glove manufacturer, ek during use that the gloves are still retaining their protective properties. It ald be noted that the time to breakthrough for any glove material may be rent for different glove manufacturers. In the case of mixtures, consisting of eral substances, the protection time of the gloves cannot be accurately mated.	
sev	eral substances, the protection time of the	

Version 10.01

Product name SIGMAGLIDE 790 HARDENER

# Section 8. Exposure controls/personal protection

Gloves	: nitrile neoprene
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

Appearance		
Physical state	:	Liquid.
Color	:	Not available.
Odor	:	Characteristic.
Odor threshold	:	Not available.
рН	1	insoluble in water.
Melting point	:	May start to solidify at the following temperature: 9°C (48.2°F) This is based on data for the following ingredient: dibutyltin di(acetate). Weighted average: 2.95°C (37.3°F)
Boiling point	:	>37.78°C (>100°F)
Flash point	:	Closed cup: 109°C (228.2°F)
Evaporation rate	:	Not available.
Flammability (solid, gas)	1	liquid
Lower and upper explosive (flammable) limits	1	Not available.
Vapor pressure	:	Highest known value: 0.1 kPa (0.8 mm Hg) (at 20°C) (triacetoxyethylsilane). Weighted average: 0.1 kPa (0.75 mm Hg) (at 20°C)
Relative density	1	1.15
Bulk Density (g/cm³)	:	1.18
Solubility(ies)		Media Result
Condumity (ics)	Ċ	cold water Not soluble
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	:	480°C
Decomposition temperature	:	Stable under recommended storage and handling conditions (see Section 7).
Viscosity	;	Kinematic (40°C): >21 mm²/s

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	<ul> <li>Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides</li> </ul>

# Section 11. Toxicological information

#### Information on toxicological effects

Product/ingredient name		Result	Species	Dose	Exposure
triacetoxyethylsilane		LD50 Oral	Rat	1.462 g/kg	-
dibutyltin di(acetate)		LD50 Dermal	Rabbit	2318 mg/kg	-
Conclusion/Summary	: There	are no data available on the	e mixture itself.		
Irritation/Corrosion					
Conclusion/Summary					
Skin	: There	are no data available on the	e mixture itself.		
Eyes	: There	are no data available on the	e mixture itself.		
Respiratory	: There	are no data available on the	e mixture itself.		
Sensitization					
Conclusion/Summary					
Skin	: There	are no data available on the	e mixture itself.		
Respiratory	: There	are no data available on the	e mixture itself.		
<u>Mutagenicity</u>					
Conclusion/Summary	: There	are no data available on the	e mixture itself.		
Carcinogenicity					
Conclusion/Summary	: There	are no data available on the	e mixture itself.		
Reproductive toxicity					
Conclusion/Summary	: There	are no data available on the	e mixture itself.		
Teratogenicity					
Conclusion/Summary	: There	are no data available on the	e mixture itself.		
Specific target organ toxic	city (sinal	e exposure)			

# Section 11. Toxicological information

Name	• •	Route of exposure	Target organs
dibutyltin di(acetate)	Category 1	oral	thymus

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
díbutyltin di(acetate)	Category 1	-	immune system

#### **Aspiration hazard**

Not available.

# Information on the likely : Not available. routes of exposure

#### Potential acute health effects

Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	<ul> <li>Causes severe burns. May be harmful in contact with skin. May cause damage to organs following a single exposure in contact with skin. May cause an allergic skin reaction.</li> </ul>
Ingestion	<ul> <li>Harmful if swallowed. Corrosive to the digestive tract. Causes burns. May cause damage to organs following a single exposure if swallowed.</li> </ul>

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain watering redness	
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations	
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations	

Product name SIGMAGLIDE 790 HARDENER

## Section 11. Toxicological information

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
General	: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: Suspected of causing genetic defects.
Reproductive toxicity	: May damage fertility or the unborn child.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
	1444.19 mg/kg
Dermal	2586.3 mg/kg

#### Other information

Causes digestive tract burns.

# Section 12. Ecological information

ŝ

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
díbutyltin di(acetate)	Acute EC10 3.1 mg/l Acute EC50 0.5 mg/l	Fish Algae	72 hours 72 hours
Conclusion/Summary	ry : There are no data available on the mixture itself.		

Persistence/degradability

Conclusion/Summary	: There are no data available on the mixture itself.			
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability	
díbutyltin di(acetate)	-	-	Not readily	

# Section 12. Ecological information

#### **Bioaccumulative potential**

Not available.

<u>Mobility in soil</u>	
Soil/water partition coefficient (Koc)	: Not available.
Other adverse effects	: No known significant effects or critical hazards.

### Section 13. Disposal considerations

```
Disposal methods
```

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	UN	IMDG	IATA
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8
Packing group	II	II	
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(dibutyltin di(acetate))	Not applicable.

#### **Additional information**

UN	: None identified.
IMDG	: The marine pollutant mark is not required when transported in sizes of $\leq 5$ L or $\leq 5$ kg.
ΙΑΤΑ	<ul> <li>The environmentally hazardous substance mark may appear if required by other transportation regulations.</li> </ul>

Product code 00188976

Date of issue 21 March 2024

Version 10.01

Product name SIGMAGLIDE 790 HARDENER

### Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

### Section 15. Regulatory information

#### Harmful Chemicals List

: Listed

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

#### International regulations

**Montreal Protocol** 

Not listed.

# Stockholm Convention on Persistent Organic Pollutants

Not listed.

# Section 16. Other information

#### **History**

<u>HISTOLA</u>	
Date of issue/Date of revision	: 21 March 2024
Date of previous issue	: 11/29/2023
Version	: 10.01
Prepared by	: EHS
Key to abbreviations	: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations
	af baaa ahaan waal fucus waxaana ka laasaal waxaalaa

#### ✓ Indicates information that has changed from previously issued version.

#### Notice to reader

# Section 16. Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.