# SAFETY DATA SHEET



Date of issue/Date of revision 21 March 2024

**Version 1** 

# **Section 1. Identification**

Product name : PSX-700=RAL 6009 K-7 NV

Product code : 19AE046405 Other means of : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Consumer applications.

Use of the substance/

mixture

identification

: Coating.

Uses advised against : Not applicable.

**Manufacturer** : Distribuidora Kroma S.A. de C.V.

Autopista México - Querétaro Km 33.5, No. 104

Lecheria, Tultitlán

Estado de México CP. 54940

Tel. (55)5864 0700, (55) 1669-1000 (México)

Emergency telephone

<u>number</u>

: (412) 434-4515 (U.S.) (514) 645-1320 (Canada)

SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

**Customer Service /** 

**Technical Phone Number**: 800 7126-639 (México)

# Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 92.2% (oral), 94.1% (dermal), 74.1% (inhalation)

**GHS label elements** 

Hazard pictograms :





United States Page: 1/14

Product name PSX-700=RAL 6009 K-7 NV

## Section 2. Hazards identification

Signal word

: Danger

**Hazard statements** 

: May cause an allergic skin reaction. Causes serious eye irritation.

May cause cancer.

Suspected of damaging fertility or the unborn child.

**Precautionary statements** 

**Prevention** 

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Wash thoroughly after handling.

Response

: IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**Storage** 

: Store locked up.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label

elements

: Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Emits toxic fumes when heated.

Hazards not otherwise classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Product name : PSX-700=RAL 6009 K-7 NV

Ingredient name	%	CAS number
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	≥20 - ≤50	30583-72-3
Wollastonite	≥10 - ≤20	13983-17-0
Poly(oxy-1,2-ethanediyl), $\alpha$ -(nonylphenyl)- $\omega$ -hydroxy-, branched, phosphates	≥1.0 - <3.0	68412-53-3
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	≥0.10 - ≤2.7	41556-26-7
crystalline silica, respirable powder (<10 microns)	<1.0	14808-60-7
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	<1.0	82919-37-7
carbon black	≤1.0	1333-86-4

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

United States Page: 2/14

Product name PSX-700=RAL 6009 K-7 NV

## Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

## **Description of necessary first aid measures**

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep

person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

## Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

United States Page: 3/14

Product name PSX-700=RAL 6009 K-7 NV

## Section 4. First aid measures

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon oxides nitrogen oxides

halogenated compounds metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

United States Page: 4/14

Product code 19AE046405

Date of issue 21 March 2024

Version 1

Product name PSX-700=RAL 6009 K-7 NV

# Section 6. Accidental release measures

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Special precautions** 

: Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, : including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

**Control parameters** 

Occupational exposure limits

United States Page: 5/14

Date of issue 21 March 2024 Version 1

Product code 19AE046405

Product name PSX-700=RAL 6009 K-7 NV

# Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with	None.
1-chloro-2,3-epoxypropane	40000 707 (11.14 104 4 4/0000)
Wollastonite	ACGIH TLV (United States, 1/2023). TWA: 1 mg/m³ 8 hours. Form: Inhalable fraction
Poly(oxy, 1.2 othorodiyl) a (nonylphonyl) (x hydroxy, bronchod	None.
Poly(oxy-1,2-ethanediyl), $\alpha$ -(nonylphenyl)- $\omega$ -hydroxy-, branched, phosphates	None.
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	None.
crystalline silica, respirable powder (<10 microns)	ACGIH TLV (United States, 1/2023). [Silica, crystalline]
	TWA: 0.025 mg/m³ 8 hours. Form:
	Respirable
	OSHA PEL Z3 (United States, 6/2016).
	TWA: 10 mg/m³ / (%SiO2+2) 8 hours. Form:
	Respirable
	TWA: 250 mppcf / (%SiO2+5) 8 hours. Form:
	Respirable
	OSHA PEL (United States, 5/2018). [Silica,
	crystalline]
	TWA: 50 μg/m³ 8 hours. Form: Respirable
	dust
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	None.
carbon black	ACGIH TLV (United States, 1/2023).
	TWA: 3 mg/m³ 8 hours. Form: Inhalable
	fraction
	OSHA PEL (United States, 5/2018).
	TWA: 3.5 mg/m³ 8 hours.

#### Key to abbreviations

= Acceptable Maximum Peak S = Potential skin absorption ACGIH = American Conference of Governmental Industrial Hygienists. SR = Respiratory sensitization = Ceiling Limit SS = Skin sensitization С F = Fume STEL = Short term Exposure limit values = Internal Permissible Exposure Limit **IPEL** TD = Total dust OSHA = Occupational Safety and Health Administration. TLV = Threshold Limit Value R TWA = Time Weighted Average Z = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

### Consult local authorities for acceptable exposure limits.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

**United States** Page: 6/14

Product name PSX-700=RAL 6009 K-7 NV

# Section 8. Exposure controls/personal protection

: Wash hands, forearms and face thoroughly after handling chemical products, before **Hygiene measures** 

> eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.

Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection

**Hand protection** 

Skin protection

: Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

butyl rubber Gloves

Personal protective equipment for the body should be selected based on the task being **Body protection** 

performed and the risks involved and should be approved by a specialist before

handling this product.

: Chemical splash goggles.

: Appropriate footwear and any additional skin protection measures should be selected Other skin protection

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

: Respirator selection must be based on known or anticipated exposure levels, the Respiratory protection

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying

with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

# Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liauid.

Color : Not available. Odor : Not available. **Odor threshold** : Not available. pН Not applicable. **Melting point** : Not available.

: >37.78°C (>100°F) **Boiling point** 

Flash point : Closed cup: 97°C (206.6°F)

**Auto-ignition temperature** : Not available. : Not available. **Decomposition temperature Flammability** : Not available. Lower and upper explosive : Not available.

(flammable) limits

: Not available. **Evaporation rate** : Not available. **Vapor pressure** 

**United States** Page: 7/14

Product name PSX-700=RAL 6009 K-7 NV

# Section 9. Physical and chemical properties

Vapor density : Not available.

Relative density : 1.33 Density ( lbs / gal ) : 11.1

Media Result

cold water Not soluble

Partition coefficient: n-

octanol/water

Solubility(ies)

: Not applicable.

Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

**Volatility** : 3% (v/v), 4.57% (w/w)

% **Solid.** (w/w) : 95.43

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials**: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition** 

products

: Depending on conditions, decomposition products may include the following materials:

carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides

# **Section 11. Toxicological information**

## Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate	LD50 Oral	Rat	3.125 g/kg	-
methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	LD50 Oral	Rat	3.125 g/kg	-
carbon black	LD50 Oral	Rat	>10 g/kg	-

**Conclusion/Summary** 

: There are no data available on the mixture itself.

Irritation/Corrosion

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.Eyes : There are no data available on the mixture itself.

United States Page: 8/14

Product name PSX-700=RAL 6009 K-7 NV

# **Section 11. Toxicological information**

**Respiratory**: There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Classification** 

Product/ingredient name	OSHA	IARC	NTP
Wollastonite crystalline silica, respirable powder (<10 microns)	-+		- Known to be a human carcinogen.
carbon black	ı	2B	-

#### Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

## **Reproductive toxicity**

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
crystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-

<u>Target organs</u>: Contains material which causes damage to the following organs: upper respiratory tract,

skin, eyes.

Contains material which may cause damage to the following organs: lungs.

### **Aspiration hazard**

Not available.

## Information on the likely routes of exposure

## Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

United States Page: 9/14

Product name PSX-700=RAL 6009 K-7 NV

# **Section 11. Toxicological information**

## Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation

watering redness

**Inhalation**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

## Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary

There are no data available on the mixture itself. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

**Potential immediate** : There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

Potential immediate : There are no data available on the mixture itself.

effects

Potential delayed effects: There are no data available on the mixture itself.

Potential chronic health effects

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : Suspected of damaging fertility or the unborn child.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

United States Page: 10/14

Product name PSX-700=RAL 6009 K-7 NV

# **Section 11. Toxicological information**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	(gases)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
PSX-700=RAL 6009 K-7 NV bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	7356.1	12545.2	N/A	N/A	N/A
	3125	N/A	N/A	N/A	N/A
	3125	N/A	N/A	N/A	N/A

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours

### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

# Section 13. Disposal considerations

### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

United States Page: 11/14

Product name PSX-700=RAL 6009 K-7 NV

# 14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	UN3082	UN3082
UN proper shipping name	-	HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis(1,2,2,6,6-pentamethyl-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis(1,2,2,6,6-pentamethyl-
		4-piperidyl) sebacate)	4-piperidyl) sebacate)
Transport hazard class (es)	-	9	9
Packing group	-	III	III
<b>Environmental hazards</b>	No.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate)	Not applicable.

### **Additional information**

DOT : None identified.

**IMDG**: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

# Section 15. Regulatory information

#### **United States**

United States inventory (TSCA 8b): All components are active or exempted.

**SARA 302/304** 

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

**SARA 311/312** 

Classification : EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION - Category 2

**Composition/information on ingredients** 

United States Page: 12/14

Product name PSX-700=RAL 6009 K-7 NV

# **Section 15. Regulatory information**

Name	%	Classification
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	≥20 - ≤50	SKIN SENSITIZATION - Category 1B
Poly(oxy-1,2-ethanediyl), α- (nonylphenyl)-ω-hydroxy-, branched, phosphates	≥1.0 - <3.0	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1
bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate	≥0.10 - ≤2.7	SKIN SENSITIZATION - Category 1B TOXIC TO REPRODUCTION - Category 2
crystalline silica, respirable powder (<10 microns)	<1.0	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	<1.0	SKIN SENSITIZATION - Category 1B TOXIC TO REPRODUCTION - Category 2
carbon black	≤1.0	COMBUSTIBLE DUSTS CARCINOGENICITY - Category 2

### **SARA 313**

Chemical nameCAS numberConcentrationSupplier notification: lead massive7439-92-10.0000026878

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### California Prop. 65

★ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

# **Section 16. Other information**

Hazardous Material Information System (U.S.A.)

Health: 3 \* Flammability: 1 Physical hazards: 1

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**National Fire Protection Association (U.S.A.)** 

Health: 3 Flammability: 1 Instability: 1

Date of previous issue : No previous validation

Organization that prepared : EHS

the SDS

United States Page: 13/14

Product name PSX-700=RAL 6009 K-7 NV

## Section 16. Other information

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

UN = United Nations

## ▼ Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 14/14