SAFETY DATA SHEET



Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 7 April 2024

Version 4.01

Date of issue 7 April 2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name	: SL60 JS JOINT SEALANT SIGNAL GRAY 1365 - B
Product code	: 00465175
Other means of identification	: Not applicable.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Product use	: Industrial applications, Professional applications.
Use of the substance/ mixture	: Coating.; Pigment paste
Uses advised against	: Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)
Technical Phone Number	: 888-977-4762

SECTION 2: Hazards identification

Classification of the substance or mixture	:	Not classified.
		Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 41.1% (oral), 45.9% (dermal), 41.1% (inhalation)
GHS label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.

Product name SL60 JS JOINT SEALANT SIGNAL GRAY 1365 - B

SECTION 2: Hazards identification

Other hazards which do not : Emits toxic fumes when heated.

result in classification

See toxicological information (Section 11)

SECTION 3: Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: SL60 JS JOINT SEALANT SIGNAL GRAY 1365 - B
Other means of identification	: Not applicable.

Ingredient name	%	CAS number
titanium dioxide	≥20 - ≤50	13463-67-7
aluminium oxide	≥1.0 - ≤5.0	1344-28-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

Description of necessary first aid measures

Eye contact	1	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	1	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects	5	
Eye contact	÷	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	÷	No known significant effects or critical hazards.

Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

See toxicological information (Section 11)

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

Version 4.01

Product name SL60 JS JOINT SEALANT SIGNAL GRAY 1365 - B

SECTION 5: Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

Personal precautions, protec	tive equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ontainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue 7 April 2024

TWA = Time Weighted Average

Product name SL60 JS JOINT SEALANT SIGNAL GRAY 1365 - B

SECTION 7: Handling and storage

Precautions for safe handling	L	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8).
Special precautions	:	Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingre	dient name		Exposure limits
titaniu	m dioxide		NOM-010-STPS-2014 (Mexico, 4/2016).
alumir	nium oxide		TWA: 10 mg/m³ 8 hours. NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 10 mg/m³ 8 hours.
		Key to abbreviations	
С	= Ceiling Limit	STEL	 Short term exposure limit
IPEL	 Internal Permissible Exposure Limit 	TLV	= Threshold Limit Value

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.Appropriate engineering controls: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.Individual protection measures Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
proceduresnational guidance documents for methods for the determination of hazardous substances will also be required.Appropriate engineering controls: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
proceduresnational guidance documents for methods for the determination of hazardous substances will also be required.Appropriate engineering controls: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process
proceduresnational guidance documents for methods for the determination of hazardous substances will also be required.Appropriate engineering: Good general ventilation should be sufficient to control worker exposure to airborne
procedures national guidance documents for methods for the determination of hazardous

Product name SL60 JS JOINT SEALANT SIGNAL GRAY 1365 - B

SECTION 8: Exposure controls/personal protection

Eye/face protection	: Safety glasses with side shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: butyl rubber, nitrile rubber
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

SECTION 9: Physical and chemical properties

Appearance

Appearance		
Physical state	1	Liquid.
Color	1	Various
Odor	1	Faint odor.
Odor threshold	1	Not available.
Molecular weight	4	Not applicable.
рН	÷	Not available.
Melting point	4	Not available.
Boiling point	4	>37.78°C (>100°F)
Flash point	1	Closed cup: 94°C (201.2°F)
Auto-ignition temperature	1	Not available.
Decomposition temperature	1	Not available.
Flammability	4	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Evaporation rate	4	Not available.
Vapor pressure	1	Not available.
Vapor density	1	Not available.
Relative density	1	1.68
Density(lbs / gal)	:	14.02
		Media Result
Solubility(ies)	÷	cold water Soluble
Solubility in water	:	Not available.
Partition coefficient: n- octanol/water	:	Not applicable.

Date of issue 7 April 2024

Version 4.01

Product name SL60 JS JOINT SEALANT SIGNAL GRAY 1365 - B

SECTION 9: Physical and chemical properties

Viscosity	: Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)
Volatility	: 0% (v/v), 0% (w/w)
% Solid. (w/w)	: 100

SECTION 10: Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	 When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	 Depending on conditions, decomposition products may include the following material carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure		
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours		
	LD50 Dermal	Rabbit	>5000 mg/kg	-		
	LD50 Oral	Rat	>5000 mg/kg	-		
aluminium oxide	LC50 Inhalation Dusts and mists		7.6 mg/l	4 hours		
	LD50 Oral	Rat	>15900 mg/kg	-		
Conclusion/Summary	: There are no data available on	the mixture its	elf.			
rritation/Corrosion						
Conclusion/Summary						
Skin	: There are no data available on	the mixture its	elf.			
Eyes	: There are no data available on	: There are no data available on the mixture itself.				
Respiratory	: There are no data available on	the mixture its	elf.			
Sensitization						
Conclusion/Summary						
Skin	: There are no data available on	the mixture its	elf.			
Respiratory	: There are no data available on	the mixture its	elf.			
<u>Autagenicity</u>						
Conclusion/Summary	: There are no data available on	the mixture its	elf.			
Carcinogenicity						
Conclusion/Summary	: There are no data available on	the mixture its	elf.			
<u>Classification</u>						

Version 4.01

Product name SL60 JS JOINT SEALANT SIGNAL GRAY 1365 - B

SECTION 11: Toxicological information

Product/ingrodient name	OSHA	IARC	NTP
Product/ingredient name	USHA		
titanium dioxide carbon black	-	2B 2B	-
Carcinogen Classification	n code:		
IARC: 1, 2A, 2B, 3 NTP: Known to b OSHA: + Not listed/not reg	e a human ca	arcinogen; F	Reasonably anticipated to be a human carcinogen
Reproductive toxicity			
Conclusion/Summary	: There a	re no data	a available on the mixture itself.
Teratogenicity			
Conclusion/Summary	: There a	re no data	a available on the mixture itself.
Specific target organ toxicity	<mark>/ (single e</mark>)	<u>kposure)</u>	
Not available.			
Specific target organ toxicity Not available.	<u>/ (repeated</u>	<u>l exposur</u>	<u>.e)</u>
<u>Target organs</u>			which may cause damage to the following organs: kidneys, lungs, atory tract, immune system, skin, eyes, central nervous system
Aspiration hazard			
Not available.			
Information on the likely route	os of oxno	euro	
Potential acute health effects		Suie	
Eye contact	•	wn sianifi	cant effects or critical hazards.
Inhalation		-	cant effects or critical hazards.
Skin contact		•	cant effects or critical hazards.
Ingestion		U	cant effects or critical hazards.
Over-exposure signs/sympto			
Eve contact	: No spe	cific data.	
Inhalation	: No spe		
Skin contact	: No spe		
Ingestion	: No spe	cific data.	
Delayed and immediate effec	ts and also	o chronic	effects from short and long term exposure
Conclusion/Summary	as a raw bound ir particles coating duration equipme raw mat particles unbound Sanding dependi	v material n a matrix s of TiO2 v surface of and level ent and/or cerial in ma s are bour d particles the coati ng on the	a available on the mixture itself. For many products, TiO2 is utilized in a liquid coating formulation. In this case, the TiO2 particles are with no meaningful potential for human exposure to unbound when the product is applied with a brush or roller. Sanding the r mist from spray applications may be harmful depending on the of exposure and require the use of appropriate personal protective engineering controls (see Section 8). Carbon black is utilized as a any liquid coating formulations. In this case, the carbon black and in a matrix with no meaningful potential for human exposure to of carbon black when the product is applied with a brush or roller. Ing surface or mist from spray applications may be harmful duration and level of exposure and require the use of appropriate re equipment and/or engineering controls (see Section 8). Most

Mexico Page: 7/10

Product name SL60 JS JOINT SEALANT SIGNAL GRAY 1365 - B

SECTION 11: Toxicological information

		-
		carbon blacks contain trace quantities of polyaromatic hydrocarbons (PAH). PAHs are not expected to be released in biological fluids and are therefore not likely available for biological activity. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
<u>Short term exposure</u>		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
<u>Long term exposure</u>		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Potential chronic health effe	<u>cts</u>	
General	1	No known significant effects or critical hazards.
Carcinogenicity	1	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.
Numerical measures of toxic	<u>ity</u>	
Acute toxicity estimates		

Product/ingredient name				(mg/l)	Inhalation (dusts and mists) (mg/l)
aluminium oxide	N/A	N/A	N/A	N/A	7.6

SECTION 12: Ecological information

Т	oxi	С	ity	
_			_	

Product/ingredient name	Result	Species	Exposure
	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Other adverse effects

Soil/water partition	: Not available.
coefficient (Koc)	

: No known significant effects or critical hazards.

Product name SL60 JS JOINT SEALANT SIGNAL GRAY 1365 - B

SECTION 13: Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

SECTION 14: Transport information

	Mexico Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

- Mexico : None identified.
- **IMDG** : None identified.
- IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Date of issue 7 April 2024

Version 4.01

Product name SL60 JS JOINT SEALANT SIGNAL GRAY 1365 - B

SECTION 15: Regulatory information

Mexico

Classification

Flammability : 1 Health : 1 Reactivity : 0

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

SECTION 16: Other information

Hazardous Material Information System (U.S.A.)

Health : 1 * Flammability : 1 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of previous issue	: 3/29/2024
Organization that prepared the SDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations
7 I I	have a base of the second s

Indicates information that has changed from previously issued version.

Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.