

SAFETY DATA SHEET



Date of issue/Date of revision 8 April 2024

Version 5.03

Section 1. Identification

Product code : 00314663
Product name : SIGMADUR 550 BASE RAL 7046
CAS number : Not applicable.
EC number : Mixture.
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Coating.
Professional applications, Used by spraying.
Uses advised against : Product is not intended, labelled or packaged for consumer use.

Supplier's details : PPG Yung Chi Coatings Co. Ltd
Lot 219, Amata Street, Long Binh IZ
Bien Hoa City, Dong Nai Province
Vietnam
Tel : +84 61 3936121/22

Emergency telephone number (with hours of operation) : CHEMTREC +(84)-444581938 (CCN 17704)

Section 2. Hazards identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY (dermal) - Category 5
ACUTE TOXICITY (inhalation) - Category 4
SKIN IRRITATION - Category 2
SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 1
AQUATIC TOXICITY (ACUTE) - Category 3
AQUATIC TOXICITY (CHRONIC) - Category 3
Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 41.3%
Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 70.6%
Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 60.8%

GHS label elements

Hazard pictograms :



Signal word : Danger

Section 2. Hazards identification

Hazard statements	: Flammable liquid and vapor. May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Harmful if inhaled. May cause cancer. Harmful to aquatic life with long lasting effects.
<u>Precautionary statements</u>	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Routes of entry	: Not available.
Other hazards which do not result in classification	: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

CAS number/other identifiers

CAS number

: Not applicable.

EC number

: Mixture.

Ingredient name	CAS number	Chemical formula	%
2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate, ethenylbenzene, 1,2-propanediol mono(2-methyl-2-propenoate) and 2-propenoic acid	37237-99-3	(C8H8.C7H12O3.C7H12O2.C5H8O2.C3H4O2)x	≥25 - ≤50
barium sulfate	7727-43-7	O4-S.Ba	≥10 - ≤25
Solvent naphtha (petroleum), light aromatic	64742-95-6	C36H48	≤10
Talc , not containing asbestiform fibres	14807-96-6	3Mg-O.4Si-O2.H2-O	≤9.5
1,2,4-trimethylbenzene	95-63-6	C9-H12	≤7
n-butyl acetate	123-86-4	C6-H12-O2	≤7.2
ethylbenzene	100-41-4	C8-H10	≤3
xylene	1330-20-7	C8-H10	≤2
2,6-dimethylheptan-4-one	108-83-8	C9-H18-O	≤1.3
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	C30H56N2O4	≤0.3
cumene	98-82-8	C9-H12	≤0.3

Section 3. Composition/information on ingredients

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Harmful if inhaled.
- Skin contact** : May be harmful in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon oxides
sulfur oxides
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
barium sulfate	ACGIH TLV (United States, 1/2023). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction
Talc , not containing asbestiform fibres	Ministry of Health (Viet Nam, 6/2019). TWA: 3 mg/m ³ 8 hours. Form: inhalable dust TWA: 1 mg/m ³ 8 hours. Form: respirable dust TWA: 2 mg/m ³ 8 hours. Form: total dust concentration
1,2,4-trimethylbenzene	ACGIH TLV (United States, 1/2023). TWA: 10 ppm 8 hours.
n-butyl acetate	Ministry of Health (Viet Nam, 6/2019). STEL: 700 mg/m ³ 15 minutes. TWA: 500 mg/m ³ 8 hours.
ethylbenzene	ACGIH TLV (United States, 1/2023). Ototoxicant. TWA: 20 ppm 8 hours.
xylene	Ministry of Health (Viet Nam, 6/2019). [xylene] STEL: 300 mg/m ³ 15 minutes. TWA: 100 mg/m ³ 8 hours.
2,6-dimethylheptan-4-one	ACGIH TLV (United States, 1/2023). TWA: 145 mg/m ³ 8 hours. TWA: 25 ppm 8 hours.
cumene	Ministry of Health (Viet Nam, 6/2019). STEL: 100 mg/m ³ 15 minutes. TWA: 80 mg/m ³ 8 hours.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles.

Skin protection

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state	: Liquid.				
Color	: Various				
Odor	: Aromatic.				
Odor threshold	: Not available.				
pH	: Not applicable.				
Melting point	: Not available.				
Boiling point	: >37.78°C (>100°F)				
Flash point	: Closed cup: 31°C (87.8°F)				
Evaporation rate	: Not available.				
Flammability (solid, gas)	: Not available.				
Lower and upper explosive (flammable) limits	: Greatest known range: Lower: 1.4% Upper: 7.6% (Solvent naphtha (petroleum), light aromatic)				
Vapor pressure	: Not available.				
Vapor density	: Not available.				
Relative density	: 1.34				
Bulk Density (g/cm³)	: 1.351				
Solubility(ies)	<table><tr><th>Media</th><th>Result</th></tr><tr><td>cold water</td><td>Not soluble</td></tr></table>	Media	Result	cold water	Not soluble
Media	Result				
cold water	Not soluble				
Partition coefficient: n-octanol/water	: Not applicable.				
Auto-ignition temperature	: Not available.				
Decomposition temperature	: Not available.				

Section 9. Physical and chemical properties

Viscosity : Kinematic (40°C): >21 mm²/s

Section 10. Stability and reactivity

- Reactivity : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability : The product is stable.
- Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.
- Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
- Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate, ethenylbenzene, 1,2-propanediol mono (2-methyl-2-propenoate) and 2-propenoic acid barium sulfate	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Solvent naphtha (petroleum), light aromatic	LD50 Dermal	Rabbit	3.48 g/kg	-
1,2,4-trimethylbenzene	LD50 Oral	Rat	8400 mg/kg	-
	LC50 Inhalation Vapor	Rat	18000 mg/m³	4 hours
	LD50 Oral	Rat	5 g/kg	-
n-butyl acetate	LC50 Inhalation Vapor	Rat	>21.1 mg/l	4 hours
	LC50 Inhalation Vapor	Rat	2000 ppm	4 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
ethylbenzene	LD50 Oral	Rat	10.768 g/kg	-
	LC50 Inhalation Vapor	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
xylene	LD50 Oral	Rat	3.5 g/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
2,6-dimethylheptan-4-one	LD50 Dermal	Rabbit	16 g/kg	-
	LD50 Oral	Rat	5750 mg/kg	-
	LD50 Oral	Rat	3.125 g/kg	-
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate cumene	LC50 Inhalation Vapor	Rat	39000 mg/m³	4 hours
	LD50 Dermal	Rabbit	12.3 g/kg	-

Section 11. Toxicological information

	LD50 Oral	Rat	2260 mg/kg	-
--	-----------	-----	------------	---

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate, ethenylbenzene, 1,2-propanediol mono (2-methyl-2-propenoate) and 2-propenoic acid	skin	Mouse	Sensitizing

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), light aromatic	Category 3	-	Narcotic effects
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation
1,2,4-trimethylbenzene	Category 3	-	Respiratory tract irritation
n-butyl acetate	Category 3	-	Narcotic effects
xylene	Category 3	-	Respiratory tract irritation
2,6-dimethylheptan-4-one	Category 3	-	Respiratory tract irritation
cumene	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs
cumene	Category 2	-	-

Aspiration hazard

Name	Result
Solvent naphtha (petroleum), light aromatic	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1
2,6-dimethylheptan-4-one	ASPIRATION HAZARD - Category 1
cumene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure
: Not available.

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Harmful if inhaled.
Skin contact	: May be harmful in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.

Long term exposure

Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.

Potential chronic health effects

General	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.

Section 11. Toxicological information

Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	47341.17 mg/kg
Dermal	4389.06 mg/kg
Inhalation (vapors)	50.73 mg/l
Inhalation (dusts and mists)	4.71 mg/l

Other information :

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Solvent naphtha (petroleum), light aromatic	Acute LC50 8.2 mg/l	Fish	96 hours
n-butyl acetate	Acute LC50 18 mg/l	Fish	96 hours
ethylbenzene	Acute EC50 1.8 mg/l Fresh water Chronic NOEC 1 mg/l Fresh water	Daphnia Daphnia - <i>Ceriodaphnia dubia</i>	48 hours -

Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
n-butyl acetate	TEPA and OECD 301D	83 % - Readily - 28 days	-	-
ethylbenzene	-	79 % - Readily - 10 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-butyl acetate	-	-	Readily
ethylbenzene	-	-	Readily
xylene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
1,2,4-trimethylbenzene	3.63	120.23	Low
n-butyl acetate	2.3	-	Low
ethylbenzene	3.6	79.43	Low
xylene	3.12	7.4 to 18.5	Low
2,6-dimethylheptan-4-one	3.71	-	Low
cumene	3.55	35.48	Low

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3
Packing group	III	III	III
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

UN : None identified.
IMDG : None identified.
IATA : None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Circular no. 05/1999/TT-BYT

Ingredient name	Category	Notes
1,4-dioxane	Category 2	
chloromethane	Category 2	
Formaldehyde, solution	Category 2	
ethylene oxide	Category 2	
benzene	Category 1	
toluene	Category 2	
xylene	Category 2	
lead massive	Category 2	
Cadmium (Non-pyrophoric)	Category 2	
arsenic	Category 1	
antimony	Category 2	
chromium	Category 2	
1,1'-Biphenyl, chloro derivs.	Category 2	

Toxic classification (TCVN 3164-79) : 4

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

History

Date of issue/Date of revision : 8 April 2024

Date of previous issue : 12/20/2023

Version : 5.03

Prepared by : EHS

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

Notice to reader

Section 16. Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.