# **SAFETY DATA SHEET**



Date of issue/Date of revision14 December 2023Version 1.05

Section 1. Identification		
Product code	: 00445091	
Product name	: SIGMAZINC 158/SIGMAGUARD 750 PIGMENT	
Product type	: Powder.	
Relevant identified uses o	f the substance or mixture and uses advised against	
Product use	Coating. Professional applications, Used by spraying.	
Supplier's details	: PPG Industries (Singapore) Pte. Ltd., No. 1 Tuas Basin Close, Singapore 638803. Tel +65 68653737	
Emergency telephone number (with hours of operation)	: CHEMTREC +(65)-31581349 (CCN 17704)	

# Section 2. Hazards identification

Classification of the substance or mixture	:	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
GHS label elements, includin	g	precautionary statements
Hazard pictograms	:	₩ <u>2</u>
Signal word	:	Warning
Hazard statements	:	Very toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Avoid release to the environment.
Response	:	Collect spillage.
Storage	:	Not applicable.
Disposal	1	Not applicable.
Other hazards which do not result in classification	:	May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Singapore	English (GB)	Page: 1/11
-----------	--------------	------------

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture

#### **CAS number/other identifiers**

CAS number	: Not applicable.
EC number	: Mixture.

Ingredient name	%	CAS number
	50 - 100 3 - <5	7440-66-6 1314-13-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show the container or label.</li> <li>Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>

#### Most important symptoms/effects, acute and delayed

Potential acute health e	effects
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/s	<u>ymptoms</u>
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

Singapore	English (GB)	Page: 2/11
-----------	--------------	------------

Date of issue 14 December 2023 Version 1.05

Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

### Section 4. First aid measures

Indication of immediate med	<u>lica</u>	l attention and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.

#### See toxicological information (Section 11)

### Section 5. Firefighting measures

#### **Extinguishing media** Suitable extinguishing : Use dry chemical powder. media Unsuitable extinguishing : Avoid high pressure media which could cause the formation of a potentially media explosible dust-air mixture. : May form explosible dust-air mixture if dispersed. This material is very toxic to Specific hazards arising from the chemical aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. Hazardous thermal : Decomposition products may include the following materials: metal oxide/oxides decomposition products **Special protective actions** : Promptly isolate the scene by removing all persons from the vicinity of the incident if for fire-fighters there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. : Fire-fighters should wear appropriate protective equipment and self-contained **Special protective** equipment for fire-fighters breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Singapore	English (GB)	Page: 3/11
-----------	--------------	------------

## Section 6. Accidental release measures

Methods and material for containment and cleaning up		
Small spill :	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.	
Large spill :	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.	

# Section 7. Handling and storage

### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### **Control parameters**

### **Occupational exposure limits**

Ingredient name			Exposure limits
zinc oxide			Workplace Safety and Health Act (Singapore, 2/2006). PEL (long term): 10 mg/m <sup>3</sup> 8 hours. Form: Dust PEL (short term): 10 mg/m <sup>3</sup> 15 minutes. Form: Fume PEL (long term): 5 mg/m <sup>3</sup> 8 hours. Form: Fume
Recommended monitoring procedures	:		riate monitoring standards. Reference to nods for the determination of hazardous
Appropriate engineering controls	:	vapour or mist, use process enclosure engineering controls to keep worker e recommended or statutory limits. The	user operations generate dust, fumes, gas, es, local exhaust ventilation or other exposure to airborne contaminants below any e engineering controls also need to keep gas, any lower explosive limits. Use explosion-proof
Environmental exposure controls	:		
Individual protection measured	res		
Hygiene measures	:	eating, smoking and using the lavator Appropriate techniques should be use	bughly after handling chemical products, before y and at the end of the working period. ed to remove potentially contaminated clothing. eusing. Ensure that eyewash stations and tation location.
Eye/face protection	:	Safety glasses with side shields.	
Skin protection			
Hand protection	:	be worn at all times when handling ch this is necessary. Considering the pa check during use that the gloves are s should be noted that the time to break	s complying with an approved standard should emical products if a risk assessment indicates rameters specified by the glove manufacturer, still retaining their protective properties. It through for any glove material may be rers. In the case of mixtures, consisting of ne of the gloves cannot be accurately
Body protection	:		body should be selected based on the task d and should be approved by a specialist

Product code 00445091

Date of issue 14 December 2023 Version 1.05

Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

# Section 8. Exposure controls/personal protection

Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# **Section 9. Physical and chemical properties**

<u>Appearance</u>		
Physical state	Solid. Powder.	
Odour	Aromatic.	
рН	insoluble in water.	
Flash point	Closed cup: Not applicable.	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Vapour pressure	Not available.	
Vapour density	Highest known value: 5.47 (Air = 1) (zinc oxide).	
Relative density	7.1	
Bulk Density (g/cm³)	7.1	
Solubility(ies)	Media Result	
Solubility(les)	cold water Not soluble	
Auto-ignition temperature	500°C	
Viscosity	Kinematic (40°C (104°F)): Not applicable.	

# Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Singapore	English (GB)	Page: 6/11
-----------	--------------	------------

### Section 10. Stability and reactivity

Hazardous decomposition<br/>products: Evolves hydrogen on contact with water. Depending on conditions, decomposition<br/>products may include the following materials: metal oxide/oxides

### Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

	1e	Result	Species	Dose	Exposure
Zinc powder - zinc dust (stabilized)		LC50 Inhalation Dusts and mists	Rat	>5.4 mg/l	4 hours
		LD50 Oral	Rat	>2000 mg/kg	-
zinc oxide		LC50 Inhalation Dusts and mists	Rat	>5700 mg/m <sup>3</sup>	4 hours
		LD50 Dermal LD50 Oral	Rat Rat	>2000 mg/kg >5000 mg/kg	-
Conclusion/Summary		There are no data available on the		· coco mg/ng	
Conclusion/Summary Irritation/Corrosion			mixture itsen.		
Conclusion/Summary					
Skin	• •	There are no data available on the	mivture itself		
Eyes		There are no data available on the			
Respiratory		There are no data available on the			
<u>Sensitisation</u>					
Conclusion/Summary					
Skin	: 1	There are no data available on the	mixture itself.		
Respiratory		There are no data available on the			
Mutagenicity					
Conclusion/Summary	:	There are no data available on the	mixture itself.		
<b>Carcinogenicity</b>					
<b>Conclusion/Summary</b>	: 1	There are no data available on the	mixture itself.		
Reproductive toxicity					
Conclusion/Summary	: 1	There are no data available on the	mixture itself.		
Teratogenicity					
Conclusion/Summary	: 1	There are no data available on the	mixture itself.		
Specific target organ tox	icity	(single exposure)			
Not available.					
Specific target organ tox	icity	(repeated exposure)			
Not available.					
Aspiration hazard					
Not available.					

Information on likely routes : Not available. of exposure

### Section 11. Toxicological information

### Potential acute health effects

Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to t	the physical, chemical and toxicological characteristics
Eve contact	Advorse symptome may include the following:

Eye contact	irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>'S</u>
General	1	Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	1	No known significant effects or critical hazards.
Mutagenicity	1	No known significant effects or critical hazards.
Reproductive toxicity	1	No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Not available.

#### **Other information**

Sanding and grinding dusts may be harmful if inhaled.

ŝ,

Singapore	English (GB)
-----------	--------------

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure	
Zínc powder - zinc dust (stabilized)	Acute EC50 0.106 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours	
. ,	Chronic EC10 6.3 µg/l	Daphnia - <i>Daphnia magna -</i> Neonate	21 days	
zinc oxide	Acute EC50 0.17 mg/l	Algae	72 hours	
	Acute EC50 0.481 mg/l Fresh water	Daphnia - <i>Daphnia magna -</i> Neonate	48 hours	
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours	
Conclusion/Summary	: There are no data available on the m	ixture itself.		
Persistence/degradability				
Not available.				
Conclusion/Summary	: There are no data available on the mixture itself.			
Bioaccumulative potential				
Not available.				
Mohility in soil				
Mobility in soil Soil/water partition coefficient (Koc)	: Not available.			

### Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff
	and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	UN	IMDG	IATA
UN number	UN3077	UN3077	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(Zinc powder - zinc dust (stabilized))	Not applicable.

#### **Additional information**

UN	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The segregation group has been manually assigned based upon product analysis.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
<b>Special precautions for user</b> : <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in	

the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

# Section 15. Regulatory information

Singapore - hazardous chemicals under government control

None.

International regulations

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 14 December 2023
Date of previous issue	: 10/25/2023
Version	: 1.05
Prepared by	: EHS
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>

✓ Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.