SAFETY DATA SHEET

Europe

Date of issue/Date of revision

: 12 April 2024

Version

: 3.03



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier		
Product name	: PPG AQUACOVER ONE 645 (TINTED)	
Product code	: 000001189976	
Other means of identi	fication	
00452714; 00452715; 00454115; 00454116		

1.2 Relevant identified uses of the substance or mixture and uses advised against		
Product use	: Professional applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Product is not intended, labelled or packaged for consumer use.	

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person : Product.Stewardship.EMEA@ppg.com responsible for this SDS

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture **Product definition** : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

English (GB)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commiss	sion Regulation (EU)
2020/878	

2020/878	
Code : 000001189976	
PPG AQUACOVER ONE 645	(TINTED)
SECTION 2: Hazards	identification
Signal word	: No signal word.
Hazard statements	: Harmful to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Avoid release to the environment.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
	P273, P501
Hazardous ingredients	: Not applicable.
Supplemental label elements	 Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	<u>ients</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

	:	Mixture
--	---	---------

3.2 Mixtures

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≥1.0 - ≤5.0	Eye Irrit. 2, H319	-	[1] [2]
3-iodo-2-propynyl butylcarbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<0.10	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx)	ATE [Oral] = 1470 mg/ kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	
English (GB)		•	Europe	<u>.</u>	2/15

SECTION 3: Compo	osition/informat	ion on i	ngredients		
			Aquatic Acute 1, H400 Aquatic Chronic 1, H410		
reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8- tridecafluorooctyl) phosphates, ammonium salt	CAS: SUB141402	<0.10	Acute Tox. 1, H330 STOT RE 2, H373 (liver) Aquatic Chronic 1, H410	ATE [Inhalation (dusts and mists)] = 0.047 mg/l M [Chronic] = 10	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.050	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 1020 mg/ kg ATE [Inhalation (dusts and mists)] = 0.4 mg/l Skin Sens. 1, H317: C $\ge 0.05\%$ M [Acute] = 1	[1]
pyrithione zinc	REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7 Index: 613-333-00-7	<0.010	Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 221 mg/ kg ATE [Inhalation (dusts and mists)] = 0.14 mg/l M [Acute] = 1000 M [Chronic] = 10	[1]
reaction mass of 5-chloro- 2-methyl-2H-isothiazol- 3-one and 2-methyl-2H- isothiazol-3-one (3:1)	REACH #: 01-2120764691-48 EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0010	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/ kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Skin Irrit. 2, H315: $0.06\% \le C < 0.6\%$ Eye Dam. 1, H318: C $\ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: C $\ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Code : 000001189976

PPG AQUACOVER ONE 645 (TINTED)

Date of issue/Date of revision

: 12 April 2024

Code	: 000001189976	Date of issue/Date of revision	: 12 April 2024
PPG AQUAC	OVER ONE 645(TINTED)		

SECTION 4: First aid measures

4.1 Description of first aid n	1easures
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

<u>Potential acute nealth e</u>	<u>nects</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/sy</u>	<u>mptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway,

Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides

sewer or drain.

5.3 Advice for firefighters

English (GB)	Europe	4/15

Code : 00000118997 PPG AQUACOVER ONE 645	
SECTION 5: Firefigh	nting measures
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European at and and SCBA will previde a basis level of pretection for should be basis level of pretection for should be basis level of pretection.
	standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	tive equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information i Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	ntainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Was spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

English (GB)	Europe	5/15		
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this handled, stored and processed. Workers should wash hands and fac drinking and smoking. Remove contaminated clothing and protective entering eating areas. See also Section 8 for additional information o measures.	ce before eating, equipment before		
Protective measures	contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid the environment. Keep in the original container or an approved alternative m compatible material, kept tightly closed when not in use. Empty containers re product residue and can be hazardous. Do not reuse container.			

Conforms to Regulation	(EC) No. 1907/2006	(REACH), Annex II, as	amended by Comm	ission Regulation (EU)
2020/878				

Code	: 000001189976	Date of issue/Date of revision	: 12 April 2024
PPG AQUAC	OVER ONE 645 (TINTED)		

SECTION 7: Handling and storage

incompatibilities cool and well-ventilated area, away from incompatible materials (see Section 10) ar food and drink. Keep container tightly closed and sealed until ready for use. Conta	7.2 Conditions for safe storage, including any incompatibilities	environmental contamination. See Section 10 for incompatible materials before
---	--	---

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-(2-butoxyethoxy)ethanol	EU OEL (Europe, 1/2022). STEL: 101.2 mg/m ³ 15 minutes. STEL: 15 ppm 15 minutes. TWA: 67.5 mg/m ³ 8 hours. TWA: 10 ppm 8 hours.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-(2-butoxyethoxy)ethanol	DNEL	Long term Oral	6.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	67.5 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	101.2 mg/m ³	Workers	Local
3-iodo-2-propynyl butylcarbamate	DNEL	Long term Inhalation	0.023 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	0.07 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	1.16 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	1.16 mg/m ³	Workers	Local
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m ³	Workers	Systemic
pyrithione zinc	DNEL	Long term Dermal	0.01 mg/kg bw/day	Workers	Systemic
reaction mass of 5-chloro-	DNEL	Long term Inhalation	0.02 mg/m ³	General population	Local
English (GB)	<u>.</u>	·	Europe		6/15

Code: 000001189976Date of issue/Date of revision: 12 April 2024PPG AQUACOVER ONE 645 (TINTED)

SECTION 8: Exposure controls/personal protection

2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1)					
	DNEL	Long term Inhalation Short term Inhalation Short term Inhalation Long term Oral Short term Oral	0.02 mg/m ³ 0.04 mg/m ³ 0.04 mg/m ³ 0.09 mg/kg bw/day 0.11 mg/kg bw/day	Workers General population Workers General population General population	Local Systemic

PNECs

Product/ingredient name	Туре	Compartment Detail	Value	Method Detail
2-(2-butoxyethoxy)ethanol	- - - -	Sewage Treatment Plant Fresh water sediment Marine water sediment	1.1 mg/l 0.11 mg/l 200 mg/l 4.4 mg/kg dwt 0.44 mg/kg dwt 0.32 mg/kg dwt	Assessment Factors Assessment Factors Assessment Factors Equilibrium Partitioning Equilibrium Partitioning Equilibrium Partitioning

8.2 Exposure controls

English (GB)	Europe 7/15	5
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved a specialist before handling this product.	
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist befor handling this product.	
	Recommended: butyl rubber	
Gloves	: For prolonged or repeated handling, use the following type of gloves:	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should worn at all times when handling chemical products if a risk assessment indicates the is necessary. Considering the parameters specified by the glove manufacturer, che during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for differ glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of u as included in the user's risk assessment.	iis eck rent e ed.
Skin protection	. Chemical registent impensions glaves complying with an enproved standard should	4 6 6
Eye/face protection	: Safety glasses with side shields. Use eye protection according to EN 166.	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, befor eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and saf showers are close to the workstation location.	J.
Individual protection meas	Sures	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.	;
8.2 Exposure controls		

Code : 000001189976	Date of issue/Date of revision	: 12 April 2024
PPG AQUACOVER ONE 645 (TINTED)		
SECTION 8: Exposure controls/p	personal protection	

Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

ŝ

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>						
Physical state	1	Liquid.				
Colour	:	Various				
Odour	1	Odourless.				
Odour threshold	:	Not available.				
Melting point/freezing point		May start to solidify at the following temperature: 0°C (32°F) This is based on data for the following ingredient: water. Weighted average: -2.48°C (27.5°F)				
Initial boiling point and boiling range	:	>37.78°C				
Flammability	1	Not available.				
Upper/lower flammability or explosive limits	:	Greatest known range: Lov	ver: 0.8% Upp	er: 9.4% (2-(2-butoxyethoxy)ethanol)	
Flash point	:	Closed cup: Not applicable				
A						
Auto-ignition temperature						
Auto-ignition temperature	•	Ingredient name	°C	°F	Method	
Auto-ignition temperature		Ingredient name 2-(2-butoxyethoxy)ethanol	° C 210	° F 410	Method DIN 51794	
	:	2-(2-butoxyethoxy)ethanol	210	410	DIN 51794	
Decomposition temperature			210	410	DIN 51794	
Decomposition temperature pH	:	2-(2-butoxyethoxy)ethanol Stable under recommende	210 d storage and	410	DIN 51794	
Decomposition temperature pH Viscosity	:	2-(2-butoxyethoxy)ethanol Stable under recommende 8.4	210 d storage and	410	DIN 51794	
Decomposition temperature pH Viscosity Viscosity	:	2-(2-butoxyethoxy)ethanol Stable under recommende 8.4 Kinematic (40°C): >21 mm	210 d storage and	410	DIN 51794	
Auto-ignition temperature Decomposition temperature pH Viscosity Viscosity Solubility(ies) Media	:	2-(2-butoxyethoxy)ethanol Stable under recommende 8.4 Kinematic (40°C): >21 mm	210 d storage and	410	DIN 51794	

Vapour pressure

	Vapou	Vapour Pressure at 20°C			Vapour pressure at 50		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					

Code : 000001189976 Date of issue/Date of revision : 12 April 2024 PPG AQUACOVER ONE 645 (TINTED) **SECTION 9: Physical and chemical properties** : 0.003 (2-(2-butoxyethoxy)ethanol) compared with butyl acetate **Evaporation rate Relative density** : 1.13 Vapour density : Highest known value: 5.6 (Air = 1) (2-(2-butoxyethoxy)ethanol). The product itself is not explosive, but the formation of an explosible mixture of **Explosive properties** 2 vapour or dust with air is possible. **Oxidising properties** : Product does not present an oxidizing hazard. **Particle characteristics** Median particle size : Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
3-iodo-2-propynyl butylcarbamate	LC50 Inhalation Dusts and mists	Rat	0.67 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	_
	LD50 Oral	Rat	1470 mg/kg	_
reaction mass of mixed	LC50 Inhalation Dusts and	Rat	0.047 mg/l	4 hours
(3,3,4,4,5,5,6,6,7,7, 8,8,8-	mists		0	
tridecafluorooctyl) phosphates, ammonium salt				
1,2-benzisothiazol-3(2H)-one	LC50 Inhalation Dusts and mists	Rat	0.4 mg/l	4 hours
	LD50 Oral	Rat	1020 mg/kg	-
pyrithione zinc	LC50 Inhalation Dusts and mists	Rat	0.14 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	177 mg/kg	-
reaction mass of 5-chloro-2-methyl-2H-	LD50 Oral	Rat	53 mg/kg	-
English (GB)	Europe	1	<u> </u>	9/15

Code : 000001189976 PPG AQUACOVER ONE 645 (TINTED)	Date of issue/Date of revision	: 12 April 2024	
SECTION 11: Toxicological info	ormation		
isothiazol-3-one and 2-methyl-2H- isothiazol-3-one (3:1)			

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
iodo-2-propynyl butylcarbamate	Eyes - Severe irritant	Rabbit	-	-	-
pyrithione zinc	Eyes - Cornea opacity	Rabbit	4	24 hours	24 hours

Conclusion/Summary

Skin

: There are no data available on the mixture itself.

Eyes

: There are no data available on the mixture itself.

Respiratory Sensitisation : There are no data available on the mixture itself.

Product/ingredient nameRoute of
exposureSpeciesResult1/2-benzisothiazol-3(2H)-oneskinGuinea pigSensitising

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxici	t <u>y (repeated exposure)</u>

Product/ingredient name		Category	Route of exposure	Target organs
Aspiration hazard Not available.				
Information on likely routes of exposure	: Not available.			
Potential acute health eff	fects			
Inhalation	: No known significant ef	fects or critical ha	zards.	
Ingestion	: No known significant ef	fects or critical ha	zards.	
Skin contact	: No known significant ef	fects or critical ha	zards.	
Eye contact	: No known significant ef	fects or critical ha	zards.	
Symptoms related to the	physical, chemical and toxi	cological charact	eristics	
Inhalation	: No specific data.			
Ingestion	: No specific data.			

Code : 00000118	39976	Date of issue/Date of revision	: 12 April 2024
PPG AQUACOVER ONE	645(TINTED)		

SECTION 11: Toxicological information

•=•••••	
Eye contact	: No specific data.
Delayed and immediate effe	cts as well as chronic effects from short and long-term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Other information	: Not available.
Sanding and grinding dusts m	ay be harmful if inhaled. Contains isothiazolinones. May cause allergic reaction.
11.2 Information on other has	varde l

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Fiodo-2-propynyl butylcarbamate	Acute EC50 0.186 mg/l	Daphnia - Daphnia	48 hours
	Fresh water	magna	
	Acute LC50 0.067 mg/l	Fish	96 hours
	Chronic NOEC 0.049 mg/l	Fish	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.11 mg/l	Algae	72 hours
	Acute EC50 2.9 mg/l	Daphnia	48 hours
	Acute LC50 2.15 mg/l	Fish	96 hours
	Chronic NOEC 0.0403 mg/l	Algae	72 hours
pyrithione zinc	Acute EC50 5.513 µg/l	Algae - Nitzschia	96 hours
	Marine water	pungens	
	Acute LC50 0.0082 mg/l	Daphnia	48 hours
	Chronic NOEC 1.889 µg/l	Algae - Nitzschia	96 hours
	Marine water	pungens	
	Chronic NOEC 0.0027 mg/l	Daphnia	21 days

Conclusion/Summary

: There are no data available on the mixture itself.

12.2 Persistence and degradability

Code	: 000001189976		Date of issue/Date of revision	: 12 April 2024
PPG AQUAC	OVER ONE 645 (TINTED)		

SECTION 12: Ecological information

Product/ingredient name	Test	Result	Dose	Inoculum
<mark>3</mark> ∕iodo-2-propynyl butylcarbamate	-	25 % - Inherent - 28 da	ays -	-
pyrithione zinc Conclusion/Summary	- : There are	39 % - 28 days no data available on the mixtu	- ure itself.	-
Product/ingredient name		Aquatic half-life	Photolysis	Biodegradability

iodo-2-propynyl butylcarbamate	-	-	Inherent
1,2-benzisothiazol-3(2H)-one	-	-	Readily
pyrithione zinc	-	50%; < 28 day(s)	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-(2-butoxyethoxy)ethanol	1	-	Low
1,2-benzisothiazol-3(2H)-one	0.7	-	Low
pyrithione zinc	0.9	0.9	Low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment meth	ods
<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
European waste catalog	ue (EWC)

Waste code	Waste designation			
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances			
English (GB)	Europe 12/15	;		

Code : 000001189976 PPG AQUACOVER ONE 645 (TINTED) Date of issue/Date of revision

: 12 April 2024

SECTION 13: Disposal considerations

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging		European waste catalogue (EWC)
Container	15 01 06	mixed packaging
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of s material and runoff and contact with soil, waterways, drains and sewers.	

14. Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID	: None identified.
ADN	: The product is only regulated as a dangerous good when transported in tank vessels.
IMDG	: None identified.
IATA	: None identified.

14.6 Special precautions for user Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

: Not applicable.

bulk according to IMO instruments

14.7 Maritime transport in

English (GB)

Code	: 000001189976	Date of issue/Date of revision	: 12 April 2024	
PPG AQUAC	OVER ONE 645 (TINTED)			

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)
Apply $XIV = 1$ ist of substances subject to authorization

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market

and use of certain dangerous substances,

mixtures and articles

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

Biocidal products regulation : Contains a biocidal product; C(M)IT/MIT (3:1)

15.2 Chemical safety : No Chemica

assessment

: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number PBT = Persistent, Bioaccumulative and Toxic vPvB = Very Persistent and Very Bioaccumulative ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Full text of abbreviated H statements

H301 H302 H310 H314 H315 H317 H318 H319 H330 H331	Toxic if swallowed. Harmful if swallowed. Fatal in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Fatal if inhaled. Toxic if inhaled.	
H360D	May damage the unborn child.	
English (GB)	Europe	14/15

Code : 000001189976 PPG AQUACOVER ONE 645 (TINTED)	Date of issue/Date of revision : 12 April 2024			
SECTION 16: Other information				
H372 H373	Causes damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
H411	Toxic to aquatic life with long lasting effects.			
H412	Harmful to aquatic life with long lasting effects.			
EUH071	Corrosive to the respiratory tract.			

Full text of classifications [CLP/GHS]

Acute Tox. 1	ACUTE TOXICITY - Category 1
Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE -
	Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE -
	Category 2

<u>History</u>

: 12 April 2024
: 27 February 2024
: EHS
: 3.03

<u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.