SAFETY DATA SHEET

Date of issue/Date of revision : 17 April 2024 Version : 1.05



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

Product code : 000001099765

Other means of identification

00288942; 00288943; 00291535; 00466920; 00467028

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd. PO Box 7509, Dammam 31472

Saudi Arabia

Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34

e-mail address of person responsible for this SDS

: PS.ACEMEA@ppg.com

1.4 Emergency telephone

number

: 00966 138473100 extn 1001

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :







AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

SECTION 2: Hazards identification

Signal word : Warning

Hazard statements : Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot

surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to

the environment. Avoid breathing vapour.

Response : Collect spillage.
Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

P280, P210, P273, P261, P391, P501

Hazardous ingredients : bis-[4-(2,3-epoxipropoxi)phenyl]propane

Supplemental label

elements

: Contains epoxy constituents. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria

for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
bis-[4-(2,3-epoxipropoxi) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥50 - ≤75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
Hydrocarbons, C9, aromatics < 0.1% cumene	REACH #: 01-2119455851-35	≥5.0 - ≤10	Flam. Liq. 3, H226 STOT SE 3, H335	EUH066: C ≥ 20%	[1]

English (GB) Saudi Arabia 2/13

Code : 00000109 AMERLOCK/SIGMACOV	9765 ER 2/400 BLACK 9000AM	Date of issue/Date of revision	: 17 April 2024	
SECTION 3: Com	position/informatio	n on ingredients		
	EC: 918-668-5 CAS: 64742-95-6	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066 See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep

person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness dryness cracking

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

English (GB) Saudi Arabia 3/13

AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing

: Do not use water jet.

media

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: Decomposition products may include the following materials: carbon oxides metal oxide/oxides

5.3 Advice for firefighters

Special precautions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

English (GB) Saudi Arabia 4/13

AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

SECTION 6: Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

English (GB) Saudi Arabia 5/13

AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

Hand protection

: Chemical splash goggles.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves

Body protection

: butyl rubber

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

English (GB) Saudi Arabia 6/13

Code : 000001099765 Date of issue/Date of revision : 17 April 2024

AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

Respiratory protection

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Colour Black.

Odour Characteristic. **Odour threshold** Not available.

Melting point/freezing point : May start to solidify at the following temperature: 8 to 12°C (46.4 to 53.6°F) This is

based on data for the following ingredient: bis-[4-(2,3-epoxipropoxi)phenyl]propane.

Weighted average: 1.29°C (34.3°F)

Initial boiling point and

boiling range

: >37.78°C

Flammability : Not available.

Upper/lower flammability or

explosive limits

Greatest known range: Lower: 1.4% Upper: 7.6% (Solvent naphtha (petroleum),

°F

Method

°C

Stable under recommended storage and handling conditions (see Section 7).

light aromatic)

Flash point Closed cup: 56°C

Auto-ignition temperature Ingredient name

Hydrocarbons, C9, aromatics < 0.1% 280 to 470 536 to 878

Decomposition temperature

Not applicable. insoluble in water.

pН Kinematic (40°C): >21 mm²/s **Viscosity**

Solubility(ies)

Media	Result
cold water	Not soluble

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

Ingredient neme	Vapou	ır Pressu	re at 20°C	Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Hydrocarbons, C9, aromatics < 0.1% cumene	1.57 to 9.75	0.21 to 1.3				

Evaporation rate Not available.

Relative density

: Highest known value: 15.4 (Air = 1) (1,2-Benzenedicarboxylic acid, di-Vapour density

C9-11-branched alkyl esters, C10-rich). Weighted average: 11.56 (Air = 1)

The product itself is not explosive, but the formation of an explosible mixture of **Explosive properties**

vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

Particle characteristics

Median particle size : Not applicable.

English (GB) Saudi Arabia 7/13

AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

SECTION 9: Physical and chemical properties

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxi)phenyl]propane	LD50 Dermal LD50 Oral	Rabbit Rat	23000 mg/kg 15000 mg/kg	-
Hydrocarbons, C9, aromatics < 0.1% cumene	LD50 Dermal	Rabbit - Male,	>2000 mg/kg	-
	LDE0 Orol	Female	9400 ma/ka	
	LD50 Oral	Rat	8400 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Oedema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	8.0	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

Conclusion/Summary

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi)phenyl]propane	skin	Mouse	Sensitising

Conclusion/Summary

English (GB) Saudi Arabia 8/13

AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

SECTION 11: Toxicological information

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
	Category 3 Category 3	-	Respiratory tract irritation Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9, aromatics < 0.1% cumene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

: Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

Skin contact: Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No specific data.Ingestion: No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness dryness cracking

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

Long term exposure

Potential immediate : Not available.

effects

English (GB) Saudi Arabia 9/13

AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

SECTION 11: Toxicological information

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently

exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Acute LC50 1.8 mg/l Fresh	Daphnia - daphnia	48 hours
	water	magna	
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
Hydrocarbons, C9, aromatics < 0.1% cumene	LC50 9.2 mg/l	Fish	96 hours

Conclusion/Summary: There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Hydrocarbons, C9, aromatics < 0.1% cumene	-	78 % - 28 days	-	-

Conclusion/Summary: There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi)phenyl]propane Hydrocarbons, C9, aromatics < 0.1% cumene	-	-	Not readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Hydrocarbons, C9, aromatics < 0.1% cumene	3.7 to 4.5	10 to 2500	High

12.4 Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

English (GB)	Saudi Arabia	10/13

AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

SECTION 12: Ecological information

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)	
Container	15 01 06	mixed packaging

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

English (GB) Saudi Arabia 11/13

Code : 000001099765 Date of issue/Date of revision : 17 April 2024

AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

Additional information

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or

≤5 kg.

Tunnel code : (D/E)

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation

regulations.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

14.7 Transport in bulk according to IMO

instruments

: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other national and international regulations.

: Not applicable. **Explosive precursors** Ozone depleting substances (1005/2009/EU)

Not listed.

English (GB) Saudi Arabia 12/13 Code : 000001099765 Date of issue/Date of revision : 17 April 2024

AMERLOCK/SIGMACOVER 2/400 BLACK 9000AM

SECTION 15: Regulatory information

15.2 Chemical safety : No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

Full text of abbreviated H

statements

acronyms

: H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

May cause an allergic skin reaction. H317 H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Full text of classifications

[CLP/GHS]

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 : Aquatic Chronic 2

ASPIRATION HAZARD - Category 1 Asp. Tox. 1

Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2

Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3

Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2

Skin Sens. 1 SKIN SENSITISATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY - SINGLE STOT SE 3

EXPOSURE - Category 3

History

Date of issue/ Date of

revision

: 17 April 2024

Date of previous issue : 19 February 2024

Prepared by : EHS **Version** : 1.05

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

> English (GB) Saudi Arabia 13/13