SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 17 April 2024 Version 3.02

Section 1. Identification		
Product name	: SIGMAGLIDE 790 (TIECOAT) HARDENER	
Product code	: 000001010982	
Other means of identification	: <a>D0188976; 00198089; 00231309; 00353496; 00419105	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Professional applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Supplier	 PPG Architectural Coatings Canada, Inc. 1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4 Canada +1 450-655-3121 	
	PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 888-977-4762	

Section 2. Hazard identification

Classification of the substance or mixture	: ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1B
substance of mixture	
	SERIOUS EYE DAMAGE - Category 1
	SKIN SENSITIZATION - Category 1B
	GERM CELL MUTAGENICITY - Category 2
	TOXIC TO REPRODUCTION - Category 1
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
	Health Hazards Not Otherwise Classified - Category 1
OUO labal alamanta	U

GHS label elements

Product name SIGMAGLIDE 790 (TIECOAT) HARDENER

Section 2. Hazard identification

Hazard pictograms	
Signal word	: Danger
Hazard statements	 Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. May damage fertility or the unborn child. Causes damage to organs. (thymus) Causes damage to organs through prolonged or repeated exposure. (immune system) Causes digestive tract burns.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	: IF exposed or concerned: Call a POISON CENTER or doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Store locked up.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Do not taste or swallow. Wash thoroughly after handling. Emits toxic fumes when heated.
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 3.1% (oral), 96.6% (dermal), 99.6% (inhalation)

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: SIGMAGLIDE 790 (TIECOAT) HARDENER
Other means of identification	: <i>D</i> 0188976; 00198089; 00231309; 00353496; 00419105

CAS number/other identifiers

Product name SIGMAGLIDE 790 (TIECOAT) HARDENER

Section 3. Composition/information on ingredients

Ingredient name	Synonyms	% (w/w)	CAS number
triacetoxyethylsilane	Silanetriol, 1-ethyl-, 1,1,1-triacetate; Silanetriol, ethyl-, triacetate; Ethyltriacetoxysilane; ethylsilanetriyl triacetate; triacetoxy(ethyl)silane; Alkyl (C1-3)acyloxy(C2-20)silane; Ethylsilanetriol, triacetate; Tris(acetyloxy) ethylsilane; SILANE, ETHYLTRIACETOXY-; SILANTRIOL, ETHYL-, TRIACETATE	80 - 100*	17689-77-9
dibutyltin di(acetate)	Acetic acid, 1,1'-(dibutylstannylene) ester; Stannane, bis(acetyloxy)dibutyl-; Dibutyltin diacetate; Stannane, diacetoxydibutyl-; bis(Acetyloxy) dibutylstannane; Dibutyltin di [aliphatic monocarboxylate (C2-31)]; Dibytyltin diacetate; TIN DIACETATE, DIBUTYL; di- n-butyl tin diacetate; Acetic acid, esters, 1,1'-(dibutylstannylene) ester	1 - 5*	1067-33-0
1,1,3,3-Disiloxanetetrol, 1,3-diethyl-, tetraacetate	TETRAACETATE, 1,1,3,3-DISILOXANETETROL- 1,3-DIETHYL; 1,3-diethyl- 1,1,3,3-disiloxanetetryl tetraacetate; 1,3,- Diethyl-1, 1,3,3-tetraacetoxydisiloxan	1 - 5*	122842-90-4

*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Section 4. First-aid measures

Potential acute health effe	<u>ets</u>
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. Causes damage to organs following a single exposure in contact with skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed. Corrosive to the digestive tract. Causes burns. Causes damage to organs following a single exposure if swallowed.
<u>Over-exposure signs/symp</u>	o <u>toms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
	Canada Page: 4/13

Section 5. Fire-fighting measures

Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Product name SIGMAGLIDE 790 (TIECOAT) HARDENER

Section 7. Handling and storage

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	:	Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	•	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational	exposure limits

Ingredient name	Exposure limits			
racetoxyethylsilane	None.			
dibutyltin di(acetate)	CA Alberta Provincial (Canada, 6/2018).			
•	[Tin Organic compounds as Sn]			
	Absorbed through skin.			
	OEL: 0.2 mg/m³, (as Sn) 15 minutes.			
	OEL: 0.1 mg/m³, (as Sn) 8 hours.			
	CA British Columbia Provincial (Canada,			
	6/2022). [Tin - Organic compounds as Sn]			
	Absorbed through skin.			
	STEL: 0.2 mg/m³, (as Sn) 15 minutes.			
	TWA: 0.1 mg/m³, (as Sn) 8 hours.			
	CA Quebec Provincial (Canada, 6/2022).			
	[Tin Organic compounds] Absorbed			
	through skin.			
	STEV: 0.2 mg/m³, (as Sn) 15 minutes.			
	TWAEV: 0.1 mg/m³, (as Sn) 8 hours.			
	CA Ontario Provincial (Canada, 6/2019).			
	[Tin (Organic compounds) as Sn]			
	Absorbed through skin.			
	TWA: 0.1 mg/m³, (as Sn) 8 hours.			
	Canada Page: 6/1			

Product name SIGMAGLIDE 790 (TIECOAT) HARDENER

Section 8. Exposure controls/personal protection

	CA Saskatchewan Provincial (Canada, 7/2013). [Tin organic compounds as Sn] Absorbed through skin. STEL: 0.2 mg/m ³ , (measured as Sn) 15 minutes.
	TWA: 0.1 mg/m³, (measured as Sn) 8 hours.
1,1,3,3-Disiloxanetetrol, 1,3-diethyl-, tetraacetate	None.

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measured	res	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Chemical splash goggles and face shield.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves		nitrile neoprene
Body protection	-	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

rippoururioo				
Physical state	:	Liquid.		
Color	1	Colorless.		
Odor	:	Characteristic.		
Odor threshold	:	Not available.		
рН	1	Not applicable.		
Melting point	1	Not available.		
Boiling point	:	>37.78°C (>100°F)	
Flash point	:	Closed cup: 109°C	C (228.2°F)	
Auto-ignition temperature	:	480°C (896°F)		
Decomposition temperature	:	Not available.		
Flammability	:	Not available.		
Lower and upper explosive (flammable) limits	:	Not available.		
Evaporation rate	:	Not available.		
Vapor pressure	:	Not available.		
Vapor density	:	Not available.		
Relative density	:	1.15		
Density(lbs / gal)	:	9.6		
Bulk Density (g/cm³)	:	1.18		
Solubility(ies)		Media	Result	
Solubility(les)	Ċ	cold water	Not soluble	
Partition coefficient: n- octanol/water	:	Not applicable.		
Viscosity	:	Kinematic (40°C (1	104°F)): >21 mm²/s (>21 cSt)	
Volatility	:	94% (v/v), 94.417%	% (w/w)	
% Solid. (w/w)	:	5.583		

Section 10. Stability and reactivity

	Canada Page: 8/13
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials carbon oxides metal oxide/oxides
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Conditions to avoid	 When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
triacetoxyethylsilane	LD50 Oral	Rat	1.462 g/kg	-
dibutyltin di(acetate)	LD50 Dermal	Rabbit	2318 mg/kg	-
Conclusion/Summary	: There are no data available	e on the mixture i	tself.	
Irritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data available	e on the mixture i	tself.	
Eyes	: There are no data available	e on the mixture i	tself.	
Respiratory	: There are no data available	e on the mixture i	tself.	
Sensitization				
Skin	: There are no data available	e on the mixture i	tself.	
Respiratory	: There are no data available	e on the mixture i	tself.	
<u>Mutagenicity</u>				
Conclusion/Summary	: There are no data available	e on the mixture i	tself.	
Carcinogenicity				
Conclusion/Summary	: There are no data available	e on the mixture i	tself.	
Reproductive toxicity				
Conclusion/Summary	: There are no data available	e on the mixture i	tself.	
Teratogenicity				
Conclusion/Summary	: There are no data available	e on the mixture i	tself.	
Specific target organ toxici	<u>ty (single exposure)</u>			

Name		Route of exposure	Target organs
dibutyltin di(acetate)	Category 1	oral	thymus

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
díbutyltin di(acetate)	Category 1	-	immune system

Target organs

: Contains material which may cause damage to the following organs: blood, kidneys, liver, bladder, gastrointestinal tract, upper respiratory tract, immune system, skin, central nervous system (CNS), eye, lens or cornea.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact Inhalation : Causes serious eye damage.

: No known significant effects or critical hazards.

Product name SIGMAGLIDE 790 (TIECOAT) HARDENER

Section 11. Toxicological information

Skin contact	:	Causes severe burns. Causes damage to organs following a single exposure in contact with skin. May cause an allergic skin reaction.
Ingestion	:	Harmful if swallowed. Corrosive to the digestive tract. Causes burns. Causes damage to organs following a single exposure if swallowed.
Over-exposure signs/sympto	oms	
Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
		and also chronic effects from short and long term exposure
Conclusion/Summary	:	There are no data available on the mixture itself. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Short term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Long term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Potential chronic health eff	fect	<u>s</u>
General	:	Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	Suspected of causing genetic defects.
Reproductive toxicity	:	May damage fertility or the unborn child.
Numerical measures of toxic	<u>city</u>	
	_	

Section 11. Toxicological information

Acute toxicity estimates					
Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
GMAGLIDE 790 (TIECOAT) HARDENER triacetoxyethylsilane dibutyltin di(acetate) 1,1,3,3-Disiloxanetetrol, 1,3-diethyl-, tetraacetate	1444.2 1462 N/A 500	2586.3 N/A 2318 N/A	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
dibutyltin di(acetate)	Acute EC10 3.1 mg/l	Fish	72 hours
	Acute EC50 0.5 mg/l	Algae	72 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
díbutyltin di(acetate)	-	-	Not readily

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13 Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Disposal should be in acc	ordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14. Transport information

	TDG	IMDG	ΙΑΤΑ
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class (es)	8	8	8
Packing group	II	II	II
Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	(dibutyltin di(acetate))	(dibutyltin di(acetate))	Not applicable.

Additional information

Section 15. Regulatory information			
Proof of class statement	Sification : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.40-2.42 (Class 8), 2.7 (Marine pollutant mark).		
Transport in t to IMO instru	oulk according : Not applicable. ments		
Special preca	utions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.		
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.		
IMDG	The marine pollutant mark is not required when transported in sizes of ≤ 5 L or ≤ 5 kg.		
TDG	: The marine pollutant mark is not required when transported by road or rail.		

National Inventory List

Canada inventory (DSL)

: All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 1 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 3 Flammability : 1 Instability : 0

Canada Page: 12/13

Section 16. Other information

Date of issue/Date of revision	17 April 2024
Organization that prepared the SDS	: EHS
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

✓ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.