SAFETY DATA SHEET



Date of issue 17 April 2024

Version 1.06

Section 1. Product and company identification

Product name Product code Other means of identification Product type : NOVAGUARD 840 BASE WHITE

- : 000001099330
- : 00237773; 00463831
- : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

Supplier's details:	
Supplier	 PPG INDUSTRIES CHILE S.A. Puerto Madero 9710, Of. 23 Pudahuel - Chile Teléfono: +56 (2) 2571 0750 Fax: +56 (2) 2571 0752
Email address:	: HazComLatam@ppg.com
Emergency telephone number	: +56 (2) 2777 1994 (RITA CHILE)

Section 2. Hazards identification

Classification of the substance or mixture	: ACUTE TOXICITY (dermal) - Category 5 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
Target organs	 CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 AQUATIC HAZARD (ACUTE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2 Contains material which causes damage to the following organs: blood, liver, heart, spleen, brain, bone marrow.
	Contains material which may cause damage to the following organs: kidneys, lungs, cardiovascular system, upper respiratory tract, immune system, eyes, central nervous system (CNS).

English (US) Chile

Code 000001099330 Product name NOVAGUAR	Date of issue	17 April 2024	Version 1.06
Section 2. Hazards			
	Percentage of the mixture of toxicity: 84%	consisting of ingredient(s) of u	
	Percentage of the mixture c aquatic environment: 38.8%	consisting of ingredient(s) of u	nknown hazards to the
GHS label elements			
Hazard pictograms		¥	
Signal word	: Danger		
Hazard statements	: May be harmful in contact w Causes skin irritation. May cause an allergic skin i Causes serious eye irritation Harmful if inhaled. May cause cancer. May cause damage to orga Toxic to aquatic life with lon	reaction. n. ns through prolonged or repea	ated exposure.
Precautionary statements			
Prevention	: Obtain special instructions I and eye or face protection. Wash thoroughly after hand	Avoid release to the environm	
Response	contaminated clothing and v CENTER or doctor if you fe rash occurs: Get medical ac water for several minutes. F	d or concerned: Get medical a CENTER or doctor if you feel t wash it before reuse. IF ON S el unwell. Wash with plenty o dvice or attention. IF IN EYES Remove contact lenses, if pres ation persists: Get medical ad	unwell. Take off KIN: Call a POISON f water. If skin irritation or S: Rinse cautiously with sent and easy to do.
Storage	: Not applicable.		
Disposal	: Dispose of contents and co and international regulations		local, regional, national
Other hazards which do not result in classification	: Contains a substance that r or during cure at curing tem	nay emit formaldehyde if store peratures greater than 60C (
Classification according to NCh382:	: 9		
Label according to NCh2190:			

Section 3. Composition/information on ingredients

Substance/mixture			
Other means of			
identification			

CAS number

: Mixture

: 00237773; 00463831

CAS number/other identifiers

:	Not applicable.
---	-----------------

Ingredient name	%	CAS number
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	30 - <60	9003-36-5
crystalline silica, respirable powder (>10 microns)	15 - <20	14808-60-7
Phenol, polymer with formaldehyde, glycidyl ether (MW<=700)	10 - <12.5	28064-14-4
benzyl alcohol	10 - <12.5	100-51-6
Talc , not containing asbestiform fibres	3 - <5	14807-96-6
titanium dioxide	3 - <5	13463-67-7
crystalline silica, respirable powder (<10 microns)	2 - <3	14808-60-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Description of necessary in	
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Indication of immediate mee	lical attention and special treatment needed, if necessary
Notes to physician Specific treatments	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Potential acute health effect	<u>s</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: Harmful if inhaled.
Skin contact	: May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

Section 4. First aid measures

Ingestion

: No known significant effects or critical hazards.

See toxicological information (Section 11)

Section 5. Fire-fighting measures				
Extinguishing media				
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.			
Unsuitable extinguishing media	: None known.			
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.			
Hazardous thermal decomposition products	 Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides Formaldehyde. 			
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. 			
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. 			

Section 6. Accidental release measures

....

Personal precautions, protec	TIN	<u>re equipment and emergency procedures</u>
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

 Methods and materials for containment and cleaning up

 Small spill
 : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 6. Accidental release measures					
Product nam	NOVAGUARD 840 BASE WHIT	E			
Code 000001099330		Date of issue	17 April 2024	Version	1.06

Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	Not regulated.	
crystalline silica, respirable powder (>10 microns)	Ministry of Health (Chile, 2/2018). TWA: 0.08 mg/m ³ 8 hours. Form: Respirable fraction	
Phenol, polymer with formaldehyde, glycidyl ether (MW<=700) Alcohol bencílico Talc , not containing asbestiform fibres	Not regulated. Not regulated. Ministry of Health (Chile, 2/2018). TWA: 1.75 mg/m ³ 8 hours. Form:	
dióxido de titanio (en forma de polvo y conteniendo un 1% o más d partículas con un diámetro < 10um)	Respirable fraction ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m ³ 8 hours. Form: respira fraction, finescale particles	ble
crystalline silica, respirable powder (<10 microns)	Ministry of Health (Chile, 2/2018). TWA: 0.08 mg/m ³ 8 hours. Form: Respirable fraction	
	English (US) Chile	5/13

1.06

Section 8. Exposu	re	controls/personal protection
Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
ndividual protection measur	<u>'es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection	:	Chemical splash goggles.
Skin protection Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	:	butyl rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

		English (US)	Chile	6/13
Boiling point	: >37.78°C (>100°F)			
Melting point	: Not available.			
рН	: Not applicable.			
Odor	: Aromatic.			
Color	: White.			
Physical state	: Liquid.			
Appearance				

Code 000001099330 Product name NOVAGUAR	RD 840 BASE WHITE	Date of issue	17 April 2024	Version	1.06
Section 9. Physica	al and chem	ical proper	ties		
Flash point	: Closed cup: 15	5°C (311°F)			
Evaporation rate	: Not available.				
Flammability (solid, gas)	: Not available.				
Lower and upper explosive (flammable) limits	: Not available.				
Vapor pressure	: Not available.				
Vapor density	: Not available.				
Relative density	: 1.44				
	Media	Result	:		
Solubility(ies)	: cold water	Not so	luble		
Partition coefficient: n- octanol/water	: Not applicable.				
Auto-ignition temperature	: Not available.				

Auto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds Formaldehyde. metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	LD50 Oral	Rat	>10000 mg/kg	-
benzyl alcohol	LD50 Dermal	Rat Rabbit	>4178 mg/m ³ 2000 mg/kg	4 hours -
titanium dioxide	LD50 Oral LC50 Inhalation Dusts and mists LD50 Dermal	Rat Rat Rabbit	1.23 g/kg >6.82 mg/l >5000 mg/kg	- 4 hours -

Code 000001099330 Product name NOVAG	UARD 840 BASE WHITE	Date of issue	17 April	2024	Version	1.06
Section 11. Toxi	cological inf	ormation				
	LD50 Oral		Rat	>5000 mg/kg	-	
Conclusion/Summary Irritation/Corrosion Not available.	: There are no d	ata available on t	he mixture itsel	f.		
Conclusion/Summary	. There are no d		1	<i>c</i>		

Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Sensitization	
Not available	

Not available.

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Not available.	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Not available.	

Conclusion/Summary

: There are no data available on the mixture itself.

Classification

Product/ingredient name	OSHA	IARC	NTP
crystalline silica, respirable powder (>10 microns)	+	1	Known to be a human carcinogen.
titanium dioxide	-	2B	-
crystalline silica, respirable powder (<10 microns)	+	1	Known to be a human carcinogen.

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

Reproductive toxicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation
	Englisi	n (US) Chile	8/13

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
crystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-

Target organs

: Contains material which causes damage to the following organs: blood, liver, heart, spleen, brain, bone marrow. Contains material which may cause damage to the following organs: kidneys, lungs, cardiovascular system, upper respiratory tract, immune system, eyes, central nervous system (CNS).

Aspiration hazard

Name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

Information on the likely routes of exposure		Not available.
Potential acute health effects		
Eye contact	÷	Causes serious eye irritation.
Inhalation	3	Harmful if inhaled.
Skin contact	:	May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phy	sic	cal, chemical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	1	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	;	No specific data.
Delayed and immediate effec	<u>ts</u>	and also chronic effects from short and long term exposure
Conclusion/Summary	:	There are no data available on the mixture itself. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be

English (US)	Chile	9/13

Code000001099330Product nameNOVAC	SUARD 8	Date of issue 40 BASE WHITE	17 April 2024	Version	1.06
Section 11. Tox	icolo	gical information			
		harmful depending on the duratic appropriate personal protective e B). Exposure to component solve occupational exposure limit may membrane and respiratory system and central nervous system. Syr fatigue, muscular weakness, dro consciousness. Solvents may ca through the skin. There is some vapors in combination with const expected from exposure to noise cause irritation and reversible da vomiting. This takes into accoun and also chronic effects of comp oral, inhalation and dermal routes	equipment and/or enginee ent vapor concentrations result in adverse health e m irritation and adverse e mptoms and signs include wsiness and, in extreme ause some of the above e evidence that repeated e ant loud noise can cause e alone. If splashed in the mage. Ingestion may can it, where known, delayed onents from short-term a	ring controls (se in excess of the effects such as r iffects on the kide headache, dize cases, loss of effects by absorp xposure to orga greater hearing e eyes, the liquid use nausea, dia and immediate nd long-term ex	ee Section e stated mucous dneys, liver ziness, ption anic solvent g loss than d may urrhea and effects
Short term exposure					
Potential immediate effects	:	There are no data available on th	ne mixture itself.		
Potential delayed effect	ts :	There are no data available on th	ne mixture itself.		
Long term exposure		.			
Potential immediate effects	:	There are no data available on th	ne mixture itself.		
Potential delayed effect	ts :	There are no data available on th	ne mixture itself.		
Potential chronic health	<u>effects</u>				
Not available.					
General	:	May cause damage to organs thr sensitized, a severe allergic reac ow levels.			
Carcinogenicity	:	May cause cancer. Risk of canc	er depends on duration a	nd level of expo	osure.
Mutagenicity	: 1	No known significant effects or c	ritical hazards.		
Reproductive toxicity	: 1	No known significant effects or c	ritical hazards.		

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name		Dermal (mg/kg)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
NOVAGUARD 840 BASE WHITE benzyl alcohol	7849.7 1230		N/A N/A	2.4 1.5

Other information

: Not available.

Section 12. Ecological information

Ecotoxicity			
Product/ingredient name	Result	Species	Exposure
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Acute LC50 2.54 mg/l	Fish	96 hours
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours

Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol benzyl alcohol	2.7 0.87	-	Low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled
	containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Code	000001099330	Date of issue	17 April 2024	Version	1.06
Product nam	e NOVAGUARD 840 BASE WHITE				

Section 14. Transport information

	=			
	UN	Brazil (ANTT)	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	formaldehyde, glycidyl ether (MW<=700))	formaldehyde, glycidyl ether (MW<=700))	formaldehyde, glycidyl ether (MW<=700))	formaldehyde, glycidyl ether (MW<=700))
Transport hazard class(es)	9	9	9	9
Packing group	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	(Epoxy Resin)	Not applicable.

Additional information

UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	
Brazil	This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	
Risk number	: 90	
IMDG	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.	
Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.		
Transport in bul	k according : Not applicable.	

to IMO instruments

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product	 NCh 382 - Hazardous substances - General terminology and classification. NCh 2245 - Material Safety Data Sheet for Chemicals - Contents and section order. D. S. 148 - Sanitary regulations on hazardous waste management. D. S. 298 - Transport of dangerous goods by road. D. 2744 - Limit for Least extent in positive.
	 D. S. 374 – Limit for Lead content in paints. D. S. 594 - Regulation on basic sanitary and environmental conditions at workplace.

English (US)	Chile

NOVAGUARD 840 BASE WHITE

Date of issue

1.06

Section 16. Other information

<u>History</u>	
Date of previous issue	: 2/19/2024
Version	: 1.06 EHS
Key to abbreviations	 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations
References	ABNT NBR 14725-4: 2014 ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Chile