SAFETY DATA SHEET

Date of issue/Date of revision 26 April 2024

Version3.01

Section 1. Identification

Product code	: 00322087
Product name	: PSX 700FD HARDENER
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses	of the substance or mixture and uses advised against
Product use	: Coating. Professional applications, Used by spraying.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
Supplier's details	: PT PPG Coatings Indonesia JI. Rawagelam III No.1 13930 Jakarta Indonesia Tel +62 21 4605710 PMC.Safety@PPG.com
Emergency telephone number	: CHEMTREC 001-803-017-9114 (CCN 17704)

Section 2. Hazards identification

Classification of the	: SKIN CORROSION/IRRITATION - Category 1B
substance or mixture	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
	SKIN SENSITIZATION - Category 1
	GERM CELL MUTAGENICITY - Category 2
	TOXIC TO REPRODUCTION - Category 1B
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	AQUATIC HAZARD (LONG-TERM) - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the
	aquatic environment: 27.4%

GHS label elements, including precautionary statements

2

Hazard pictograms



Signal word

: Danger

Product code 00322087 Product name PSX 700FD HARDENER Version 3.01

Section 2. Hazards identification

Hazard statements	 Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. May damage fertility or the unborn child. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure. (immune
	system) Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	: Collect spillage. IF exposed or concerned: Call a POISON CENTER or doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not	Causes digestive tract burns

result in classification

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

CAS number/other identifiers

CAS number	: Not applicable.
EC number	: Mixture.

Ingredient name	%	CAS number
3-aminopropyltriethoxysilane	50- 100	919-30-2
3-(trimethoxysilyl)propylamine	25- <50	13822-56-5
dibutylbis(pentane-2,4-dionato-O,O')tin	5- <10	22673-19-4
Propanoic acid, 3-(trimethoxysilyl)-, methyl ester	0.1- <0.3	76301-00-3

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Potential acute	health effects
-----------------	----------------

Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause damage to organs following a single exposure in contact with skin. May cause an allergic skin reaction.
Ingestion	 Corrosive to the digestive tract. Causes burns. May cause damage to organs following a single exposure if swallowed.
Over-exposure signs/s	symptoms
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
ndication of immediate	medical attention and special treatment needed, if necessary
Notes to physician	. In case of inhalation of decomposition products in a fire, symptoms may be delayed

Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

Section 4. First aid measures

mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	Protection of first-aiders	
--	----------------------------	--

See toxicological information (Section 11)

Section 5. Fire-fighting measures Extinguishing media

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides Formaldehyde.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Section 6. Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling **Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. : Eating, drinking and smoking should be prohibited in areas where this material is Advice on general handled, stored and processed. Workers should wash hands and face before occupational hygiene eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. **Conditions for safe storage**, : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct including any sunlight in a dry, cool and well-ventilated area, away from incompatible materials incompatibilities (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters Occupational exposure limits

Section 8. Exposure controls/personal protection

Ingredient name			Exposure limits	
dibutylbis(pentane-2,4-diona	to-(D,O')tin	Minister of Labor of the Republic of Indonesia (Indonesia, 4/2018). [Organic compounds of tin] Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours.	
Recommended monitoring procedures	:		riate monitoring standards. Reference to hods for the determination of hazardous	
Appropriate engineering controls	:		es, gas, vapor or mist, use process enclosures, neering controls to keep worker exposure to ommended or statutory limits.	
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
Individual protection measu	res			
Hygiene measures		eating, smoking and using the lavator Appropriate techniques should be use Contaminated work clothing should ne	bughly after handling chemical products, before y and at the end of the working period. ed to remove potentially contaminated clothing. ot be allowed out of the workplace. Wash . Ensure that eyewash stations and safety location.	
Eye/face protection	:	Chemical splash goggles and face sh	ield.	
Skin protection				
Hand protection	:	be worn at all times when handling ch this is necessary. Considering the pa check during use that the gloves are s should be noted that the time to break	s complying with an approved standard should nemical products if a risk assessment indicates arameters specified by the glove manufacturer, still retaining their protective properties. It kthrough for any glove material may be arers. In the case of mixtures, consisting of the of the gloves cannot be accurately	
Gloves	1	nitrile neoprene		
Body protection	:		e body should be selected based on the task ad and should be approved by a specialist	
Other skin protection	:		nal skin protection measures should be formed and the risks involved and should be ing this product.	
Respiratory protection	:	hazards of the product and the safe w workers are exposed to concentration appropriate, certified respirators. Use	In known or anticipated exposure levels, the vorking limits of the selected respirator. If its above the exposure limit, they must use a properly fitted, air-purifying or air-fed d standard if a risk assessment indicates this is	

Section 9. Physical and chemical properties

Appearance

Appearance			
Physical state	:	Liquid.	
Color	1	Colorless.	
Odor	:	Aromatic.	
Odor threshold	:	Not available.	
рН	:	Not applicable.	
Melting point	:	Not available.	
Boiling point	:	>37.78°C (>100°F)	
Flash point	:	Closed cup: 82°C (179.6	°F)
Evaporation rate	:	Not available.	
Flammability/Combustible properties (solid, gas)	:	Not available.	
Lower and upper explosive (flammable) limits	1	Not available.	
Vapor pressure	:	Not available.	
Vapor density	:	Not available.	
Relative density	:	0.98	
Solubility/icc)		Media	Result
Solubility(ies)	1	cold water	Not soluble
Partition coefficient: n- octanol/water	:	Not applicable.	
Auto-ignition temperature	:	Not available.	
Decomposition temperature	:	Not available.	
Viscosity	:	Kinematic (40°C): >21 m	m²/s

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result		Species	Dose	Exposure
3-aminopropyltriethoxysilane	LC50 Inhalation [Dusts and mis	ts Rat	>7.35 mg/l	4 hours
	LD50 Dermal		Rabbit	4 g/kg	-
	LD50 Oral		Rat	1.57 g/kg	-
3-(trimethoxysilyl)	LD50 Dermal		Rabbit	11460 mg/kg	-
propylamine			Det	2010 m m///m	
dibutulbic (poptopo	LD50 Oral LD50 Dermal		Rat Rat	3010 mg/kg >2000 mg/kg	-
dibutylbis(pentane- 2,4-dionato-O,O')tin	LD50 Dermai		Rai	~2000 mg/kg	-
	LD50 Oral		Rat	1864 mg/kg	-
Conclusion/Summary	: There are no da	ata available o	on the mixture		
Irritation/Corrosion					
Conclusion/Summary					
Skin	: There are no d	lata available	on the mixture	itself	
Eyes	: There are no d				
Respiratory	: There are no d				
Sensitization					
	Destant	0		Dece II	
Product/ingredient name	Route of	Species		Result	
	exposure				
3-aminopropyltriethoxysilane	skin	Guinea pig		Sensitizing	
Conclusion/Summary					
Skin	: There are no d	data available	on the mixture	itself.	
Respiratory	: There are no d	data available	on the mixture	itself.	
Mutagenicity					
Conclusion/Summary	: There are no d	data available	on the mixture	itself.	
Carcinogenicity					
Conclusion/Summary	: There are no d	lata available i	on the mixture	itself	
Reproductive toxicity					
	• These			ite elf	
Conclusion/Summary	: There are no d	uata avallable	on the mixture	ilsell.	
Teratogenicity					
Conclusion/Summary	: There are no d		on the mixture	itself.	
Specific target organ toxicit	<u>y (single exposu</u>	<u>re)</u>			
Name		C	ategory	Route of	Target organs
				exposure	
dibutylbis(pentane-2,4-dionate	o-O,O')tin	c	ategory 1	-	-
Propanoic acid, 3-(trimethoxy			ategory 3	-	Respiratory tract
					irritation
Specific target organ toxicit	y (repeated expo	sure)			
Name		C	ategory	Route of	Target organs
				exposure	
dibutylbis(pentane-2,4-dionate	o-Q.Q')tin		ategory 1	-	immune system

Aspiration hazard

Section 11. Toxicological information

Not available.

Information on the likely routes of exposure	:	Not available.
Potential acute health effects	5	
Eye contact	:	Causes serious eye damage.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	1	Causes severe burns. May cause damage to organs following a single exposure in contact with skin. May cause an allergic skin reaction.
Ingestion	:	Corrosive to the digestive tract. Causes burns. May cause damage to organs following a single exposure if swallowed.
Symptoms related to the phy	<u>/sic</u>	cal, chemical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain watering
		redness
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate effect	<u>:ts</u>	and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	1	There are no data available on the mixture itself.
<u>Long term exposure</u>		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	1	There are no data available on the mixture itself.
Potential chronic health eff	ect	<u>s</u>
General	:	May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.

Product name PSX 700FD HARDENER

Section 11. Toxicological information

Mutagenicity

: Suspected of causing genetic defects.

Reproductive toxicity

: May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	2254.49 mg/kg

Other information

Causes digestive tract burns. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C (140F).

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
3-aminopropyltriethoxysilane	Acute LC50 >934 mg/l	Fish	96 hours

Persistence/degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
 Aminopropyltriethoxysilane (trimethoxysilyl) propylamine 	1.7 0.2	3.4	Low Low

Mobility in soil

Soil/water partition: Not available.coefficient (Koc)

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods :	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
--------------------	---

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8
Packing group	II	II	II
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(dibutylbis(pentane- 2,4-dionato-O,O')tin)	Not applicable.

Additional information

UN	: None identified.		
IMDG	: The marine pollutant mark is not required when transported in sizes of \leq 5 L or \leq 5 kg.		
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.		

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

: No known specific national and/or regional regulations applicable to this product

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

Classification



(including its ingredients).

Law No. 74/2001 - Banned

None of the components are listed.

Law No. 74/2001 - Restricted

None of the components are listed.

Law No. 74/2001 -: Not determined

Chemicals that may be used

International regulations

Montreal Protocol

Section 15. Regulatory information

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 26 April 2024
Date of previous issue	: 5/21/2021
Version	: 3.01
Prepared by	: EHS
Key to abbreviations	 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
	UN = United Nations

✓ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.