SAFETY DATA SHEET



Date of issue/Date of revision 26 April 2024

Version 2

Section 1. Identification of the substance/mixture and of the company/undertaking

Product code : 00445107

Product name : SIGMASHIELD 1090 HARDENER 0.4G

Other means of : Not available.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Coating.

Professional applications, Used by spraying.

Uses advised against: Product is not intended, labelled or packaged for consumer use.

Supplier's details : PPG Coatings (Thailand) Co., Ltd.

15 Rama 9 Road, Kwaeng Huamark, Khet Bangkapi, Bangkok 10240 Thailand

T: 662-319-4190 #224 F: 662-319-4189

Emergency telephone number (with hours of

operation)

: CHEMTREC 001-800-13-203-9987 (CCN 17704)

Section 2. Hazards identification

Classification of the substance or mixture

: ACUTE TOXICITY (oral) - Category 4
ACUTE TOXICITY (dermal) - Category 5
SKIN CORROSION/IRRITATION - Category 1

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN SENSITIZATION - Category 1A TOXIC TO REPRODUCTION - Category 2

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

AQUATIC HAZARD (ACUTE) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 38%

GHS label elements

Thailand Page: 1/13

Product code 00445107

Date of issue 26 April 2024

Version 2

Product name SIGMASHIELD 1090 HARDENER 0.4G

Section 2. Hazards identification

Hazard pictograms







Signal word : Danger

: Harmful if swallowed. **Hazard statements**

May be harmful in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure. (respiratory

Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Use personal protective equipment as required. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing

should not be allowed out of the workplace.

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove Response

person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Other hazards which do not : None known.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

CAS number : Not applicable.

> **Thailand** Page: 2/13

Product name SIGMASHIELD 1090 HARDENER 0.4G

Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
3 -aminomethyl-3,5,5-trimethylcyclohexylamine Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-	25- <50 25- <50	2855-13-2 9046-10-0 (n = 2-6)
(2-aminomethylethoxy)- 2-piperazin-1-ylethylamine	5- <10	140-31-8

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes severe burns. May be harmful in contact with skin. May cause an allergic

skin reaction.

Ingestion: Harmful if swallowed.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Thailand Page: 3/13

Product name SIGMASHIELD 1090 HARDENER 0.4G

Section 4. First aid measures

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon oxides

nitrogen oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Thailand Page: 4/13

Date of issue 26 April 2024

Product code 00445107

Product name SIGMASHIELD 1090 HARDENER 0.4G

Version 2

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

> **Thailand** Page: 5/13

Product code 00445107

Date of issue 26 April 2024

Version 2

Product name SIGMASHIELD 1090 HARDENER 0.4G

Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection **Skin protection**

Hand protection

: Chemical splash goggles and face shield.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

estimated.

Gloves Body protection : butyl rubber : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

> **Thailand** Page: 6/13

Product name SIGMASHIELD 1090 HARDENER 0.4G

Section 8. Exposure controls/personal protection

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Colorless.

Odor : Characteristic.

Odor threshold : Not available.

pH : Not available.

Melting point : May start to solidify at the following temperature: 8°C (46.4°F) This is based on data

for the following ingredient: 3-aminomethyl-3,5,5-trimethylcyclohexylamine.

Weighted average: 2.38°C (36.3°F)

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 234°C (453.2°F)

Evaporation rate : 0.007 (2-piperazin-1-ylethylamine) compared with butyl acetate

Flammability (solid, gas) : liquid

Lower and upper explosive

(flammable) limits

: Greatest known range: Lower: 1.1% Upper: 9.4% (2-piperazin-1-ylethylamine)

Vapor pressure : Fighest known value: 2.3 kPa (17.5 mm Hg) (at 20°C) (water). Weighted average:

0.46 kPa (3.45 mm Hg) (at 20°C)

Vapor density: Highest known value: 4.4 (Air = 1) (2-piperazin-1-ylethylamine).

Relative density : 0.95

Media Result

Solubility(ies) :

Partition coefficient: n-

octanol/water

Not applicable.

Auto-ignition temperature :

: Lowest known value: >300°C (>572°F) (2-piperazin-1-ylethylamine).

Decomposition temperature

Stable under recommended storage and handling conditions (see Section 7).

Viscosity : Kinematic (40°C): >21 mm²/s

Thailand Page: 7/13

Product name SIGMASHIELD 1090 HARDENER 0.4G

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides nitrogen oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3 -aminomethyl-	LC50 Inhalation Dusts and mists	Rat	>5.01 mg/l	4 hours
3,5,5-trimethylcyclohexylamine				
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
Poly[oxy(methyl-1,2-ethanediyl)], α-	LD50 Dermal	Rat	2980 mg/kg	-
(2-aminomethylethyl)-ω-				
(2-aminomethylethoxy)-				
	LD50 Oral	Rat	2885 mg/kg	-
2-piperazin-1-ylethylamine	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	866 mg/kg	-
	LD50 Oral	Rat	2140 mg/kg	-

Conclusion/Summary: There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Sensitization

3	Route of exposure	Species	Result
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	skin	Guinea pig	Sensitizing
2-piperazin-1-ylethylamine	skin	Guinea pig	Sensitizing

Conclusion/Summary

Thailand	Page: 8/13
----------	------------

Product name SIGMASHIELD 1090 HARDENER 0.4G

Section 11. Toxicological information

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	3.3	Route of exposure	Target organs
2-piperazin-1-ylethylamine	Category 1	inhalation	respiratory tract

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes severe burns. May be harmful in contact with skin. May cause an allergic

skin reaction.

Ingestion : Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Thailand Page: 9/13

Product name SIGMASHIELD 1090 HARDENER 0.4G

Section 11. Toxicological information

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

: Not available.

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General: May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
	1891.52 mg/kg 2758.18 mg/kg

Other information :

None known.

Thailand Page: 10/13

Product name SIGMASHIELD 1090 HARDENER 0.4G

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	EC50 15 mg/l	Algae	72 hours
2-piperazin-1-ylethylamine	Acute EC50 58 mg/l	Daphnia	48 hours

Conclusion/Summary: Not available.

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2 -piperazin-1-ylethylamine	OECD 301F	0 % - Not readily - 28 days	-	-

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Poly[oxy(methyl-	-	-	Not readily
1,2-ethanediyl)], α-			
(2-aminomethylethyl)-ω-			
(2-aminomethylethoxy)-			
2-piperazin-1-ylethylamine	-	-	Not readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
, , , , , ,	0.99 -1.48	-	Low Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Thailand Page: 11/13

Product name SIGMASHIELD 1090 HARDENER 0.4G

Section 14. Transport information

	UN	IMDG	IATA
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8
Packing group	II	II	II
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

UN : None identified. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

Section 15. Regulatory information

Harmful Chemicals List

Safety, health and environmental regulations specific for the product

: Listed

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Thailand Page: 12/13

Product name SIGMASHIELD 1090 HARDENER 0.4G

Section 16. Other information

History

Date of issue/Date of : 26 April 2024

revision

Date of previous issue : 8/2/2021

Version : 2
Prepared by : EHS

Key to abbreviations : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

✓ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Thailand Page: 13/13