

# SAFETY DATA SHEET



Date of issue/Date of revision : 13 July 2024 Version : 1.08

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : AMERCOAT 133 WHITE RESIN

**Product code** : 00333892

#### Other means of identification

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications, Used by spraying.

**Use of the substance/mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### Supplier

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code : 00333892

Date of issue/Date of revision

: 13 July 2024

AMERCOAT 133 WHITE RESIN

## SECTION 2: Hazards identification

### 2.2 Label elements

Hazard pictograms

:



Signal word

: Warning

Hazard statements

: Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.

### Precautionary statements

Prevention

: Wear protective gloves. Wear eye or face protection. Avoid release to the environment.  
Avoid breathing vapour. Wash thoroughly after handling.

Response

: Collect spillage.

Storage

: Not applicable.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

P280, P273, P261, P264, P391, P501

Hazardous ingredients

: Bis-[4-(2,3-epoxypropoxy)phenyl]propane oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Supplemental label elements

: Contains epoxy constituents. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

### 2.3 Other hazards

Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

Code : 00333892

Date of issue/Date of revision

: 13 July 2024

AMERCOAT 133 WHITE RESIN

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Diis-[4-(2,3-epoxipropoxy)phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	REACH #: 01-2119485289-22 EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4	≥5.0 - ≤10	Skin Irrit. 2, H315 Skin Sens. 1, H317	-	[1]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥1.0 - ≤5.0	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
Hydrocarbons, C9, aromatics > 0.1% cumene	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 128601-23-0	<1.0	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066 <b>See Section 16 for the full text of the H statements declared above.</b>	Carc. 1B, H350: C ≥ 10% EUH066: C ≥ 20%	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

#### Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

#### Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Code : 00333892

Date of issue/Date of revision

: 13 July 2024

AMERCOAT 133 WHITE RESIN

## SECTION 4: First aid measures

- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
sulfur oxides  
halogenated compounds  
metal oxide/oxides

### 5.3 Advice for firefighters

Code : 00333892

Date of issue/Date of revision

: 13 July 2024

AMERCOAT 133 WHITE RESIN

## SECTION 5: Firefighting measures

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Code : 00333892

Date of issue/Date of revision

: 13 July 2024

AMERCOAT 133 WHITE RESIN

## SECTION 7: Handling and storage

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
n-butyl acetate	<b>EU OEL (Europe, 1/2022).</b> STEL: 150 ppm 15 minutes. STEL: 723 mg/m <sup>3</sup> 15 minutes. TWA: 241 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.

#### Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
bis-[4-(2,3-epoxipropoxy)phenyl]propane	DNEL	Long term Inhalation	12.25 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	12.25 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	3.571 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Dermal	3.571 mg/kg bw/day	General population [Consumers]	Systemic

Code : 00333892

Date of issue/Date of revision

: 13 July 2024

AMERCOAT 133 WHITE RESIN

## SECTION 8: Exposure controls/personal protection

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	DNEL	Long term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic	
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic	
	DNEL	Long term Dermal	89.3 µg/kg bw/day	General population	Systemic	
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	0.75 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	0.87 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	4.93 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic	
	n-butyl acetate	DNEL	Long term Dermal	0.5 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	0.87 mg/m <sup>3</sup>	General population	Systemic
DNEL		Long term Dermal	1 mg/kg bw/day	Workers	Systemic	
DNEL		Long term Inhalation	3.6 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Long term Inhalation	300 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Long term Dermal	11 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Long term Oral	2 mg/kg bw/day	General population	Systemic	
DNEL		Short term Oral	2 mg/kg bw/day	General population	Systemic	
DNEL		Long term Dermal	3.4 mg/kg bw/day	General population	Systemic	
DNEL		Short term Dermal	6 mg/kg bw/day	General population	Systemic	
DNEL		Long term Dermal	7 mg/kg bw/day	Workers	Systemic	
DNEL		Short term Dermal	11 mg/kg bw/day	Workers	Systemic	
DNEL		Long term Inhalation	12 mg/m <sup>3</sup>	General population	Systemic	
DNEL		Long term Inhalation	35.7 mg/m <sup>3</sup>	General population	Local	
Hydrocarbons, C9, aromatics > 0.1% cumene	DNEL	Long term Inhalation	48 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Local	
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	300 mg/m <sup>3</sup>	Workers	Local	
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Local	
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Inhalation	150 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Dermal	25 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	32 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Dermal	11 mg/kg bw/day	General population	Systemic	
DNEL	Long term Oral	11 mg/kg bw/day	General population	Systemic		

### PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail	
bis-[4-(2,3-epoxipropoxy)phenyl] propane	-	Fresh water	0.006 mg/l	Assessment Factors	
	-	Marine water	0.001 mg/l	Assessment Factors	
	-	Fresh water sediment	0.996 mg/kg dwt	Equilibrium Partitioning	
	-	Marine water sediment	0.1 mg/kg dwt	Equilibrium Partitioning	
	-	Soil	0.196 mg/kg dwt	Equilibrium Partitioning	
	-	Sewage Treatment Plant	10 mg/l	Assessment Factors	
	-	Secondary Poisoning	11 mg/kg	Assessment Factors	
	n-butyl acetate	-	Fresh water	0.18 mg/l	-
		-	Marine water	0.018 mg/l	-
		-	Fresh water sediment	0.981 mg/kg	-
-		Marine water sediment	0.0981 mg/kg	-	
-		Sewage Treatment Plant	35.6 mg/l	-	
-		Soil	0.0903 mg/kg	-	



Code : 00333892

Date of issue/Date of revision

: 13 July 2024

AMERCOAT 133 WHITE RESIN

## SECTION 8: Exposure controls/personal protection

### 8.2 Exposure controls

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.



Code : 00333892

Date of issue/Date of revision

: 13 July 2024

AMERCOAT 133 WHITE RESIN

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : White.
- Odour** : Characteristic.
- Odour threshold** : Not available.
- Melting point/freezing point** : May start to solidify at the following temperature: 8 to 12°C (46.4 to 53.6°F) This is based on data for the following ingredient: bis-[4-(2,3-epoxipropoxy)phenyl]propane. Weighted average: -0.84°C (30.5°F)
- Initial boiling point and boiling range** : >37.78°C
- Flammability** : Not available.
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 1.4% Upper: 7.6% (n-butyl acetate)
- Flash point** : Closed cup: 93.33°C
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
n-butyl acetate	415	779	EU A.15

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- pH** : Not applicable. insoluble in water.
- Viscosity** : Kinematic (40°C): >21 mm<sup>2</sup>/s
- Solubility(ies)** :

Media	Result
cold water	Not soluble

- Water Solubility at room temperature** : 0 g/l
- Partition coefficient: n-octanol/water** : Not applicable.
- Vapour pressure** : 1.3 kPa (10 mm Hg)
- Evaporation rate** : 0.81 (butyl acetate = 1)
- Relative density** : 1.99
- Vapour density** : Highest known value: 11.7 (Air = 1) (bis-[4-(2,3-epoxipropoxy)phenyl]propane). Weighted average: 11.28 (Air = 1)
- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties** : Product does not present an oxidizing hazard.

#### Particle characteristics

- Median particle size** : Not applicable.

### 9.2 Other information

No additional information.

Code : 00333892  
AMERCOAT 133 WHITE RESIN

Date of issue/Date of revision : 13 July 2024

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides sulfur oxides halogenated compounds metal oxide/oxides

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxy)phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
	LD50 Oral	Rat	17100 mg/kg	-
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LC50 Inhalation Vapour	Rat	2000 ppm	4 hours
n-butyl acetate	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10.768 g/kg	-
Hydrocarbons, C9, aromatics > 0.1% cumene	LD50 Dermal	Rabbit	>3160 mg/kg	-
	LD50 Oral	Rat - Female	3492 mg/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Oedema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

#### Sensitisation

Code : 00333892

Date of issue/Date of revision

: 13 July 2024

AMERCOAT 133 WHITE RESIN

## SECTION 11: Toxicological information

Product/ingredient name	Route of exposure	Species	Result
1,4-bis-[4-(2,3-epoxipropoxy)phenyl]propane oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	skin skin	Mouse Guinea pig	Sensitising Sensitising

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
n-butyl acetate Hydrocarbons, C9, aromatics > 0.1% cumene	Category 3 Category 3 Category 3	- -	Narcotic effects Respiratory tract irritation Narcotic effects

Not available.

### Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9, aromatics > 0.1% cumene	ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

**Eye contact** : Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : No specific data.

**Ingestion** : No specific data.

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Code : 00333892

Date of issue/Date of revision

: 13 July 2024

AMERCOAT 133 WHITE RESIN

## SECTION 11: Toxicological information

### Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

### Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

**Other information** : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Avoid contact with skin and clothing.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Bis-[4-(2,3-epoxypropoxy)phenyl]propane  oxirane, mono[(C12-14-alkyloxy)methyl] derivs. n-butyl acetate Hydrocarbons, C9, aromatics > 0.1% cumene	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
	LC50 >100 mg/l	Fish	96 hours
	Acute LC50 18 mg/l	Fish	96 hours
	EC50 3.2 mg/l	Daphnia	48 hours
	LC50 9.2 mg/l	Fish	96 hours

Conclusion/Summary : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
n-butyl acetate	TEPA and OECD 301D	83 % - Readily - 28 days	-	-
Hydrocarbons, C9, aromatics > 0.1% cumene	-	75 % - Readily - 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

<b>Code</b> : 00333892	<b>Date of issue/Date of revision</b> : 13 July 2024
<b>AMERCOAT 133 WHITE RESIN</b>	

## SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxy)phenyl]propane	-	-	Not readily
n-butyl acetate	-	-	Readily
Hydrocarbons, C9, aromatics > 0.1% cumene	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
<input checked="" type="checkbox"/> xirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.77	-	Low
n-butyl acetate	2.3	-	Low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

#### European waste catalogue (EWC)

Waste code	Waste designation
08 01 99	wastes not otherwise specified

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

<b>Code</b> : 00333892	<b>Date of issue/Date of revision</b> : 13 July 2024
<b>AMERCOAT 133 WHITE RESIN</b>	

### SECTION 13: Disposal considerations

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number or ID number</b>	UN3082	UN3082	UN3082	UN3082
<b>14.2 UN proper shipping name</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  (bis-[4-(2,3-epoxipropoxi)phenyl]propane)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  (bis-[4-(2,3-epoxipropoxi)phenyl]propane)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  (bis-[4-(2,3-epoxipropoxi)phenyl]propane)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  (bis-[4-(2,3-epoxipropoxi)phenyl]propane)
<b>14.3 Transport hazard class(es)</b>	9	9	9	9
<b>14.4 Packing group</b>	III	III	III	III
<b>14.5 Environmental hazards</b>	Yes.	Yes.	Yes.	Yes.
<b>Marine pollutant substances</b>	Not applicable.	Not applicable.	(bis-[4-(2,3-epoxipropoxi)phenyl]propane)	Not applicable.

#### Additional information

**ADR/RID** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**Tunnel code** : (-)

**ADN** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not applicable.

Code : 00333892

Date of issue/Date of revision

: 13 July 2024

AMERCOAT 133 WHITE RESIN

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions** : Not applicable.  
**on the manufacture,  
placing on the market  
and use of certain  
dangerous substances,  
mixtures and articles**

**Explosive precursors** : Not applicable.

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Seveso Directive

This product is controlled under the Seveso Directive.

##### Danger criteria

Category
E2

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

### Full text of abbreviated H statements



<b>Code</b> : 00333892	<b>Date of issue/Date of revision</b> : 13 July 2024
<b>AMERCOAT 133 WHITE RESIN</b>	

**SECTION 16: Other information**

H226 H304 H315 H317 H319 H335 H336 H350 H411 EUH066	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause cancer. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.
--	---

**Full text of classifications [CLP/GHS]**

Aquatic Chronic 2 Asp. Tox. 1 Carc. 1B Eye Irrit. 2 Flam. Liq. 3 Skin Irrit. 2 Skin Sens. 1 STOT SE 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 ASPIRATION HAZARD - Category 1 CARCINOGENICITY - Category 1B SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
--	--

**History**

**Date of issue/ Date of revision** : 13 July 2024  
**Date of previous issue** : 16 February 2024  
**Prepared by** : EHS  
**Version** : 1.08

**Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*