

SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 13 September 2024

Version 1

Section 1. Identification

Product name : SIGMACOVER 380 BASE REDBROWN
Product code : 000001190994
Other means of identification : 00453508; 00453721
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.
Use of the substance/mixture : Coating.
Uses advised against : Not applicable.

Supplier : PPG Architectural Coatings Canada, Inc.
1550, rue Ampère, bureau 500
Boucherville (Québec) J4B 7L4
Canada
+1 450-655-3121

PPG Industries, Inc.
One PPG Place
Pittsburgh, PA 15272

Emergency telephone number : (412) 434-4515 (U.S.)
(514) 645-1320 (Canada)
SETIQ Interior de la República: 800-00-214-00 (México)
SETIQ Ciudad de México: (55) 5559-1588 (México)

Technical Phone Number : 888-977-4762

Section 2. Hazard identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN IRRITATION - Category 2
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1B
CARCINOGENICITY - Category 1
TOXIC TO REPRODUCTION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
Health Hazards Not Otherwise Classified - Category 1

GHS label elements

Section 2. Hazard identification

Hazard pictograms**Signal word**

: Danger

Hazard statements

: Flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause cancer.
Suspected of damaging fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure. (hearing organs)
Causes digestive tract burns.
Prolonged or repeated contact may dry skin and cause irritation.

Precautionary statements**Prevention**

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage

: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Do not taste or swallow. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 23% (oral), 60.3% (dermal), 71% (inhalation)

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Product name : SIGMACOVER 380 BASE REDBROWN
Other means of identification : 00453508; 00453721

CAS number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS number
Talc , not containing asbestiform fibres	Talc; magnesium silicate monohydrate (talc) not containing asbestiform fibres	10 - 30*	14807-96-6
crystalline silica, respirable powder (>10 microns)	alpha-quartz; Silica, crystalline (quartz); Silica, Crystalline Quartz; SILICA, CRYSTALLINE, QUARTZ; Silica-Crystalline, Quartz; Silica - Crystalline Quartz; Silica-Crystalline : Quartz; Silica, crystalline - quartz	10 - 30*	14808-60-7
bis-[4-(2,3-epoxypropoxy)phenyl] propane	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-; Bisphenol A diglycidyl ether; Bisphenol A, diglycidyl ether; Bis-[4-(2,3-epoxypropoxy)phenyl]propane; 2,2-bis[4-(2,3-epoxypropoxy)phenyl]propane; Propane, 2,2-bis(p-(2,3-epoxypropoxy)phenyl)-; diglycidyl ether of bisphenol-A; 2,2-bis(4-hydroxyphenyl) propane bis(2,3-epoxypropyl) ether; Araldite; DIPHENYLOL PROPANE DIGLYCIDYL ETHER	7 - 13*	1675-54-3
xylene	Benzene, dimethyl-; Xylol; Benzene, dimethyl-, mixed isomers; xylene, mixed isomers, pure; xylene, crude; Benzene, dimethyl-; Xylene (mixed); xylene (total); Xylenes; Dimethylbenzene; XYLENES (Isomer Mixture)	3 - 7*	1330-20-7
diiron trioxide	Iron oxide (Fe ₂ O ₃); Iron oxide; C.I. Pigment Red 101; Ferric oxide; Iron oxide, anhydrous; Iron oxide, red; Iron sesquioxide; Iron trioxide; iron oxide pigment; Iron oxide dust and fume (as Fe); Rouge	3 - 7*	1309-37-1
4-nonylphenol, branched	Phenol, 4-nonyl-, branched; Branched 4-nonylphenol (mixed isomers); Nonylphenol, 4-branched; N-NONYLPHENOL; Nonylphenol; C9-Branched alkyl phenol; Branched p-nonylphenol; 4-Nonylphenol; branched; Monoalkyl(C3-9)phenol; C9 branched alkyl phenol	1 - 5*	84852-15-3

Section 3. Composition/information on ingredients

aluminium powder (stabilised)	aluminium powder (stabilised)	1 - 5*	7429-90-5
Epoxy Resin (700<MW<=1100)	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] (700<MW<=1100)	1 - 5*	25036-25-3
Phenol, methylstyrenated	Isopropenylbenzene	1 - 5*	68512-30-1
2-methylpropan-1-ol	iso-butanol; 1-Propanol, 2-methyl-; Isobutyl alcohol; Isobutanol; 2-Methyl-1-propanol; Isopropylcarbinol; IBA; i-Butyl alcohol; isobutanol; iso-butanol; Isobutyl alcohol (I,T); 1-Propanol, 2-methyl- (I,T)	1 - 5*	78-83-1
crystalline silica, respirable powder (<10 microns)	alpha-quartz; Silica, crystalline (quartz); Silica, Crystalline Quartz; SILICA, CRYSTALLINE, QUARTZ; Silica-Crystalline, Quartz; Silica - Crystalline Quartz; Silica-Crystalline : Quartz; Silica, crystalline - quartz	1 - 5*	14808-60-7
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics		1 - 5*	64742-48-9
ethylbenzene	Benzene, ethyl-; Phenylethane; Ethylbenzol; photosensitive emulsion consisting of cyclized polyisoprene containing: — 55 % or more but not more than 75 % by weight of xylene (CAS RN 1330-20-7) and — 12 % or more but not more than 18 % by weight of ethylbenzene (CAS RN 100-41-4); EB; Mono-(or di-) methyl (ethyl,bromoallyl, bromopropyl,oxycarbonyl orchloropropyl,oxycarbonyl) benzene	0.5 - 1.5*	100-41-4

*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Section 4. First-aid measures

- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : Corrosive to the digestive tract. Causes burns.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon oxides
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for

Section 6. Accidental release measures

emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Special precautions

: Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene

: Wash hands thoroughly after handling.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Talc , not containing asbestiform fibres	<p>CA British Columbia Provincial (Canada, 8/2023). TWA: 2 mg/m³ 8 hours. Form: Respirable</p> <p>CA Quebec Provincial (Canada, 7/2023). TWAEV: 2 mg/m³ 8 hours. Form: Respirable dust.</p> <p>CA Alberta Provincial (Canada, 3/2023). OEL: 2 mg/m³ 8 hours. Form: Respirable particulate</p> <p>CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m³ 8 hours. Form: Respirable particulate matter.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable fraction</p>
crystalline silica, respirable powder (>10 microns)	<p>CA British Columbia Provincial (Canada, 8/2023). [Silica, Crystalline - alpha quartz and Cristobalite] TWA: 0.025 mg/m³ 8 hours. Form: Respirable</p> <p>CA Ontario Provincial (Canada, 6/2019). [Silica, Crystalline (Quartz/Tripoli)] TWA: 0.1 mg/m³ 8 hours. Form: Respirable</p> <p>CA Quebec Provincial (Canada, 7/2023). [Silica Crystalline -Quartz] TWAEV: 0.1 mg/m³ 8 hours. Form: Respirable dust.</p> <p>CA Alberta Provincial (Canada, 3/2023). OEL: 0.025 mg/m³ 8 hours. Form: Respirable particulate</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m³ 8 hours. Form: respirable fraction</p>
bis-[4-(2,3-epoxipropoxy)phenyl]propane xylene	<p>None.</p> <p>CA Alberta Provincial (Canada, 3/2023). [Dimethylbenzene] OEL: 651 mg/m³ 15 minutes. OEL: 150 ppm 15 minutes. OEL: 434 mg/m³ 8 hours. OEL: 100 ppm 8 hours.</p> <p>CA British Columbia Provincial (Canada, 8/2023). [Xylene (o, m & p isomers)] STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.</p> <p>CA Quebec Provincial (Canada, 7/2023). [Xylene] STEV: 651 mg/m³ 15 minutes. STEV: 150 ppm 15 minutes. TWAEV: 434 mg/m³ 8 hours. TWAEV: 100 ppm 8 hours.</p> <p>CA Ontario Provincial (Canada, 6/2019).</p>

Section 8. Exposure controls/personal protection

diiron trioxide

[Xylene (o-, m-, p-isomers)]

STEL: 150 ppm 15 minutes.

TWA: 100 ppm 8 hours.

CA Saskatchewan Provincial (Canada, 7/2013). [Xylene]

STEL: 150 ppm 15 minutes.

TWA: 100 ppm 8 hours.

CA Alberta Provincial (Canada, 3/2023).OEL: 5 mg/m³, (as Fe) 8 hours. Form: Respirable**CA Ontario Provincial (Canada, 6/2019).**TWA: 5 mg/m³ 8 hours. Form: Respirable particulate matter.**CA British Columbia Provincial (Canada, 8/2023).**TWA: 10 mg/m³ 8 hours. Form: Total dust**CA Quebec Provincial (Canada, 7/2023).**TWAEV: 5 mg/m³, (as Fe) 8 hours. Form: dust and fume**CA Saskatchewan Provincial (Canada, 7/2013).**STEL: 10 mg/m³, (measured as Fe) 15 minutes. Form: dust and fumeTWA: 5 mg/m³, (measured as Fe) 8 hours. Form: dust and fume

None.

CA Alberta Provincial (Canada, 3/2023).**Skin sensitizer.**OEL: 10 mg/m³, () 8 hours. Form: Metal Dust**CA Saskatchewan Provincial (Canada, 7/2013). [Aluminum pyro powders and metal dust]**STEL: 20 mg/m³, (measured as Al) 15 minutes. Form: Metal dustTWA: 10 mg/m³, (measured as Al) 8 hours. Form: Metal dustSTEL: 10 mg/m³, (measured as Al) 15 minutes. Form: Pyro powderTWA: 5 mg/m³, (measured as Al) 8 hours. Form: Pyro powder**CA British Columbia Provincial (Canada, 8/2023). [Aluminum metal and insoluble compounds]**TWA: 1 mg/m³ 8 hours. Form: Respirable**CA Quebec Provincial (Canada, 7/2023). [aluminum and its compounds]**TWAEV: 5 mg/m³ 8 hours. Form: Respirable dust.**CA Ontario Provincial (Canada, 6/2019). [Aluminum metal and insoluble compounds]**TWA: 1 mg/m³ 8 hours. Form: Respirable particulate matter.4-nonylphenol, branched
aluminium powder (stabilised)

Section 8. Exposure controls/personal protection

Epoxy Resin (700<MW<=1100)
Phenol, methylstyrenated
2-methylpropan-1-ol

None.

None.

CA Alberta Provincial (Canada, 3/2023).**Skin sensitizer.**OEL: 152 mg/m³ 8 hours.

OEL: 50 ppm 8 hours.

CA British Columbia Provincial (Canada, 8/2023).

TWA: 50 ppm 8 hours.

CA Ontario Provincial (Canada, 6/2019).

TWA: 50 ppm 8 hours.

CA Quebec Provincial (Canada, 7/2023).TWAEV: 152 mg/m³ 8 hours.

TWAEV: 50 ppm 8 hours.

CA Saskatchewan Provincial (Canada, 7/2013).

STEL: 60 ppm 15 minutes.

TWA: 50 ppm 8 hours.

crystalline silica, respirable powder (<10 microns)

CA British Columbia Provincial (Canada, 8/2023). [Silica, Crystalline - alpha quartz and Cristobalite]TWA: 0.025 mg/m³ 8 hours. Form:

Respirable

CA Ontario Provincial (Canada, 6/2019).**[Silica, Crystalline (Quartz/Tripoli)]**TWA: 0.1 mg/m³ 8 hours. Form: Respirable**CA Quebec Provincial (Canada, 7/2023).****[Silica Crystalline -Quartz]**TWAEV: 0.1 mg/m³ 8 hours. Form:

Respirable dust.

CA Alberta Provincial (Canada, 3/2023).OEL: 0.025 mg/m³ 8 hours. Form:

Respirable particulate

CA Saskatchewan Provincial (Canada, 7/2013).TWA: 0.05 mg/m³ 8 hours. Form:

respirable fraction

None.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2%
aromatics
ethylbenzene

CA Alberta Provincial (Canada, 3/2023).OEL: 543 mg/m³ 15 minutes.

OEL: 125 ppm 15 minutes.

OEL: 434 mg/m³ 8 hours.

OEL: 100 ppm 8 hours.

CA British Columbia Provincial (Canada, 8/2023).

TWA: 20 ppm 8 hours.

CA Ontario Provincial (Canada, 6/2019).

TWA: 20 ppm 8 hours.

CA Quebec Provincial (Canada, 7/2023).

TWAEV: 20 ppm 8 hours.

CA Saskatchewan Provincial (Canada, 7/2013).

STEL: 125 ppm 15 minutes.

TWA: 100 ppm 8 hours.

Section 8. Exposure controls/personal protection

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles and face shield.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves : butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state	: Liquid.
Color	: Brownish-red.
Odor	: Aromatic. [Slight]
Odor threshold	: Not available.
pH	: Not applicable.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 38°C (100.4°F)
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Flammability	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Evaporation rate	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.56
Density (lbs / gal)	: 13.02

Media	Result
cold water	Not soluble

Partition coefficient: n-octanol/water : Not applicable.

Viscosity : Kinematic (room temperature): >400 mm²/s (>400 cSt)
Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Volatility : 20% (v/v), 12.991% (w/w)

% Solid. (w/w) : 87.009

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.
Refer to protective measures listed in sections 7 and 8.

Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxy)phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
xylene	LD50 Oral	Rat	15000 mg/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-
diiron trioxide	LD50 Oral	Rat	4.3 g/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
4-nonylphenol, branched	LD50 Oral	Rat	10 g/kg	-
	LD50 Dermal	Rabbit	2.14 g/kg	-
aluminium powder (stabilised)	LD50 Oral	Rat	1300 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
Epoxy Resin (700<MW <=1100)	LD50 Oral	Rat	>15900 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
Phenol, methylstyrenated	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rabbit	>2000 mg/kg	-
2-methylpropan-1-ol	LD50 Oral	Rat	>2000 mg/kg	-
	LC50 Inhalation Vapor	Rat	24.6 mg/l	4 hours
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LD50 Dermal	Rabbit	2460 mg/kg	-
	LD50 Oral	Rat	2830 mg/kg	-
ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>6 g/kg	-
	LC50 Inhalation Vapor	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxy)phenyl]propane	skin	Mouse	Sensitizing

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Classification

Section 11. Toxicological information

Product/ingredient name	OSHA	IARC	NTP
crystalline silica, respirable powder (>10 microns)	+	1	Known to be a human carcinogen.
bis-[4-(2,3-epoxypropoxy)phenyl] propane	-	3	-
xylene	-	3	-
diiiron trioxide	-	3	-
crystalline silica, respirable powder (<10 microns)	+	1	Known to be a human carcinogen.
ethylbenzene	-	2B	-

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

Reproductive toxicity**Conclusion/Summary** : There are no data available on the mixture itself.**Teratogenicity****Conclusion/Summary** : There are no data available on the mixture itself.**Specific target organ toxicity (single exposure)**

Name	Category	Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation
xylene	Category 3	-	Respiratory tract irritation
2-methylpropan-1-ol	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
crystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-
ethylbenzene	Category 2	-	hearing organs

Target organs

: Contains material which causes damage to the following organs: liver, spleen, brain, skin, bone marrow, central nervous system (CNS), eye, lens or cornea.
Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, the reproductive system, cardiovascular system, upper respiratory tract, immune system, ears.

Aspiration hazard

Name	Result
xylene	ASPIRATION HAZARD - Category 1
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Section 11. Toxicological information

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : Corrosive to the digestive tract. Causes burns.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

- Conclusion/Summary** : There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

- Potential immediate effects** : There are no data available on the mixture itself.

Section 11. Toxicological information

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

General : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMACOVER 380 BASE REDBROWN	8113.4	3895.9	N/A	42.9	5.5
bis-[4-(2,3-epoxipropoxy)phenyl]propane	15000	23000	N/A	N/A	N/A
xylene	4300	1700	N/A	11	1.5
diiron trioxide	10000	N/A	N/A	N/A	N/A
4-nonylphenol, branched	1300	2140	N/A	N/A	N/A
Epoxy Resin (700<MW<=1100)	2500	2500	N/A	N/A	N/A
Phenol, methylstyrenated	2500	2500	N/A	N/A	N/A
2-methylpropan-1-ol	2830	2460	N/A	24.6	N/A
ethylbenzene	3500	17800	N/A	17.8	1.5

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
diiron trioxide	Chronic NOEC 0.3 mg/l	Daphnia	21 days
4-nonylphenol, branched	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute EC50 0.044 mg/l	Crustaceans - <i>Moina macrocopa</i>	48 hours
	Acute LC50 0.221 mg/l	Fish	96 hours
2-methylpropan-1-ol	Acute EC50 1100 mg/l	Daphnia	48 hours
ethylbenzene	Acute EC50 1.8 mg/l Fresh water	Daphnia	48 hours
	Chronic NOEC 1 mg/l Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	-

Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
ethylbenzene	-	79 % - Readily - 10 days	-	-

Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxy)phenyl]propane	-	-	Not readily
xylene	-	-	Readily
ethylbenzene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
4-nonylphenol, branched	5.4	251.19	Low
Phenol, methylstyrenated	3.627	-	Low
2-methylpropan-1-ol	1	-	Low
ethylbenzene	3.6	79.43	Low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14. Transport information

	TDG	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class (es)	3	3	3
Packing group	III	III	III

Product code 00001190994

Date of issue 13 September 2024 Version 1

Product name SIGMACOVER 380 BASE REDBROWN

Section 14. Transport information

Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	(bis-[4-(2,3-epoxipropoxy)phenyl]propane)	(bis-[4-(2,3-epoxipropoxy)phenyl]propane)	Not applicable.

Additional information

- TDG** : The marine pollutant mark is not required when transported by road or rail.
- IMDG** : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.3.2.5.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Proof of classification statement : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark).

Section 15. Regulatory information

National Inventory List

Canada inventory (DSL) : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 2 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 3 Flammability : 2 Instability : 0

Date of issue/Date of revision 13 September 2024

Organization that prepared the SDS : EHS

Section 16. Other information

Key to abbreviations

: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
UN = United Nations

✔ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.