

# SAFETY DATA SHEET



Date of issue/Date of revision : 26 September 2024 Version : 1.02

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : PITTHANE ULTRA LS LIGHT TINT BASE

**Product code** : 00440506

#### Other means of identification

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### Supplier

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225  
Skin Sens. 1, H317  
STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code : 00440506

Date of issue/Date of revision


: 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 2: Hazards identification

### 2.2 Label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: Highly flammable liquid and vapour.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.

### Precautionary statements

Prevention

: Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapour.

Response

: IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Storage

: Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

P280, P210, P261, P304 + P312, P403 + P233, P501

Hazardous ingredients

:  heptan-2-one  
methyl acetate  
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate  
Poly(oxy-1,2-ethanediyl),  $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxy-  
Fatty acids, C14-18 and C16-18-unsatd., maleated  
maleic anhydride

Supplemental label elements

:  Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

### 2.3 Other hazards

Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

Code : 00440506 Date of issue/Date of revision : 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures : Mixture

| Product/ingredient name   | Identifiers   | % by weight | Classification   | Specific Conc. Limits, M-factors and ATEs                         | Type    |
|---|---|-------------|--|---|---------|
| heptan-2-one  | REACH #:<br>01-2119902391-49<br>EC: 203-767-1<br>CAS: 110-43-0<br>Index: 606-024-00-3 | ≥10 - ≤25   | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Acute Tox. 4, H332<br>STOT SE 3, H336  | ATE [Oral] = 1600 mg/kg<br>ATE [Inhalation (vapours)] = 16.7 mg/l | [1] [2] |
| methyl acetate  | EC: 201-185-2<br>CAS: 79-20-9<br>Index: 607-021-00-X                                  | ≥5.0 - ≤8.5 | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br>EUH066  | -   | [1] [2] |
| propylene carbonate   | REACH #:<br>01-2119537232-48<br>EC: 203-572-1<br>CAS: 108-32-7<br>Index: 607-194-00-1 | ≤1.4        | Eye Irrit. 2, H319   | -   | [1]     |
| Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | REACH #:<br>01-2119491304-40<br>EC: 915-687-0<br>CAS: 1065336-91-5                    | <0.25       | Skin Sens. 1A, H317<br>Repr. 2, H361f<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410  | M [Acute] = 1<br>M [Chronic] = 1                                  | [1]     |
| Poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-hydroxy- | EC: 400-830-7<br>CAS: 104810-48-2<br>Index: 607-176-00-3                              | ≤0.30       | Skin Sens. 1A, H317<br>Aquatic Chronic 2, H411   | -   | [1]     |
| Fatty acids, C14-18 and C16-18-unsatd., maleated  | REACH #:<br>01-2119978273-29<br>EC: 288-306-2<br>CAS: 85711-46-2                      | ≤0.30       | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1B, H317   | -   | [1]     |
| propylidynetrimethanol  | REACH #:<br>01-2119486799-10<br>EC: 201-074-9<br>CAS: 77-99-6                         | ≤0.30       | Repr. 2, H361fd  | -   | [1]     |
| maleic anhydride  | REACH #:<br>01-2119472428-31<br>EC: 203-571-6<br>CAS: 108-31-6<br>Index: 607-096-00-9 | ≤0.10       | Acute Tox. 4, H302<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Resp. Sens. 1, H334<br>Skin Sens. 1A, H317<br>STOT RE 1, H372 (respiratory system) (inhalation)<br>EUH071 | ATE [Oral] = 400 mg/kg<br>Skin Sens. 1, H317: C ≥ 0.001%          | [1] [2] |

Code : 00440506 Date of issue/Date of revision : 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

### SECTION 3: Composition/information on ingredients

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

##### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

Code : 00440506 Date of issue/Date of revision : 26 September 2024  
PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 4: First aid measures

**Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

Code : 00440506 Date of issue/Date of revision : 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 6: Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Code : 00440506 Date of issue/Date of revision : 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name | Exposure limit values   |
|-------------------------|---|
| heptan-2-one            | <b>EU OEL (Europe, 1/2022). Absorbed through skin.</b><br>STEL: 475 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 238 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours. |
| methyl acetate          | <b>ACGIH TLV (United States, 7/2023).</b><br>STEL: 757 mg/m <sup>3</sup> 15 minutes.<br>STEL: 250 ppm 15 minutes.<br>TWA: 606 mg/m <sup>3</sup> 8 hours.<br>TWA: 200 ppm 8 hours.             |
| maleic anhydride        | <b>ACGIH TLV (United States, 7/2023). Skin sensitiser. Inhalation sensitiser.</b><br>TWA: 0.01 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction and vapor                                  |

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs

| Product/ingredient name | Type                | Exposure              | Value                    | Population            | Effects  |
|-------------------------|---------------------|-----------------------|--------------------------|-----------------------|----------|
| heptan-2-one            | DNEL                | Long term Oral        | 23.32 mg/kg bw/day       | General population    | Systemic |
|                         | DNEL                | Long term Dermal      | 23.32 mg/kg bw/day       | General population    | Systemic |
|                         | DNEL                | Long term Dermal      | 54.27 mg/kg bw/day       | Workers               | Systemic |
|                         | DNEL                | Long term Inhalation  | 84.31 mg/m <sup>3</sup>  | General population    | Systemic |
|                         | DNEL                | Long term Inhalation  | 394.25 mg/m <sup>3</sup> | Workers               | Systemic |
|                         | DNEL                | Short term Inhalation | 1516 mg/m <sup>3</sup>   | Workers               | Systemic |
| methyl acetate          | DNEL                | Long term Oral        | 21.5 mg/kg bw/day        | General population    | Systemic |
|                         | DNEL                | Long term Dermal      | 21.5 mg/kg bw/day        | General population    | Systemic |
|                         | DNEL                | Long term Dermal      | 43 mg/kg bw/day          | Workers               | Systemic |
|                         | DNEL                | Long term Inhalation  | 64 mg/m <sup>3</sup>     | General population    | Systemic |
|                         | DNEL                | Long term Inhalation  | 133 mg/m <sup>3</sup>    | General population    | Local    |
|                         | DNEL                | Short term Oral       | 203 mg/kg bw/day         | General population    | Systemic |
|                         | DNEL                | Short term Dermal     | 203 mg/kg bw/day         | General population    | Systemic |
|                         | DNEL                | Long term Inhalation  | 300 mg/m <sup>3</sup>    | Workers               | Systemic |
|                         | DNEL                | Short term Inhalation | 3777 mg/m <sup>3</sup>   | General population    | Systemic |
|                         | DNEL                | Short term Inhalation | 3777 mg/m <sup>3</sup>   | Workers               | Systemic |
|                         | DNEL                | Long term Inhalation  | 620 mg/m <sup>3</sup>    | Workers               | Local    |
|                         | propylene carbonate | DNEL                  | Long term Dermal         | 10 mg/cm <sup>2</sup> | Workers  |
| DNEL                    |                     | Long term Oral        | 10 mg/kg bw/day          | General population    | Systemic |
| DNEL                    |                     | Long term Dermal      | 10 mg/kg bw/day          | General population    | Systemic |
| DNEL                    |                     | Long term Inhalation  | 10 mg/m <sup>3</sup>     | General population    | Local    |
| DNEL                    |                     | Long term Inhalation  | 17.4 mg/m <sup>3</sup>   | General population    | Systemic |
| DNEL                    |                     | Long term Dermal      | 20 mg/kg bw/day          | Workers               | Systemic |



|  |   |
|--|---|
| <b>Code</b> : 00440506                   | <b>Date of issue/Date of revision</b> : 26 September 2024 |
| <b>PITTHANE ULTRA LS LIGHT TINT BASE</b> |   |

**SECTION 8: Exposure controls/personal protection**

|   |                       |                       |                         |                                |          |
|---|-----------------------|-----------------------|-------------------------|--------------------------------|----------|
| Poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-hydroxy- | DNEL                  | Long term Inhalation  | 20 mg/m <sup>3</sup>    | Workers                        | Local    |
|   | DNEL                  | Long term Inhalation  | 70.53 mg/m <sup>3</sup> | Workers                        | Systemic |
|   | DNEL                  | Long term Inhalation  | 0.35 mg/m <sup>3</sup>  | Workers                        | Systemic |
|   | DNEL                  | Long term Dermal      | 0.5 mg/kg               | Workers                        | Systemic |
|   | DNEL                  | Long term Inhalation  | 0.085 mg/m <sup>3</sup> | General population [Consumers] | Systemic |
|   | DNEL                  | Long term Dermal      | 0.25 mg/kg              | General population [Consumers] | Systemic |
|   | DNEL                  | Long term Oral        | 0.025 mg/kg             | General population [Consumers] | Systemic |
|   | DNEL                  | Long term Oral        | 0.025 mg/kg bw/day      | General population             | Systemic |
|   | DNEL                  | Long term Dermal      | 0.025 mg/kg bw/day      | General population             | Systemic |
|   | DNEL                  | Long term Inhalation  | 0.085 mg/m <sup>3</sup> | General population             | Systemic |
| Fatty acids, C14-18 and C16-18-unsatd., maleated  | DNEL                  | Long term Dermal      | 0.25 mg/kg bw/day       | Workers                        | Systemic |
|   | DNEL                  | Long term Inhalation  | 0.35 mg/m <sup>3</sup>  | Workers                        | Systemic |
|   | DNEL                  | Long term Oral        | 1.5 mg/kg bw/day        | General population             | Systemic |
|   | DNEL                  | Long term Dermal      | 1.5 mg/kg bw/day        | General population             | Systemic |
| propylidynetrimethanol  | DNEL                  | Long term Dermal      | 3 mg/kg bw/day          | Workers                        | Systemic |
|   | DNEL                  | Long term Oral        | 0.34 mg/kg bw/day       | General population             | Systemic |
|   | DNEL                  | Long term Dermal      | 0.34 mg/kg bw/day       | General population             | Systemic |
|   | DNEL                  | Long term Inhalation  | 0.58 mg/m <sup>3</sup>  | General population             | Systemic |
| maleic anhydride  | DNEL                  | Long term Dermal      | 0.94 mg/kg bw/day       | Workers                        | Systemic |
|   | DNEL                  | Long term Inhalation  | 3.3 mg/m <sup>3</sup>   | Workers                        | Systemic |
|   | DNEL                  | Long term Inhalation  | 0.4 mg/m <sup>3</sup>   | Workers                        | Systemic |
|   | DNEL                  | Long term Inhalation  | 0.4 mg/m <sup>3</sup>   | Workers                        | Local    |
|   | DNEL                  | Long term Inhalation  | 0.05 mg/m <sup>3</sup>  | General population             | Systemic |
|   | DNEL                  | Long term Oral        | 0.06 mg/kg bw/day       | General population             | Systemic |
|   | DNEL                  | Long term Inhalation  | 0.08 mg/m <sup>3</sup>  | General population             | Local    |
|   | DNEL                  | Long term Inhalation  | 0.081 mg/m <sup>3</sup> | Workers                        | Local    |
|   | DNEL                  | Long term Inhalation  | 0.081 mg/m <sup>3</sup> | Workers                        | Systemic |
|   | DNEL                  | Short term Oral       | 0.1 mg/kg bw/day        | General population             | Systemic |
|   | DNEL                  | Short term Dermal     | 0.1 mg/kg bw/day        | General population             | Systemic |
|   | DNEL                  | Long term Dermal      | 0.1 mg/kg bw/day        | General population             | Systemic |
|   | DNEL                  | Short term Dermal     | 0.2 mg/kg bw/day        | Workers                        | Systemic |
|   | DNEL                  | Long term Dermal      | 0.2 mg/kg bw/day        | Workers                        | Systemic |
| DNEL  | Short term Inhalation | 0.2 mg/m <sup>3</sup> | Workers                 | Local                          |          |
| DNEL  | Short term Inhalation | 0.2 mg/m <sup>3</sup> | Workers                 | Systemic                       |          |

**PNECs**

| Product/ingredient name   | Type | Compartment Detail     | Value        | Method Detail            |
|---|------|------------------------|--------------|--------------------------|
| heptan-2-one  | -    | Fresh water            | 0.0982 mg/l  | Assessment Factors       |
|   | -    | Marine water           | 0.00982 mg/l | Assessment Factors       |
|   | -    | Fresh water sediment   | 1.89 mg/kg   | Equilibrium Partitioning |
|   | -    | Marine water sediment  | 0.189 mg/kg  | Equilibrium Partitioning |
|   | -    | Sewage Treatment Plant | 12.5 mg/l    | Assessment Factors       |
|   | -    | Soil                   | 0.321 mg/kg  | Equilibrium Partitioning |
|   | -    | Fresh water            | 0.0023 mg/l  | -                        |
| Poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω- | -    |                        |              |                          |



|  |   |
|--|---|
| <b>Code</b> : 00440506                   | <b>Date of issue/Date of revision</b> : 26 September 2024 |
| <b>PITTHANE ULTRA LS LIGHT TINT BASE</b> |   |

**SECTION 8: Exposure controls/personal protection**

|  |   |                        |                 |                          |
|--|---|------------------------|-----------------|--------------------------|
| hydroxy-<br><br><br><br><br><br><br><br><br><br>maleic anhydride | - | Marine water           | 0.00023 mg/l    | -                        |
|  | - | Sewage Treatment Plant | 10 mg/l         | -                        |
|  | - | Fresh water sediment   | 3.06 mg/kg dwt  | -                        |
|  | - | Marine water sediment  | 0.306 mg/kg dwt | -                        |
|  | - | Soil                   | 2 mg/kg         | -                        |
|  | - | Fresh water            | 0.1 mg/l        | Assessment Factors       |
|  | - | Marine water           | 0.01 mg/l       | Assessment Factors       |
|  | - | Sewage Treatment Plant | 44.6 mg/l       | Assessment Factors       |
|  | - | Fresh water sediment   | 0.334 mg/kg dwt | Equilibrium Partitioning |
|  | - | Marine water sediment  | 0.033 mg/kg dwt | Equilibrium Partitioning |
|  | - | Soil                   | 0.042 mg/kg dwt | Equilibrium Partitioning |

**8.2 Exposure controls**

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety glasses with side shields. Use eye protection according to EN 166.

**Skin protection**

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Code : 00440506 Date of issue/Date of revision : 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : White.
- Odour** : Characteristic.
- Odour threshold** : Not available.
- Melting point/freezing point** : May start to solidify at the following temperature: <-20°C (<-4°F) This is based on data for the following ingredient: heptan-2-one. Weighted average: -45.56°C (-50°F)
- Initial boiling point and boiling range** : >37.78°C
- Flammability** : Not available.
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 3.1% Upper: 16% (methyl acetate)
- Flash point** : Closed cup: 9.5°C
- Auto-ignition temperature** :

| Ingredient name | °C  | °F    | Method |
|-----------------|-----|-------|--------|
| heptan-2-one    | 393 | 739.4 |        |

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- pH** : Not applicable. insoluble in water.
- Viscosity** : Kinematic (40°C): >21 mm<sup>2</sup>/s
- Solubility(ies)** :

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

- Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure** :

| Ingredient name | Vapour Pressure at 20°C |      |        | Vapour pressure at 50°C |      |        |
|-----------------|-------------------------|------|--------|-------------------------|------|--------|
|                 | mm Hg                   | kPa  | Method | mm Hg                   | kPa  | Method |
| methyl acetate  | 171.01454               | 22.8 |        | 590.30018               | 78.7 |        |

**Evaporation rate** :

Code : 00440506 Date of issue/Date of revision : 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 9: Physical and chemical properties

Highest known value: 11.8 (methyl acetate) Weighted average: 3.68 compared with butyl acetate

Relative density : 1.53

Vapour density : Highest known value: 3.9 (Air = 1) (heptan-2-one). Weighted average: 3.5 (Air = 1)

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

### Particle characteristics

Median particle size : Not applicable.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

| Product/ingredient name  | Result                 | Species            | Dose        | Exposure |
|--|------------------------|--------------------|-------------|----------|
| heptan-2-one   | LC50 Inhalation Vapour | Rat                | 16.7 mg/l   | 4 hours  |
|  | LD50 Dermal            | Rabbit             | 10.206 g/kg | -        |
|  | LD50 Oral              | Rat                | 1.6 g/kg    | -        |
| methyl acetate   | LD50 Dermal            | Rabbit             | >5 g/kg     | -        |
|  | LD50 Oral              | Rat                | 3.705 g/kg  | -        |
| propylene carbonate  | LD50 Oral              | Rat                | 29 g/kg     | -        |
| Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate                  | LD50 Dermal            | Rat                | >3170 mg/kg | -        |
|  | LD50 Oral              | Rat - Male, Female | 3230 mg/kg  | -        |
| Poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxy- | LD50 Dermal            | Rat - Male, Female | >2000 mg/kg | -        |
|  | LD50 Oral              | Rat - Male, Female | >5000 mg/kg | -        |

Code : 00440506 Date of issue/Date of revision : 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 11: Toxicological information

|                        |             |        |             |   |
|------------------------|-------------|--------|-------------|---|
| propylidynetrimethanol | LD50 Dermal | Rabbit | 10 g/kg     | - |
|                        | LD50 Oral   | Rat    | 14000 mg/kg | - |
| maleic anhydride       | LD50 Dermal | Rabbit | 2620 mg/kg  | - |
|                        | LD50 Oral   | Rat    | 400 mg/kg   | - |

**Conclusion/Summary** : There are no data available on the mixture itself.

### Acute toxicity estimates

| Route                | ATE value      |
|----------------------|----------------|
| Oral                 | 10922.65 mg/kg |
| Inhalation (vapours) | 114.01 mg/l    |

### Irritation/Corrosion

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Sensitisation

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs    |
|-------------------------|------------|-------------------|------------------|
| heptan-2-one            | Category 3 | -                 | Narcotic effects |
| methyl acetate          | Category 3 | -                 | Narcotic effects |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs      |
|-------------------------|------------|-------------------|--------------------|
| maleic anhydride        | Category 1 | inhalation        | respiratory system |

### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

**Ingestion** : Can cause central nervous system (CNS) depression.

Code : 00440506

Date of issue/Date of revision

: 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 11: Toxicological information

**Skin contact** : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.

**Eye contact** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

**Ingestion** : No specific data.

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

**Eye contact** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

**Other information** : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

### 11.2.2 Other information

Not available.

Code : 00440506 Date of issue/Date of revision : 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name  | Result  | Species                            | Exposure                                    |
|--|---|------------------------------------|---|
| heptan-2-one   | Acute LC50 131 mg/l<br>EC50 1.68 mg/l   | Fish<br>Algae                      | 96 hours<br>72 hours                        |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate                   | LC50 0.9 mg/l<br>Acute EC50 16.6 mg/l   | Fish<br>Algae                      | 96 hours<br>72 hours                        |
| Poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxy- | Acute EC50 4 mg/l<br>Acute LC50 2.8 mg/l<br>Chronic NOEC 0.23 mg/l<br>Acute LC50 >1000 mg/l | Daphnia<br>Fish<br>Daphnia<br>Fish | 48 hours<br>96 hours<br>21 days<br>96 hours |
| propylidynetrimethanol   |   |                                    |   |

**Conclusion/Summary** : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

| Product/ingredient name  | Test  | Result                       | Dose | Inoculum |
|--|---|------------------------------|------|----------|
| heptan-2-one   | OECD 310  | 69 % - Readily - 28 days     | -    | -        |
| Poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxy- | OECD 301B<br>Ready<br>Biodegradability -<br>CO2 Evolution<br>Test | 24 % - Not readily - 28 days | -    | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

| Product/ingredient name  | Aquatic half-life | Photolysis | Biodegradability |
|--|-------------------|------------|------------------|
| heptan-2-one   | -                 | -          | Readily          |
| Poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxy- | -                 | -          | Not readily      |

### 12.3 Bioaccumulative potential

| Product/ingredient name  | LogP <sub>ow</sub> | BCF | Potential |
|--|--------------------|-----|-----------|
| heptan-2-one   | 2.26               | -   | Low       |
| methyl acetate   | 0.18               | -   | Low       |
| propylene carbonate  | -0.41              | -   | Low       |
| Poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxy- | 5.9                | -   | High      |
| propylidynetrimethanol   | -0.47              | -   | Low       |
| maleic anhydride   | -2.78              | -   | Low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

Code : 00440506 Date of issue/Date of revision : 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 12: Ecological information

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

#### Hazardous waste

#### European waste catalogue (EWC)

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information



Code : 00440506 Date of issue/Date of revision : 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 14: Transport information

|                                 | ADR/RID         | ADN             | IMDG            | IATA            |
|---------------------------------|-----------------|-----------------|-----------------|-----------------|
| 14.1 UN number or ID number     | UN1263          | UN1263          | UN1263          | UN1263          |
| 14.2 UN proper shipping name    | PAINT           | PAINT           | PAINT           | PAINT           |
| 14.3 Transport hazard class(es) | 3               | 3               | 3               | 3               |
| 14.4 Packing group              | II              | II              | II              | II              |
| 14.5 Environmental hazards      | No.             | No.             | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

### Additional information

ADR/RID : None identified.

Tunnel code : (D/E)

ADN : None identified.

IMDG : None identified.

IATA : None identified.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

None of the components are listed.

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#) : Not applicable.

[Explosive precursors](#) : Not applicable.

[Ozone depleting substances \(1005/2009/EU\)](#)

Code : 00440506

Date of issue/Date of revision

: 26 September 2024

PITTHANE ULTRA LS LIGHT TINT BASE

## SECTION 15: Regulatory information

Not listed.

### Seveso Directive

This product is controlled under the Seveso Directive.

### Danger criteria

#### Category

P5c

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

### Full text of abbreviated H statements

|        |  |
|--------|--|
| ✔ H225 | Highly flammable liquid and vapour.  |
| H226   | Flammable liquid and vapour.   |
| H302   | Harmful if swallowed.  |
| H314   | Causes severe skin burns and eye damage.                                   |
| H315   | Causes skin irritation.  |
| H317   | May cause an allergic skin reaction.                                       |
| H318   | Causes serious eye damage.   |
| H319   | Causes serious eye irritation.   |
| H332   | Harmful if inhaled.  |
| H334   | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H336   | May cause drowsiness or dizziness.   |
| H361f  | Suspected of damaging fertility.   |
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child.   |
| H372   | Causes damage to organs through prolonged or repeated exposure.            |
| H400   | Very toxic to aquatic life.  |
| H410   | Very toxic to aquatic life with long lasting effects.                      |
| H411   | Toxic to aquatic life with long lasting effects.                           |
| EUH066 | Repeated exposure may cause skin dryness or cracking.                      |
| EUH071 | Corrosive to the respiratory tract.  |

### Full text of classifications [CLP/GHS]

|  |   |
|--|---|
| <b>Code</b> : 00440506                   | <b>Date of issue/Date of revision</b> : 26 September 2024 |
| <b>PITTHANE ULTRA LS LIGHT TINT BASE</b> |   |

**SECTION 16: Other information**

|   |   |
|---|---|
| Acute Tox. 4<br>Aquatic Acute 1<br>Aquatic Chronic 1<br>Aquatic Chronic 2<br>Eye Dam. 1<br>Eye Irrit. 2<br>Flam. Liq. 2<br>Flam. Liq. 3<br>Repr. 2<br>Resp. Sens. 1<br>Skin Corr. 1B<br>Skin Irrit. 2<br>Skin Sens. 1<br>Skin Sens. 1A<br>Skin Sens. 1B<br>STOT RE 1<br><br>STOT SE 3 | ACUTE TOXICITY - Category 4<br>SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1<br>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1<br>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2<br>SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1<br>SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2<br>FLAMMABLE LIQUIDS - Category 2<br>FLAMMABLE LIQUIDS - Category 3<br>REPRODUCTIVE TOXICITY - Category 2<br>RESPIRATORY SENSITISATION - Category 1<br>SKIN CORROSION/IRRITATION - Category 1B<br>SKIN CORROSION/IRRITATION - Category 2<br>SKIN SENSITISATION - Category 1<br>SKIN SENSITISATION - Category 1A<br>SKIN SENSITISATION - Category 1B<br>SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1<br>SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |
|---|---|

**History**

**Date of issue/ Date of revision** : 26 September 2024  
**Date of previous issue** : 18 August 2023  
**Prepared by** : EHS  
**Version** : 1.02

**Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*