



# SAFETY DATA SHEET

Date of issue/Date of revision

: 9 October 2024

Version

: 5

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : FREITAPOX SR 213/220 HARDENER

**Product code** : 00419271

#### Other means of identification

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying, Application by non spray methods..

**Use of the substance/mixture** :  Coating.; Hardener.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd.  
PO Box 7509  
Dammam 31472  
Saudi Arabia  
Tel: 00966 138 47 31 00  
Fax: 00966 138 47 17 34

**e-mail address of person responsible for this SDS** : ndpic@sfda.gov.sa

**1.4 Emergency telephone number** : 00966 138473100 extn 1001

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Flam. Liq. 2, H225  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
STOT RE 1, H372

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

Code : 00419271 Date of issue/Date of revision : 9 October 2024  
 FREITAPOX SR 213/220 HARDENER

## SECTION 2: Hazards identification

- Hazard statements** : Highly flammable liquid and vapour.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 Causes damage to organs through prolonged or repeated exposure.
- Precautionary statements**
- Prevention** : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour. Wash thoroughly after handling.
- Response** : Get medical advice/attention if you feel unwell.
- Storage** : Not applicable.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.  
 P280, P210, P260, P264, P314, P501

**Supplemental label elements** : Contains ethylenediamine. May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Special packaging requirements

- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

- Product meets the criteria for PBT or vPvB** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
- Other hazards which do not result in classification** : Prolonged or repeated contact may dry skin and cause irritation.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

| Product/ingredient name                             | Identifiers  | %          | Classification  | Specific Conc. Limits, M-factors and ATEs | Type    |
|---|--|------------|---|---|---------|
| crystalline silica, respirable powder (<10 microns) | EC: 238-878-4<br>CAS: 14808-60-7   | ≥10 - ≤25  | STOT RE 1, H372 (inhalation)                                | -   | [1] [2] |
| propan-2-ol   | REACH #:<br>01-2119457558-25<br>EC: 200-661-7<br>CAS: 67-63-0<br>Index: 603-117-00-0 | ≥5.0 - ≤10 | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336 | -   | [1] [2] |
| xylene  | REACH #:<br>01-2119488216-32   | ≥5.0 - ≤10 | Flam. Liq. 3, H226<br>Acute Tox. 4, H312                    | ATE [Dermal] = 1700 mg/kg                 | [1] [2] |

Code : 00419271

Date of issue/Date of revision

: 9 October 2024

FREITAPOX SR 213/220 HARDENER

### SECTION 3: Composition/information on ingredients

|   |  |             |   |   |         |
|---|--|-------------|---|---|---------|
|   | EC: 215-535-7<br>CAS: 1330-20-7  |             | Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412  | ATE [Inhalation (vapours)] = 11 mg/l  |         |
| 2,4,6-tris (dimethylaminomethyl) phenol | REACH #: 01-2119560597-27<br>EC: 202-013-9<br>CAS: 90-72-2                         | ≥1.0 - <3.0 | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Skin Corr. 1C, H314<br>Eye Dam. 1, H318   | ATE [Oral] = 1200 mg/kg<br>ATE [Dermal] = 1280 mg/kg                                      | [1]     |
| ethylbenzene                            | REACH #: 01-2119489370-35<br>EC: 202-849-4<br>CAS: 100-41-4<br>Index: 601-023-00-4 | ≥1.0 - ≤4.1 | Flam. Liq. 2, H225<br>Acute Tox. 4, H332<br>STOT RE 2, H373 (hearing organs)<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412  | ATE [Inhalation (vapours)] = 17.8 mg/l  | [1] [2] |
| ethylenediamine                         | REACH #: 01-2119480383-37<br>EC: 203-468-6<br>CAS: 107-15-3<br>Index: 612-006-00-6 | ≤0.30       | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Acute Tox. 3, H311<br>Acute Tox. 4, H332<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Resp. Sens. 1B, H334<br>Skin Sens. 1, H317<br>Aquatic Chronic 3, H412<br><b>See Section 16 for the full text of the H statements declared above.</b> | ATE [Oral] = 841 mg/kg<br>ATE [Dermal] = 560 mg/kg<br>ATE [Inhalation (gases)] = 6000 ppm | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Code : 00419271

Date of issue/Date of revision

: 9 October 2024

FREITAPOX SR 213/220 HARDENER

## SECTION 4: First aid measures

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** :  Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Code : 00419271

Date of issue/Date of revision

: 9 October 2024

FREITAPOX SR 213/220 HARDENER

## SECTION 5: Firefighting measures

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flames, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapour or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Code : 00419271

Date of issue/Date of revision

: 9 October 2024

FREITAPOX SR 213/220 HARDENER

## SECTION 7: Handling and storage

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

|   |  |
|---|--|
| crystalline silica, respirable powder (<10 microns) | <b>Ministry of Labor (France, 9/2023)</b><br>TWA 8 hours: 0.1 mg/m <sup>3</sup> . Form: Respirable fraction.   |
| propan-2-ol   | <b>Ministry of Labor (France, 9/2023)</b><br>STEL 15 minutes: 400 ppm.<br>STEL 15 minutes: 980 mg/m <sup>3</sup> .   |
| xylene  | <b>Ministry of Labor (France, 9/2023) [xylènes, isomères mixtes, purs]</b> Absorbed through skin.<br>STEL 15 minutes: 442 mg/m <sup>3</sup> .<br>STEL 15 minutes: 100 ppm.<br>TWA 8 hours: 221 mg/m <sup>3</sup> .<br>TWA 8 hours: 50 ppm. |
| ethylbenzene  | <b>Ministry of Labor (France, 9/2023)</b> Absorbed through skin.<br>TWA 8 hours: 20 ppm.<br>TWA 8 hours: 88.4 mg/m <sup>3</sup> .<br>STEL 15 minutes: 442 mg/m <sup>3</sup> .<br>STEL 15 minutes: 100 ppm.                                 |
| ethylenediamine                                     | <b>Ministry of Labor (France, 9/2023)</b><br>TWA 8 hours: 10 ppm.<br>TWA 8 hours: 25 mg/m <sup>3</sup> .<br>STEL 15 minutes: 15 ppm.<br>STEL 15 minutes: 35 mg/m <sup>3</sup> .  |

Code : 00419271

Date of issue/Date of revision

: 9 October 2024

FREITAPOX SR 213/220 HARDENER

| Product/ingredient name                             | Exposure limit values   |
|---|---|
| Mica-group minerals                                 | <p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016)</b><br/>TWA 8 hours: 3 mg/m<sup>3</sup>. Form: measured as respirable fraction of the aerosol.</p> <p><b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)</b><br/>TWA 8 hours: 3 mg/m<sup>3</sup>.</p> <p><b>ACGIH TLV (United States, 7/2023)</b><br/>TWA 8 hours: 0.1 mg/m<sup>3</sup>. Form: Respirable fraction.</p>  |
| crystalline silica, respirable powder (>10 microns) | <p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) [quartz silica crystalline-α-quartz and cristobalite] A2.</b><br/>TWA 8 hours: 0.025 mg/m<sup>3</sup>. Form: measured as respirable fraction of the aerosol.</p> <p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) [silica]</b><br/>TWA 8 hours: 3 mg/m<sup>3</sup>. Form: respirable particulate.<br/>TWA 8 hours: 10 mg/m<sup>3</sup>. Form: inhalable particle.</p> <p><b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)</b><br/>TWA 8 hours: 0.1 mg/m<sup>3</sup>.</p> <p><b>ACGIH TLV (United States, 7/2023) [Silica, crystalline] A2.</b><br/>TWA 8 hours: 0.025 mg/m<sup>3</sup>. Form: Respirable fraction.</p>   |
| crystalline silica, respirable powder (<10 microns) | <p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) [quartz silica crystalline-α-quartz and cristobalite] A2.</b><br/>TWA 8 hours: 0.025 mg/m<sup>3</sup>. Form: measured as respirable fraction of the aerosol.</p> <p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) [silica]</b><br/>TWA 8 hours: 3 mg/m<sup>3</sup>. Form: respirable particulate.<br/>TWA 8 hours: 10 mg/m<sup>3</sup>. Form: inhalable particle.</p> <p><b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)</b><br/>TWA 8 hours: 0.1 mg/m<sup>3</sup>.</p> <p><b>ACGIH TLV (United States, 7/2023) [Silica, crystalline] A2.</b><br/>TWA 8 hours: 0.025 mg/m<sup>3</sup>. Form: Respirable fraction.</p>   |
| propan-2-ol   | <p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) [silica]</b><br/>TWA 8 hours: 3 mg/m<sup>3</sup>. Form: respirable particulate.<br/>TWA 8 hours: 10 mg/m<sup>3</sup>. Form: inhalable particle.</p> <p><b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)</b><br/>TWA 8 hours: 0.1 mg/m<sup>3</sup>.</p> <p><b>ACGIH TLV (United States, 7/2023) [Silica, crystalline] A2.</b><br/>TWA 8 hours: 0.025 mg/m<sup>3</sup>. Form: Respirable fraction.</p> <p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) A4.</b><br/>TWA 8 hours: 492 mg/m<sup>3</sup>.<br/>TWA 8 hours: 200 ppm.<br/>STEL 15 minutes: 984 mg/m<sup>3</sup>.<br/>STEL 15 minutes: 400 ppm.</p> <p><b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)</b><br/>STEL 15 minutes: 500 ppm.<br/>TWA 8 hours: 983 mg/m<sup>3</sup>.<br/>STEL 15 minutes: 1230 mg/m<sup>3</sup>.<br/>TWA 8 hours: 400 ppm.</p> <p><b>ACGIH TLV (United States, 7/2023) A4.</b><br/>TWA 8 hours: 200 ppm.<br/>STEL 15 minutes: 400 ppm.</p> |
| xylene  | <p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) [xylene (o, m &amp; p isomers)] A4.</b><br/>STEL 15 minutes: 651 mg/m<sup>3</sup>.<br/>STEL 15 minutes: 150 ppm.</p>   |

Code : 00419271 Date of issue/Date of revision : 9 October 2024

FREITAPOX SR 213/220 HARDENER

|                 |  |
|-----------------|--|
| ethylbenzene    | <p>TWA 8 hours: 434 mg/m<sup>3</sup>.<br/>TWA 8 hours: 100 ppm.</p> <p><b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006) [xylene (all isomers)]</b></p> <p>STEL 15 minutes: 150 ppm.<br/>TWA 8 hours: 434 mg/m<sup>3</sup>.<br/>STEL 15 minutes: 651 mg/m<sup>3</sup>.<br/>TWA 8 hours: 100 ppm.</p> <p><b>ACGIH TLV (United States, 7/2023) [p-xylene and mixtures containing p-xylene] A4. Ototoxicant.</b></p> <p>TWA 8 hours: 20 ppm.</p> <p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) A3.</b></p> <p>STEL 15 minutes: 543 mg/m<sup>3</sup>.<br/>STEL 15 minutes: 125 ppm.<br/>TWA 8 hours: 100 ppm.<br/>TWA 8 hours: 434 mg/m<sup>3</sup>.</p> <p><b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)</b></p> <p>STEL 15 minutes: 125 ppm.<br/>TWA 8 hours: 434 mg/m<sup>3</sup>.<br/>STEL 15 minutes: 543 mg/m<sup>3</sup>.<br/>TWA 8 hours: 100 ppm.</p> <p><b>ACGIH TLV (United States, 7/2023) A3. Ototoxicant.</b></p> <p>TWA 8 hours: 20 ppm.</p> |
| ethylenediamine | <p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) A4. Absorbed through skin.</b></p> <p>TWA 8 hours: 10 ppm.<br/>TWA 8 hours: 25 mg/m<sup>3</sup>.</p> <p><b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)</b></p> <p>Absorbed through skin.<br/>TWA 8 hours: 25 mg/m<sup>3</sup>.<br/>TWA 8 hours: 10 ppm.</p> <p><b>ACGIH TLV (United States, 7/2023) A4. Absorbed through skin.</b></p> <p>TWA 8 hours: 10 ppm.</p>  |

|              |  |
|--------------|--|
| propan-2-ol  | <p><b>DOL BEI (South Africa, 3/2021)</b></p> <p>BEI: 40 mg/l, acetone [in urine]. Sampling time: end of shift at end of workweek.</p>                                |
| xylene       | <p><b>DOL BEI (South Africa, 3/2021) [xylenes]</b></p> <p>BEI: 1.5 g/g creatinine, methylhippuric acid [in urine]. Sampling time: end of shift.</p>                  |
| ethylbenzene | <p><b>DOL BEI (South Africa, 3/2021)</b></p> <p>BEI: 0.15 g/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift.</p> |

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.



Code : 00419271

Date of issue/Date of revision

: 9 October 2024

FREITAPOX SR 213/220 HARDENER

## 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

May be used: nitrile rubber

Recommended: butyl rubber, polyvinyl alcohol (PVA), Viton®

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** :

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.

**Colour** : Colourless.

**Odour** : Aromatic.

Code : 00419271

Date of issue/Date of revision

: 9 October 2024

FREITAPOX SR 213/220 HARDENER

## SECTION 9: Physical and chemical properties

- Odour threshold** : Not available.
- Melting point/freezing point** : Not determined.
- Initial boiling point and boiling range** : >37.78°C
- Flammability** : Not determined. There are no data available on the mixture itself.
- Upper/lower flammability or explosive limits** : Not available.
- Flash point** : Closed cup: 18°C

**Auto-ignition temperature** :

| Ingredient name                     | °C  | °F    | Method  |
|-------------------------------------|-----|-------|---------|
| 4,6-tris(dimethylaminomethyl)phenol | 382 | 719.6 | EU A.15 |

**Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).

**pH** : Not applicable. insoluble in water.

**Viscosity** : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): >21 mm<sup>2</sup>/s

**Solubility(ies)** :

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure** :

| Ingredient name | Vapour Pressure at 20°C |     |        | Vapour pressure at 50°C |     |        |
|-----------------|-------------------------|-----|--------|-------------------------|-----|--------|
|                 | mm Hg                   | kPa | Method | mm Hg                   | kPa | Method |
| Propan-2-ol     | 33.00268                | 4.4 |        |                         |     |        |

**Relative density** : 1.61

**Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

**Oxidising properties** : Product does not present an oxidizing hazard.

### Particle characteristics

**Median particle size** : Not applicable.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

Code : 00419271 Date of issue/Date of revision : 9 October 2024  
 FREITAPOX SR 213/220 HARDENER

## SECTION 10: Stability and reactivity

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

| Product/ingredient name               | Result                 | Species            | Dose                    | Exposure |
|---------------------------------------|------------------------|--------------------|-------------------------|----------|
| propan-2-ol                           | LC50 Inhalation Vapour | Rat                | 72600 mg/m <sup>3</sup> | 4 hours  |
|                                       | LD50 Dermal            | Rabbit             | 12800 mg/kg             | -        |
|                                       | LD50 Oral              | Rat                | 5045 mg/kg              | -        |
| xylene                                | LD50 Dermal            | Rabbit             | 1.7 g/kg                | -        |
|                                       | LD50 Oral              | Rat                | 4.3 g/kg                | -        |
| 2,4,6-tris(dimethylaminomethyl)phenol | LD50 Dermal            | Rat                | 1280 mg/kg              | -        |
|                                       | LD50 Oral              | Rat                | 1200 mg/kg              | -        |
| ethylbenzene                          | LC50 Inhalation Vapour | Rat                | 17.8 mg/l               | 4 hours  |
|                                       | LD50 Dermal            | Rabbit             | 17.8 g/kg               | -        |
|                                       | LD50 Oral              | Rat                | 3.5 g/kg                | -        |
| ethylenediamine                       | LC50 Inhalation Gas.   | Rat                | 6000 ppm                | 4 hours  |
|                                       | LD50 Dermal            | Rabbit - Male      | 560 mg/kg               | -        |
|                                       | LD50 Oral              | Rat - Male, Female | 841 mg/kg               | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure        | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| xylene                  | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

#### Sensitisation

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

#### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Code : 00419271 Date of issue/Date of revision : 9 October 2024  
 FREITAPOX SR 213/220 HARDENER

## SECTION 11: Toxicological information

| Product/ingredient name | Category                 | Route of exposure | Target organs                                    |
|-------------------------|--------------------------|-------------------|--|
| propan-2-ol<br>xylene   | Category 3<br>Category 3 | -<br>-            | Narcotic effects<br>Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name   | Category                 | Route of exposure | Target organs       |
|---|--------------------------|-------------------|---------------------|
| crystalline silica, respirable powder (<10 microns)<br>ethylbenzene | Category 1<br>Category 2 | inhalation<br>-   | -<br>hearing organs |

### Aspiration hazard

| Product/ingredient name | Result   |
|-------------------------|--|
| xylene<br>ethylbenzene  | ASPIRATION HAZARD - Category 1<br>ASPIRATION HAZARD - Category 1 |

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Eye contact** : Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : No specific data.
- Ingestion** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

**Carcinogenicity** : No known significant effects or critical hazards.

Code : 00419271 Date of issue/Date of revision : 9 October 2024  
 FREITAPOX SR 213/220 HARDENER

## SECTION 11: Toxicological information

- Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.  
**Other information** : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name               | Result                               | Species                                | Exposure |
|---------------------------------------|--------------------------------------|--|----------|
| propan-2-ol                           | Acute EC50 10100 mg/l<br>Fresh water | Daphnia - <i>Daphnia magna</i>         | 48 hours |
| 2,4,6-tris(dimethylaminomethyl)phenol | Acute LC50 >100 mg/l                 | Daphnia                                | 48 hours |
|                                       | Acute LC50 >100 mg/l                 | Fish                                   | 96 hours |
| ethylbenzene                          | Acute EC50 1.8 mg/l Fresh<br>water   | Daphnia                                | 48 hours |
|                                       | Chronic NOEC 1 mg/l Fresh<br>water   | Daphnia -<br><i>Ceriodaphnia dubia</i> | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

| Product/ingredient name                   | Test  | Result                      | Dose | Inoculum |
|---|---|-----------------------------|------|----------|
| 2,4,6-tris<br>(dimethylaminomethyl)phenol | OECD 301D<br>Ready<br>Biodegradability -<br>Closed Bottle<br>Test | 4 % - Not readily - 28 days | -    | -        |
| ethylbenzene                              | -   | 79 % - Readily - 10 days    | -    | -        |
| ethylenediamine                           | -   | 95 % - 28 days              | -    | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

| Product/ingredient name               | Aquatic half-life | Photolysis | Biodegradability |
|---------------------------------------|-------------------|------------|------------------|
| xylene                                | -                 | -          | Readily          |
| 2,4,6-tris(dimethylaminomethyl)phenol | -                 | -          | Not readily      |
| ethylbenzene                          | -                 | -          | Readily          |
| ethylenediamine                       | -                 | -          | Readily          |

### 12.3 Bioaccumulative potential

| Product/ingredient name               | LogP <sub>ow</sub> | BCF         | Potential |
|---------------------------------------|--------------------|-------------|-----------|
| propan-2-ol                           | 0.05               | -           | Low       |
| xylene                                | 3.12               | 7.4 to 18.5 | Low       |
| 2,4,6-tris(dimethylaminomethyl)phenol | 0.219              | -           | Low       |
| ethylbenzene                          | 3.6                | 79.43       | Low       |
| ethylenediamine                       | -2.04              | -           | Low       |

Code : 00419271

Date of issue/Date of revision

: 9 October 2024

FREITAPOX SR 213/220 HARDENER

## SECTION 12: Ecological information

### 12.4 Mobility in soil

Soil/water partition coefficient ( $K_{oc}$ ) : Not available.

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

#### European waste catalogue (EWC)

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Code : 00419271

Date of issue/Date of revision

: 9 October 2024

FREITAPOX SR 213/220 HARDENER

## SECTION 14: Transport information

|                                 | ADR/RID         | IMDG            | IATA            |
|---------------------------------|-----------------|-----------------|-----------------|
| 14.1 UN number or ID number     | UN1263          | UN1263          | UN1263          |
| 14.2 UN proper shipping name    | PAINT           | PAINT           | PAINT           |
| 14.3 Transport hazard class(es) | 3               | 3               | 3               |
| 14.4 Packing group              | II              | II              | II              |
| 14.5 Environmental hazards      | No.             | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable. | Not applicable. |

### Additional information

ADR/RID : None identified.

Tunnel code : (D/E)

IMDG : None identified.

IATA : None identified.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

| Intrinsic property   | Ingredient name | Status      | Reference number | Date of revision |
|--|-----------------|-------------|------------------|------------------|
| <input checked="" type="checkbox"/> Substance of equivalent concern for human health | ethylenediamine | Recommended | D(2021) 4569-DC  | 4/12/2023        |

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

[Other national and international regulations.](#)

Explosive precursors :  Not applicable.

Code : 00419271

Date of issue/Date of revision

: 9 October 2024

FREITAPOX SR 213/220 HARDENER

## SECTION 15: Regulatory information

### Ozone depleting substances (1005/2009/EU)

Not listed.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number

### **Full text of abbreviated H statements**

: ~~H~~225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

### **Full text of classifications [CLP/GHS]**

: ~~A~~cute Tox. 3 ACUTE TOXICITY - Category 3  
Acute Tox. 4 ACUTE TOXICITY - Category 4  
Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3  
Asp. Tox. 1 ASPIRATION HAZARD - Category 1  
Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1  
Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2  
Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2  
Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3  
Resp. Sens. 1B RESPIRATORY SENSITISATION - Category 1B  
Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B  
Skin Corr. 1C SKIN CORROSION/IRRITATION - Category 1C  
Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2  
Skin Sens. 1 SKIN SENSITISATION - Category 1  
STOT RE 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1  
STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2  
STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

### **History**

**Date of issue/ Date of revision** : 9 October 2024

**Date of previous issue** : 2 March 2023



Code : 00419271

Date of issue/Date of revision

: 9 October 2024

FREITAPOX SR 213/220 HARDENER

## SECTION 16: Other information

Prepared by : EHS

Version : 5

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*