

SAFETY DATA SHEET



Date of issue/Date of revision

: 13 November 2024 Version

: 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMACOVER 380 BASE GREEN 4100

Product code : 000001090002

Other means of identification

00250040

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/
mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Pittsburgh Paints Nigeria Limited
1, Coker Street, Coker Bus-stop, Badagry Expressway, Orile Iganmu, Lagos
Nigeria
Tel: 00 234 (0) 8138672483

e-mail address of person
responsible for this SDS : PS.ACEMEA@ppg.com

1.4 Emergency telephone
number : 00234 127 173 85

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Dam. 1, H318

Skin Sens. 1, H317

Repr. 2, H361fd

STOT RE 2, H373

Aquatic Acute 1, H400

Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

: Danger

Code : 000001090002 **Date of issue/Date of revision** : 13 November 2024
 SIGMACOVER 380 BASE GREEN 4100

SECTION 2: Hazards identification

Hazard statements : Flammable liquid and vapour.
 Causes skin irritation.
 May cause an allergic skin reaction.
 Causes serious eye damage.
 Suspected of damaging fertility. Suspected of damaging the unborn child.
 May cause damage to organs through prolonged or repeated exposure.
 Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour.

Response : Collect spillage.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.
 P280, P210, P273, P260, P391, P501

Supplemental label elements : Contains epoxy constituents. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB : This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.

Other hazards which do not result in classification : Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.
 May cause endocrine disruption.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type

Code : 000001090002

Date of issue/Date of revision

: 13 November 2024

SIGMACOVER 380 BASE GREEN 4100

SECTION 3: Composition/information on ingredients

1,4-bis-[4-(2,3-epoxipropoxy)phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥5.0 - ≤10	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
4-nonylphenol, branched	REACH #: 01-2119510715-45 EC: 284-325-5 CAS: 84852-15-3 Index: 601-053-00-8	≥1.0 - <5.0	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 2, H361fd Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 1300 mg/kg M [Acute] = 10 M [Chronic] = 10	[1] [4]
Epoxy Resin (700<MW ≤1100)	CAS: 25036-25-3	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
Phenol, methylstyrenated	REACH #: 01-2119555274-38 EC: 270-966-8 CAS: 68512-30-1	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	[1] [3]
2-methylpropan-1-ol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≥1.0 - ≤5.0	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	-	[1] [2]
crystalline silica, respirable powder (<10 microns)	EC: 238-878-4 CAS: 14808-60-7	≥1.0 - ≤5.0	STOT RE 1, H372 (inhalation)	-	[1] [2]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9 CAS: 64742-48-9	≥1.0 - ≤5.0	Asp. Tox. 1, H304 EUH066	EUH066: C ≥ 20%	[1]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
Octadecanamide, N, N'-1,6-hexanediyldis [12-hydroxy-	CAS: 55349-01-4	≥1.0 - ≤5.0	Skin Sens. 1, H317 Aquatic Chronic 4, H413 See Section 16 for the full text of the H statements declared above.	-	[1]

Code : 000001090002

Date of issue/Date of revision

: 13 November 2024

SIGMACOVER 380 BASE GREEN 4100

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance with endocrine disrupting properties

This mixture contains $\geq 1\%$ of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : Corrosive to the digestive tract. Causes burns.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
 - pain
 - watering
 - redness
- Inhalation** : Adverse symptoms may include the following:
 - reduced foetal weight
 - increase in foetal deaths
 - skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
 - pain or irritation
 - redness
 - dryness
 - cracking
 - blistering may occur
 - reduced foetal weight
 - increase in foetal deaths

Code : 000001090002

Date of issue/Date of revision

: 13 November 2024

SIGMACOVER 380 BASE GREEN 4100

SECTION 4: First aid measures

- Ingestion** : skeletal malformations
: Adverse symptoms may include the following:
stomach pains
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Code : 000001090002

Date of issue/Date of revision

: 13 November 2024

SIGMACOVER 380 BASE GREEN 4100

SECTION 6: Accidental release measures

6.2 Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Code : 000001090002 Date of issue/Date of revision : 13 November 2024
SIGMACOVER 380 BASE GREEN 4100

SECTION 7: Handling and storage

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m ³ .
2-methylpropan-1-ol	ACGIH TLV (United States, 7/2023) TWA 8 hours: 50 ppm. TWA 8 hours: 152 mg/m ³ .
crystalline silica, respirable powder (<10 microns)	ACGIH TLV (United States, 7/2023) [Silica, crystalline] A2. TWA 8 hours: 0.025 mg/m ³ . Form: Respirable fraction.
ethylbenzene	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 442 mg/m ³ . STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m ³ .
xylene	DOL BEI (South Africa, 3/2021) [xylenes] BEI: 1.5 g/g creatinine, methylhippuric acid [in urine]. Sampling time: end of shift.
ethylbenzene	DOL BEI (South Africa, 3/2021) BEI: 0.15 g/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Code : 000001090002 Date of issue/Date of revision : 13 November 2024
SIGMACOVER 380 BASE GREEN 4100

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Chemical splash goggles and face shield.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** :
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Green.
- Odour** : Aromatic.
- Odour threshold** : Not available.
- Melting point/freezing point** : Not determined.
- Initial boiling point and boiling range** : >37.78°C
- Flammability** : Not determined. There are no data available on the mixture itself.
- Upper/lower flammability or explosive limits** : Not available.
- Flash point** : Closed cup: 38°C
- Auto-ignition temperature** :

Code : 000001090002 **Date of issue/Date of revision** : 13 November 2024
SIGMACOVER 380 BASE GREEN 4100

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>230	>446	

Decomposition temperature : Stable under recommended storage and handling conditions (see Section 7).

pH : Not applicable. insoluble in water.

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): >21 mm²/s

Viscosity : > 100 s (ISO 6mm)

Solubility(ies) :

Media	Result
cold water	Not soluble

Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
2-methylpropan-1-ol	<12.00102	<1.6	DIN EN 13016-2			

Relative density : 1.55

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

Code : 000001090002

Date of issue/Date of revision

: 13 November 2024

SIGMACOVER 380 BASE GREEN 4100

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxy)phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
xylene	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
4-nonylphenol, branched	LD50 Dermal	Rabbit	2.14 g/kg	-
	LD50 Oral	Rat	1300 mg/kg	-
Epoxy Resin (700<MW<=1100)	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
Phenol, methylstyrenated	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
2-methylpropan-1-ol	LC50 Inhalation Vapour	Rat	24.6 mg/l	4 hours
	LD50 Dermal	Rabbit	2460 mg/kg	-
	LD50 Oral	Rat	2830 mg/kg	-
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>6 g/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Oedema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
4-nonylphenol, branched	Skin - Erythema/Eschar	Rabbit	4	-	-

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxy)phenyl]propane	skin	Mouse	Sensitising

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Code : 000001090002 **Date of issue/Date of revision** : 13 November 2024
 SIGMACOVER 380 BASE GREEN 4100

SECTION 11: Toxicological information

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 3	-	Respiratory tract irritation
2-methylpropan-1-ol	Category 3	-	Respiratory tract irritation
	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
crystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-
ethylbenzene	Category 2	-	hearing organs

Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : Corrosive to the digestive tract. Causes burns.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Eye contact** : Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 stomach pains
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
 pain or irritation
 redness
 dryness
 cracking
 blistering may occur
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations
- Eye contact** : Adverse symptoms may include the following:
 pain
 watering
 redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Code : 000001090002 Date of issue/Date of revision : 13 November 2024
SIGMACOVER 380 BASE GREEN 4100

SECTION 11: Toxicological information

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : Suspected of damaging fertility. Suspected of damaging the unborn child.

Other information : Not available.

Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Bis-[4-(2,3-epoxipropoxy)phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
4-nonylphenol, branched	Acute EC50 0.044 mg/l	Crustaceans - <i>Moina macrocopa</i>	48 hours
	Acute LC50 0.221 mg/l	Fish	96 hours
2-methylpropan-1-ol ethylbenzene	Acute EC50 1100 mg/l	Daphnia	48 hours
	Acute EC50 1.8 mg/l Fresh water	Daphnia	48 hours
	Chronic NOEC 1 mg/l Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	-

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
ethylbenzene	-	79 % - Readily - 10 days	-	-

Code : 000001090002 **Date of issue/Date of revision** : 13 November 2024
SIGMACOVER 380 BASE GREEN 4100

SECTION 12: Ecological information

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Bis-[4-(2,3-epoxipropoxy)phenyl]propane	-	-	Not readily
xylene	-	-	Readily
ethylbenzene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
4-nonylphenol, branched	5.4	251.19	Low
Phenol, methylstyrenated	3.627	-	Low
2-methylpropan-1-ol	1	-	Low
ethylbenzene	3.6	79.43	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Bis-[4-(2,3-epoxipropoxy)phenyl]propane	No	N/A	N/A	No	N/A	N/A	N/A
xylene	No	N/A	No	No	No	N/A	No
4-nonylphenol, branched	No	N/A	No	Yes	No	N/A	No
Epoxy Resin (700<MW ≤1100)	No	N/A	N/A	No	N/A	N/A	N/A
Phenol, methylstyrenated	No	N/A	N/A	No	SVHC (Candidate)	Specified	Specified
2-methylpropan-1-ol	No	N/A	N/A	No	N/A	N/A	N/A
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	No	N/A	N/A	No	N/A	N/A	N/A
ethylbenzene	No	N/A	No	Yes	No	N/A	No
Octadecanamide, N, N'-1,6-hexanediylbis [12-hydroxy-	No	N/A	N/A	No	N/A	N/A	N/A

12.6 Endocrine disrupting properties

May cause endocrine disruption.

12.7 Other adverse effects

No known significant effects or critical hazards.

Code : 000001090002	Date of issue/Date of revision : 13 November 2024
SIGMACOVER 380 BASE GREEN 4100	

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxy)phenyl]propane)	Not applicable.

Additional information

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Tunnel code : (D/E)

Code : 000001090002 **Date of issue/Date of revision** : 13 November 2024
SIGMACOVER 380 BASE GREEN 4100

SECTION 14: Transport information

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
VPvB Endocrine disrupting properties for environment	Oligomerisation and alkylation reaction products of 2-phenylpropene and phenol 4-nonylphenol, branched and linear substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof	Candidate Candidate	D(2023) 8585-DC ED/169/2012	1/23/2024 12/19/2012

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other national and international regulations.

Explosive precursors : This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

Ozone depleting substances (1005/2009/EU)

Not listed.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

Code : 000001090002 **Date of issue/Date of revision** : 13 November 2024
SIGMACOVER 380 BASE GREEN 4100

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms	:	ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number
Full text of abbreviated H statements	:	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life. EUH066 Repeated exposure may cause skin dryness or cracking.
Full text of classifications [CLP/GHS]	:	Acute Tox. 4 ACUTE TOXICITY - Category 4 Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 Aquatic Chronic 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4 Asp. Tox. 1 ASPIRATION HAZARD - Category 1 Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2 Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3 Repr. 2 REPRODUCTIVE TOXICITY - Category 2 Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1 SKIN SENSITISATION - Category 1 STOT RE 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
History		
Date of issue/ Date of revision	:	13 November 2024
Date of previous issue	:	24 May 2024
Prepared by	:	EHS
Version	:	6

Code : 000001090002

Date of issue/Date of revision

: 13 November 2024

SIGMACOVER 380 BASE GREEN 4100

SECTION 16: Other information

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.