

SAFETY DATA SHEET



Date of issue/Date of revision : 28 December 2024 Version : 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMASHIELD 680 HARDENER
Product code : 000001204045
Product type : Liquid.
Other means of identification : 00480000

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.
Use of the substance/mixture : Coating.; Hardener.
Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier
+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Flam. Liq. 3, H226
Skin Corr. 1C, H314
Eye Dam. 1, H318
Skin Sens. 1, H317
STOT SE 3, H335
STOT SE 3, H336
Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Code : 000001204045 **Date of issue/Date of revision** : 28 December 2024
SIGMASHIELD 680 HARDENER

SECTION 2: Hazards identification

Hazard statements : Flammable liquid and vapour.
 Causes severe skin burns and eye damage.
 May cause an allergic skin reaction.
 May cause respiratory irritation.
 May cause drowsiness or dizziness.
 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response : IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.
 P280, P210, P304 + P310, P301 + P310, P303 + P361 + P353, P501

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	REACH #: 01-2119972320-44 EC: 500-191-5 CAS: 68082-29-1	≥10 - <25	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1] [2]
2-methylpropan-1-ol	REACH #: 01-2119484609-23	≥10 - ≤25	Flam. Liq. 3, H226 Skin Irrit. 2, H315	[1] [2]

Code : 000001204045	Date of issue/Date of revision : 28 December 2024
SIGMASHIELD 680 HARDENER	

SECTION 3: Composition/information on ingredients

2,4,6-tris(dimethylaminomethyl) phenol	EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1 REACH #: 01-2119560597-27	≥1.0 - ≤5.0	Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314	[1]
ethylbenzene	EC: 202-013-9 CAS: 90-72-2 REACH #: 01-2119489370-35	≥1.0 - ≤5.0	Eye Dam. 1, H318 Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1] [2]
3,6-diazaoctanethylenediamin	EC: 203-950-6 CAS: 112-24-3 Index: 612-059-00-5	≥1.0 - <5.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	≤0.30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Code : 000001204045	Date of issue/Date of revision : 28 December 2024
SIGMASHIELD 680 HARDENER	

SECTION 4: First aid measures

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : Corrosive to the digestive tract. Causes burns. Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides

5.3 Advice for firefighters

Code : 000001204045 **Date of issue/Date of revision** : 28 December 2024
SIGMASHIELD 680 HARDENER

SECTION 5: Firefighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flames, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Code : 000001204045 **Date of issue/Date of revision** : 28 December 2024
SIGMASHIELD 680 HARDENER

SECTION 7: Handling and storage

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-,m-,p- or mixed isomers] Absorbed through skin. STEL 15 minutes: 441 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m ³ . STEL 15 minutes: 100 ppm.
2-methylpropan-1-ol	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 231 mg/m ³ . STEL 15 minutes: 75 ppm. TWA 8 hours: 154 mg/m ³ . TWA 8 hours: 50 ppm.
ethylbenzene	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 552 mg/m ³ . STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm. TWA 8 hours: 441 mg/m ³ .
toluene	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin.

Code : 000001204045	Date of issue/Date of revision : 28 December 2024
SIGMASHIELD 680 HARDENER	

SECTION 8: Exposure controls/personal protection

STEL 15 minutes: 384 mg/m³.
 TWA 8 hours: 191 mg/m³.
 TWA 8 hours: 50 ppm.
 STEL 15 minutes: 100 ppm.

Biological exposure indices

Product/ingredient name	Exposure indices
xylene	EH40/2005 BMGVs (United Kingdom (UK), 8/2018) [Xylene, o-, m-, p- or mixed isomers] BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	DNEL	Long term Oral	97.2 µg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	97.2 µg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	0.169 mg/m ³	General population	Systemic	
	DNEL	Long term Dermal	0.272 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	0.952 mg/m ³	Workers	Systemic	
	xylene	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	65.3 mg/m ³	General population	Local
		DNEL	Long term Inhalation	65.3 mg/m ³	General population	Systemic
		DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
		DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
		DNEL	Long term Inhalation	221 mg/m ³	Workers	Local
		DNEL	Long term Inhalation	221 mg/m ³	Workers	Systemic
		DNEL	Short term Inhalation	260 mg/m ³	General population	Local
		DNEL	Short term Inhalation	260 mg/m ³	General population	Systemic
DNEL		Short term Inhalation	442 mg/m ³	Workers	Local	
DNEL		Short term Inhalation	442 mg/m ³	Workers	Systemic	
2-methylpropan-1-ol		DNEL	Long term Inhalation	55 mg/m ³	General population	Local
		DNEL	Long term Inhalation	310 mg/m ³	Workers	Local
2,4,6-tris (dimethylaminomethyl)phenol		DNEL	Long term Oral	0.075 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.075 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	0.075 mg/kg bw/day	General population	Systemic	
	DNEL	Short term Inhalation	0.13 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	0.13 mg/m ³	General population	Systemic	
	DNEL	Long term Dermal	0.15 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	0.53 mg/m ³	Workers	Systemic	
	DNEL	Short term Dermal	0.6 mg/kg bw/day	Workers	Systemic	
	ethylbenzene	DNEL	Short term Inhalation	2.1 mg/m ³	Workers	Systemic
		DMEL	Long term Inhalation	442 mg/m ³	Workers	Local
		DMEL	Short term Inhalation	884 mg/m ³	Workers	Systemic
		DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	15 mg/m ³	General population	Systemic
		DNEL	Long term Inhalation	77 mg/m ³	Workers	Systemic
DNEL		Long term Dermal	180 mg/kg bw/day	Workers	Systemic	
DNEL		Short term Inhalation	293 mg/m ³	Workers	Local	

Code : 000001204045	Date of issue/Date of revision : 28 December 2024
SIGMASHIELD 680 HARDENER	

SECTION 8: Exposure controls/personal protection

3,6-diazaoctanethylenediamin	DNEL	Long term Dermal	28 µg/cm ²	Workers	Local	
	DNEL	Long term Dermal	0.25 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	0.29 mg/m ³	General population	Systemic	
	DNEL	Long term Oral	0.41 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	0.43 mg/cm ²	General population	Local	
	DNEL	Long term Dermal	0.57 mg/kg bw/day	Workers	Systemic	
	DNEL	Short term Dermal	1 mg/cm ²	General population	Local	
	DNEL	Long term Inhalation	1 mg/m ³	Workers	Systemic	
	DNEL	Short term Dermal	8 mg/kg bw/day	General population	Systemic	
	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic	
	DNEL	Short term Inhalation	1600 mg/m ³	General population	Systemic	
	toluene	DNEL	Short term Inhalation	5380 mg/m ³	Workers	Systemic
		DNEL	Long term Oral	8.13 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	56.5 mg/m ³	General population	Local
		DNEL	Long term Inhalation	56.5 mg/m ³	General population	Systemic
		DNEL	Long term Inhalation	192 mg/m ³	Workers	Local
		DNEL	Long term Inhalation	192 mg/m ³	Workers	Systemic
		DNEL	Long term Dermal	226 mg/kg bw/day	General population	Systemic
		DNEL	Short term Inhalation	226 mg/m ³	General population	Local
		DNEL	Short term Inhalation	226 mg/m ³	General population	Systemic
		DNEL	Long term Dermal	384 mg/kg bw/day	Workers	Systemic
		DNEL	Short term Inhalation	384 mg/m ³	Workers	Local
		DNEL	Short term Inhalation	384 mg/m ³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Fresh water	0.043 mg/l	Assessment Factors	
	Marine water	0 mg/l	Assessment Factors	
	Sewage Treatment Plant	3.84 mg/l	Assessment Factors	
	Fresh water sediment	434.02 mg/kg dwt	Equilibrium Partitioning	
	Marine water sediment	43.4 mg/kg dwt	Equilibrium Partitioning	
	Soil	86.78 mg/kg dwt	Equilibrium Partitioning	
	xylene	Fresh water	0.327 mg/l	-
		Marine water	0.327 mg/l	-
Sewage Treatment Plant		6.58 mg/l	-	
Fresh water sediment		12.46 mg/kg dwt	-	
Marine water sediment		12.46 mg/kg dwt	-	
Soil		2.31 mg/kg	-	
2-methylpropan-1-ol		Fresh water	0.4 mg/l	Assessment Factors
	Marine water	0.04 mg/l	Assessment Factors	
	Sewage Treatment Plant	10 mg/l	Assessment Factors	
	Fresh water sediment	1.56 mg/kg dwt	Equilibrium Partitioning	
	Marine water sediment	0.156 mg/kg dwt	-	
	Soil	0.076 mg/kg dwt	Equilibrium Partitioning	
	ethylbenzene	Fresh water	0.1 mg/l	Assessment Factors
		Marine water	0.01 mg/l	Assessment Factors
Sewage Treatment Plant		9.6 mg/l	Assessment Factors	
Fresh water sediment		13.7 mg/kg dwt	Equilibrium Partitioning	
Marine water sediment		1.37 mg/kg dwt	Equilibrium Partitioning	
Soil		2.68 mg/kg dwt	Equilibrium Partitioning	
toluene		Secondary Poisoning	20 mg/kg	-
		Fresh water	0.68 mg/l	Sensitivity Distribution
		Marine water	0.68 mg/l	Sensitivity Distribution
	Sewage Treatment Plant	13.61 mg/l	Sensitivity Distribution	
	Fresh water sediment	16.39 mg/kg dwt	Equilibrium Partitioning	
	Marine water sediment	16.39 mg/kg dwt	-	

8.2 Exposure controls

Code : 000001204045 **Date of issue/Date of revision** : 28 December 2024
SIGMASHIELD 680 HARDENER

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles and face shield.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
 nitrile neoprene

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Colour : Colourless.
Odour : Aromatic.
Odour threshold : Not available.

Code : 000001204045 **Date of issue/Date of revision** : 28 December 2024
SIGMASHIELD 680 HARDENER

SECTION 9: Physical and chemical properties

Melting point/freezing point :
Initial boiling point and boiling range : >37.78°C (>100°F)
Flammability (solid, gas) : liquid
Upper/lower flammability or explosive limits : Not available.
Flash point : Closed cup: 25°C (77°F)
Auto-ignition temperature :

Ingredient name	°C	°F	Method
3,6-diazaoctanethylenediamin	337.78	640	

pH : Not applicable.
 Not applicable. insoluble in water.
Viscosity : Dynamic (room temperature): Not available.
 Kinematic (room temperature): Not available.
 Kinematic (40°C): >21 mm²/s

Solubility(ies) :

Media	Result
cold water	Not soluble

Miscible with water : No.
Partition coefficient: n-octanol/ water : Not applicable.
Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
2-methylpropan-1-ol	<12.00102	<1.6	DIN EN 13016-2			

Relative density : 0.93
Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties : Product does not present an oxidizing hazard.
Particle characteristics
Median particle size : Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides

Code : 000001204045
SIGMASHIELD 680 HARDENER

Date of issue/Date of revision : 28 December 2024

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	LD50 Dermal	Rat	>2000 mg/kg	-
xylene	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-
2-methylpropan-1-ol	LD50 Oral	Rat	4.3 g/kg	-
	LC50 Inhalation Vapour	Rat	24.6 mg/l	4 hours
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rabbit	2460 mg/kg	-
	LD50 Oral	Rat	2830 mg/kg	-
ethylbenzene	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
3,6-diazaoctanethylenediamin	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
toluene	LD50 Oral	Rat	3.5 g/kg	-
	LD50 Dermal	Rabbit	1465 mg/kg	-
	LD50 Oral	Rat	1716 mg/kg	-
	LC50 Inhalation Vapour	Rat	49 g/m ³	4 hours
	LD50 Dermal	Rabbit	8.39 g/kg	-
	LD50 Oral	Rat	5580 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.**Acute toxicity estimates**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMASHIELD 680 HARDENER	18040.0	5315.8	N/A	43.9	N/A
xylene	4300	1700	N/A	11	N/A
2-methylpropan-1-ol	2830	2460	N/A	24.6	N/A
2,4,6-tris(dimethylaminomethyl)phenol	1200	1280	N/A	N/A	N/A
ethylbenzene	3500	17800	N/A	17.8	N/A
3,6-diazaoctanethylenediamin	1716	1465	N/A	N/A	N/A
toluene	5580	8390	N/A	49	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Eyes - Severe irritant	Rabbit	-	-	-
xylene	Skin - Irritant	Human	-	-	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary : Not available.**Skin** : There are no data available on the mixture itself.**Eyes** : There are no data available on the mixture itself.**Respiratory** : There are no data available on the mixture itself.**Sensitisation**

Code : 000001204045 **Date of issue/Date of revision** : 28 December 2024
SIGMASHIELD 680 HARDENER

SECTION 11: Toxicological information

Product/ingredient name	Route of exposure	Species	Result
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	skin	Mouse	Sensitising
3,6-diazaoctanethylenediamin	skin	Guinea pig	Sensitising

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 3	-	Respiratory tract irritation
2-methylpropan-1-ol	Category 3	-	Respiratory tract irritation
toluene	Category 3	-	Narcotic effects
	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs
toluene	Category 2	-	-

Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
toluene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.

Ingestion : Corrosive to the digestive tract. Causes burns. Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Code : 000001204045 **Date of issue/Date of revision** : 28 December 2024
SIGMASHIELD 680 HARDENER

SECTION 11: Toxicological information

- Eye contact** : Adverse symptoms may include the following:
 pain
 watering
 redness
- Inhalation** : Adverse symptoms may include the following:
 respiratory tract irritation
 coughing
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 unconsciousness
- Skin contact** : Adverse symptoms may include the following:
 pain or irritation
 redness
 dryness
 cracking
 blistering may occur
- Ingestion** : Adverse symptoms may include the following:
 stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	EC10 1.78 mg/l	Algae	72 hours
2-methylpropan-1-ol	Acute EC50 1100 mg/l	Daphnia	48 hours
2,4,6-tris (dimethylaminomethyl) phenol	Acute LC50 >100 mg/l	Daphnia	48 hours

Code : 000001204045 **Date of issue/Date of revision** : 28 December 2024
SIGMASHIELD 680 HARDENER

SECTION 12: Ecological information

ethylbenzene	Acute LC50 >100 mg/l Acute EC50 1.8 mg/l Fresh water Chronic NOEC 1 mg/l Fresh water	Fish Daphnia Daphnia - <i>Ceriodaphnia dubia</i>	96 hours 48 hours -
--------------	--	--	---------------------------

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2,4,6-tris (dimethylaminomethyl) phenol	OECD 301D Ready Biodegradability - Closed Bottle Test	4 % - Not readily - 28 days	-	-
ethylbenzene	-	79 % - Readily - 10 days	-	-

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	-	-	Not readily
xylene	-	-	Readily
2,4,6-tris (dimethylaminomethyl) phenol	-	-	Not readily
ethylbenzene	-	-	Readily
toluene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
2-methylpropan-1-ol	1	-	Low
2,4,6-tris (dimethylaminomethyl) phenol	0.219	-	Low
ethylbenzene	3.6	79.43	Low
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	Low
toluene	2.73	8.32	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

Code : 000001204045 **Date of issue/Date of revision** : 28 December 2024
SIGMASHIELD 680 HARDENER

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

Waste catalogue

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN3469	UN3469	UN3469	UN3469
14.2 UN proper shipping name	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE
14.3 Transport hazard class(es)	3 (8)	3 (8)	3 (8)	3 (8)
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID : None identified.

Tunnel code : (D/E)

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

IMDG : None identified.

IATA : None identified.

Code : 000001204045 **Date of issue/Date of revision** : 28 December 2024
SIGMASHIELD 680 HARDENER

SECTION 14: Transport information

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Explosive precursors : Not applicable.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
SIGMASHIELD 680 HARDENER toluene	3 48

Labelling : Not applicable.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
 GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = GB CLP-specific Hazard statement
 N/A = Not available
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 SGG = Segregation Group
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Code : 000001204045 **Date of issue/Date of revision** : 28 December 2024
SIGMASHIELD 680 HARDENER

SECTION 16: Other information

Classification	Justification
Flam. Liq. 3, H226 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 STOT SE 3, H336 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision : 28 December 2024
Date of previous issue : No previous validation
Prepared by : EHS
Version : 1

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.