

GLIDDEN® PRO

Interior/Exterior Latex Blockfiller

20056A

Water based product, Flat Finish

Technical Data Sheet



Technical Specifications (21°C (70°F))

Solids by Volume:	50% ($\pm 1\%$)
Solids by Weight:	70% ($\pm 1\%$)

Volatile Organic Compounds (VOCs)*

According to ASTM D3960-05:	< 50 g/L
Canadian regulation:	< 200 g/L

Available Colour

20056A	White
--------	-------

Can be tinted to light pastel colours, max 4 oz. of colourant per 3.78 L.

Gloss Level	Not applicable (primer)
-------------	-------------------------

Practical Coverage

7 - 9.5 sq. metres (75 - 100 sq. ft.) per 3.78 litres
1.9 - 2.5 sq. metres per litre

Coverage figures do not include loss due to surface irregularities and porosity or material losses due to application method or mixing.

Resin Type

- Vinyl-Acrylic

Viscosity* Ready to use (110 \pm 5 Krebs Units)

Manufacturing specification, working viscosity may vary

Flammability	Non Flammable
--------------	---------------

Flash Point*	Not applicable
--------------	----------------

Film Thickness requirements on smooth surfaces*

• Wet:	407 to 543 μm
	16 to 21 mils

• Dry:	206 to 274 μm
	8 to 11 mil

(Thickness varies according to the surface porosity)

Drying* @ 25°C/77°F - 50% Relative Humidity

Touch dry:	1 hour
To recoat:	minimum 24 hours
Full curing:	30 days

When relative humidity is higher than 50%, double the required time.

Drying times listed may vary depending on temperature, humidity, film build, colour, and air movement.

*Technical Data Source: 20056A

Product Description

Glidden PRO flat 20056A is an interior/exterior latex blockfiller formulated to meet the requirements of the construction painter.

Glidden PRO 20056A provides excellent filling properties on interior and exterior bare porous surfaces of concrete, concrete block, cinder block, stucco, or masonry.

Features

- For interior or exterior uses
- Excellent filling properties
- Good adhesion
- Easy application

Intended Uses

- Priming and sealing bare concrete or masonry surfaces in commercial and institutional applications such as schools, hospitals and industrial buildings.
- Walls and ceilings.

Surfaces

- Aged stucco, masonry, concrete, concrete block, or cinder block.

Limitations of Use

- Not formulated to be used on floors.
- Not formulated to be used over aged alkyd finishes.
- Exterior applications must be topcoated.
- Some colours, or drastic colour changes, may require additional coats of paint.

Certifications

- MPI #4 Block Filler, Latex, Interior/Exterior.

PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labour or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special or consequential damages.

04/2018



Available at Dulux Paints Stores across Canada and Bétonel-Dulux Stores in Quebec

SURFACE PREPARATION

Surface must be clean and dry.

Remove all loose, peeling paint, dirt, grease, mildew, form oil, curing compounds, loose or excess mortar, mortar spatter, salt deposits, and any other surface contaminants.

Crumbly soft surface layers or previous coatings softened by water must be completely removed.

All large voids, cracks, and surface imperfections should be filled with a cement-sand grout.

Plaster, concrete, and masonry must be completely dry, free of efflorescence, and allowed to cure for 30 days prior to painting.

Surfaces of "hot" cement-sand grout requires spot priming with an alkali resistant primer.

PRECAUTION: Dry sanding will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. Wear suitable respiratory protective equipment when exposure cannot be avoided by adequate local ventilation. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Contact a regional Health Canada office for more information.

Application

This is a ready-to-use product, do not thin. Shake well before and frequently during use. Keep containers closed when not in use.

Apply using brushes, rollers or spray equipment.

Application Conditions

Apply with good ventilation only when air and surface temperatures are between 10°C (50°F) and 32°C (90°F).

Tools

- Brush: synthetic bristles (nylon, polyester)
- Roller:
 - smooth: 10 mm (3/8 in.)
 - semi-rough: 13 to 20 mm (1/2 – 3/4 in.)
 - rough: 25 to 32 mm (1 – 1 1/4 in.)
- Spray (Airless equipment)*: tip size: 0.021 to 0.031 in.
pressure: 190 psi

*Spray recommendations may vary from figures listed depending on equipment manufacturer.

Spray equipment must be handled with due care and in accordance with the manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

SYSTEM RECOMMENDATIONS

Two topcoats are recommended on all surfaces for better durability and appearance.

All recommended surfaces:

- *Glidden PRO 20056A Interior/Exterior Latex Blockfiller*
 - one coat to total surface.
- *Appropriate Glidden or Dulux topcoat*
 - 2 coats for better durability and appearance.

Cleanup

Remove as much product quantity as possible and clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

Storage and Transportation

Keep product cool and dry. DO NOT FREEZE

Disposal

Consult your municipality in order to dispose of paint residues according to environmental regulations. Do not pour down a drain or storm sewer.

Safety Measures

Before use, be sure to read and follow the instructions and warnings on the label and Safety Data Sheet (SDS). Keep out of the reach of children. Avoid contact with eyes or skin. Wear protective gloves/clothing and eye/face protection. Use only in well-ventilated area.

MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. Avoid breathing vapours, spray or mists. Avoid contact with skin and eyes. Wear protective gloves/clothing and eye/face protection.

FIRST AID: If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call poison centre or doctor/physician.

For product information call: 1-800-387-3663

www.dulux.ca

The PPG Logo is a registered trademark of PPG Industries Ohio, Inc.

Dulux is a registered trademark of AkzoNobel and are licensed to PPG Architectural Coatings Canada, Inc. for use in Canada only.

The Multi-Coloured Swatches Design and Glidden are registered trademarks of PPG Architectural Finishes, Inc.

The Glidden Logo is a trademark of PPG Architectural Finishes, Inc.

MPI is a trademark of Master Painters Institute, Inc.



PPG Architectural Coatings Canada, Inc.
2505, de la Metropole
Longueuil QC, Canada, J4G 1E5