



Architectural Coatings

Mulco Zip Seal'N Peel, Removable Thermoplastic Sealant Interior*/Exterior (*Interior use requires proper ventilation)**GENERAL DESCRIPTION**

Easily removable and transparent sealant used to temporarily seal joints around windows, doors, air conditioners, and other areas where air can penetrate.

RECOMMENDED SUBSTRATES

Temporarily seals interior* or exterior joints where air can penetrate between two perpendicular surfaces. Can be used around patio doors, windows, air conditioners, etc.

*Interior use requires proper ventilation.

FEATURES / BENEFITS

- Temporarily seal joints where air can penetrate.
- Removes cleanly.
- Withstands humidity and condensation.
- Saves energy by filling gaps and joints.
- Resists cracking.
- Transparent when dry.

PRODUCT INFORMATION / PACKAGING

Mulco 300 mL Tube: 141000 Clear (vanilla scent)

LIMITATIONS OF USE

Not to be used to seal permanently. Not for joints sealed for more than 12 months.

Does not adhere to polyethylene, polypropylene, recycled plastic, Teflon or other comparable materials.

Make sure the joint variation does not exceed «ZIP SEAL'N PEEL» elasticity.

The drying time of «ZIP SEAL'N PEEL» depends on temperature, relative humidity and ventilation.

Do not use on areas where silicone or asphalt was previously applied.

Do not use in contact with surfaces such as asphalt or tar products and insulation panels (polystyrene, etc.) which can be damaged by solvents.

Not intended for joints that will be submerged or exposed to abrasion (foot traffic).

Does not withstand immersion (tank).

New metal and solvent resistant oily surfaces must be washed with acetone and dried.

Scrape rusty metal with a metallic brush prior to cleaning.

Surfaces sensitive to solvents such as vinyl or dirty plastic materials must be washed with a soapy solution, then rinsed and dried.

Adhesion to materials not specifically mentioned are not guaranteed.

Read Label and Safety Data Sheet Prior to Use. See other cautions on last page.

PRODUCT DATA

COMPOSITION: Thermoplastic rubbers, synthetic resins (binder), promoter of adhesion (agents), solvents (volatile material) and other additives.

COLOUR: Clear, Vanilla scent when dry.

APPEARANCE: Homogeneous paste without lumps, easy to extrude.

MATERIAL TEMPERATURE: 10°C to 30°C (50°F to 86°F).

APPLICATION TEMPERATURE: -30 to 40°C (-22 to 104°F).

SERVICE TEMPERATURE: -30 to 50°C (-22 to 122°F).

APPLICATION METHOD: Caulking gun.

EXTRUDABILITY: Easy to gun at room temperature.

DRY TO TOUCH: < 48 hours at room temperature.

FULL CURE: < 2 weeks.

FLAMMABILITY*: Flammable; combustible when dry.

FLASH POINT*: 28°C (82.4°F).

FREEZE/THAW STABILITY: Stable

SHELF LIFE: One year from date of purchase.

CLEANER (wet product): Use mineral spirits.

CLEANER (dry product): Use a putty knife to lift the bead. Pull slowly at an angle to remove the sealant. Use a dry cloth to rub away any residue as needed. Mineral spirits may be used if necessary, but be careful not to damage any surrounding surfaces with solvent.


MAX VOC*: < 65% by weight.

*Technical data source: 141000, Clear

GENERAL SURFACE PREPARATION/APPLICATION

SURFACE PREPARATION: Surface must be clean, dry, and free from all loose or foreign materials.

APPLICATION: Can be applied from -30 to 40°C (-22 to 104°F). Product must be above 10°C (50°F) and should be below 30°C (86°F) when applied. Cut nozzle tip at a 90° angle and leave an orifice that will allow a bead between 6 and 16 mm in width. Pierce the seal inside the nozzle. Use a caulking gun and apply a uniform, convex bead, pulling the gun away from the bead as shown. The angle of the caulking gun should be approximately 45°. Make sure the sealant makes at least 3 mm (1/8 in.) contact with each surface of the joint. Do not tool the bead to avoid defects during drying.



REMOVAL: To remove the sealant, use a putty knife to lift the bead. Pull slowly at an angle to remove the sealant. Use a dry cloth to rub away any residue as needed. Mineral spirits may be used if necessary, but be careful not to damage any surrounding surfaces with solvent.

STORAGE: Freeze/Thaw stable.

CLEANUP: Clean tools with mineral spirits. Wash hands with soap and water.

DISPOSAL: Consult your municipality about proper disposal procedure of residue in accordance with the laws and respect the environment.

PERMISSIBLE TEMPERATURES DURING APPLICATIONS

Material:	10 to 30°C	50 to 86°F
Ambient:	-30 to 40°C	-22 to 104°F
Substrate:	-30 to 40°C	-22 to 104°F

PRECAUTIONS

DANGER FLAMMABLE IRRITANT. CONTENTS MAY CATCH FIRE. MAY IRRITATE EYES. MAY IRRITATE SKIN. Do not smoke. Do not get in eyes. Do not get on skin or clothing. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Keep out of reach of children. Wear protective gloves and eye/face protection: Chemical splash goggles. Use chemical-resistant, impervious gloves. **Prior to use, read and follow product-specific SDS and label information. FIRST AID TREATMENT:** Contains: Hydrocarbons, C11-C12, isoalkanes, <2% aromatics; xylene; ethylbenzene. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. Inhalation of high concentrations of vapour may affect the central nervous system. Repeated exposure to high vapour concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapour concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. Keep container tightly closed and sealed until ready for use. For workplace use, an SDS is available from your retailer or by calling 1-800-463-7426 (Canada). EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.), (514) 645-1320 (Canada).

LIMITED WARRANTY: This product is covered by a Limited Warranty. For details, visit www.mulco.ca/en-ca/limited-warranty or call 1-866-660-2220.

The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. *Zip Seal 'N Peel* is a registered trademark of PPG Architectural Coatings Canada, Inc. *Mulco* is a registered trademark of AkzoNobel.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-866-660-2220.

