

GENERAL DESCRIPTION

Ideal for indoor use on well-prepared walls, ceilings or trim composed of new gypsum board, or on previously painted or primed drywall, plaster, masonry, and wood.

It dries to a dead flat finish to help hide tape joints and surface imperfections.

This paint is recommended for high volume new home builders and commercial contractors.

RECOMMENDED SUBSTRATES

Gypsum Wallboard Plaster
Masonry Wood

See details in the "recommended primers" section.

CONFORMANCE STANDARDS

Complies with the Canadian Volatile Organic Compound Concentration Limits for Architectural Coatings Regulations.

TINTING AND BASE INFORMATION

Refer to the appropriate colour formula book, automatic tinting equipment, and/or computer colour-matching system for colour formulas and tinting instructions.

8-112C High Hide / Commercial White

Some colours, drastic colour changes, or porous substrates may require more than one coat to achieve a uniform finish.

PACKAGING

3.78 L & 18.9 L

PRODUCT DATA

PRODUCT TYPE: Vinyl Acetate Ethylene
SHEEN: Flat 0 - 2 %
(60° & 85° Gloss Meter)
VOLUME SOLIDS*: 29% ± 2%
WEIGHT SOLIDS*: 46% ± 2%
VOC*: < 50 g/L
DENSITY*: 1.3 kg/L

*Product data calculated on product 8-112C.

SPREADING RATE PER COAT: Approximately 28 to 37 m² (300 to 400 ft²) per 3.78 litres on smooth, nonporous surfaces.

Wet Film Thickness: 102 microns
4.0 mils

Dry Film Thickness: 30 microns
1.2 mils

Coverage figures do not include loss due to surface irregularities and porosity or material losses due to application method or mixing.

DRYING: Dry time @ 25°C (77°F); 50% relative humidity.

To Touch: 1 hour
To Recoat: 4 hours minimum
Before cleaning: 30 days
Full curing: 30 days

Drying times listed may vary depending on temperature, humidity, film build, colour, and air movement.

Permissible temperatures during the application:

| | | |
|------------|------------|------------|
| Material: | 10 to 32°C | 50 to 90°F |
| Ambient: | 10 to 32°C | 50 to 90°F |
| Substrate: | 10 to 32°C | 50 to 90°F |

CLEANUP: Remove as much product quantity as possible and clean tools with lukewarm soapy water immediately after use.

WASHING INSTRUCTIONS: Wait at least 30 days before cleaning the surface (longer in conditions of high humidity or low temperature) use a non-abrasive mild cleaner.

DISPOSAL: Consult your municipality in order to dispose of paint residues according to environmental regulations. Do not pour down a drain or storm sewer.

FLASH POINT: Over 93 °C (200 °F)

FEATURES / BENEFITS

- Self-Priming on gypsum wallboard
- Excellent Touch-Up properties
- Low Spatter
- Easy Application
- Good hiding power
- Provides a uniform flat finish
- Good Scrubs

LIMITATIONS OF USE

FOR INTERIOR USE ONLY.

PROTECT FROM FREEZING. USE WITH ADEQUATE VENTILATION. **KEEP OUT OF REACH OF CHILDREN.**

Apply when air, surface and product temperatures are between 10°C to 32°C (50°F to 90°F).

Do not use on floors, in high humidity areas, or on submerged surfaces.

Optimum touch-up may not be achieved with darker colours.

GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all loose, peeling paint, dirt, grease, and any other surface contaminants. Putty all nail holes and caulk all cracks or open seams. Sand all glossy, rough, and patched surfaces.

Plaster, concrete, and masonry must be completely dry, free of efflorescence, and allowed to cure for 30 days prior to priming and painting.

Primers: This paint may be used as a primer coat on bare gypsum surface. Prime all bare wood, plaster, masonry, metal, and porous surfaces with an appropriate primer.

Before use, be sure to read and follow the instructions and warnings on the label.

Contact your local representative for any additional surface preparation guidelines.

RECOMMENDED PRIMERS

Concrete, Masonry: Block filler: 6-7C,

Primer-sealer: 4-603XIC, 17-921XIC

Gypsum Wallboard: Self-priming, 6-2C, 6-4C, 9-900C, 12-900XIC

Plaster: 4-603XIC, 17-921XIC

Wood: 6-2C, 9-900C, 12-900XIC, 4-603XIC, 17-921XIC

APPLICATION INFORMATION

KEEP OUT OF REACH OF CHILDREN. USE WITH ADEQUATE VENTILATION. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available from your retailer, through our website or by calling 1-800-463-7426.

Stir thoroughly before use and occasionally during use. When using more than one container of the same colour, intermix to ensure colour uniformity.

Application Equipment: Apply with a high quality synthetic brush, roller, paint pad, or by spray equipment. Where necessary, apply a second coat and allow each coat to dry thoroughly before applying the next coat.

Brush: High quality polyester/nylon brush.

Roller: 10 to 20 mm (3/8 – 3/4 in.) nap synthetic roller cover.

Airless Spray: Pressure 2000 psi, tip 0.015 in. - 0.019 in.

Spray equipment must be handled with due care and in accordance with the manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

Thinning: Do not thin.

PRECAUTIONS

Keep out of the reach of children. Keep containers tightly closed and sealed until ready for use.

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Use personal protective equipment as required. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation.

MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. Avoid breathing vapours, spray or mists. Avoid contact with skin and eyes. Wear protective gloves/clothing and eye/face protection.

FIRST AID: If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call poison centre or doctor/physician. For workplace use, an SDS are available from your retailer, through our website or by calling 1 800 463-7426.

EMERGENCY SPILL INFORMATION: 1 514 645-1320 or 1 800 463-7426.

LIMITED WARRANTY

PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labour or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special or consequential damages.

The *PPG Paints* is a registered trademark of PPG Industries Ohio, Inc. *Speed Finish Plus* is a trademark of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-866-660-2220.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpaints.com

PPG Architectural Coatings Canada Inc.
2505, de la Metropole
Longueuil, QC, Canada, J4G 1E5

| | | |
|--------------------|----------------|---------------------|
| Technical Services | 450 442-2220 | |
| | 1 866 660-2220 | Architect/Specifier |
| Fax: | 450 679-8893 | 1-888-PPG-IDEA |
| | 1 800 278-8893 | |