

Architectural Coatings

*Pittsburgh Paints Anti-Scuff Interior Epoxy-Fortified Acrylic Paint Matte*

## GENERAL DESCRIPTION

*Pittsburgh Paints Anti-Scuff* interior zero VOC\* paint delivers unrivaled scuff resistance across all sheens and tint bases, making it ideal for high-traffic areas in both commercial and residential spaces. It also provides a smooth application and finish, as well as high-hiding, great coverage, and excellent touch-up.

\*Colorants added to this base paint may increase VOC level significantly depending on color choice.

## RECOMMENDED SUBSTRATES

Concrete/Masonry	Gypsum Wallboard-Drywall
Concrete Block (CMU)	Plaster
Ferrous Metal	Wood

## CONFORMANCE STANDARDS

GREENGUARD® Gold Emissions Certified  
Eligible for LEED® v4.1 low-emitting credit  
Qualified for CHPS low-emitting credit  
Meets CDPH v1.2 2017 Emissions Standard criteria  
Suitable for incidental food contact in USDA-inspected facilities  
Meets MPI High Performance 138  
Meets MPI Institutional 144

## PRODUCT INFORMATION

619-210	White & Pastel Base
619-220	Midtone Base*
619-240	Ultra Deep Base*

\*Must be tinted before use. Refer to the appropriate color formula book, automatic tinting equipment, and/or computer color matching system for color formulas and tinting instructions.

## PACKAGING

1-Gallon (3.78 L)  
5-Gallon (18.9 L)

Not all products are available in all sizes.

## PRODUCT DATA

<b>PRODUCT TYPE:</b>	100% Acrylic
<b>SHEEN*:</b>	Matte, 4-14 @ 60°; 10-20 @ 85°
<b>VOLUME SOLIDS*:</b>	37% +/- 2%
<b>WEIGHT SOLIDS*:</b>	49% +/- 2%
<b>WEIGHT/GALLON*:</b>	10.3 lbs. (4.7 kg) +/- 0.2 lbs. (91 g)
<b>VOC:</b>	0 g/L (0.0 lbs./gal.)**

\*Product data calculated on product 619-210.

\*\*Colorants added to this base paint may increase VOC level significantly depending on color choice.

**COVERAGE:** Up to 400 sq. ft. (37 sq. meters) per U.S. gallon (3.78 L) on primed, smooth, nonporous surfaces.

Wet Film Thickness:	4 mils
Wet Microns:	102
Dry Film Thickness:	1.5 mils
Dry Microns:	38

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing. Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

**DRYING TIME:** Dry time @ 77°F (25°C); 50% relative humidity.

To Touch:	30-60 minutes
To Recoat:	2-4 hours
To Full Cure:	30 days

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement. Wait at least 30 days after painting before cleaning the surface with a non-abrasive, mild cleanser. Very deep colors may require longer to fully cure.

**CLEANUP:** Clean tools with warm, soapy water.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** Over 200°F (93°C)

## FEATURES / BENEFITS

### Features

Unrivaled scuff resistance across all sheens & bases

High-hiding & great coverage

Smooth application & finish

Excellent touch-up

Quick drying

Zero VOC\*

Can help earn LEED v4 & v4.1 EQ Low-Emitting Materials Credit

### Benefits

Ideal for high traffic areas that are prone to scuffs in commercial and residential spaces

Saves money; less material required

Great look on walls

Reduces amount of rework

Enables quick turnaround after painting

Meets the most stringent VOC regulations nationwide

Contributes to sustainable design

\*Colorants added to this base paint may increase VOC level significantly depending on color choice. However, Formula Pro and HS colorants (96-xxxXI, 96-xxx, 96-xxxx, 96-xxxxx), even if used at maximum tint load in any color, contributes less than 8 g/L of VOC to the final tinted product.

Read Label and Safety Data Sheet prior to use. See other cautions on last page.

## GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all loose, peeling paint, dirt, grease, and any other surface contaminants. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Plaster, concrete, and masonry surfaces must be completely dry, free of efflorescence, and allowed to cure for 30 days prior to painting. Prime all bare wood, drywall, plaster, masonry, metal, and porous surfaces with an appropriate primer.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**CONCRETE/MASONRY:** New concrete and masonry should cure for at least 30 days and preferably 90 days prior to priming and painting. The pH of the substrate must be less than 10 before priming. Use of an alkali resistant primer is recommended.

**CONCRETE BLOCK (CMU):** Mortar should cure for at least 30 days and preferably 90 days prior to painting. Fill block with an appropriate block filler.

**FERROUS METAL:** The surface must be cleaned thoroughly to remove any dust, rust, and surface contaminants, and then primed with a metal primer.

**GYPSUM WALLBOARD-DRYWALL:** Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust prior to priming the substrate.

**PLASTER:** Plaster, hardcoat, skim coat, or other alkaline surfaces should be allowed to cure for at least 30 days prior to priming and painting. The pH of the substrate must be less than 10 before priming. Use of an alkali resistant primer is recommended.

**WOOD:** Countersink all nails, putty flush with surface. Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, then primed. Any knots or resinous areas must be sealed before painting.

## RECOMMENDED PRIMERS

Concrete/Masonry	4-603XI, 17-921XI
Concrete Block (CMU)	6-7, 6-15XI
Ferrous Metal	90-1908, 90-1909, 90-1912
Gypsum Wallboard-Drywall	6-2, 6-4, 9-900, 12-900XI, 17-921XI
Plaster	4-603XI, 17-921XI
Wood	6-2, 9-900, 12-900XI, 17-921XI

## LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Apply when air, product and surface temperatures are between 50°F (10°C) and 90°F (32°C).

Do not use on floors, in areas of saturating humidity, or on submerged surfaces.

PROTECT FROM FREEZING.

## APPLICATION INFORMATION

Stir thoroughly before using and occasionally when in use. When using more than one can of the same color, intermix to ensure color uniformity. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our web site or by calling 1-800-441-9695.

**Application Equipment:** Apply with a high-quality brush, roller, paint pad, or by spray equipment. Where necessary, apply a second coat and allow each coat to dry thoroughly before applying the next coat.

**Airless Spray:** Pressure 1500 to 2000 psi; tip 0.015" to 0.021". Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

**Brush:** Nylon/Polyester Brush

**Roller (nap roller cover):** 3/8" - 3/4"

**Thinning:** Do not thin.

**Permissible temperatures during application:**

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 90°F	10 to 32°C
Substrate:	50 to 90°F	10 to 32°C

## PRECAUTIONS

For warning information, please refer to the product label and SDS available at the online listing for this product at [www.pittsburghpaintsco.com](http://www.pittsburghpaintsco.com). Keep container tightly closed and sealed until ready for use. SDS, spill, and emergency information are available by calling 1-833-477-1553.

© 2025 The Pittsburgh Paints Co. All Rights Reserved. *Pittsburgh Paints*, *Pittsburgh Paints Anti-Scuff*, and the *P Logo* are trademarks of The Pittsburgh Paints Co. *UL Greenguard* is a registered certification mark of UL LLC.

The Pittsburgh Paints Co. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



The Pittsburgh Paints Co.  
400 Bertha Lamme Drive  
Cranberry Township, PA 16066  
[www.pittsburghpaints.com](http://www.pittsburghpaints.com)

Technical Services  
1-800-441-9695

619-210 - 11/2025