

Product Description

High-build coating that seals and fills small concrete surface irregularities to provide a smoother and more uniform surface.

Advantages

- Can help earn LEED® (Leadership in Energy and Environmental Design) 2009 credits.
- Super sealing; gives the finishing coats a better appearance.
- High hiding.
- Dries quickly and has very little odour.
- Ready for use and easy to apply.
- Water-based product which allows tool clean-up with water.
- Low VOC content complies with the Canadian Volatile Organic Compound (VOC) Concentration Limits for Architectural Coatings Regulations requirements.

Available Colour

675-115 White

Projects
Environment

Interior and exterior

Use

New and maintenance work.
Residential and commercial sites.
Walls, ceilings and columns.

Surfaces

Poured concrete, prefabricated concrete, concrete blocks, brick or other masonries.

Notes

Must be coated with a topcoat.
Do not apply directly over steel, iron or other metals.
Not formulated to be used on floors.
Some colours, or drastic colour changes, may require additional coats of paint.
Do not mix with other paints or thinners.

Certifications*

MPI #4 Block Filler, Latex, Interior/Exterior.

Technical Specifications (21°C (70°F))
Appearance

Opaque

Gloss Level

Not applicable (primer)

• Gloss at 60°: Not applicable

• Gloss at 85°: Not applicable

Composition

• Diluent: Water

• Binder: Vinyl-acrylic polymer

Volatile Organic Compounds (VOCs)*

According to ASTM D3960-05: < 50 g/L

Canadian regulation: < 200 g/L

Addition of colourant will introduce VOCs.

Viscosity*

Ready to use (118 ± 5 Krebs Units)

Manufacturing specification, working viscosity may vary.

Density* 1.6 ± 0.1 kg/L

Solids by Volume* 51%

Solids by Weight* 69%

Flammability Non flammable

Flash Point* Not applicable

Spreading Rate per Coat

3.78 L: 5.5 to 8.25 m² (59 to 89 ft²)

75.8 m² per 3.78 L at 1 mil D. F. T.

20 m² per litre at 1 mil D. F. T.

Coverage figures do not include loss due to surface irregularities and porosity or material losses due to application method or mixing.

Film Thickness requirements*

Not available: Film Thickness varies greatly depending on the surfaces porosity.

Drying Time*

• Touch dry: 30 to 60 minutes

• Dust free: 1 to 2 hours

• Before recoating: 2 to 4 hours

• Prior to withstanding rain: 24 hours

• Full curing: 14 days

When relative humidity is higher than 50%, double the required time.

Drying times listed may vary depending on temperature, humidity, film build, colour, and air movement.

*Technical data source: 675-115

Limited Warranty

PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labour or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special or consequential damages.

Surface Preparation

Surfaces must be clean and dry. Remove loose and peeling paint, dirt, dust mildew oil, wax, concrete curing agents and bond breakers, chalk, efflorescence, rust, and other surface contamination.

Concrete and masonry: New surfaces must age at least 28 days, be thoroughly dry and free of any efflorescence salts. Clean the concrete surfaces per ASTM Standard Practice D4258: Standard Practice for Surface Cleaning Concrete for Coating. Vacuum cleaning, water cleaning, detergent water wash, power wash cleaning, steam cleaning, hand tool and mechanical cleaning are acceptable cleaning methods.

Painted surfaces: Remove loose and peeling paint, chalk, and efflorescence by wire brushing, scraping, sanding, and/or pressure washing. Eliminate stains caused by mildew with a solution of household bleach (1 part household bleach to 3 parts of water). Wear rubber gloves and eye protection. Rinse thoroughly with clear water and let dry completely.

Remove all surface contaminants by washing with an appropriate cleaner.

Rinse thoroughly with water and allow to dry.

Repair holes and cracks.

PRECAUTION: Dry sanding will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. Wear suitable respiratory protective equipment when exposure cannot be avoided by adequate local ventilation. Clean up carefully with a HEPA vacuum and a wet mop. Follow these instructions to control exposure to hazardous substances that may be released during surface preparation. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Contact a regional Health Canada office for more information.

Before use, cover or mask surfaces that are not to be painted, be sure to read and follow the instructions and warnings on the label and Safety Data Sheet.

Contact your local representative for any additional surface preparation guidelines.

Systems recommendation according to surfaces

Concrete and masonry:

- *Sico Expert* block filler 675-115 in an even coat;

Note : For exterior use, must be topcoated with a finishing paint within 24 hours.

- *Sico Expert* or *Ecosource* interior top coats of your choice. Two coats for better durability and appearance.

Recommendations

Application Conditions

Temperature: 10 to 32°C (50 to 90°F)
(ideal 20°C ± 5°C [68°F ± 9°F])

Relative humidity: Ideal between 15 and 55%, maximum 85%.

Maintain these conditions during the application and the following 24 hours. Low temperature, high humidity, thick films or poor ventilation extend drying time.

Surface must be at a temperature at least 3°C (5°F) higher than dew point. Do not apply in direct sunlight or during windy conditions. Do not apply if lower temperatures are expected within 3 to 6 hours. Do not apply when rain is expected within 24 hours.

Tools

- Paintbrush: Synthetic bristles (nylon, polyester)
- Roller: 31 mm (1 1/4 in.)
- *Spray (airless equipment)
 - Tip size: 0.021 to 0.025 in.;
 - Pressure: 2000 to 2500 psi.

Always use top quality application tools.

*Spray recommendations may vary from figures listed depending on equipment manufacturer.

Cleaning Tools

Remove as much product quantity as possible and clean tools with lukewarm soapy water immediately after use.

Storage and Transportation

Keep in a dry and ventilated area, between 10 and 30°C (50 and 86°F). Under such conditions, unopened containers may be stored up to 5 years from manufacturing date.

PROTECT FROM FREEZING.

Disposal

Consult your municipality in order to dispose of paint residues according to environmental regulations. Do not pour down a drain or storm sewer.

Application

FOR PROFESSIONAL APPLICATION ONLY. NOT INTENDED OR LABELED FOR CONSUMER USE.

Do not thin. Stir thoroughly before use and occasionally during use. Pour the quantity of paint needed into another container to avoid contaminating the original paint container. Keep containers closed when not in use.

Apply the product by complying with its spreading rate, leaving no bare spots or excessively coated areas.

Provide adequate ventilation. Observe drying time between coats. Low temperatures or high humidity will affect drying time. Applying two coats will provide better durability and appearance.

For more information, visit the website at www.sico.ca or call our customer service: 1-800-463-7426.

Safety Measures

Store locked up. Do not handle until all safety precautions have been read and understood warnings on the label and Safety Data Sheet (SDS). For workplace use, an SDS are available from your retailer, through our website or by calling 1-800-463-7426. Keep out of the reach of children. Use only in well-ventilated area. Keep containers tightly closed and sealed until ready for use. Wear personal protective equipment as required; gloves and eye or face protection. Avoid contact with skin and clothing. Avoid breathing spray or mists. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Warning: Suspected of causing cancer. Emits toxic fumes when heated.

First aid treatment: If you feel unwell or in case of proven or suspected overexposure: Consult a physician.

Emergency spill information: 1-514-645-1320 or 1-800-463-7426.

Surface Maintenance

Must be overcoated with finishing paint.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-866-660-2220.



PPG Architectural Coatings Canada, Inc.
2505, de la Metropole
Longueuil, QC, Canada, J4G 1E5

The *PPG Logo* is a registered trademark of PPG Industries Ohio, Inc., *Sico Expert*, *Sico* and *Ecosource* are registered trademarks of the PPG Group of Companies. *MPI* is a trademark of Master Painters Institute, Inc. *LEED* is a registered trademark of the US Green Building Council.