



AQUACRON® MV398C EQUIPMENT CLEANER

DESCRIPTION:

AQUACRON® MV398C Equipment Cleaner is recommended to be used for the cleanup of tools, spray equipment, paint lines, etc. that have been used to spray any of the Aquacron® waterbased primers or topcoats. MV398C may also be used as a surface cleaner prior to painting non porous surfaces.

HIGHLIGHTS:

- ❖ Cleans fluid lines of residual waterbased paint
- ❖ Cleans dried paint off spray guns & spray equipment
- ❖ Can be used to clean non porous parts and surfaces prior to painting
- ❖ Compatible with Aquacron® waterbased coatings

PHYSICAL PROPERTIES:

PROPERTY	VALUE
Weight per gallon	8.04 lbs./gal.
VOC (less water)	7.38 lbs./gal.
VOE (actual)	2.66 lbs./gal.
Flash Point	213°F
Shelf Life - unopened container	2 years

WHERE & HOW TO USE:

Aquacron waterbased coatings are highly resistant to solvents, acids, and caustics and cannot readily be removed from equipment using commercial paint removers. MV398C is designed exclusively for this purpose and can be used for cleaning painting tools, spray equipment and paint lines. After cleaning the equipment, flush liberally with clean, warm water. If used as a surface or parts type cleaner be sure to change rags frequently and to rinse the parts thoroughly with water prior to applying any of the Aquacron primers or topcoats.

ADDITIONAL INFORMATION:

- ❖ Protect from freezing
- ❖ Do not add to any waterbased coating
- ❖ Do not apply at temperatures below 50°F
- ❖ MV398C is not to be used as substitute for a good parts pretreatment or conversion coating

AQUACRON® IS A REGISTERED TRADEMARK OF PPG INDUSTRIES, INC.

FOR MORE INFORMATION CONTACT:

PPG INDUSTRIES, 19699 PROGRESS DRIVE, STRONGSVILLE, OH 44149, 1-800-647-6050
PPG CANADA INC., 2301 ROYAL WINDSOR DRIVE, MISSISSAUGA, ONTARIO L5J 1K5, 1-888-310-4762

The technical data presented is information believed by PPG to be currently accurate; however, no guarantee of accuracy, comprehensiveness or performance is given or implied. Continuous improvements in coating technology may cause future technical data to vary from what is in this document. Product is intended for application by trained personnel in a factory or shop application. Do not attempt to use product without the current Material Safety Data Sheet. The performance of a product can fluctuate due to surface preparation technique, method of application, operating conditions, the material it is applied to or with, and use. It is strongly recommended that products be tested with respect to these factors prior to full scale use.