



## Universal Flexibilizer

P-192

# DX814

DX814 Universal Flexibilizer, when used as recommended, will form a coating that will withstand the customary abuse of impact and flexing in topcoats and undercoats during and after installation of the part.



### Preparation

- For bare plastic substrates, apply appropriate PPG plastic adhesion promoter before applying flexilized undercoat or topcoat.
- If the DX814 is stored in a cold area, it must be allowed to come up to room temperature and shaken before use.
- See the specific undercoat, clearcoat, or color product bulletin for the proper mix ratio with DX814.

### Technical Data:

Color	Clear Liquid
Intended Use	Flex Additive
VOC (Package)	5.06 lbs./ US Gal. (607 g/L)
Weight Solids	34.1%
Volume Solids	29.9%

## DX814

**See Material Safety Data Sheet and Labels for additional safety information and handling instructions.**

**Important:** The contents of this package must be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

**EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (412) 434-4515; IN CANADA (514) 645-1320**

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the public. Products mentioned may be hazardous and should only be used according to direction, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to PPG Industries. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does PPG Industries warrant freedom from patent infringement in the use of any formula or process set forth herein.

PPG Automotive Refinish  
19699 Progress Drive  
Strongsville, OH 44149  
800.647.6050

PPG Canada Inc.  
2301 Royal Windsor Drive, Unit #6  
Mississauga, Ontario L5J 1K5  
888.310.4762

Follow us online:  

[www.ppgrefinish.com](http://www.ppgrefinish.com)

**PPG Automotive Refinish**

Bringing innovation to the surface.™

The PPG Logo Bringing innovation to the surface, and DELTRON® are trademarks of PPG Industries Ohio, Inc.

© 2015 PPG Industries, Inc. All rights reserved.

Product Information Effective 5/15

