




FOR PROFESSIONAL USE ONLY



# I2400

Date of issue: July 2002

## Silver Wheel Enamel P166-2

Product	
P166-2	Silver Wheel Enamel

### PRODUCT DESCRIPTION






Nexa Autocolor's Silver Wheel Enamel in an aerosol provides a fast application, weather resistant, acrylic paint for renewing and touching up paint on motor vehicle wheels.

P166-2 should only be applied over well cleaned substrates in sound condition, flatted with fine abrasive paper if appropriate.

**Note: - P166-2 should not be applied directly over etch primers.**

**THESE PRODUCTS ARE FOR THE PROFESSIONAL PAINTING OF AUTOMOTIVE VEHICLES ONLY AFTER REFERENCE TO THE MANUFACTURER'S MATERIAL SAFETY DATA SHEET**

## PROCESS

	Supplied ready for use Shake aerosol for at least 1 minute before use
	Spraying range : 20-30 cm
	Apply the finish in several thin layers until a smooth opaque film is obtained.
	Allow the paint to flash-off between coats for 2 to 3 minutes.
	<b>Air Dry at 20°C</b> Dust Free        15 mins Handleable      60 mins Into service     24 hours
<b>RECOAT</b>	After 'into service' time

**This information is given in good faith but without warranty.**

For further information please contact:  
Customer Service and Sales Group  
PPG Industries (UK) Ltd  
Needham Road  
Stowmarket  
Suffolk, IP14 2AD

**Tel: 01449 771771**  
**Fax: 01449 773472**

**Nexa Autocolor**, **ZK**, **ACS**, Aquabase, Aquadry, Belco and Ecofast are trademarks of PPG Industries.  
Copyright © 2002 PPG Industries, all rights reserved.  
Copyright in the above product numbers that are original is asserted by PPG Industries.

**Scotchbrite** is a trademark of 3M UK Plc.

9950-1873