

# Product Data Sheet

March 2013



INTERNATIONAL MASTER FOR PROFESSIONAL USE ONLY

## G0402V

### 1K Rub Through Primers P565-9081/-9085/-9086/-9087

Product	Description
P565-9081	1K Rub Through Primer – SG01 White
P565-9085	1K Rub Through Primer – SG05 Grey
P565-9086	1K Rub Through Primer – SG06 Dark Grey
P565-9087	1K Rub Through Primer – SG07 Extra Dark Grey

#### Product Description

P565-9081, 9085, 9086 and 9087 are mild etch primers, which can be used under **Nexa Autocolor** 2K topcoat systems.

They are designed and formulated for rub-throughs to bare metal and for small spot repairs. For premium performance over large areas either Chromate-Free Etch Primer (P565-713) should be used.

#### Substrates and Preparation

P565-9081/9085/9086/9087 should only be applied over :

Well scuffed and degreased bare steel and aluminium.  
Well-flatted GRP, polyester fillers, works primer and old finishes in sound condition.

Good preparation is vital in order to obtain the best results from this product.  
The following grades of flattening paper are recommended :-

	If undercoating :	If topcoating direct :
Wet or dry paper	P280-P320 (GRP P400)	P800
Machine dry sanding	P220-P280	P360

#### NOTE

1. Old synthetic finishes must be thoroughly through hardened.
2. Not recommended over thermoplastic acrylic substrates.

