

Product Data Sheet

November 2007

INTERNATIONAL MASTER
FOR PROFESSIONAL USE ONLY



J4600V

Aerosol 1K Clearcoat P190-482





<i>Product</i>	<i>Description</i>
P190-482	1K Clearcoat - Aerosol

Product Description

P190-482 is a 1-Pack Clearcoat which is fast air-dry and has easy polishability. **Aerosol 1K Clearcoat** is recommended as suitable for repair of internal surfaces only.

Product Data Sheet

Innovating Repair Solutions

PROCESS	
	Supplied ready for use in an aerosol. Shake for 2 minutes before use.
	1 single and 2 double coats
	10 minutes between coats
	<p>Air-dry (20°C)</p> <p>Dust Free 10-15 mins Handleable 45-60 mins Into Service 4 hours Recoatable 4 hours Polishable 2-4 hours</p>

VOC INFORMATION


The EU limit value for this product (product category: IIB.e) in ready to use form is max. 840g/litre of VOC. The VOC content of this product in ready to use form is max. 840g/litre.

These products are for the professional painting of Automotive Vehicles only and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose.

For Health and Safety information please refer to the material Safety Data Sheet, also available at: http://www.ppg.com/Autocolor_MSDS

For further information please contact:

Customer Service Sales Group
 PPG Industries (UK) Ltd
 Needham Road
 Stowmarket
 Suffolk IP14 2AD
Tel: 01449 771771
Fax: 01449 773472

Nexa Autocolor, , Aquabase, Aquadry and Ecofast are trademarks of PPG Industries.
 Copyright © 2007 PPG Industries, all rights reserved.
 Copyright in the above product numbers that are original is asserted by PPG Industries.

