

Product Data Sheet

November 2006



FOR PROFESSIONAL USE ONLY

E1300V

Precleaners P980-251 and P980-9010

<i>Product</i>	<i>Description</i>
P980-251	Waterborne precleaner
P980-9010	Precleaner

Product Description

P980-251/P980-9010 have been formulated to remove flatting residues produced by wet or dry flatting of the undercoat prior to topcoating. They are especially designed to remove soluble salts produced by the wet flatting process. Failure to use P980-251/P980-9010, or poor preparation, may result in film defects.

P980-251 contains very low levels of volatile organic compound and further reduces overall solvent emissions from the bodyshop.

P980-9010 is designed to give faster process times.

Product Data Sheet

Innovating Repair Solutions

Process		
	WATERBORNE PRECLEANER P980-251	PRECLEANER P980-9010
	<p>Products may be applied by cloth or by spray bottle.</p> <p>When using spray bottle, apply precleaners evenly and wipe off with a clean cloth. Spray bottle application offers the fastest process.</p> <p>When using cloths alone, use one clean cloth for application and one clean cloth for wiping off contaminants.</p>	
	<p>P980-251/-9010 will freeze if subjected to frost. Store above 4°C</p>	
Waste Disposal	<p>Surplus P980-251 must be disposed of according to local regulations.</p>	<p>Surplus P980-9010 must be disposed of according to local regulations</p>

VOC INFORMATION

The EU limit value for these products (product category: IIB.a) in ready to use form is max. 200g/litre of VOC. The VOC content of these products in ready to use form is max. 200g/litre.

These products are for professional use only and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose.

For Health and Safety information please refer to the material Safety Data Sheet, also available at: http://www.ppg.com/Autocolor_MSDS

For further information please contact:

Customer Service Sales Group
 PPG Industries (UK) Ltd
 Needham Road
 Stowmarket
 Suffolk IP14 2AD
Tel: 01449 771771
Fax: 01449 773472

Nexa Autocolor, , Aquabase, Aquadry, Belco and Ecofast are trademarks of PPG Industries.
 Copyright © 2006 PPG Industries, all rights reserved.
 Copyright in the above product numbers that are original is asserted by PPG Industries.

Scotchbrite is a trademark of 3M UK Plc.

Product Data Sheet



Innovating Repair Solutions