


AD 1208 PLAST

1.975.1208

ADDITIVE FOR APPLICATIONS ON PLASTIC

AD 1208 PLAST is a product based on elastomeric resins with plasticizing effect. It is used for application on plastic substrates, both flexible and semi-rigid

AD 1208 PLAST can be mixed to 2K ground products and topcoats.



SUBSTRATES

Plastic parts, flexible or semi-rigid.


PREPARATION

Add 10-30% to the following groundcoats and topcoats, up to the flexibility of the plastic component:

HS Filler 3011
MS Filler 4020
Filler 0310
MS Filler 4206
Filler 0205
Filler 8700/8900

HS Clear 420
HS Clear 0200
MS Clear 0440
UHS Clear 0330

Duralit Car
Premium UHS Duralit
UHS Duralit Extra



Important:

Never add to MaxiCar HS basecoat

HARDENERS - THINNERS

Catalyze and thin groundcoat and topcoat as usual, according to relevant Technical Data Sheet.


APPLICATION

Application is the same as for the unmodified product. Please refer to relevant Technical Data Sheet.

DRYING

Drying times of modified products will be longer. With 30% addition, product will turn out 30-40% longer in drying.





TECHNICAL DATA

Pack size	0.500 l
Storage	store in a cool dry place away from heat

VOC INFORMATION

The EU limit value for this product (product category: IIB.e) in ready to use form is 840 g/litre of VOC.

The VOC content of this product in ready to use form is max. 840g/litre.

Depending upon the chosen mode of use, the actual ready to use VOC of this product may be lower than that specified by the EU Directive code.



SAFETY AND HANDLING

These products are for professional use only and are not to be used for purposes other than those specified.

The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose.

For Health and Safety information, please refer to the material Safety Data Sheet, also available at :
http://www.ppg.com/Maxmeyer_MSDS

For further information please contact:

PPG Industries (UK) Limited.

MaxMeyer Division

Customer Service & Sales Group,

Needham Road,

Stowmarket,

Suffolk.

IP14 2AD,

England.

Tel: 01449 771779

Fax: 01449 773495

