

Nitro Putty 1.835.3300

GREY

Stopper 3300 is a nitrosynthetic putty displaying smoothness, easy sanding, good hold out and fast drying. Nitro putty is used to fill fine imperfections in existing finishes.



SUBSTRATES

All the fillers in MaxMeyer Car Refinish range
Old finishes in sound condition, sanded.

Important:

Do not apply over bare metal.

PREPARATION

Clean surface with mild detergent and water (warm water recommended).
Sand old finishes with P320-400. Degrease with antsiliconic Degreaser 3600.
Product is ready for use.



APPLICATION

2-3 coats	
Suggested thickness	100-200 microns
Maximum thickness	250-300 microns




Important:

To speed up drying, it is recommended to apply several thin applications rather than one single thick coat.

Nitro Putty 1.835.3300

DRYING



AIR DRYING

Flash between coats
Sanding

5-10 minutes
after 1-3 hours

SANDING



WET
DRY

P600-800
P360-400

RECOAT WITH

All topcoats in MaxMeyer Car Refinish range.

TECHNICAL DATA



Pack size
Storage

1 Kg
Store in a cool dry place from heat

SAFETY AND HANDLING



These products are for professional use only and are not to be used for purposes other than those specified.

The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose.

For Health and Safety information, please refer to the material Safety Data Sheet, also available at:
www.maxmeyer.com

For further information please contact:

PPG Industries (UK) Limited. MaxMeyer Division Customer Service & Sales Group, Needham Road,
Stowmarket, Suffolk. IP14 2AD, England. Tel: 01449 771779 Fax: 01449 773495

MaxMeyer and the MaxMeyer logo are trademarks of PPG industries.

© 2011 PPG Industries. All rights reserved.