

DEL FLEET F381

DEL FLEET F381 SYSTEM PRODUCTS

Delfleet Accelerator

F381

Delfleet 2 pack products

PRODUCT DESCRIPTION

Delfleet 2 pack Accelerator is an additive used to assist the drying of polyurethane / isocyanate systems only , when the temperature is below 15°C or reduced cure times are required.

SUBSTRATES PRE-TREATMENT

Please refer to the relevant data sheet for preparation details.

APPLICATION GUIDE

Delfleet Accelerator F381 may be added to the colour prior to activation in the proportion of 3 – 6% by weight (40 – 80 cc or 35 – 70 grams per litre). Alternatively F381 may be added to the rfu mix in the proportion of 2 – 4 % by weight (26 – 52 cc or 23 – 46 grams per litre).

PERFORMANCE AND LIMITATIONS

The addition of accelerator reduces the potlife and should be used for smaller surfaces only. An excess of accelerator can reduce the flow and gloss.

These products are for professional painting only, and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose. For Health and Safety information please refer to the material Safety Data Sheet, also available at: http://www.ppg.com/PPG_MSDS

PPG Industries (UK) Limited.
Needham Road, Stowmarket,
Suffolk.
IP14 2AD, England.
Tel: 01449 771775
Fax: 01449 773480
www.ppgrefinish.com

