



GLOBAL REFINISH
SYSTEM



January 2009

Product Information



D8407 WB FLATTING PASTE

PRODUCT

WB Flattening Paste

D8407

PRODUCT DESCRIPTION

D8407 is a water-based abrasive, which provides a fast and effective method of preparing surfaces for repainting particularly for fade-out repairs. It is silicone and wax-free, and any residue is easily washed off with water.

PREPARATION PROCESS

1. Ensure the whole area to be repaired has been thoroughly pre-cleaned.
2. Apply the D8407 WB Flattening Paste onto a Scotch-Brite abrasive pad (Ultrafine Grey or equivalent).
3. Use the Paste and Scotch-Brite pad with water to 'key' or 'flat' the surface to be painted.
4. Wash off all residues with clean water and dry thoroughly with a clean cloth.
The surface should now have a uniformly matt appearance.
Note: Failure to remove all residues could affect the adhesion of subsequent paint layers.
5. Wipe the area to be repaired with a suitable Precleaner before applying paint.
6. Tak off the area to be painted.
7. Apply topcoat.
Refer to Aerosol Fade Out Thinner – Rapid Blender TDS (RLD199V).

VOC INFORMATION

This product falls outside of the scope of EU Directive 2004/42 and therefore does not have a VOC product category classification.

This product can be used by professional motor vehicle repairers.

HEALTH AND SAFETY

These products are for professional use only, and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose. For Health and Safety information please refer to the material Safety Data Sheet, also available at: www.ppgrefinish.com

PPG Industries (UK) Limited.
Auto Refinish
Customer Service and Sales Group,
Needham Road,
Stowmarket,
Suffolk.
IP14 2AD,
England.
Tel: 01449 771775
Fax: 01449 773480



Copyright ©2009 PPG Industries, all rights reserved

